MILITARY SPECIFICATION

ACTUATOR ASSEMBLY, ROTARY

This amendment forms a part of Military Specification MIL-A-62463A(AT), dated 30 March 1984, and is approved for use within the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

*2.1, under "SPECIFICATIONS, MILITARY", after "MIL-T-46167", add the following:

"MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.
MIL-C-53039	- Coating Aliphatic Polyurethane, Single Components, Chemical Agent Resistant."

*2.1, under "STANDARDS, MILITARY", after "MIL-STD-130", add the following:

"MIL-STD-193	- Painting Procedures and Marking for Vehicles, Construction Equipment and Material Handling Equipment."

PAGE 3

* Add the following paragraph:

"3.2.3 Recycled, virgin and reclaimed materials. There are no requirements for the exclusive use of virgin materials. The use of recycled or reclaimed (recovered) materials is acceptable provided that all other requirements of this specification are met (see 6.3.2)."

3.4.1a.2, delete "15,000 psi (103,425 kPa) minimum" and substitute: "7500-8000 psi (52,000-55,000 kPa)".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:41Z
Check the source to verify that this is the current version before use.

PAGE 4

3.4.1g, delete "None" and substitute: "A weep or seep is permitted in the area of the shaft seal."

* TABLE I, delete in its entirety and substitute:

TABLE I. Leveling valve travel.

Cam position	Angle of travel	Direction of travel
1R	59 ± 3°	Clockwise
1L	59 ± 3°	Counterclockwise
4R	46 ± 3°	Counterclockwise
4L	46 ± 3°	Clockwise

PAGE 5

3.4.2a.2, delete "15,000 psi (103,425 kPa) minimum" and substitute: "7500-8000 psi (52,000-55,000 kPa)".

3.4.2g, delete "None" and substitute: "A weep or seep is permitted in the area of the shaft seal."

*3.7, delete in its entirety and substitute with the following paragraph:

"3.7 Finish. Unless otherwise specified (see 6.2), actuator assemblies shall be cleaned, treated, primed and painted in accordance with MIL-STD-193. All parts that are exposed directly to chemical contaminations shall be painted with a coating conforming to MIL-C-46168 or MIL-C-53039."

PAGE 6

4.3.2b, delete "15000 psi (103,425 kPa) (minimum)" and substitute: "7500-8000 psi (52,000-55,000 kPa)".

PAGE 9

Table III, delete in its entirety and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:41Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of tests.

Title	Requirement	Tests	First article	Quality conformance	
				Acceptance (100%)	Con-trol
Characteristics Type I	3.4.1	4.6			
Operating pressure	a.1	4.6	X	X	
Proof pressure	a.2	4.6	X		X
Break-out pressure	a.3	4.6	X	X	
Displacement	b.	4.6	X		X
Torque	c.	4.6	X		X
Weight	d.	4.6	X		X
Travel	e.	4.6	X	X	
Travel buffing	f.	4.6	X		
External leaks	g.	4.6	X	X	
Internal leaks	h.	4.6	X	X	
Leveling valves	i.	4.6	X	X	
Relief valve setting	j.	4.6	X	X	
Characteristics Type II	3.4.2	4.6			
Operating pressure	a.1	4.6	X	X	
Proof pressure	a.2	4.6	X		X
Break-out pressure	a.3	4.6	X	X	
Displacement	b.	4.6	X		X
Torque	c.	4.6	X		X
Weight	d.	4.6	X		X
Travel	e.	4.6	X	X	
Travel buffing	f.	4.6	X		
External leaks	g.	4.6	X	X	
Internal leaks	h.	4.6	X	X	

*5.1, delete in its entirety and substitute:

"5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking for the desired level shall be in accordance with the applicable packaging requirements specified by the contracting authority (see 6.2)."

PAGE 10

*6.2c and 6.2d, delete in their entireties and substitute with the following:

"c. If the finish shall be other than as specified (see 3.7).
d. If first article inspection is not required (see 4.4).
e. Selection of applicable level and packaging requirements (see 5.1)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:41Z
Check the source to verify that this is the current version before use.

Add the following paragraphs:

* "6.3 Definitions.

6.3.1 Leakage.

a. Weep - Any evidence of fluid beyond a seal or joint.

b. Seep - any evidence of fluid beyond a seal or joint that does not result in the formation of a droplet.

c. Leak - Any evidence of fluid beyond a seal or joint that results in the formation of a droplet.

d. Drip - Any evidence of fluid beyond a seal or joint where droplets form and fall.

* 6.3.2 Recovered materials. "Recovered materials" means materials that have been collected or recovered from solid waste (see 6.3.3).

* 6.3.3 Solid waste. "Solid waste" means (a) any garbage, refuse, or sludge from a waste treatment plant, water supply treatment plant, or air pollution control facility; and (b) other discarded material, including solid, liquid, semisolid, or contained gaseous material resulting from industrial, commercial, mining, and agricultural operations, and from community activities. It does not include solid or dissolved material in domestic sewage, or solid or dissolved material in irrigation return flows or industrial discharges which are point sources subject to permits under section 402 of the Clean Water Act, (33 U.S.C. 1342 et seq.), or source, special nuclear, or byproduct material as defined by the Atomic Energy Act of 1954 (42 U.S.C. 2011 et seq.) (Source: Federal Acquisition Regulations, section 23.402).

* 6.4 Subject term (key word) listing.

Assembly, rotary actuator.
Rotary actuator assembly.
Suspension system rotary actuator."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AT

Preparing activity:
Army - AT

(Project 2530-A006)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:41Z
Check the source to verify that this is the current version before use.