INCH-POUND

MIL-PRF-62548A(AT)
30 April 1996
SUPERSEDING
MIL-L-62548(AT)
24 November 1987

PERFORMANCE SPECIFICATION

LEAD, IGNITION

This specification is approved for use by the US Army Tank-automotive and Armaments Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an ignition lead that transmits high energy and high tension voltage from an ignition exciter to an igniter plug with energy to ignite and start a gas turbine engine (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 2920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications and standards. The following specifications and standards form a part of this document cited to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

A-A-52557	- Fuel Oil, Diesel.
P-C-437	- Cleaning Compound, High Pressure (Steam Cleaner).

DEPARTMENT OF DEFENSE

MIL-G-3056	- Gasoline, Automotive, Combat.
MIL-T-5624	- Turbine Fuel, Aviation, Grades JP-4 and JP-5.
MIL-H-6083	- Hydraulic Fluid, Petroleum Base, for Preservation and Operation.
MIL-L-7808	- Lubricating Oil, Aircraft Turbine Engine, Synthetic Base.
MIL-F-16884	- Fuel Oil, Naval Distillate.
MIL-L-23699	- Lubricating Oil, Aircraft Turbine Engine, Synthetic Base.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-462	- Electromagnetic Interference Characteristics.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-45662	- Calibration Systems Requirements.

(Unless otherwise indicated, copies of the above specifications and standards are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

DRAWING

12286829 - Lead, Ignition.

OTHER

PUBLICATIONS

DEOS 1505 - Nuclear Hardening Criteria.

(Copies of these drawings are available from the U.S. Army Tank-automotive and Armaments Command, AMSTA-TR-E/BLUE, Warren, MI 48397-5000.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

INSTITUTE FOR INTERCONNECTING AND PACKAGING ELECTRONIC CIRCUITS (IPC)

G400 - Guide Manual of Standard and Specifications for Electronic Component Packaging.

(Application for copies should be addressed to the Institute for Interconnecting and Packaging Electronic Circuits, 7380 North Lincoln Avenue, Lincolnwood, IL 60646-1776.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

ANSI AS748 - Identification Marking Methods.

(Application for copies should be addressed to Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Materials. Materials used shall be in accordance with the manufacturer's materials specifications for ignition leads (see 6.2). The materials shall be capable of meeting all the operational and environmental requirements specified herein. Material shall not contain defects that adversely affect performance or serviceability of the lead (see 4.4.1).

3.2.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The use of recycled or reclaimed (recovered) materials is acceptable provided that all other requirements of this specification are met (see 4.4.1 and 6.3.1).

3.3 Design and construction. The ignition shall conform to the physical configuration of Drawing 12286829 (see 4.4.1, 4.4.2, and 6.2).

3.3.1 Wire. The ignition lead wire shall be number 16 American Wire Gage (AWG) minimum (see 4.4.2).

3.3.2 Nuclear control. The ignition lead shall have optimum protection against electro-magnetic impulse (EMP) and transient radiation effects (TREE). There shall be at least two layers of copperweld shielding or equivalent shielding material (see 4.4.1).

3.3.3 Insulation resistance. The ignition lead insulation resistance between conductor and the cable shield shall be a minimum of 100 megohms using an applied potential of 490 to 500 volts direct current (Vdc) (see 4.5.1).

3.3.4 Maximum voltage. The ignition lead insulation shall show no evidence of breakdown with the application of 20 kilovolts (kv) root mean square (rms) voltage between the conductor and cable shield for 5 to 10 seconds duration (see 4.5.1.1).

3.3.5 Accelerated aging. The ignition lead insulation shall withstand a 392 degrees Fahrenheit (°F) (200 degrees Celsius (°C)) a minimum of 168 hours and continue to meet requirements of 3.3.3 and 3.3.4 (see 4.5.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

3.3.5.1 High temperature. The ignition lead insulation shall withstand a consecutive exposure to a temperature of 212°F (100°C) for a period of 100 hours and still meet the requirements of 3.3.3 and 3.3.4 (see 4.5.2.2).

3.3.5.2 Room temperature. The ignition lead insulation shall meet the requirements of 3.3.3 and 3.3.4 after exposure to room temperature of 77°F (25°C) for 8 hours (see 4.5.2.3).

3.3.5.3 Low temperature. The ignition lead insulation shall meet the requirements of 3.3.3 and 3.3.4 after exposure to a temperature of -65°F (-54°C) for a 30 hour period (see 4.5.2.4).

3.3.6 Operational altitude range. The ignition lead shall function fully in its intended application in a range of altitude between 1300 ±5% feet below sea level and 10,000 ±2% feet above sea level (see 4.5.2.5).

3.3.7 Humidity. The ignition lead shall be fully satisfactory in its intended application in a 15 day environment varying from relative humidity zero to 100% and temperature range of 70 ±5°F (21 ±3°C) to 129 ±5.4°F (54 ±3°C) (see 4.5.2.6).

3.3.8 Salt spray. Insulation resistance and maximum voltage performance shall not deteriorate after environmental exposure between 90 to 95°F (32 to 35°C) in a fog density of 5% NaC1, 95% distilled water (by weight) for a minimum of 48 hours (see 4.5.2.7).

3.3.9 Sand and dust. The ignition lead insulation resistance and maximum voltage performance shall not be deteriorated by exposure to sand and dust testing performed equal to Method 510 of MIL-STD-810 (see 4.5.2.8).

3.3.10 Fungus. Fungus growth equal to that described in MIL-STD-810, Method 508, in a 96 to 100% humidity (80 to 84°F) environment for a minimum of 28 days shall not cause malfunction of the lead (see 4.5.2.9).

3.3.11 Chemical resistance. The ignition lead shall be operative when exposed to the following materials in operating, non-operating and transit conditions (see 4.5.2.10):

a. Fuel vapors equal to A-A-52557, MIL-G-3056, MIL-T-5624 or MIL-F-16884.
b. Hydraulic fluid equal to MIL-H-6083.
c. Lubricating oil equivalent to MIL-L-7808 and MIL-L-23699.

3.3.12 Vibration. The ignition lead shall be operative when exposed to vibration levels up to 5 gravity units (g), from 5 to 2000 hertz (Hz) (see 4.5.2.11).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

3.3.13 Shock.

3.3.13.1 Gun firing shock. The ignition lead shall be capable of sustaining shock impulses of 100 ±10 g intensity, 1.5 ±2 milliseconds (ms) duration in any direction without malfunction (see 4.5.2.12.1).

3.3.13.2 Ballistic shock. The ignition lead shall be capable of sustaining impact shock waves generated by thread application of 200 ±20 g half-sine wave shock pulses in any direction without malfunction (see 4.5.2.12.2).

3.3.13.3 Basic shock. The ignition lead shall be capable of sustaining half-sine wave shock pulses of 40 g intensity, 18 ms duration in any direction without malfunction (see 4.5.2.12.3).

3.3.14 Submergence. The ignition lead shall perform after a submergence in 6 feet of water for a period of 30 minutes (see 4.5.2.13).

3.3.15 Electromagnetic interference (EMI). The ignition lead shall meet the requirements of MIL-STD-461 on a component level as part of the engine electronic control system (see 4.5.3).

3.3.16 Nuclear hardening. The ignition lead shall withstand nuclear threat environment as defined in “Nuclear Hardening Criteria,” document control number DEOS 1505 (see 4.5.4).

3.4 Identification and marking. The ignition lead shall be permanently marked and identified in accordance with Drawing 12286829 (see 4.4.2).

3.5 Workmanship. Guidance for establishing quality of workmanship shall be in accordance with requirements of IPC G400 as included in the contract (see 4.4.2).

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspections (see 4.3).
    1. Examination (see 4.3.2).
    2. Acceptance (see 4.3.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

4.2 First article inspection. First article inspection shall be evidenced that all items already produced prior to completion of the first article inspection is similarly deficient unless contrary evidence satisfactory to all items shall be corrected by the contractor. First article samples shall be inspected as specified in table I.

TABLE I. Classification of inspection.

Title	Requirement	Inspection	First article	Conformance	
				Exami-nation	Tests
Materials and construction	3.2 thru 3.3.2	4.4.1	X		
Defects	3.3, 3.3.2, 3.3.4 and 3.5	4.4.2	X	X	
Insulation resistance	3.3.3	4.5.1	X		X
Maximum voltage	3.3.4	4.5.1.1	X		X
Accelerated aging	3.3.5	4.5.2.1	X		
High temperature	3.3.5.1	4.5.2.2	X		
Room temperature	3.3.5.2	4.5.2.3	X		
Low temperature	3.3.5.3	4.5.2.4	X		
Altitude range	3.3.6	4.5.2.5	X		
Humidity	3.3.7	4.5.2.6	X		
Salt fog	3.3.8	4.5.2.7	X		
Sand and dust	3.3.9	4.5.2.8	X		
Fungus	3.3.10	4.5.2.9	X		
Chemical	3.3.11	4.5.2.10	X		
Vibration	3.3.12	4.5.2.11	X		
Gun firing shock	3.3.13.1	4.5.2.12.1	X		
Ballistic shock	3.3.13.2	4.5.2.12.2	X		
Basic shock	3.3.13.3	4.5.2.12.3	X		
Submergence	3.3.14	4.5.2.13	X		
Electromagnetic interference	3.3.15	4.5.3	X		
Nuclear hardening	3.3.16	4.5.4	X		

4.3 Conformance inspection.

4.3.1 Sampling. Samples from an inspection lot for conformance inspection (see 6.2) shall be selected in accordance with ASQC/ANSI Z1.4. Each sample selected shall be inspected as specified herein for defects listed in table II. Conformance to a lot shall be accepted when zero (0) defects are found and rejected when one (1) or more defects are found.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

4.3.2 Examination. Each sample selected with 4.3.1 shall be examined and shall be free from any defect as listed in table II.

4.3.3 Classification of defects. For examination purposes, defects shall be classified as listed in table II.

TABLE II. Classification of defects.

Category	Defect	Method of examination
Critical	None	
Major:		
101	Incomplete assembly (see 3.3).	SIE 1/
102	Dimensions affecting interchangeability, out of tolerance (see 3.3).	SIE
103	Faulty workmanship affecting performance (see 3.5).	Visual
Minor:		
201	Dimensions not affecting interchangeability, out of tolerance (see 3.3).	SIE
202	Improper marking (see 3.4).	Visual
203	Faulty workmanship, affecting appearance (see 3.5).	Visual

1/ SIE = Standard Inspection Equipment.

4.3.4 Acceptance tests. Each pickup shall be subjected to the acceptance tests specified in table III.

4.3.4.1 Test tolerances. Unless otherwise specified, test conditions, as indicated by instrumentation, shall not deviate from the conditions specified herein by more than the following:

a. Temperature: Under +100°F (38°C) ±4°F (2.2°C).
   Over + 100°F (38°C) ±4% (2.2°C).
b. Pressure: ±5%.
c. Humidity: ±5% relative
d. Vibration amplitude:
   (1) Random: ±3 decibels at resonance and ±1 decibel elsewhere.
   (2) Sinusoidal: ±2%.
e. Vibration frequency: ±2%.
f. Shock: ±5%.
g. Acceleration: ±5%.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

h. Voltage, current and time:
   (1) Value specified as a whole number ±0.5.
   (2) Value specified to 1 decimal place ±0.05.
   (3) Value specified to 2 decimal place ±0.005.

4.4 Methods of inspection.

4.4.1 Materials. Conformance to 3.2 through 3.3.2 shall be determined by inspection of contractor records providing proof or certification that materials conform to requirements. Applicable records shall include drawings, specifications, design data, receiving inspection records, processing and quality control standards, vendor catalogs and certifications, industry standards, test reports, and rating data.

4.4.2 Defects. Conformance to 3.3 through 3.3.2, 3.4 and 3.5 shall be determined by examination for the defects listed in table II. Examination shall be visual, tactile, or by measurement with standard inspection equipment.

4.5 Performance tests.

4.5.1 Insulation resistance test. To determine conformance to 3.3.3 measure the insulation resistance between conductor and cable shield using an applied potential of 490 to 510 Vdc.

4.5.1.1 Maximum voltage test. To determine conformance to 3.3.4 a voltage of 20 kv rms shall be applied between conductor and cable shield for 5 to 10 seconds.

4.5.2 Environmental tests.

4.5.2.1 Accelerated aging test. To determine conformance to 3.3.5, the ignition lead shall be placed dry, in an air oven and maintained at a maximum operating ambient temperature of 392°F (200°C) for a minimum period of 168 hours. During and upon completion of test repeat tests 4.5.1 and 4.5.1.1.

4.5.2.2 High temperature test. To determine conformance to 3.3.5.1, following test 4.5.2.1, ignition lead shall be subjected to a high temperature of 212°F (100°C) for a period of 100 hours. Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

4.5.2.3 Room temperature test. To determine conformance to 3.3.5.2, following test 4.5.2.2, ignition lead shall be subjected to room a temperature of 77°F (25°C) for a period of 8 hours. Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

4.5.2.4 Low temperature test. To determine conformance to 3.3.5.3, following test 4.5.2.3, ignition lead shall be subjected to low temperature of -65°F (-54°C) for a period of 30 hours. Upon completion of test repeat tests 3.5.1 and 4.5.1.1.

4.5.2.5 Altitude range test. To determine conformance to 3.3.6, ignition lead shall be subjected to a maximum atmospheric pressure of 31.19 inches of mercury (1300 feet below sea level) and a minimum atmospheric pressure of 20.01 inches of mercury (10,000 feet above sea level). During and upon completion of test repeat tests 4.5.1 and 4.5.1.1.

4.5.2.6 Humidity test. To determine conformance to 3.3.7, the ignition lead shall be subjected to an atmosphere of clear water vapor for a period of 15 days under the conditions and cycle specified in table III. Immediately after 12 hours of the first test cycle, check the ignition lead for proper operation with the maximum specified voltage. During the last cycle of the 15 day test, operate the ignition lead throughout its entire range of operation under each of the ambient conditions specified. At the end of the 15 days of test, dry the ignition lead without forced convection for 12 hours in air at less than 69.8°F (21°C) with not less than 50% relative humidity. After this, disassemble and inspect the ignition lead. There shall be no corrosion or other defects present that affect the function or structural strength of the assembly. Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

TABLE III. Humidity conditions test cycle.

Time period (hours)	Relative humidity (percent)	Ambient temperature
8	95 ± 5	129 ± 5.4°F (54 ± 3°C)
4	Holding chamber moisture content constant	129 ± 5.4°F (54 ± 3°C) gradually down to 70 ±5.4°F (21 ± 3°C)
8	Holding chamber moisture content constant	70 ± 5.4°F (21 ± 3°C)
4	Up to 95 ± 5, holding chamber moisture content or adding vapor to reach required value	70 ± 5.4°F (21 ± 3°C) uniformly up to 129 ± 5.4°F (54 ± 3°C)

4.5.2.7 Salt fog. To determine conformance to 3.3.8, ignition lead shall be exposed to salt fog for a minimum of 48 hours. The fog solution shall be 5 percent NaCl by weight in 95 percent distilled water by weight. The temperature shall be maintained between 90 to 95°F (32 and 35°C). Fog density shall be 3 quarts of solution per 10 cubic feet of chamber volume per 24 hours. Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

4.5.2.8 Sand and dust test. To determine conformance to 3.3.9, the ignition lead shall be subjected to the sand and dust test in accordance with MIL-STD-810, method 510. The ignition lead need not be operated during the test; however, at the conclusion of the test and prior to any cleaning of the ignition lead, repeat tests 4.5.1 and 4.5.1.1.

4.5.2.9 Fungus test. To determine conformance to 3.3.10, ignition lead shall be inoculated with a spore suspension and tested in accordance with MIL-STD-810, method 508. Temperature shall range from 80 to 84°F and the relative humidity from 96 to 100 percent for a period of 28 days. Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

4.5.2.10 Chemical test. To determine conformance to 3.3.11, ignition lead shall be exposed to fluids and vapors of materials listed in 3.3.11. Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

4.5.2.11 Vibration test. To determine conformance to 3.3.12, ignition lead shall be subjected to vibrations when normally mounted (with vibration isolators in place) and powered. The vibrations shall be of 5 g magnitude in each direction along 3 mutually perpendicular axes at a logarithmic sweep rate. The vibration cycle time shall be equivalent to 20 minutes per axis from 5 to 2000 to 5 Hertz (Hz) with each 20 minute test period representing 1000 miles of vehicle operation. Conduct a resonance sweep to identify up to four of the most severe resonances and then accomplish resonance dwells for one-sixth of the total cycling vibration time at each resonance at the specified levels. Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

4.5.2.12 Shock.

4.5.2.12.1 Gun firing shock test. To determine conformance to 3.3.13.1, the ignition lead while mounted normally (with vibration isolators in place, if any) and powered shall be subjected to 3 shocks of 100 $\pm$ 10 g, 1.5 $\pm$ 0.2 milliseconds (ms) along each of 3 mutually perpendicular axes (18 shocks). Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

4.5.2.12.2 Ballistic impact shock test. To determine conformance to 3.3.13.2, the ignition lead while mounted normally (with vibration isolators in place, if any) and powered shall be subjected to 3 shock waves of 200 $\pm$ 20 g half sine shock pulses along each of 3 mutually perpendicular axes (18 shocks). Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

4.5.2.12.3 Basic shock test. To determine conformance to 3.3.13.3, the ignition lead while mounted normally (with vibration isolators in place, if any) and powered shall be subjected to 3 half-sine wave shock pulses of 40 g, 18 ms along each of 3 mutually perpendicular axes (18 shocks). Upon completion of test repeat tests 4.5.1 and 4.5.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

4.5.2.13 Submergence test. To determine conformance to 3.3.14, ignition lead shall be tested in association with a fording test of a vehicle. The ignition lead when installed on an engine shall be utilized in the starting system. It shall be capable of meeting all performance requirements after submergence in 6 feet of water for 30 minutes.

4.5.3 Electromagnetic interference. To determine conformance to 3.3.15, the ignition lead shall be tested in accordance with MIL-STD-462.

4.5.4 Nuclear hardening. Verification that the ignition lead meets nuclear environment specified in 3.3.16 shall be determined by the acquisition activity on the basis of circuit analysis and laboratory testing or through nuclear test of a complete vehicle.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature which may be helpful, but is not mandatory.)

6.1 Intended use. The ignition lead covered by this specification is intended to provide electrical continuity between the ignition exciter and spark igniter on the AGT 1500 gas turbine engine in the M1 (Abrams) military tank.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1, 2.2.2 and 2.3).
c. If first article inspection is not required (see 3.1).
d. If material is other than as specified (see 3.2).
e. If dimensioning is other than as specified (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

f. If first article sample size is other than as specified (see 4.3.1).
g. Packaging requirements (see 5.1).

6.3 Definitions.

6.3.1 Recovered materials. "Recovered materials" means materials that have been collected or recovered from solid waste (see 6.3.2).

6.3.2 Solid waste. "Solid waste" means (a) any garbage, refuse, or sludge from a waste treatment plant, water supply treatment plant, or air pollution control facility; and (b) other discarded material, including solid, liquid, semisolid, or contained gaseous material resulting from industrial, commercial, mining, and agricultural operations, and from community activities. It does not include solid or dissolved material in domestic sewage, or solid or dissolved material in irrigation return flows or industrial discharges which are point sources subject to permits under section 402 of the Clean Water Act, (33 U.S.C. 1342 et seq.), or source, special nuclear, or byproduct material as defined by the Atomic Energy Act of 1954 (42 U.S.C. 2011 et seq.) (Source: Federal Acquisition Regulations, section 23.402).

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

6.5 Subject term (key word) listing.

Electrical starter
Engine exciters
High energy
High tension voltage

Custodian:
Army - AT

Preparing Activity:
Army - AT

(Project 2920-0463)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-PRF-62548A(AT)	960430

3. DOCUMENT TITLE

Lead, Ignition

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (810) 574-8745	(2) AUTOVON 786-8745
c. ADDRESS (Include Zip Code) Commander U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE Warren, MI 48397-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.