MIL-D-48865 (AR)
Amendment 1
29 March 1981

MILITARY SPECIFICATION

DETONATOR, ELECTRIC, PA500
PARTS FOR, LOADING, ASSEMBLING
AND PACKING

This Amendment forms a part of Military Specification MIL-D-48865 (PA) dated 30 March 1976.

PAGE 1

2.1, after the paragraph number add: "Issues of documents."

2.1 Under the heading SPECIFICATIONS, MILITARY: delete "MIL-G-45204 - Gold Plating, Electro deposited"

PAGE 2

2.1 After the heading DRAWINGS: add "(see 6.5)"

Under the heading DRAWINGS: delete "PICATINNY ARSENAL" and substitute "US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND"

After the last drawing listed insert the following parenthetical statement: "(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer)."

3.3 line 3: delete the words, "when tested as specified in 4.5.2"

3.4 line 3: delete the words, "when tested as specified in 4.5.3"

PAGE 3

3.6.1 line 3: delete the words "when tested as specified in 4.5.8.1"

3.6.2 line 2: after 3.6.1 add "and 3.6.3."
line 4: delete the words ", when tested as specified in 4.5.8.2"

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

3.6.3 line 2: delete the words "when tested as specified in 4.5.8.3"

3.7.1 line 5: delete the words "and tested as specified in 4.5.9.1"

3.7.2 line 3: delete the words "and tested as specified in 4.5.9.2"

3.7.3 line 3: delete the words "and tested as specified in 4.5.9.3"

Add new paragraph 3.10 as follows:

"3.10 GOLD PLATING FINISH - Gold Plating shall be smooth, fine grained, adherent and free from exposed base metal or underplate, visible blisters, pits, nodules, porosity, indications of burning, excessive edge build up, residual plating salts, and other detrimental defects. Correction of a burned condition by burnishing or tumbling is not acceptable."

PAGE 5

Table I, in the column "Requirement Paragraph" for Gold Plating of Electrodes: change "3.2" to "3.10".

PAGE 11

4.4.2.4, delete Major Defects 101 and 102 in their entirety.

PAGE 12

4.4.2.5 Major Defect 105: change the last four column entries to read "(a)", "0.40%", "3.10", "4.5.4/Gage".

Under the heading Notes: change note (a) to read "Sampling applies to each plating lot".

PAGE 18

4.4.2.11 Major Defect 108: change the last column entry to read "Visual"

PAGE 19

4.4.4, line 8: change "6.2" to read "6.3".

Source: https://assist.dla.mil -- Downloaded: 20260-22T19:42Z
Check the source to verify that this is the current version before use.

4.5.4, delete in its entirety and substitute:

"Gold Plating of Electrodes. The gold plating shall be visually examined at four (4) diameters magnification, minimum, for compliance to the requirements."

PAGE 21

4.5.8.2, line 11, after "shall be recorded": add "and evaluated to determine compliance with the requirements".

PAGE 22

4.5.9.2, add the following note after the end of the paragraph:

"NOTE: If functioning at the maintained conditioning temperature is impractical, the detonator shall be functioned within one (1) minute of its removal from the conditioning chamber. All components, used in this functioning test (that is detonator, containment fixture, and witness block) shall be temperature conditioned."

4.5.9.3, add the following note after the end of the paragraph:

"NOTE: IF functioning at the maintained conditioning temperature is impractical, the detonator shall be functioned within one (1) minute of its removal from the conditioning chamber. All components, used in this functioning test (that is detonator, containment fixture, and witness block) shall be termperature conditioned".

PAGE 23

6.1, delete in its entirety and substitute:

"6.1 Intended Use. Detonators covered by this specification are intended for use in the M934 Fuze for the Stinger Missile."

6.2, delete in its entirety and substitute:

"6.2 Ordering Data. See MIL-A-48078 (AR)".

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:42Z
Check the source to verify that this is the current version before use.

6.3, delete in its entirety and substitute:

"6.3 Submission of Inspection Equipment Designs for Approval. See MIL-A-48078 - Submit equipment designs, as required, to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey, 07801."

Add new paragraph as follows:

"6.4 Check Test for Possible Deterioration. The following test is designed to prevent the loading of detonators which have deteriorated, into a major ammunition item. The test shall be performed on detonators from each lot which has been stored under normal conditions for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are loaded does not require that the check test be performed, the contracting officer should insert a provision for the performance of the check test in that contract. The contracting officer will arrange for the contractor to be reimbursed for expenses incurred in the performance of the check test for possible deterioration. Two hundred (200) detonators shall be selected from each lot for this test."

Add new paragraph as follows:

"6.4.1 Functioning. The detonators shall be selected at random from each lot. The detonators shall be tested in the following sequence.

a. Measure resistance between electrodes, using a current limited to one milliampere. The resistance shall be no less than 2.5 ohms nor more than 4.0 ohms. If any detonator fails to meet the requirement, it shall be classed defective. If four or more defectives occur, the lot shall be rejected.

b. The detonators that are not classed defective in step a. shall be functioned as specified in 4.5.8.1 and meet the requirements of 3.6.1. If any detonator fails to meet the requirements, it shall be classed defective. If one or more defectives occur, the lot shall be rejected."

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:42Z
Check the source to verify that this is the current version before use.

Add new paragraph as follows:

"6.5 Drawings. Drawings listed in Section 2 of this specification under the headings US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical Data originally prepared by these activities is now under the cognizance of ARRADCOM."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1375-A173

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

NOTICE
OF VALIDATION

MIL-D-48865(AR)
NOTICE 1
30 January 1987

MILITARY SPECIFICATION

DETONATOR, ELECTRIC, PA500
PARTS FOR, LOADING, ASSEMBLING
AMD PACKING

MIL-D-48865(AR), dated 29 March 1981, has been reviewed and determined to be valid for use in acquisition.

Preparing activity:
Army - AR

AMSC N/A

FSC 1375

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:42Z
Check the source to verify that this is the current version before use.