MILITARY SPECIFICATION

MACHINE GUN, 7.62MM: M240C

This specification is approved for use by the U.S. Army Armament Research and Developent Command, and is available for use by all departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the performance, design, developement, foromg. packaging and quality assurance requirements for one tvpe of 7.62 millimeter (MM) gas operated, air cooled, link belt fed, light weight, machine qun furnished with one spare interchangeable barrel assembly in carrying case and one ruptured cartridge case extractor. This machine gum is for use as a coaxial weapon in tank application or other vehicle.

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The followina documents of issue in effect on rate of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-P-116	- Preservation-Packing, Methods of
MIL-D-1000	- Drawings, Engineering and Associated Lists
MIL-W-13855	- weapon, Small Arms and Aircraft Armament Subsystems, General Specification For

FSC: 1005

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

MIL-W-63150 - Weapons and Support Material Standard Quality Assurance Provisions For
MIL-I-45607 - Inspection Equipment, AcqulsItions Maintenance and Disposition of
MIL-L-46000 - Lubricant, Semi-fluid [Automatic Weapons)

STANDARDS

MILITARY

MIL-STD-1188 - Commerical Packaging of Supplies and Equipment
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND

J11826004 - Machine Gun 7.62mm, M240C
P11826175 - packaging Data Sheet, Machine Gun, 7.62mm M240C (R.H.)

INSPECTION EQUIPMENT DRAWINGS

11826302 - Gage, Headspace, Minimum
11826303 - Gage, Headspace, Maximum
11826304 - Gage, Flush Pin, Firing Pin Protrusion
11826305 - Gage, Plug, Extractor Engagement
11826306 - Gage, Plug, Extractor Clearance
11826373 - Gage, Functional (max. Operating Rod)
11826322 - Gage, Functional (max. Breech Bolt)

2.2 Other publications.

ANSI Y14.36 - Surface Texture Symbols
ANSI/ASTM E380-76 - Standard for Metric Practice

Department of Defense

DOD-STD-1476 - International System of Units (SE)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. Requirements for submission of the first article shall be specified in the contract. Unless otherwise specified, the first article shall include the pilot pack.

3.2 Materials and construction. Machine guns and parts shall conform materlals, dimensions. conditions and construction requirements specified herein and on Drawing .11826004 and drawlngs applicable thereto and shall be in accordance with the applicable material and constructon previsions of MIL-W-13855.

3.2.1 Packaging. Packaging Data Sheet Pl1826175 (see 5.0 dimensions are in the inch-pound unit system).

3.2.1.1 Drawings. Dimensions of Drawing 11826004 and drawings applicable thereto arein the metric unit system.

3.2.1.1.1 Surface roughness. Surface roughness (ANSI Y14.36) is stated in micro-inch units on drawings in accordance with ANSI/ASTM E380-76.

3.2.2 Manufacturing. Unless otherwise specified, manufacturing procedures stated on drawings are for guidance only.

3.2.2.1 Heat treatment. Hardness shall be as specified on the drawings. Dimensions on drawings prior to heat treatment are for guidance only.

3.3 Design. All drawings are presented in first angle projection.

3.3.1 Barrel assembly (dwg 11825985). The barrel assembly with gas regulator shall be so manufactured that when the machine gun is completely assembled, the requirements for targeting and accuracy shall be met (see para 3.4.3.2).

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:42Z
Check the source to verify that this is the current version before use.

3.3.1.1 Condition. The barrel assembly shall be free of cracks and seams. The bore and chamber shall be free of pits. The chromium plating shall be free of nodules, flaking, stripping, anode burns and evidence of etched steel. Mechanical methods for removal of chromium plating in the barrel (dwg 11825987) bore shall not be permitted. Burrs and sharp edges shall be removed from chamber edges prior to chrome plating. Scratches and marks occuring in a chamber which otherwise meets the surface texture requirements.shall be permitted providing those scratches and marks do not cause marks on the case of a high pressure test cartridge fired In the chamber (See 3.4.2).Every accepted barrel assembly shall be marked in accordance with Drawing 11825985 after proof firing and magnetic particle inspection.

3.3.1.1.1 Plug, gas regulator (dwg 1826003) and collar as regulator (dwg 1186992). The plug gas regulator and the co llar, gas regulator shall be assembled to the barrel. Gas position #1 on the plug. gas regulator shall produce a machine gun firing rate of 700 to 850 rounds per minute. Position #3 shall produce a firing rate of 800 rounds per minute or greater.

3.3.1.1.2 Barrel gun (dwg 11825986) and adapter, barrel (dwg 1186001). The release, barrel (dwg 11825997) and latch, barrel (dwg 11825999) shall be assembled to the barrel with free movement between all three parts which shall be held in place by the adapter, barrel. The adapter, barrel shall be tightened against the barrel and then loosened until the latch barrel fits into its notch. The adapter, barrel, latch, barrel and release, barrel shall be held in place by a pin (MS 16562-122).

3.3.2 Receiver assembly (R.H.) (dwg 11825984). Every receiver assembly shall operate smoothly and accept a maximum sized bolt and operating rod assembly (dwg 11826070) following the firing of a Government Standard 7.62mm M60 high pressure test cartridge and the application of a protective finish. The rod assembly, driving spring (dwg 11826024) shall fit into the extension, piston rod (dwg 11826074) and shall be locked in place in the rear end of the receiver assembly. The latch, barrel locking (dug 11826124) shall function without binding. The barrel is locked in position when the assembly of the release, barrel; latch barrel; adapter barrel and pin are engaged with the latch, barrel locking with 2 to 5 clicks. The buffer assembly (dwg 11826211) shall be locked and unlocked without the use of tools. The trigger and frame assembly (dwg 11826230) shall be assembled to the rear part of the receiver assembly and locked in position with the pin, trigger mechanism (dwg 11826160), assembly and disassembly being accomplished without the use of tools. The cover assembly (R.H.) (dwg 11826038) with the tray feed, (right hand feed) (dwg 11826020) shall be assembled and disassembled without the use of tools by manually placing and removing the pin, axis, tray and cover (dwg 11826037). The slide charger (dwg li826135) with the cable, charger (dwg 11826145) shall be assembled to the receiver assembly and shall function freely.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

3.3.2.1 Bolt and operating rod assembly (dwg 11826070). The bolt and operating rod assembly shall be assembly manually to the rear end of the receiver assembly prior to the assembly of the buffer assembly (dwg 11826211). The bolt and operating rod assembly must readily move forward and backward in the guides in the receiver assembly. The bolt assembly and operating rod assembly shall consist of the rod assembly, operating (dwg 11826072), pin, firing (dwg 11826065), bolt, -assembly (11826057) and pin, spring loaded (dwg 11826054) and pin, spring'(F?S 16562-129). The firing pin shall move freely when assembled to the rod assembly, operating. All surfaces which contact guide ways to shoulders shall be polished to 32 micro inches.

3.3.2.2 Extractor, cartridge (dwg 11826060). The extractor, cartridge shall be assembled into the bolt, breech (dwg 11826041). The spring, extractor assembly (dwg 11826062) and the exterior of the plunger, extractor (dwg 11826061) shall be lubricated with grease (MIL-L-46000) prior to being assembled into the bolt, breech body (dwg 11826040). A clearance (1.68 ± 0.18 mm) between the cartridge case seat and the inner face of the extractor, cartridge shall be verified after movement of the extractor, cartridge has been verified. The extractor, cartridge engagement (10.9 ± 0.25 mm) shall be verified.

3.3.2.3 Ejector, cartridge (dwg 11826067). The ejector, cartridge and spring. heical compression, ejector (dwg 11826069) shall be greased and then assembled into the bolt, breech. The ejector, cartridge-shall be oriented and compressed using the tool, removed ejector and shall be secured with a pin, spring.

3.3.2.4 Rod assembly, operating (dwg 11826072). The piston rod dwg 11826073) shallbe assembled to the extension, piston rod (dwg 11826074) and secured with a pin, straight-headless (dwg 11826075) and permanently riveted together per dwg 11826072, Note 4.

3.3.2.5 Pin, firing (dwg 11826065). The pin, firing when assembled into the bolt and operating rod assembly. shall function freely in the bolt, breech assembly.

3.3.2.6 Rod assembly, driving spring (dwg 11826024). The rod assembly, driving spring shall be assembled manually into the bolt and operating rod assembly in the receiver assembly and locked into position by inserting a pin into the key hole slot in the rear end of the bottom of the receiver assembly. The rod assembly, driving spring shall be disassembled from the bolt and operating rod assembly by manually disengaging the pin of the rod assembly, driving spring from the rear of the receiver assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

3.3.3 Cover assembly (R.H.) (dwg 11826038). The cover assembly contains the mechanism to feed cartridges linked with m13 links (MIL-L-45403) through the firlng cycle, All rollers, links, pawls and cams shall operate smoothly and freely. When in the operating position the cover assembly shall be latched securely to the receiver assembly to hold both the cover assembly and the tray, feed in operating position. There shall be a maximum clearance between the feed pawl, Inner (dug 11826188) and the tray, feed per dwg 11826004, sheet 1. The cover assembly shall be assembled to the tray, feed and the receiver assembly with pin, axis tray and cover (R.H.) (dwg 11826037).

3.3.4 Tray, feed (right hand feed) (dwg 11826020). The tray, feed and the cover assembly together shall be assembled to the receiver assembly. The tray, feed-shall move easily both with and independently of the cover assembly.

3.3.5 Cable, charger (dwg 11826145). The cable, charger shall be assembly to the slide, charger (dwg 11826135) and pass through the support, cocking cable, guide (dwg 11826236). The cable, charger shall be flexible and return to normal position rapidly through the guide, charger cable without snagging, seizing or otherwise fouling when released. The handle (dwg 11826148) shall remain pliable.

3.3.5.1 Slide, charge (dwg 11826135). The slide, charger when assembled to the receiver assembly with the spring, extension, helical (dwg 11826155), plate spring, mounting (dwg 11826153) and the cable, charger shall operate freely and allow the bolt and operating rod assembly (dwg 11826070) to move forward and backward as required.

3.3.6 Trigger and frame assembly (dwg 11826230). The trigger and frame assembly shall be held in position by the pin, spring, trigger (dwg 11826160). The trigger and frame assembly component parts shall include the guide, charger cable (dwg 11826234), trigger assembly (dug 11826240), safety, small arms (dwg 11826258) and sear (dwg 11826253).

3.3.6.1 Guide, charger cable (dwg 11826234). The guide, charger cable shall be assembled to the trigger and frame assembly and held in position by a bolt (MS 9286-26) which clamps the entire trigger and frame assembly together.

3.3.7 Buffer assembly (dwg 11826211). The buffer assembly shall be assembled and disassembled, without the use of tools, in the grooves at the rear of the receiver assembly. The buffer assembly shall-be secured in position by the latch, buffer block (dwg 11826213) at the bottom of the plate, back buffer (dwg 11826212).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

3.3.8 Headspace. The headspace shall be as specified-on dug. 11826004.

3.3.9 Firing pin protrusion. The firing pin protrusion shall be as specified on dwg. 11826004.

3.4 Performance characteristics.

3.4.1 Trigger pull (dwg 11826241). The trigger pull shall not be less than 4 and at the most 7 kilograms.

3.4.2 High pressure resistance. The machine gun and all of its component parts shall be capable of withstanding the firing of one standard 7.62mm M60 high pressure test cartridge (MIL-C-46477). The component parts shall be subjected to the firing as integral parts of the machine gun. Replacement component parts, (barrel assembly, 11825985; bolt, breech body, 11826040), shall also be subjected to the high pressure test. The receiver assembly shall be tested in the “white condition", i.e.,prior to phosphate coating. After firing, all coponent parts shall be free of cracks, seams, and other defects. Testing shall be as specified in 4.4.3.4.

3.4.3 Functioning. The machine gun shall operate with standard 7.62mm M80 MIL-C-46931) cartridges and 7.62mm M13 links without malfunctions or unserviceable parts. The cyclic rate of fire shall be 700 to 850 rounds per minute with the plug, gas regulator in the position #1. The rate of fire shall not be less than 800 rounds per minute with the plug, gas regulator set at position #3. Testing shall be as specified in 4.4.3.5.

3.4.3.1 Belt pull. The machine gun, under normal operating conditions, shall be capable of pulling a belt weighing 4.5 Kg without malfunction. This shall be demonstrated in accordance with 4.4.3.5.

3.4.3.2 Accuracy. Accuracy shall be measured at a firing distance of 100 meters. Testing. shall be in accordance with 4.4.3.6.

3.4.3.2.1 The machlne gun shall be capable of placing nine out of ten shots fired single shot within a rectangle, half the perimeter (height + width) of which shall not exceed 25 cm. This is required for both the assigned and spare barrel.

3.4.3.2.2 The mean points of impact of both barrels shall be located in a square 20 X 20 cm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

3.4.3.3 Endurance. The machine gun with assigned barrel shall be capable of firing a 10,000 round endurance test without incurring more than three immediately clearable stoppages. No unserviceable parts or stoppages which require disassembly of the machine gun and/or in excess of one minute to correct are allowed. A stoppage is defined as any unplanned cessation in firing or the inability to commence firing. Testing shall be in accordance with 4.4.3.7.

3.4.3.4 Reliability. The machine gun shall demonstrate a Mean Round Between Stoppage (MRBS) of 4,500 rounds and a Mean Round Between Failure (MRBF) of 10,000 rounds over minlnum receiver service life of 50,000 rounds. Barrel life shall be 15,000 rounds minimum. Testing shall be in accordance with 4.4.3.9.

3.4.3.4.1 MRBS is determined by dlviding the total numberof rounds fired by the total number of stoppages. A stoppage is defined as any unplanned cessation in firing or the inability- to comence firing attributable to the gun. All incidents shall be recorded and any considered as not chargeable to the machine gun shall be substantiated by the contractor.

3.4.3.4.2 MRBF is determined by dividing the total number of rounds fired by the total number of failures. A failure is defined as any stoppage (as described above) which involves part replacement and/or requires in excess of one minute to correct; and/or involve any failed or damaged part detected during scheduled preventive maintenance, the replacement of which is not authorized at the crew or organizational level of maintenance as prescribed by Source Maintenance Recoverability Code and TM (Note: MRBF is a subset of MRBS). Only parts determined unserveable may be replaced. Simultaneous replacement of unserviceable parts is treated as one chargeable failure. Incidents attributable to personnel, test equipment, and/or parts found broken at the conclusion of testing are not chargeable; however, they shall be recorded.

3.4.3.5 Interchangeability. Unless otherwise specified on the drawings, all parts are interchangeable. Testing shall be as specified in 4.4.3.8.

3.4.4 Marking. Marking shall be in accordance with the applicable drawing and :MIL-W-13855.

3.4.5 Workmanship. Workmanship shall be in accordance with the workmanship requirements of MIL-W-63150. In addition, the machine gun shall be free of dust, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts nor shall the parts be contaminated by the cleaning agent. All markings and stampings shall be neat and clearly defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibity for impection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein Except as otherwise specified in the contract or order, the suppller may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. In addition, the Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-M-13855 shall apply.

4.2 Classification of Inspections. Unless otherwise specified in the specification, or contract, the following types of inspection shall be conducted on the unit of product:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection. The first article shall be subjected to quality conformance inspection scecified herein and SQAP'S and such other inspection as necessary to determine compliance with contract requirements. The first article shall be representative of the manufacturing methods and processes to be used for quantity production. The first article or articles shall deselected, as specified in the contract, from articles produced prior to the beginning of quantity production.

4.3.1 First article submission. The first article shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Combination of Adopted Item for Machine gun, 7.62mm M240C (R.H.) with Basic Items of Issue	11826175	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

4.3.2 Rejection. any assembly, component, or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly, component, or test specimen in the sample to comply with any of the stated requirements.

4.4 Quality conformance Inspection

4.4.1 Inspection lot.

4.4.1.1 Machine guns. The number of machine guns in an Inspection lot shall be 200 or one months production, whichever is smaller.

4.4.1.2 Parts. The number of parts in an inspection lot shall be determined in accordance with MIL-STD-105 and MIL-W-13855.

4.4.2 Examination. The examinations Iisted in the specification and SQAP'S shall be performed on inspection lots as defined in 4.4.1 of this specification.

a. Sampling plans. Sampling plans are incorporated in this specification either by reference to appropriate military standards or by stipulating other specific acceptance criteria. In cases where sampling is specified in accordance with MIL-STD-105, the contractor may request permission from the procuring activity to use an equivalent continuous sampling plan from MIL-STD-1235.

4.4.2.1 Component parts and concurrent repair parts. Examination of component parts and concurrent repair parts shall be performed in accordance-with criteria specified in the contract. Machine gun and concurrent repair parts consisting of more than one part shall be assembled with accepted parts.

4.4.2.2 Machine guns. Examination of each machine gun shall be performed after completion of all testing and immediately prior to preservation and packaging. A visual inspection in accordance with MIL-W-13855 shall be performed on the machine gun and on component parts at each examination step below for the following characteristics:

a. Cleaning improper

b. Specified protective-coating missing

c. Evidence of poor general quality

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

d. Manufacturing operations inccomplete.

e. Assembly improper

f. Evidence of poor workmanship.

g. Parts damaged

h. Finish Incorrect

i. Marking incorrect or illegible

Machine guns and component parts failing to meet the requirements shall be rejected.

4.4.2.2.1 Assembly characteristics. Each machine gun shall be examined as specified below.

4.4.2.2.1.1 Barrel assembly.

a. Manually disassemble the barrel assembly from the receiver assembly. Manually assemble to and manually disassemble the spare barrel assembly from the receiver assembly. Determine compliance with 3.3.1.1.2 by examining the operation of the release, barrel. -

b. Visually examine both barrel assemblies to determine compliance with 3.3.1.1.

c. Examination of the high pressure test cartridge case to determine whether or not specified scratches and marks occuring in the chamber are permitted, shall be performed immediately following the firing of the designated test cartridge. Visually examine every barrel assembly for proof marking and magnetic particle inspection.

4.4.2.2.1.1.1- Plug; gas regulator and collar, gas regulator.

a. Visually examine the barrel and the gas-hole bushing for compliance with 3.3.1.1.1.

4.4.2.2.1.1.2 Barrel and adapter, barrel.

a. Visually and manually examine the assembly of the parts to the barrel to determine compliance with 3.3.1.1.2.

b. Manually examine the assembly for free movement between all parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

4.4.2.2.1.2 Receiver assembly. Visually and manually examine the following characteristics to determine compliance with 3.3.2.

a. The receiver assembly operates smoothly and accepts Gage, Functional (max operating rod) 11826373 and Gage, Functional (max breech bolt) 11826322 after firing a high pressure test cartridge and the application of a protective finish.

b. The rod assembly, driving spring fits into the extension piston rod and is locked In place In the rear end of the receiver assembly.

c. The latch, barrel functions without blndlng and securely locks the barrel in position.

d. The buffer assembly locks to and unlocks from the.receiver assembly without the use of tools.

e. The trigger and frame assembly assembles to and disassembles from, without the use of tools, the rear part of the receiver assembly and locks In position with the pin, trigger mechanism.

f. The cover assembly with the tray, feed assembles to and disassembles from, wtthout the use of tools, the receiver assembly by placing and removing the pin, axis, tray and cover.

g. The cable, charger assembles to the receiver assembly and functions freely.

4.4.2.2.1.2.1 Bolt and operating rod assembly. Visually and manually examine the following characteristics to determine compliance with 3.3.2.1.

a. The component parts of the assembly are the rod assembly operating, the pin, firing, the bolt, assembly and the pin, securing, link assembly.

b. All surfaces contacting the guide ways or shoulders are polished to 32 micro inches.

c. The assembly readily moves forward and backward in the guide of the receiver assembly.

d. The assembly manually assembles to and disassembles from the rear end of the receiver assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

4.4.2.2.1.2.2 Extractor, cartridge.

a. Visually examine the springs and exterior of the plunger, extractor for the presence of lubrication.

b. Measure the clearance, using gage number 11826306, between the cartridge case seat and the inner face of the extractor, cartridge.

c. Measure the engagement, using gage number 11826305, of the extractor, cartridge.

4.4.2.2.1.2.3 Ejector, cartridge.

a. Visually examine the ejector, cartridge for the presence of lubrication.

b. Visually and manually examine the ejector, cartridge for proper orientation and the correct fastening with a roll pin.

4.4.2.2.1.2.4 Rod assembly, operating. Visually and manually examine the following characterstics to determine compliance with 3.3.2.4.

a. The pin, firing is fastened to the assembly with a roll pin and moves freely.

b. The piston, rod and extension, piston rod are permanently riveted together.

c. Pleasure the clearance described by the axis of the piston, rod for conformance.

4.4.2.2.1.2.5 Pin firing. Using gage number 11826304, determine compliance of the pin, firing protusion.

4.4.2.2.1.2.6 Rod assembly, driving spring. Manually disassemble and assemble the rod assembly, driving spring into the bolt and operating rod assembly in the receiver assembly to determine compliance with 3.3.2.6. Unlock and lock the rod assembly, driving spring from and into position by disengaging and engaging a pin out of and into the key hole slot in the rear end of the bottom of the-receiver assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

4.4.2.2.1.3 Cover assembly (R.H.). Visually and manually examine the following characteristics to determine compliance with 3.3.3.

a. Rollers, links, pawls and cams operate smoothly and freely.

b. The cover assembly is latched securely to the receiver assembly and holds both the cover assembly and the tray, feed in . operating position.

c. Assure that the clearance between the pawl, inner and the tray, feed is not more than maximum in accordance with drawing No. 11826004.

4.4.2.2.1.4 Tray, feed, visually and manually examine the cover assembly and tray, feed for compliance with 3.3.4.

4.2.2.1.5 Cable charger. Visually and manually examine the cable, charger for compliance with 3.3,5.1.

4.4.2.2.1.6 Slide charger assembly Visually and manually examine the folling characteristics to determine compliance with 3.3.5.2.

a. Free movement of the bolt and operating rod assembly both forward and backward.

4.4.2.2.1.7 Trigqer and frame assembly. Visually and manually examine the trigger and frame assembly for compliance with 3.3.6 and 3.3.6.1.

4.4.2.2.1.8 Buffer assembly.

a. Manually examine for secure fastening of buffer assembly to the receiver assembly by the latch, buffer block.

b. Disassemble and assemble, without the use of tools, the buffer assembly from and to the grooves at the rear of the receiver assembly.

4.4.3 Testing. The conformance tests listed in this specification shall be performed on inspection lots as defined in 4.4.1. The sampling plans shall conform to the provisions of 4.4.2a above..

4.4.3.1 Headspace testing. Every machine gun shall be tested for minimum and maximum headspace using the method specified in 4.5.1. Machine guns which fail to meet the requirements per dwg 11826004 shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

4.4.3.2 Trigger pull testing. A sample of 10 machine guns selected by the Government representative from each inspection lot shall be tested for trigger pull using the test methods specified in 4.5.2. Failure of any machine gun in the sample to meet requirements shall cause-rejection of the represented lot subject to retest.

4.4.3.2.1 The sample for a retest shall consist of 20 machine guns. If the retest is successful, the nonconforming machine gun in the first sample shall be corrected and verified and the lot accepted.

4.4.3.2.2 If any of the machine guns fail the retest, the inspection lot shall be rejected and the contractor shall inspect and correct all machine guns in the lot to insure that the defect(s) revealed during testing are purged from the represented lot and not presented to the Government for acceptance. The contractor shall also correct the appliable production and inspection processes to prevent the recurrence of the defects revealed during the test.

4.4.3.3 Pin, firing protrusion. A sample of 10 machine guns selected by the Government representative from each inspection lot shall be tested for pin, firing protrusion using the test methods specified in 4.5.3. Failure of any machine gun in the sample to meet requirements per dwg 11826004 shall cause rejection of the represented lot subject to retest as described in paragraphs 4.4.3.2.1 and 4.4.3.2.2.

4.4.3.4 High pressure resistance. Every machine gun shall be tested for high pressure resistance using the method in 4.5.4. Every barrel assembly and bolt, breech body to-be used as a repair or spare part shall be tested for high pressure resistance. Failure to meet the requirements shall cause rejection of the machine gun and the part.

4.4.3.5 Functioning. Every machine gun shall be tested for function firing using the test method specified in 4.5.5. The cyclic firing rate for two positions of the plug, gas regulator setting shall be measured for both the assigned and spare barrel. A machine gun shall be rejected if it does not achieve the cyclic rate requirements and/or has a malfunction. The belt pull requirement shall be demonstrated concurrently with the function firing.

4.4.3.5.1 Rejected machine guns. Machine guns rejected because of malfunction or failure to meet cyclic rate during the test shall be corrected by the contractor and the corrective action recorded. The machine guns shall be retested by repeating the firing procedures and paragraph 4.5.5. The machine guns shall operate without malfunction and shall meet the cyclic rate requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

4.4.3.6 Accuracy. Every machine gun with Its assigned and spare barrel shall tested or the accuracy requirement of 3.4.3.5 using the test method specified in 4.5.8. Failure to meet the requirements shall be cause to reject the machine gun.

4.4.3.6.1 Machine guns rejected because of failure to meet the accuracy requirements shall be corrected by the contractor and the corrective action recorded. Corrected machine guns shall be retested by repeating the accuracy test twice. Each target shall be checked to determine that the accuracy requirements are met for both tests. Machine guns failing the retest shall be rejected.

4.4.3.7 Endurance. One machine gun randomly selected by the Government from each inspection lot shall be tested for endurance. The first five endurance test lots shall each consist of 200 machine guns or a month's production, whichever is smaller. When five successive-lots meet the endurance requirements, as prescribed in 4.5.9, the lot size shall be increased to 500 machine guns or a month's production, whichever is smaller. When five successive lots of the increasecl size have met the endurance requirements, the lot size shall be further increased to 1,000 machine guns or a month's production, whichever is smaller. If rejection of a lot occurs at any time, the next smaller test lot size critieria shall be reinstated and the above procedure repeated in returning to the larger lot size.

4.4.3.8 Interchangeability testing.

4.4.3.8.1 In plant.

4.4.3.8.1.1 Machine guns. Ten machine guns, selected at random by the Government from each inspection lot, shall be tested for interchangeability (see 3.4.3.5) using the test method specified in 4.5.10. Machine guns taken for interchangeability testing shall have been found satisfactory in all other examinations and tests. Test frequency may be reduced to not less than 1 test of 10 machine guns each month after three consecutive inspection lots have been accepted. If rejection of a lot occurs, reinstate above procedure. After interchange of parts, the 10 machine guns shall be tested for the following:

a. Pin, Firing Protrusion per Para 3.3.9

b. Headspace per Para 3.3.8

c. Functioning per Para 3.4.3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

d. Belt Pull per Para 3.4.3.l

e. Rate of Fire Position #l per Para .3.4.3

f. Rate of Fire PositIon #3 per Para 3.4.3

g. Accuracy per Para 3.4.3.2

h. Trigger Pull per Para 3.4.1

i. Extractor clearance and engagement per Para 3.3.2.2

No failures shall be allowed.

Failure of the interchangeability test shall be cause retest or rejection of the represented lot. At the discretion of the Government, an interchangeability retest may be allowed without reconditioning the lot of machine guns. Failure in the retest shall cause rejection of the represented lot subject to reconditioning and further test as a reconditioned lot. A sample of 20 machine guns from each retest or reconditioned lot shall be tested using the same procedure described above.

4.4.3.8.1.2 Concurrent repair parts. At least two parts from each Inspection lot of concurrent repair parts shall be subjected to the interchangeability test specified in 4.5.8. Failure of any part to meet the requirements shall be cause for rejection of the represented lot of parts subject to reconditionlng and further test as a reconditioned lot. A sample of double the nunber of parts used in the original test shall be tested from each reconditioned lot using the test method specified in 4.5.10.

4.4.3.8.2 Interplant. When machine guns are manufactured concurrently by more than one contractor, each contractor shall forward monthly five machine guns, for the interplant interchangeability test specified in 4.5.8.2 See 6.1). The contractor will be informed of any failure of the machine guns to meet prescribed requirements.

4.4.3.9 Reliability As specified in the contract (See 6.1), three machine guns randomly selected by the. Government shall be each tested to 50,000 rounds using the test method specified in 4.5.9. Failure of the machine guns to meet, collectively, the MRBS and MRBF requirements shall be cause for deferment of acceptance of product and shall cause the contractor to determine the cause(s) of test failure and to perform the necessary corrective action on all products in house, both finished items and items in process. If test failure occurs and is believed to be attributed to causes other than machine guns, the contractor shall submit an analysis report supporting his contention to the contracting officer for review and final resolution.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T02:42Z
Check the source to verify that this is the currentversion before use.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the applicable paragraphs. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6.2.

4.5 Test methods and procedures.

4.5.1 Headspace test. Every machine gun with both its component barrel assembly and spare barrel assembly shall be gaged for minimum headspace and maximum headspace requirements after proof firing, prlor to acceptance, using gage number 11826302 for minimum and gage number 11826303 for maximum measurements.

4.5.2 Trigger pull test. Place the machine gun in an unloaded firing mode. Apply masses gradually to the center of the trigger bow in a rearward direction parallel to the barrel. For acceptance, a 4 kilogram mass will not fire the machine gun and a7 kilogram mass will fire the machine gun.

4.5.3 Pin, firing protrusion test. The pin, firing protrusion shall be gaged for compliance using gage number 11826304.

4.5.4 High pressure resistance test. Fire one high pressure test cartridge in every machine gun. Fire one high pressure test cartridge in every barrel assembly and with every bolt, breech body to be used as a repair or spare part. Machine gun testing and repair part testing are independent. After firing, apply magnetic particle inspection to the barrel assembly to be used as a repair or spare part. After firing, examine the machine gun for cracks, deformations and other evidence of damage. After firing, examine the cartridge case for bulges, splits, rings and other indications of defective barrels. Determine that specific scratches and marks, if present in the chamber which meets surface texture requirements, have not caused marks on the cartridge case.

4.5.5 Functioning test. Testing for the functioning and belt pull requirements of 3.4.33 and .4.3.1 shall be accomplished using a 100 round link belt. The belt is separated into five 20 round belts. Ten linked dummy rounds are attached to the end of one of the 20 round belts forming a 30 round belt. Mounted in a Government approved firing fixture, the weapon is first loaded with a 30 round link belt. A 3.7 Kg weight (minimum) shall be attached to the end of the belt. The belt with weight attached shall hang unsupported vertically from the feed tray. The plug, gas regulator is set at position #1 and the first 20 rounds (with 10 dummy rounds and weight attached) are fired in interrupted bursts with at

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

least three interruptions. Visually examine the firing operation to determine that firing is controlled-by the trigger and-that every spent cartridge is properly ejected. The four remaining 20 round link belts are used to obtain cyclic rates. With the assigned barrel, fire a 20 round continuous burst at gas position #1 and determine the cyclic rate over the 20 rounds. Set the plug, gas regulator at position #3. Fire 20 rounds in one continuous burst and measure the cyclic rate. Repeat the cyclic rate firings with the spare barrel. Failure to meet the cyclic rate requirements or the occurrence of any malfunction shall be cause to reject the machine.

4.5.6 Accuracy test. From a Government approved fixture, the machine gun loaded. with a 20 round link belt, is fired 10 consecutive single shots at a fixed target 100 meters away. The target shall be checked to assure that at least nine out of ten shots are within the required rectangle (sum of height and width 25 cm or less). The rectangle may be drawn or superimposed on the target. Location of a shot hole shall be determined by its center. Without adjustment to the weapon or fixture, the assigned barrel is replaced by the spare barrel and the remaining 10 consecutive rounds in the belt are fired single shot at a target at 100 meters. At least nine out of 10 shots from the spare barrel must be within the required rectangle. In addition, the mean " points of impact of both barrels shall be within a 20 cm by 20 cm square. A maximum of three warming shots are allowed per barrel prior to firing for record. All firing shall be performed with the plug, gas regulator set at the #1 position. Prior to firing, the weapon with assigned barrel shall be aligned with the 100 meter point of aim using a boresight.

4.5.7 Endurance test. The machine gun shall be fired 10,000 rounds in 250-round complements with compressed air cooling to ambient temperature after each complement. Each complement-should be fired in short burst (10-12 rounds) at a rate of one burst every 6-8 seconds. The plug, gas regulator shall be set at the #1 position. The machine guns are lubricated every 2,000 rounds and completely cleaned, inspected, and lubricated after every 4,000 rounds. Firing is from a Government-approved firing fixture. If the endurance requirements we not met, the represented lot shall be rejected subject to retest or reconditioning and further test as a reconditioned lot. An endurance retest of two other machine guns from the same lot shall be made without reconditioning the represented lot, unless in the opinion of the Governemnt representative the failure indicates serious defects in the item, in which case retest shall be made only when authorized by the procuring agency.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

Failure of either machine gun in the retest to meet the requirements shall cause rejection of the represented lot subject to reconditioning and further testing as a reconditioned lot, Prior to submission of a lot of machine guns as a reconditioned lot, the cause of failure shall be determined and contractor correction shall be effected on all machine guns in the lot. Sample size and test methods for reconditioned lots shall be the same as for retest.

4.5.8 Interchange of parts.

4.5.8.1 In plant.

4.5.8.1.1 Machine guns. Machine guns shall be tested by disassembling and then reassembling parts using the parts and prearranged system prescribed below. Interchange of parts shall be accomplished by dividing the parts of each machine gun into 10 gross of nonmating parts as shown below and distributing the-groups into 10 different trays until each tray contains a complete machine gun. Groups of parts from machine gun number 1 shall be taken in order and placed in trays 1 through 10; groups of parts from machine gun number 2 shall be taken in order and placed in trays 2 through 10 to 1; groups of parts from machine gun number 3 shall be taken in order and placed in trays 3 through 10 to 2, etc. Commerical parts such as screws, nuts, washers, and pins shall be placed in the same tray as their mating or associated part. Any commerical part rendered unserviceable by disassembly shall be replaced without penalty to the interchangeability test. The machine guns Shall be reassembled using only those parts which are in the same tray.

Groups of nonmating parts

GROUP I

1. Barrel, Gun With Flash Hider Mounted	(11825986) (11826002)
2. Pin, Spring Release	(MS 16562-122)
3. Cover, Frame with rollers	(11826022)
4. Pin, Spring	(MS 16562-105)
5. Plate, Spring Mounting	(11826153)
6. Pin, Straight Headless	(11826250)
7. Rod Assembly, Driving Spring	(11826024)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

GROUP II

1.	Latch, Barrel	11825999
2.	Pin, Straight Headed“	(11826216)
3.	Pin, Straight Catch Stop	(MS 9047-016)
4.	Plunger, Detent Buffer Catch	(11826215)
5.	Cone, Buffer Braking	(11826219)
6.	Washer, Spring Tension .	(11826221-)
7.	Plug, Machine, Thread	(11826223
8.	Tray, Feed (R.H.)	(11826019)
9.	Pin, Straight, Headed	(11826137)

GROUP III

1.	Release, Barrel	(11825997)
2.	Plate, Back Buffer	(11826212)
3.	Pin, Axis, Tray& Cover	(1182677)
4.	Pin, Spring Trigger	(11826277
5.	Rod, Assembly Operating	(11826072)
6.	Guide, Cartridge Rear (R.H.)	(11826035)
7.	Plunger, Detent	(11826156)

GROUP IV

1.	Spring, Helical Compression	(11826214)
2.	Plug, Buffer	(11826218)
3.	Guide, Charger Cable	(11826234)
4.	Grip, Machine Gun Left	(11826232-1)
5.	Sear	(11826253)
6.	Slide, Charger	(11826135)
7.	Adapter, Barrel	(11826001)

GROUP V

1.	Ring, Extension Braking	(11826220)
2.	Pin, Spring Loaded	(11826054)
3.	Pin, Firing	(11826065)
4.	Pin, Pawl Retaining (R.H.)	(11826205)
5.	Guide, Cartridge Front (R.H.)	(11826023)
6.	Clip, Retaining	(11826204)
7.	Grip, Machine gun, Right	11826232-2)
8.	Spring, Helical Torsion Sear	(11826254)
9.	Latch, Barrel Locking	(11826124)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

GROUP VI

1.	Spacer, Sleeve Masher, Support	(11826222)
2.	Pin, Spring	(11826068-1)
3.	Bolt, Breech Body	(11826040
4.	Trigger, Assembly	(11826240
5.	Pawl, Feed Assembly (RH).	(11826017)
6.	Clip, Spring Tension Feed Lever	(11826202)
7.	Clip, Retaining Catch	(11826203)
8.	Latch, Back Plate	(11826213)

GROUP VII

1.	Housing, Trigger	(11826231)
2.	Nut, Plain, Hexagon	(MS 35650-3384B)
3.	Ring, Retaining	{11826200)
4.	Latch, Cover	(11826206)
5.	Lever, Feed (R.H.)	(11826209)
6.	Screw, Cap, Hexagon Head Flat Metal, Round	(MS 9286-26)
7.	Spring, Helical, Compression, Detent Plunger	(11826158)
8.	Ejector, Cartridge	(11826067)
9.	Spring, Helical Compression	(11826201)

GROUP VIII

1.	Cover, Access Front	(11826122)
2.	Pin, Grooved Head	(11826130)
3.	Pin, Spring Plunger	(1182068-2)
4.	Pin, Cotter	(AS3259-67)
5.	Pin, Cotter	(AS3259-53)
6.	Plunger, Extractor	(11826061)
7.	Screw, Pan Head	(11826120)
8.	Extractor, Cartridge	(11826060)
9.	Plug, Gas Regulator	(11826003)

GROUP IX

1.	Washer, Flat	(11826121)
2.	Spring, Helical Compression, Barrel Latch	(11826131)
3.	Spring, Extension	(11826155)
4.	Cable, Charger	(11826145)
5.	Spring, Extractor Assembly	(11826062)
6.	Washer, Lock, Flat Internal Tooth	(MS 35333-42)
7.	Spring, Helical Compression, Ejector	(11826069)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

GROUP X

1.	Receiver Assembly	(11825984)
2.	Safety, Small Arms	(11826258)
3.	Collar, Gas Regulator	(11825992)
4.	Washer, Flat Metal, Round, General Purpose	(MS 15795-814B)
5.	Pin, Spring, Steel, Phosphate Finish	MS 9047-016)
6.	Pin, Straight, Headless	(11826255)

4.5.8.1.2 Concurrent repair parts. Concurrent repair-parts shall be tested by disassembling two machine guns, previously tested in 4.4.3.8, as necessary and then reassembling them using the concurrent repair parts. The machine guns shall operate and function properly, This test may be performed independently of the machine gun interchangeability test specified in 4.4.3.8, and at more frequent intervals using accepted machine guns taken from current production. .

4.5.8.2 Interplant. Machine guns which are to be subjected to the interplant interchangeability test shall be given preliminary hand functioning to assure proper operation before parts are disassembled form the gun. Machine guns shall be Interchanged in a manner similar to the detalled plan in 4.5.8.1.1. When disassembling, every other gun used shall be one produced by a different manufacturer. The machine guns shall be tested for and shall comply with the requirements of para. 4.4.3.8.1.1. Parts shall be identified with their manufacturer throughout the test. Before guns are returned to the contractors, the original parts shall be reassembled to their respective guns and the guns given a hand functioning test to assure proper operation.

4.5.9 Reliability test. The three machine guns are each fired 50,000 rounds in 10,000-round cycles from a Government-approved firing fixture simulating tank mounting. Unless otherwise specified, the firing is conducted in 250-round complements, alternating between firing schedules No. 1 and No. 2 (below), using gas port setting #1. Two barrel assemblies are to be used alternately (change after 250 rounds) with each weapon and are air cooled to ambient temperature after each 250 rounds.

4.5.9.1 Firing schedulesm.

4.5.9.1.1 Schedule No. 1: 10-round burst at a rate of one burst every 6 seconds; use for complete complement of 250 rounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

4.5.9.1.2 Schedule No. 2: 25-round burst at a rate of one burst every 15 seconds; use for complete complement of 250 rounds,

4.5.9.2 The weapons shall be cleaned, inspected, and lubricated after each 4,000 rounds and re-lubricated after each 2,000 rounds. Semi-fluid lubricant conforming to MIL-L-46000A is to be used.

4.5.9.3 Barrel life.

4.5.9.3.1 At the start of test and during the last 50 rounds of each of the final 250-round complements for each barrel in each 10,000 round cycle, velocities shall be measured and evidence of yaw of keyholing determined.

4.5.9.3.2 Targets shall be placed at a range of 100 meters. Projectile velocities shall measured and recorded instrumentally at a point 9 meters forward of the muzzle. Results shall be compared to the criteria in 3.4.3.4. When a barrel is suspected of being unserviceable during cycles, a check of barrel velocities and yaw shall be made. A barrel is considered unserviceable when (a) 20 percent of any burst exhibits yaw of 15 degrees or more, or (b) a mean velocity of a burst drops 200 feet per second below the mean of the velocity initially recorded at the start of the test. If declared unserviceable, the rounds fired on the barrel shall be recorded and the barrel replaced with a new barrel.

4.6 Testing stipulations.

4.6.1 Mounts. All firing tests shall be accomplished with the machine guns affixed to a Government approved mount.

4.6.2 Ammunition. All firing tests shall use cartridges per MIL-C-46931 except the high pressure test which shall use cartridges per MIL-C-46477. Defective ammunition shall void the test. Links shall be per MIL-L-45403.

5. PACKAGING

5.1 Preservation, Packaging. The requirements for packaging of machine guns shall be in accordance with Packaging Data Sheet P11826175.

5.2 Packing and Marking Packing and marking shall be as specified on Packaging Data Sheet P11826289)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

6.1.1 Procurement requirements.

a. Title, number and date of this specification and all applicable Supplementary Quality Assurance Provisions (SQAP's).

b. Quantity required and delivery schedules

c. Serialization requirements, if applicable.

d. Quality Conformance Inspection, if other than specified in Section 4 of specification.

e. Packaging requirements. if other than specified in Section 5 of specification.

f. Certificates of conformance for each lot or shipment of product.

g. Responsibilities for furnishing ammunition and links.

h. Shipping instructions for machine guns when an interplant interchangeability test is required.

i. The packages opened for examination shall be repackaged by the contractor at the contractor's expense.

j. Disposition of tested machine guns.

k. Requirement to conduct reliability test.

l. Responsibility for test firing facilities and operating procedures.

6.1.2 Contract data requirements.

a. Contract data requirements for inspection equipment designs (conforming to Data Item Description DI-E-7031 or DI-R-1714 with appropriate addendum to each). see 6.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

6.2 Insection Equipment Designs.Inspection equipment designs are of two types- Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" heading in Section 4. Design responsibility for all other inspection equipment is assigned-to the contractor. However, the contractor need not furnish any design when a-complete Government SIE is part of the Technical Data Package (TDP). Unless otherwise specified, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.2.2 and 6.2.3 should he elect to do Son

6.2.1 SIE designs. SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection. equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-1OO.

c. An envelope drawing, as defined in MIL-STD-KIO, which established the criteria which a detailed design shall meet. -When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein. .

6.2.2 Contractor designs. Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commerical equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commerical equipment. or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423).

The specification number, paragraph number, and defect number from Section 4 shall be referenced on each contractor design together with the component or assembly drawing number, revision letter and date to which the specific design applies.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:42Z
Check the source to verify that this is the current version before use.

6.2.3 Submission of designs for approval. Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for-approval In accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements Lists (DD Form 1423) or in the contract. Partial submission of Inspection equipment designs is permissible and encouraged. However, the completion data for design review will be based on the date of the final submission of designs and the required delivery schedule as stipulated In the contracct. The specific segment of ARRADCOM to which the Contractor designs shall be sent will be DRDAR-QAA-I.

When the contractor submits Inspection equipment designs to the Government for approval he shall give the following information in his letter of transmittal:

The contract number
The contract item (name, model number, etc.)
c. The designs remaining to be submitted and the expected date of submittal.

6.3 Definitions.

6.3.1 Contractor. Unless otherwise specified, the word Contractor used throughout this or the item detail specification shall mean any supplier or producer of items or material to the Government. this shall include commerical contractors, sub-contractors, Government Owned, Contractor Operated (GOCO) and Government Owned, Government Operated (GOGO) plants.

6.3.2 Technical data package (TDP). A technical description of an item adequate for use in proccurement. The description defines the required design configuration and assures adequacey of item performance. It consists of all applicable technical data such as plans, drawings, and associted lists specifications, standards, models, performance requirements, quality assurance provisions, and packaging data.

6.3.3 Critical defect. A defect that judgement and experience indicate is likely to result in hazardous or unsafe conditions for individuals using, maintaining, or depending upon the product; or a defect that judgement and experience indicate is likely to prevent performance of the tactical function of a major end item such as an aircraft, tank, land vehicle, missle, artillery, or other major weapon system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

6.3.4 Special defect. A defect, other Critical, that judgement and experience indidiate may, depending upon the degree of variance from the design, requirement:

a. Result in hazardous or unsafe, conditions for individuals using, maintaining or depending upon the product or
b. Prevent performance of the tactical function of a major end item.

6.4 To avoid delay in test firing the contractor should maintain a minimum of 2 mounts supply of ammunition as determined by anticipated firing requirements.

6.5 Test firing facilities and operating procedures should be designated by the contractor in conformance with local, state, and federal regulations. They should be suitable for carrying out prescribed firing tests and insure the safety of operation and personnel. Copies of these contractor designs should be forwarded to the contracting officer. Government facilities may be viewed upon application to the contracting officer.

6.6 When action by a testing agency is required, work programing will be effected with the testing agency at the earliest practical date.

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1005-A608

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-M-63356A Machine Gun, 7.62MM: M240C

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:42Z
Check the source to verify that this is the current version before use.