INCH-POUND

MIL-C-70775A (AR)
AMENDMENT 1
06 September 1994

MILITARY SPECIFICATION

CARTRIDGE, 25MM, TARGET PRACTICE

DISCARDING SABOT WITH TRACER (TPDS-T), M910

This amendment forms a part of MIL-C-70775A (AR), dated 15 February 1994, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.2: Delete the last sentence and substitute:

"The primer used in the cartridge shall be within the family of the M115 Percussion Primer."

PAGE 4

3.3.2: Delete in its entirety and substitute:

"3.3.2 25mm weapon/ammunition. Performance and acceptance as required in this specification apply only when tests are conducted in weapons which conform to the requirements of dwg. 12013697. Autogun test barrels shall be in accordance with dwg. 12524001 or 12524507. Testing from a firm fixed mount is required."

PAGE 5

3.12, lines 4 and 5: Delete "milliradians (mr)" and substitute "mils".

Lines 6, 7, 14 and 15: Delete "mr" and substitute "mils".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

PAGE 6

3.19, last sentence: Delete "required".

PAGE 10

Table I, sheet 2 of 4, Note 5, second sentence:
Delete "In addition".

Table I, sheet 2 of 4, Note 5b: Delete in its entirety and substitute: "5b. Criteria X (mean) + 3 sigma is less than or equal to 454 MPa."

PAGE 11

Table I, sheet 3 of 4, Note 7: After "X-direction .40" add "Mils max".

Note 7: After "y-direction .40" add "mils max"

Note 8: After "x-direction .484" add "mils max"

Note 8: After "y-direction .484" add "mils max"

Note 9: After "x-direction .65" add "mils max"

Note 9: After "y-direction .65" add "mils max"

PAGE 15

4.4.2.1, Special Characteristic 3., under Inspection Method:
Delete "Visual" and substitute "SMTE"

Add special defect 4. as follows:

"4. Profile and alignment (1) 100% 3.2 Dwg. 9391399"

Delete Major Defect 102 in its entirety.

PAGE 16

4.4.2.1: Delete Minor Defect 202 in its entirety.

PAGE 18

Table III, for Projectile Torque test, under Acceptance Criteria:
Delete "20 0, 2" and substitute "1"

For Projectile Extraction test, under Acceptance Criteria:
Delete "40 1, 2" and substitute "1, 2"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

PAGE 19

Delete "1." in its entirety and substitute:

"1. Failure of two or more sample cartridges to comply with the minimum requirement shall be cause for rejection of the lot. If one cartridge of the sample fails to comply with the minimum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if two or more cartridges of the combined sample fail to comply with the minimum requirement."

Delete "2." in its entirety and substitute:

"2. Failure of four or more sample cartridges to comply with the maximum requirement shall be cause for rejection of the lot. If more than one, but less than four sample cartridges fail to comply with the maximum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if five or more cartridges of the combined sample fail to comply with the maximum requirement."

Delete "8." in its entirety and substitute:

"8. The lot shall be accepted if no failures occur in the first sample. The lot shall be rejected if two or more cartridges in the first sample fail to comply with the minimum requirements. If one cartridge of the first sample fails to comply, a second sample of 35 cartridges shall be tested. The lot shall be rejected if three or more cartridges of the combined sample fail to comply with the minimum requirements. These provisions apply to blinds and/or short burn times."

PAGE 23

4.5.5.b, last line: Delete "(NOTE: Sodium...with this test.)"

PAGE 24

4.5.10, line 6, after "71 ± 3C": Add "as applicable".

PAGE 25

4.5.11, line 8: Delete "21C ± 10C" and substitute "range ambient conditions".

4.5.11.1, line 6, after "54 ± 3C and": Delete "a like amount of" and substitute "two hundred and forty".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

PAGE 25 (continued)

4.5.11.1: Delete the last two sentences and substitute:

"Any cracking, splitting, or disengaging of the cartridge protective cap shall be cause for rejection of the lot. Ninety cartridges from each temperature shall then be randomly selected and fired per the requirements of 3.8, 3.9, 3.10, 3.12, 3.14, and 3.17."

PAGE 26

4.5.11.2: Delete the last two sentences and substitute:

"Any disengaging of the cartridge protective cap shall be cause for rejection of the lot. Any cracked, split or similarly damage cartridge protective caps which remain attached to the cartridge shall be identified and selected for subjection to loose cargo transportation vibration testing (4.5.11.3). Forty-five (one box and one 15-round belt) cartridges shall then be selected (excluding cartridges with damaged protective caps if any) from each temperature environment and fired per the requirements of 3.17."

PAGE 28

4.5.11.3, line 7, after "-54C ± 3C and": Delete "a similar quantity and configuration of" and substitute "ninety repacked and the one loose belt of fifteen".

Delete the last two sentences and substitute:

"Any cracking, splitting, or disengaging of the cartridge protective cap, additional to damage sustained as a result of the 2.1 meter packaged drop (see 4.5.11.2) shall be cause for rejection of the lot. Any previously identified cracked or split cartridge protective cap shall be selected for subjection to 1.5 meter unpacked drop testing (see 4.5.11.4). Forty-five cartridges from each temperature environment shall then be selected (excluding cartridges with damaged protective caps, if any) and fired per the requirements of 3.17."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

PAGE 28 (continued)

4.5.11.4, line 7: Delete the sentence "After the drop test.... inspected for damage." and substitute:

"Any cartridge with a cracked or split cartridge protective cap shall, to the maximum extent possible, be selected for the all-orientation series. At the conclusion of test, the external surfaces of all cartridges will be visually inspected for evidence of deformation, damage, or unusual defects that would render then unsafe to handle, transport or fire (see 4.5.11.5)."

4.5.11.5, line 1: Delete "Sabot damage that would....to the following:" and substitute:

"Sabot damage that would render the M910 cartridge unsafe to handle, transport, or fire, and thus be cause for rejection of the lot, is defined as, but not limited to the following:"

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-0100)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.