INCH - POUND

MIL-P-60818C (AR)
AMENDMENT 3
18 April 1991
SUPERSEDING
AMENDMENT 2
22 November 1983

MILITARY SPECIFICATION

PROJECTILE, 4.2 INCH, ILLUMINATING, M335A2
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-P-60818C (AR), dated 22 February 1977, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1:

Add: "8861520 - Marking diagram for pallets for projectiles, 75mm to 120mm."

* 2.2:

Add: "ANSI-Y14.5M-1982 - Dimensioning and Tolerance
ANSI-Y14.6 - Screw Thread Representation"

PAGE 7

* 4.3.2.2:

Delete in its entirety

PAGE 8

4.3.2.2.1:

Delete: Major defects 101, 102, 103 and 104

Add: Major defects:

"108 Outside diameter forward of shoulder Gage

109 Length of outside diameter forward of shoulder Gage".

Delete: Minor defect 208

* 4.3.2.3:

Delete: Major defects 102, 105 and 106

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:58Z
Check the source to verify that this is the current version before use.

Add: Major defect 107

"107 Length from front face to spacer seat Gage"

PAGE 9

* 4.3.2.4:

Add: Major defect:

"103. Swaging of spacer improper (Less than 360 degrees) Visual (See Note)

NOTE: This inspection is to be performed 100 percent"

PAGE 11

4.3.2.7.1: Delete Major defects 101 and 102.

PAGE 12

4.3.2.7.1:

Delete: Major defect 105.

Add: Major defects.

"108 Diameter of through hole Gage

109 Run-out of through hole diameter with bourrelet Gage"

* Add new paragraph:

"4.3.2.7.2 Body Assembly, Drawing D10551974 and Body Assembly Alternate, D10551973, Covering a detail of drawing F10534155.

CRITICAL

None defined

MAJOR

101. Swaging of spacer improper (Less than 360 degrees) Visual (See Note)

NOTE: This inspection is to be performed 100 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:58Z
Check the source to verify that this is the current version before use.

MINOR

None defined"

PAGE 13

4.3.2.9: Add new Major defect and note:

"110. Swaging of spacer improper (less than 360 degrees) Visual (See Note).

NOTE: This inspection is to be performed 100 percent."

4.3.3.2.2.2.1, line 3:

Delete "nor" substitute "not".

Delete "each".

Delete "hours for" substitute "bars from".

PAGE 16

Add new paragraph:

"4.3.3.5 Disassembly test of spacer. The sampling for this test shall be in accordance with MIL-STD-105, Special Inspection Level S-4 and an AQL of 0.65%, The test shall be performed as specified in 4.4.4."

PAGE 17

4.4.1.2.1, line 3: Delete "R" add "T".

PAGE 19

Add new paragraph:

"4.4.4 Disassembly test of spacer. The projectile shall be held in a fixture and a disassembly force shall be applied to the spacer. The space must withstand a specified minimum force. The equipment shall be capable of indicating the applied force and the force shall be recorded. The assembly that withstand the specified requirement may be return to the production lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:58Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This is done as a convenience only and the Government assumes no liabilty whatsoever for any inaccuracies in these notations. Bidders are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1315-AD15)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:58Z
Check the source to verify that this is the current version before use.