MILITARY SPECIFICATION

RADAR SETS AN/APS-115B AND AN/APS-122

This amendment forms a part of Military Specification MIL-R-81858(AS) dated 12 June 1973 and has been approved by the Naval Air Systems Command; Department of the Navy.

Page 1, paragraph 2.1 - Change "MIL-N-18307D" to "MIL-N-18307C"

Page 6, paragraph 3.3.7 - Delete the paragraph and add the following:

"3.3.7 Provisions for Maintainability - The maintenance concept, Built-in Test features, construction and packaging, provisions for test points and other maintainability parameters shall be as specified herein."

Page 7, paragraph 3.3.7.2 - After the second sentence add "Special tools will be allowed for removal of the AFC Assembly."

Page 7, paragraph 3.3.7.3 - Delete the last sentence.

Page 9, paragraph 3.3.9 - Change "18 VAC" to "18 VDC"

Page 9, paragraph 3.3.10.1 - Delete "except that the console control panel shall meet Curve III."

Page 10, paragraph 3.3.12.3 - Delete the last sentence and substitute:

"In addition, the equipment operation shall return to normal with no resulting damage to the equipment, without the need for reset of any controls which are inaccesible to the operator during normal use."

Page 11, paragraph 3.3.12.4 - Delete the last sentence.

Page 11, paragraph 3.4.1 - After "...aircraft navigation computer" add "or Central Repeater Unit."

Page 12, paragraph 3.4.1.2 - Change "0.5 ± 1.0" to "0.5 ± 0.1."

Page 17, paragraph 3.5.2.3 - Change "140.0" to "141.0."

Page 20, paragraph 3.5.3.5.2 - Delete the last sentence and substitute:

"The AN/APS-122 system configuration as described in this specification will indicate No-Go in positions (7), (9), (10), (13) and (16) of Paragraph 3.5.3.5.1."

FSC 5841

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:17Z
Check the source to verify that this is the current version before use.

Page 21, paragraph 3.5.3.6.1.2 - Change "4 to 1" to "4 $^{+2.0}_{-0.2}$ to 1."

Page 21, paragraph 3.5.3.6.1.5 - Change "OFF" to "OPERATE."

Page 22, paragraph 3.5.3.6.3.2.5 - After the first sentence add:

"Pulse rise time shall be 3 ± 1 microseconds and fall time as fast as practical. Pulse duration shall be a minimum of 6 microseconds and a maximum of 1 millisecond."

Page 23, paragraph 3.5.3.6.3.3.1 - Delete the first sentence and substitute:

"Two separate aircraft headings with respect to North shall be supplied to the antenna position programmer unit for the AN/APS-115B system and one aircraft heading with respect to North for the AN/APS-122 system."

Page 24, paragraph 3.5.4.4.5 - Add new paragraph:

"Paragraph 3.5.4.4.5 - HEADING - NORTH STAB" - A lighted push-button switch shall provide for selecting either North Stabilized or Heading (relative) Stabilized bearing information. The switch shall automatically return to the North Stabilized position when power is turned off."

Preparing Activity:
NAVY-AS

Project Number:
5841-N-066

☆U.S. GOVERNMENT PRINTING OFFICE: 1977—703-020/6067

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:17Z
Check the source to verify that this is the current version before use.