AN103401
THRU
AN103500

FED SUP CLASS
5306


MATERIAL IDENTIFICATION PER AMS2800 RAISED OR DEPRESSED .010 MAX
.875
.865
.990 MIN
E11
.12-.030
DRILL NO 50 (.070) .5310 ...° DIA BOTH ENDS
L
3.2
Y TO FULL THD
CHAMPER .062 x 45° APPROX
.015 OR CHAMPER
.015 .005R
MAX 2 IMPERFECT THD
.875 DIA
.56 .558 DIA
.5625-18UNF-3A SPEC MIL-S-7742
THIS SURFACE MUST BE SQUARE WITH SHANK WITHIN .003 FIR
CHAMPER 30° TO .875 DIA (OPPOSITE SIDE OPTIONAL)

SECTION THRU THREAD PROFILE

	K +.000 -.060	PART NO	L	K +.000 -.060	PART NO	L	Y +.000 -.060	PART NO	L	K +.000 -.060	PART NO
			1.812	.438	AN103417	3.000	1.625	AN103431	4.750	3.375	AN103445
			1.875	.500	AN103418	3.125	1.750	AN103432	4.875	3.500	AN103446
			1.938	.562	AN103419	3.250	1.875	AN103433	5.000	3.625	AN103447
1.125	(a)	AN103406	2.000	.625	AN103420	3.375	2.000	AN103434	5.125	3.750	AN103448
1.188	(a)	AN103407	2.062	.688	AN103421	3.500	2.125	AN103435	5.250	3.875	AN103449
1.250	(a)	AN103408	2.125	.750	AN103422	3.625	2.250	AN103436	5.375	4.000	AN103450
1.312	(a)	AN103409	2.188	.812	AN103423	3.750	2.375	AN103437	5.500	4.125	AN10345
1.375	(a)	AN103410	2.250	.875	AN103424	3.875	2.500	AN103438	5.625	4.250	AN103452
1.438	(a)	AN103411	2.312	.938	AN103425	4.000	2.625	AN103439	5.750	4.375	AN103453
1.500	(a)	AN103412	2.375	1.000	AN103426	4.125	2.750	AN103440	5.875	4.500	AN103454
1.562	(a)	AN103413	2.500	1.125	AN103427	4.250	2.875	AN103441	6.000	4.625	AN103455
1.625	.250	AN103414	2.625	1.250	AN103428	4.375	3.000	AN103442			
1.688	.312	AN103415	2.750	1.375	AN103429	4.500	3.125	AN103443			
1.750	.375	AN103416	2.875	1.500	AN103430	4.625	3.250	AN103444			

(a) THREAD TO HEAD MAXIMUM TWO IMPERFECT THREADS

NOTE (1) SHANK SHALL BE STRAIGHT [illegible] PER INCH OF BOLT LENGTH
(2) THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR
(3) THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .026 FIR

MATERIAL STEEL AMS6322

HARDNESS ROCKWELL C26 - 32

FINISH CADMIUM PLATE AMS2400

SURFACE ROUGHNESS AS102

MFG [illegible]

INSPECTION ALL PARTS SHALL UNDERGO MAGNETIC INSPECTION IN ACCORDANCE WITH AMS2640

BREAK SHARP EDGES .003 - .015 UNLESS OTHERWISE SPECIFIED

DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED TOLERENCES LINEAR DIMENSIONS ±.010 ANGULAR DIMENSIONS ±2°

DO NOT USE UNASSIGNED PART NUMBERS

INACTIVE FOR NEW DESIGN AFTER 3 MARCH 1969 NO SUPERSEDING STANDARD

THIS STANDARD WAS DEVELOPED COOPERATIVELY BY THE ENGINE AND PROPELLER UTILITY PARTS COMMITTEE OF THE SAE

APPROVED 8 June 4_ REVISED ① 31 Aug 56 ② 3 Mar 69 ③ 30 June 86

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

P A AF-11 **CUST NAVY-AS** **ARMY-AV**	**AIR FORCE-NAVY AERONAUTICAL STANDARD** BOLT - DRILLED HEX HEAD, 1 HOLE, .5625-18	AN103401 THRU AN103500

Project No 5306-1019

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:24Z
Check the source to verify that this is the current version before use.