
AN104501 THRU AN104600

FED. SUP. CLASS. 5306



SECTION THRU THREAD PROFILE

L	K +.000 -.060	PART NO.	L	K +.000 -.060	PART NO.	L	K +.000 -.060	PART NO.	L	K +.000 -.060	PART NO.
			2.188	.438	AN104517	3.375	1.625	AN104531	5.125	3.375	AN104545
			2.250	.500	AN104518	3.500	1.750	AN104532	5.250	3.500	AN104546
			2.312	.562	AN104519	3.625	1.875	AN104533	5.375	3.625	AN104547
1.500	(a)	AN104506	2.375	.625	AN104520	3.750	2.000	AN104534	5.500	3.750	AN104548
1.562	(a)	AN104507	2.438	.688	AN104521	3.875	2.125	AN104535	5.625	3.875	AN104549
1.625	(a)	AN104508	2.500	.750	AN104522	4.000	2.250	AN104536	5.750	4.000	AN104550
1.688	(a)	AN104509	2.562	.812	AN104523	4.125	2.375	AN104537	5.875	4.125	AN104551
1.750	(a)	AN104510	2.625	.875	AN104524	4.250	2.500	AN104538	6.000	4.250	AN104552
1.812	(a)	AN104511	2.688	.938	AN104525	4.375	2.625	AN104539			
1.875	(a)	AN104512	2.750	1.000	AN104526	4.500	2.750	AN104540			
1.938	(a)	AN104513	2.875	1.125	AN104527	4.625	2.875	AN104541			
2.000	.250	AN104514	3.000	1.250	AN104528	4.750	3.000	AN104542			
2.062	.312	AN104515	3.125	1.375	AN104529	4.875	3.125	AN104543			
2.125	.375	AN104516	3.250	1.500	AN104530	5.000	3.250	AN104544			

(a) THREAD TO HEAD. MAXIMUM TWO IMPERFECT THREADS.

NOTE: (1) SHANK SHALL BE STRAIGHT WITHIN .002 FIR. PER INCH OF BOLT LENGTH.
(2) THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.
(3) THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .032 FIR.

MATERIAL: STEEL AMS6322

HARDNESS: ROCKWELL C26-32

FINISH: CADMIUM PLATE AMS2400

SURFACE ROUGHNESS: AS107

MANUFACTURING SPECIFICATION: AMS7452

(3) INSPECTION: ALL PARTS SHALL UNDERGO MAGNETIC INSPECTION IN ACCORDANCE WITH AMS2640

BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED: TOLERANCES; LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±2°.

DO NOT USE UNASSIGNED PART NUMBERS.

INACTIVE FOR NEW DESIGN AFTER 3 MARCH 1969 NO SUPERSEDING STANDARD.

THIS STANDARD WAS DEVELOPED COOPERATIVELY BY THE ENGINE AND PROPELLER UTILITY PARTS COMMITTEE OF THE SAE.

APPROVED 8 June 49 REVISED (1) 32 Aug 54 (2) 3 Mar 69 (3) 30 June 86

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

P.A. AF-11 CUST. NAVY-AS ARMY-AV	AIR FORCE-NAVY AERONAUTICAL STANDARD BOLT - DRILLED HEX HEAD, 6 HOLES, .750-16	AN104501 THRU AN104600

Project No. 5306-1029

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:25Z
Check the source to verify that this is the current version before use.