MILITARY SPECIFICATION SHEET

CABLE ASSEMBLY, T4140

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-50288(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for cable assembly, T4140.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-50288(MU) - Cable Assemblies for War Reserve Atomic Demolition Charges, General Specification for
MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MS15795-204 - Washer
MS20450C8AD12 - Rivet, Tublar
MS25281-3W - Clamp
MS35036-49 - Lug

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8823646 - Connector, Plug, Electrical
8836735 - Clip
8838890 - Cable Assembly, T4140
8838900 - Connector, Plug, Electrical
8838904 - Cap with Chain, Dust
8846960 - Carton, Packing, Ammunition, for Cable Assembly, Special Purpose Electrical, Branched: T4140
8858702 - Insulator
EL-8838890 - Equipment List

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-50288(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit resistance (see dwg 8838890)

From P4-1 Connector Pin	To P5-2 Connector	To	Ohms Max
F	Pin		0.2
A	Shell		0.2
D		Red clip	0.2
C		Black clip	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-C-50288(MU) and as specified herein.

4.2 Classification of characteristics.

4.2.1 Connector, plug, electrical (see dwgs 8823646 and 8838900); clip (see dwg 8836735); cap with chain, dust (see dwg 8838904); insulator (see dwg 8858702); washer (see MS15795-204); rivet, tublar (see MS20450C8AD12); clamp (see MS25281-3W); and lug (see MS35036-49)covering details of dwg 8838890.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for component in accordance with applicable drawing or standard.....	Visual
Minor: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.2.2 Cable assembly, T4140 (see dwg 8838890).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Torque on connector nut	Gage
102.	Length	*Measure
103.	Length of sleeving	*Measure
104.	Length to clips	*Measure
105.	Marking	Visual
106.	Clamp tight on cable	Manual

* Measure with suitable scale.

Minor:		
201.	Serialization (see Serialization, section 3, MIL-C-50288(MU)	Visual

4.3 Carton, packing, ammunition, for cable assembly, special purpose electrical, branched: T4140 (see dwg 8846960).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Cable ends and clips wrapped and taped	Visual
102.	Cable tight in carton	Manual
103.	Carton sealed properly	Visual
104.	Carton ends blunted	Visual
105.	Air exhausted from bag	Visual-Manual
106.	Proper heat seal	Visual-Manual
107.	Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for heat seal test in accordance with MIL-P-116	Visual
108.	Materials (see Material, section 3, MIL-C-50288(MU)	Visual
109.	Marking	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.1 Acceptance inspection equipment. Acceptance inspection equipment shall be in accordance with MIL-C-50288(MU) and EL-8838890.

4.4 Test Methods.

4.4.1 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II

Insulation resistance (see dwg 8838890)

Positive potential applied to P4-1 connector pin	Minus potential to all other pins, shells and clips except
F	other connector pin
A	connector shells
D	red clip
C	black clip

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-50288(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-50288(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8846960 and 8808362 and as specified in MIL-C-50288(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs 8846960 and 8808362 and MIL-C-50288(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8846960 and 8808362 and MIL-C-50288(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8846960 and 8808362 and MIL-C-50288(MU).

6. NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-50288(MU).

Custodian:
Army - MU

Preparing Agency
Army - MU

Project No. - 1125-A042

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-C-50288/4(MU) Cable Assembly, T..140

ORGANIZATION

CITY AND STATE	CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*	DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.