MIL-C-62500(AT)
AMENDMENT 2
24 January 1989
SUPERSEDING
AMENDMENT 1
12 December 1986

MILITARY SPECIFICATION

CARRIER, ELECTRONIC WARFARE SYSTEM,
FULL-TRACKED: M1015A1

This amendment forms a part of Military Specification MIL-C-62500(AT), dated 11 September 1985, and is approved for use within the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

3.4.7.1, delete paragraph title and substitute: "Generating system voltage (alternator)."

3.4.7.1, line 3, delete "EW generator governor" and substitute "alternator".

3.4.7.1.1, delete paragraph in its entirety.

3.4.7.1.2, delete paragraph in its entirety.

AMSC N/A FSC 2350

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:44Z
Check the source to verify that this is the current version before use.

PAGE 8

3.4.11.1, line 2 delete "engine-drive" and substitute "engine-driven".

3.4.11.2, line 6, add "transient" between "voltage" and "change".

3.4.11.3, line 5, add "transient" between "frequency" and "change".

3.4.11.4.1d, delete "Low gearbox oil pressure." and substitute "Low speed increaser oil pressure."

3.4.11.4.1e, delete "Low actuator fluid pressure." and substitute "Speed increaser temperature high."

3.4.11.4.2c, delete "800" and substitute "50".

PAGE 9

3.4.11.4.3a, add to end of line: "or lower than 380 Hz."

3.4.11.4.3b, delete "Output frequency less than 380 Hz." and substitute "Generator temperature high."

3.4.11.5.3, line 2, insert "EW system" between "the" and "load".

3.4.11.5.4, line 2, insert "EW system" between "the" and "load".

PAGE 11

3.4.12.3, delete in its entirety and substitute:

"3.4.12.3 Ground rod driver brake. The ground rod driver hoist shall be capable of being locked to prevent accidental dropping of the hammer carriage when the hoist is left unattended (see 4.8.3.11.5)."

3.4.13c, delete "block" and substitute "blocks".

3.4.13e, delete "bracket" and substitute "blocks".

PAGE 12

3.5.5, delete in its entirety and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:44Z
Check the source to verify that this is the current version before use.

"3.5.5 Acceleration. With the vehicle at a standstill, transmission in the 1-3 range and engine at idle speed, the vehicle shall accelerate from 0 to 20 mph in not more than 18 seconds with rated payload or 11 seconds without load on a smooth, level, hard-surfaced road (see 4.8.4.5)."

PAGE 15

3.9, line 4 delete "rod" and substitute "road".

PAGE 16

4.1.2, line 7 delete "MIL-STD-4662" and substitute "MIL-STD-45662".

PAGE 17

4.3.1.2.1, delete in its entirety and substitute:

"4.3.1.2.1 Contractor inspection. The contractor shall subject the vehicle to a road test and the FPVI specified in table III to determine conformance to contract and specifications. The road test shall be specified in 4.5. After inspection, the contractor shall submit the acceptable vehicle (and all inspection records and certifications) to the responsible Government inspection element at contractor's plant for preliminary examination."

PAGE 18

Table III, line 41, delete title and substitute: "Generating system voltage (alternator)".

Table III, delete lines 43 through 46.

PAGE 19

Table III, delete lines 1 through 3.

Table III, line 44, delete title and substitute: "Fault Reset Switch"

PAGE 20

Table III, lines 7 and 8, delete in its entirety

Table III, second column, line 28, delete "3.4.12.5" and substitute "3.4.12.3".

Table III, line 34, delete "operational" and substitute "operation".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:44Z
Check the source to verify that this is the current version before use.

PAGE 28

4.8.3.7.1, delete in its entirety and substitute:

"4.8.3.7.1 Generating system voltage (alternator) test. To determine conformance to 3.4.7.1 with the alternator operating at specified voltage, measurement shall be made with a voltmeter after the described load is removed. Conformance to 3.4.7.1 shall be determined immediately after the road test."

PAGE 32

6.3.3, first line, in title after "voltage" add "and high current". On second line at end of sentence after "voltage" add "and high current".

PAGE 33

Add new paragraph:
"6.10 Subject term (key word) listing.

Electronic Warfare System Carrier: M1015A.
Full Tracked Cattier, Electronic Warfare System.
M1015A1, Carrier, Electronic Warfare System.

Custodian:
Army - AT

Preparing activity:
Army - AT

(Project 2350-A393)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:44Z
Check the source to verify that this is the current version before use.