MIL-C-51361B(EA)
AMENDMENT 1
22 January 1988

MILITARY SPECIFICATION

CANISTER, SMOKE, HC, 105 MM PROJECTILE, M1, COMPONENTS FOR

This amendment forms a part of MIL-C-51361B(EA), dated 20 October 1976, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FEDERAL SPECIFICATIONS: Delete "PPP-B-587 - Box, Wood, Wirebound Pallet Type." and substitute "PPP-B-636 - Boxes, Shipping, Fiberboard."

MILITARY SPECIFICATIONS: Add the following:

"MIL-B-117 - Bags, Sleeves and Tubing - Interior Packaging
MIL-P-3420 - Packaging Materials, Volatile Corrosion Inhibitor Treated, Opaque
MIL-I-8574 - Inhibitors, Corrosion, Volatile, Utilization Of"

PAGE 3

4.1.1: Add the following sentence: "The provisions of MIL-A-2550 apply."

PAGE 7

4.4.3.3: Add the following paragraph:

"(e) Packaging (section 5)

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Packaging materials incorrect
102	Heat-sealed bag improperly closed or damaged
103	Packaging component missing or damaged"

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

PAGE 8

5.1.1: Add the following: "A uniform quantity of empty metal canister body assemblies shall be packed together in an economical and efficient manner which will assure delivery of the canister body assemblies to a first receiving activity in an undamaged condition. Interlocking fiberboard partitions shall be used to separate the canister body assemblies from each other. In addition, full size fiberboard separator pads shall be used, as required, to separate any layers of canister body assemblies. The partitions and separator pads shall be constructed from material conforming to grade V3c of PPP-F-320. The above canister, partitions, and separators (when used) shall then be encased in a protective bag conforming to type I, class B, style 2 of MIL-B-117 and heat sealed closed in accordance with the requirements specified therein. Volatile Corrosion Inhibitor (VCI) paper conforming to MIL-P-3420 shall be included within the protective bag as follows: One full sheet shall be placed at the bottom of the bagged assembly, between the bag and the bottom of the canister assembly. One full sheet shall be placed at the top of the bagged assembly, between the bag and the top of the canister assembly. When items are packaged in multiple tiers or layers, all faces of the separators shall be lined with the VCI-treated material. The bagged items shall be overpacked in a fiberboard box conforming to grade V3c, style FOL of PPP-B-636. The box, bag, and all interior dunnage shall not be larger than required to provide a snug fit when all of the package is assembled. Closure of the fiberboard box shall be in accordance with the requirements of method V of the appendix to PPP-B-636. Proper handling, storage, and general utilization of VCI materials is specified in MIL-I-8574."

5.1.1.1: Delete paragraph in its entirety.

5.1.4: Add the following: "Stacks of closing disks shall be afforded the protection of VCI paper conforming to MIL-P-3420 and shall be utilized in accordance with the requirements of MIL-I-8574. The stacks shall be separated from each other by fiberboard interlocking partitions constructed of material conforming to grade V3c of PPP-F-320. The above closing disks and interlocking partitions shall then be encased in a protective bag conforming to type I, class B, style 2 of MIL-B-117 and heat sealed closed in accordance with the requirements specified herein. The bagged items shall then be overpacked in a fiberboard box conforming to grade V3c, style FOL of PPP-B-636. The box, bag, and all interior dunnage shall not be larger than required to provide a snug fit when all of the package is assembled. Closure of the fiberboard box shall be in accordance with the requirements of method V of the appendix to PPP-B-636. Proper handling, storage, and general utilization of VCI materials is specified in MIL-I-8574."

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1315-A950

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:58Z
Check the source to verify that this is the current version before use.