
INCH-POUND
MIL-C-55302/148B
17 November 1988
SUPERSEDING
MIL-C-55302/148A
18 December 1984


MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES RECEPTACLE WITH PIN CONTACTS, 2 FEMALE KEYING GUIDES, 3.917 INCHES LENGTH, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-55302.






Inches	mm	Inches	mm	Inches	mm
.006	0.15	.071	1.80	.248	6.30
.012	0.31	.100	2.54	.252	6.40
.016	0.41	.122	3.10	.305	7.75
.0229	0.58	.142	3.61	.317	8.05
.024	0.61	.153	3.89	3.600	91.44
.0244	0.620	.189	4.80	3.917	99.49
.050	1.27	.200	5.08		


NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only
3. Unless otherwise specified all tolerances are ±.005 (0 13 mm)
4. Standoffs are located between each cable hole and between each hole and contact hole set

FIGURE 1 Connector, plug (100 inch spacing)

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:53Z
Check the source to verify that this is the current version before use.






Inches	mm
.030	0.76
.050	1.27
.060	1 52
.070	1.78
.100	2.54
.106	2.69
.118	3.00
.200	5.08
.240	6.10
.320	8.13
3.60	91.4


NOTES.
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3 Unless otherwise specified, tolerance is ±.005 (0.13 mm).

FIGURE 2. Recommended hole patterns.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.




Flexible cables subpart "A"




Semirigid cables subpart "B"




90° Flexible cables subpart "C"




90° Semirigid cables subpart "D"



90° PCB mounting subpart "E"




Vertical mounting PCB subpart "F"




Solder posts twisted braid subpart "G"

FIGURE 3. Coaxial configurations.


Source: https://assist.dla.mil -- Downloaded: 202610-22T22:53Z
Check the source to verify that this is the current version before use.



Solder bucket subpart H



90° PCB mounting subpart J



Vertical mounting PCB subpart K

Inches	mm	Inches	mm
.020	0.51	.138	3.51
.03	0.8	.139	3.53
.063	1.60	.155	3.94
.071	1.80	.157	3.99
.079	2.01	.158	4.01
.094	2.39	.177	4.50
.095	2.41	.185	4.70
.100	2.54	.271	6.88
.110	2.79	.303	7.70
.122	3.10	.317	8.05
.126	3.20	.374	9.50

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± 005 (0.13 mm).

FIGURE 3. Coaxial configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.





FIGURE 4. Contact and keying arrangements.


Source: https://assist.dla.mil -- Downloaded: 202610-22T22:53Z
Check the source to verify that this is the current version before use.




NOTES.
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).
4. Contact accepts no. 22 AWG wire.
5. Contact, crimp type, accepts no 22-26 AWG wires.
6. Contact with .025 inch (0.64 mm) wrappost in accordance with MIL-STD-1130.

FIGURE 5. Connector terminations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.



FIXED MOUNT



FLOATING MOUNT

Inches	mm	Inches	mm
.004	0.10	.374	9.50
.008	0.20	1.711	43.46
.116	2.95	1.800	45.72
.187	4.75	3.422	86.92
.197	5.00	3.600	91.44

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Floating mount panel thickness .085 (2.16 mm) maximum

FIGURE 6. Recommended panel cutouts

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:53Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration See figures 1 through 6.

Contact identification: See figure 4

Contact retention. Coaxial and power: 11.25 pounds minimum.
Signal: 4 pounds minimum.

Mating and unmating force (per contact):

	Coaxial	Power	Signal
(Min)	7.2 ounces	3.6 ounces	0.7 ounce
(Max)	36 ounces	18 ounces	3.6 ounces

Values for each connector to be addition of contacts according to contact type.

Contact resistance: 12 milliohms maximum.

Dielectric withstanding voltage:

Sea level: 1,000 V rms, 60 Hz.

High altitude: 300 V rms, 60 Hz.

Current rating:

Power contacts: 25 amperes at 25°C.

Coaxial contacts: .5 ampere at 25°C.

Signal contacts: 3 amperes at 25°C.

Keying: Moldings and mounting hardware provide 16 or 36 polarizing positions according to choice of 4 or 6 way capability. Keys are constructed in accordance with MIL-C-55302/154. Connectors are supplied keyed in "1" and "A" positions, except for 1/4-turn which are keyed "F" and "6". When required connectors can be easily keyed to desired position by using a simple wrench.

Removal tools: Coaxial and power contacts: M81969/41-01.
Signal contacts. M81969/40-01.

Hood types: See MIL-C-55302/155.

Mounting hardware: See MIL-C-55302/154.

Mating connectors: Shall conform to MIL-C-55302/153.

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:53Z
Check the source to verify that this is the current version before use.

Part number: Consists of the letter M, the basic number of the specification sheet, and a dash number compiled as follows:

Example:

M55302/148	*	*	*	2	*

Specification sheet number
Receptacle with pin contacts

Contact arrangement
(see figure 3)

Contact terminations - 3 amperes
(see figure 4)
0 - not applicable

Contact configurations - coaxial/power (see figure 3)
X - less coaxial and power contact

Indexing type
2 - square post (16 positions)
1 - hex post (36 positions)

Mounting hardware
(See MIL-C-55302/154)

NOTE: Revision letters are not used to denote changes due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 17

Review activities:
Army - AR, AT, AV, MI
Navy - AS, OS, SH
Air Force - 11, 85, 99
DLA - ES

User activities:
Army - ME
Navy - MC
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3652-09)

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:53Z
Check the source to verify that this is the current version before use.