MIL-L-62548(AT)
24 November 1987
SUPERSEDING
(see 6.5)

MILITARY SPECIFICATION

LEAD, IGNITION

This specification is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an ignition lead that transmits high energy and high tension voltage from an ignition exciter to an igniter plug with energy to Ignite and start a gas turbine engine.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 2920
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS
FEDERAL

P-C-437	- Cleaning Compound, High Pressure (Steam Cleaner.)
VV-F-800	- Fuel Oil, Diesel.

MILITARY

MIL-G-3056	- Gasoline, Automotive, Combat.
MIL-T-5624	- Turbine Fuel, Aviation, Grades JP-4 and JP-5.
MIL-H-6083	- Hydraulic Fluid, Petroleum Base, for Preservation and Operation.
MIL-L-7808	- Lubricating Oil, Aircraft Turbine Engine, Synthetic Base.
MIL-F-16884	- Fuel Oil, Naval Distillate.
MIL-L-23699	- Lubricating Oil, Aircraft Turbine Engine, Synthetic Base.

STANDARDS
MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-454	- Standard General Requirements for Electronic Equipment.
MIL-STD-461	- Electromagnetic Interference Characteristics, Requirements for Equipment.
MIL-STD-462	– Electromagnetic, Interference Characteristics, Measurement of.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-45662	- Calibration Systems Requirements.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS
ARMY

12286829	- Lead, Ignition.

OTHER
PUBLICATIONS

DEOS 1505	- Nuclear Hardening Criteria.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. Unless otherwise specified (see 6.2), the contractor shall furnish ignition lead(s) which shall be subjected to first article inspection (see 4.4). First article inspection samples, properly marked with identifying information shall be representative of the unit to be furnished to the Government. All subsequent ignition leads delivered to the Government shall conform to these samples in all their pertinent physical and performance attributes.

3.2 Materials. Materials shall be as specified herein and in referenced specifications, standards and drawings. External surfaces shall be corrosion resistant. Material shall be free from defects which adversely affect performance or serviceability of the finished product (see 4.7.1).

3.2.1 Recycled, virgin and reclaimed materials. There are no requirements for the exclusive use of virgin materials. The use of recycled or reclaimed (recovered) materials is acceptable provided that all other requirements of this specification are met (see 4.7.1 and 6.3.1).

3.3 Design and construction. The ignition lead, input and output terminations shall conform to Drawing 12286829 (see 4.7.1 and 4.7.2).

3.3.1 Wire. The ignition lead wire shall be number 16 American Wire Gage (AWG) minimum (see 4.7.1).

3.3.2 Nuclear control. The ignition lead shall have optimum protection against electromagnetic impulse (EMP) and transient radiation effects (TREE). There shall be at least two layers of copperweld shielding or equivalent shielding material (see 4.7.1).

3.4 Performance.

3.4.1 Insulation resistance. The ignition lead insulation resistance between conductor and cable shield shall be 100 megohms minimum at 500 volts (V) direct current (de) (see 4.7.3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

3.4.1.1 Maximum voltage. The ignition lead insulation shall show no evidence of breakdown with the application of 20 kilovolts (kv) root mean square (rms) voltage between the conductor and cable shield for 5 to 10 seconds duration (see 4.7.3.2).

3.4.2 Environmental operation.

3.4.2.1 Accelerated aging. The ignition lead shall meet the requirements of 3.4.1 and 3.4.1.1 when exposed to an accelerated aging temperature of 392 degrees Fahrenheit (°F) [200 degrees Celsius (°C)] (see 4.7.4.1).

3.4.2.2 High temperature. The ignition lead shall meet the requirements of 3.4.1 and 3.4.1.1 when exposed to a temperature of 212°F (100°C) for 100 hours (see 4.7.4.2).

3.4.2.3 Room temperature. The ignition lead shall meet the requirements of 3.4.1 and 3.4.1.1 when exposed to a room temperature of 77°F (25°C) for 8 hours (see 4.7.4.3).

3.4.2.4 Low temperature. The ignition lead shall meet the requirements of 3.4.1 and 3.4.1.1 when exposed to a temperature of -65°F (-54°C) for a period of 30 hours (see 4.7.4.4).

3.4.2.5 Operational altitude range. The operational altitude range of the ignition lead shall be 1300 feet below sea level to 10,000 feet above sea level (see 4.7.4.5).

3.4.2.6 Humidity. The ignition lead shall be operative when exposed to relative humidity of zero to 100 percent (%) (see 4.7.4.6).

3.4.2.7 Salt fog. The ignition lead shall be operative when exposed to salt laden atmosphere of 5% by weight of sodium chloride (Nacl) in 95% distilled water by weight (see 4.7.4.7).

3.4.2.8 Sand and dust. The ignition lead shall be operative when exposed to sand and dust conforming to MIL-STD-810 (see 4.7.4.8).

3.4.2.9 Fungus. The ignition lead shall be operative when exposed to conditions favorable to fungus growth in conformance with MIL-STD-810 (see 4.7.4.9).

3.4.2.10 Chemical. The ignition lead shall be operative when exposed to the following materials in operating, nonoperating and transit conditions (see 4.7.4.10).

a. Fuel vapors per VV-F-800, MIL-G-3056, MIL-T-5624 and MIL-F-16884.
b. Hydraulic fluid per MIL-H-6083.
c. Cleaning fluids per P-C-437.
d. Lubricating oil per MIL-L-7808 and MIL-L-23699.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

3.4.2.11 Vibration. The ignition lead shall be operative when exposed to vibration levels up to 5 gravity units (g), from 5 to 2000 Hertz (Hz) (see 4.7.4.11).

3.4.2.12 Shock.

3.4.2.12.1 Gun firing shock. The ignition lead shall be capable of sustaining shock impulses of 100 ± 10 g intensity, 1.5 ± 2 ms duration in any direction without malfunction (see 4.7.4.12.1).

3.4.2.12.2 Ballistic shock. The ignition lead shall be capable of sustaining impact shock waves generated by threat application of 200 ± 20 g half-sine wave shock pulses in any direction without malfunction (see 4.7.4,12.2).

3.4.2.12.3 Basic shock. The ignition lead shall be capable of sustaining half-sine wave shock pulses of 40 g intensity, 18 milliseconds (ins) duration in any direction without malfunction (see 4.7.4.12.3).

3.4.2.13 Submergence. The ignition lead shall perform after a submergence in 6 feet of water for a period of 30 minutes (see 4.7.4.13).

3.5 Electromagnetic interference (EMI). The ignition lead shall meet the requirements of MIL-STD-461 on a component level as part of the engine electronic control system (see 4.7.5).

3.6 Nuclear hardening. The ignition lead shall withstand nuclear threat environment as defined in "Nuclear Hardening Criteria", document control number DEOS 1505 (see 4.7.6).

3.7 Identification and marking. The ignition lead shall be marked for identification in accordance with MIL-STD-130 and as noted on Drawing 12286829 (see 4.7.2).

3.8 Workmanship. Workmanship shall be in accordance with MIL-STD-454, requirement 9 (see 4.7.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform or witness any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items q ust meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Inspection equipment. Unless otherwise specified in the contract (see 6.2), the contractor is responsible for the provision and maintenance of all inspection equipment necessary to assure that supplies and services conform to contract requirements. Inspection equipment must be capable of repetitive measurements to an accuracy of 10 percent of the measurement tolerance. Calibration of inspection equipment shall be in accordance with MIL-STD-45662.

4.2 Classification of inspection:

a. First article inspection (see 4.4).
b. Quality conformance inspections (see 4.5).
    1. Examination (see 4.5.2).
    2. Acceptance tests (see 4.5.3).

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all tests required by this specification shall be made at an atmospheric pressure of approximately 30 inches of mercury and at a temperature of 70 to 80°F (21 to 27°C) and a relative humidity of 90% or less.

4.3.1 Test tolerances. Unless otherwise specified, test conditions, as indicated by instrumentation, shall not deviate from the conditions specified herein by more than the following:

a. Temperature - Under plus 100°F (38°C) plus or minus 4°F (2.2°C).
    - Over plus 100°F (38°C) plus or minus 4%.

b. Pressure - Plus or minus 5%.

c. Humidity - Plus or minus 5% relative.

d. Vibration amplitude:

    (1) Random - Plus or minus 3 decibels at resonance and plus or minus 1 decibel elsewhere.

    (2) Sinusoidal - Plus or minus 2%.

e. Vibration frequency - Plus or minus 2%.

f. Shock - Plus or minus 5%.

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:47Z
Check the source to verify that this is the current version before use.

g. Acceleration - Plus or minus 5%.

h. Voltage, current and time:

(1) Value specified as a whole number ± 0.5.

(2) Value specified to 1 decimal place ± 0.05.

(3) Value specified to 2 decimal places ± 0.005.

4.4 First article inspection. Unless otherwise specified (see 6.2), the Government shall select 3 ignition leads produced under the production contract for first article inspection. First article samples shall be inspected at specified in table I. Approval of the first article sample by the Government shall not relieve the contractor of his obligation to supply ignition leads that are fully representative of those inspected as a first article sample. Any changes or deviation of the production units from the first article sample shall be subject to the approval of the contracting officer.

4.4.1 First article inspection failure. Deficiencies found during, or as a result of, first article inspection shall be cause for rejection of the first article sample until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiency. Any deficiency found during, or as a result of, first article inspection, shall be evidence that all items already produced prior to completion of the first article inspection are similarly deficient unless contrary evidence satisfactory to the contracting officer is furnished by the contractor. Such deficiencies on all items shall be corrected by the contractor. The Government will not accept products until first article inspection is completed to the satisfaction of the Government.

4.5 Quality conformance inspections.

4.5.1 Sampling.

4.5.1.1 Lot formation. An inspection lot shall consist of all the ignition leads of one type and part number, from an identifiable production period, from one manufacturer, submitted at one time for acceptance.

4.5.1.2 Sampling for examination. Samples for quality conformance examination shall be selected in accordance with general inspection level II of MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of inspections.

Title	Requirement	Inspection	First article	Quality conformance	
				Examination	Tests
Materials and construction	3.2 thru 3.3.2	4.7.1	X		
Defects (see 4.5.2 and and table II)	3.3, 3.3.2, 3.7 and 3.8	4.7.2	X		
Insulation resistance	3.4.1	4.7.3.1	X		X
Maximum voltage	3.4.1.1	4.7.3.2	X		X
Accelerated aging	3.4.2.1	4.7.4.1	X		
High temperature	3.4.2.2	4.7.4.2	X		
Room temperature	3.4.2.3	4.7.4.3	X		
Low temperature	3.4.2.4	4.7.4.4	X		
Altitude range	3.4.2.5	4.7.4.5	X		
Humidity	3.4.2.6	4.7.4.6	X		
Salt fog	3.4.2.7	4.7.4.7	X		
Sand and dust	3.4.2.8	4.7.4.8	X		
Fungus	3.4.2.9	4.7.4.9	X		
Chemical	3.4.2.10	4.7.4.10	X		
Vibration	3.4.2.11	4.7.4.11	X		
Gun firing shock	3.4.2.12.1	4.7.4.12.1	X		
Ballistic shock	3.4.2.12.2	4.7.4.12.2	X		
Basic shock	3.4.2.12.3	4.7.4.12.3	X		
Submergence	3.4.2.13	4.7.4.13	X		
Electromagnetic interference	3.5	4.7.5	X		
Nuclear hardening	3.6	4.7.6	X		

4.5.2 Examination.

4.5.2.1 Acceptable quality level. Each sample selected in accordance with 4.5.1.2 shall be examined to determine conformance to the following acceptable quality levels (AQL) on the basis of percent defective:

Classification	AQL
Major	1.0
Minor	2.5

4.5.2.2 Classification of defects. For examination purposes, defects shall be classified as listed in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects.

Category	Defect	Method of examination
Critical	None	
Major	AQL 1.0% Defective	
101	Incomplete assembly (see 3.3).	SIE 1/
102	Dimensions affecting interchangeability, out of tolerance (see 3.3).	SIE
103	Faulty workmanship affecting performance (see 3.8).	Visual
Minor	AQL 2.5% Defective	
201	Dimensions not affecting interchangeability, out of tolerance (see 3.3).	SIE
202	Improper marking (see 3.7).	Visual
203	Faulty workmanship, affecting appearance (see 3.8).	Visual

1/ SIE = Standard Inspection Equipment.

4.5.3 Acceptance test. Each ignition lead shall be subjected to the acceptance tests specified in table I.

4.5.3.1 Failure. Failure of any ignition lead to pass any of the acceptance tests shall be cause for rejection of the failed item unless authorization is obtained from the Government to repair the failed item. All repaired items shall be subjected to the acceptance tests specified in table I.

4.6 Failure. Failure of any ignition lead to pass any of the specified quality conformance or control tests shall be cause for the Government to refuse acceptance of the production quantity represented, until action taken by the contractor to correct defects and prevent recurrence has been approved by the Government.

4.7 Methods of inspection.

4.7.1 Materials and construction. Conformance to 3.2 through 3.3.2 shall be determined by inspection of contractor records providing proof or certification that design, construction, processing, and materials conform to requirements, Applicable records shall include drawings, specifications, design data, receiving inspection records, processing and quality control standards, vendor catalogs and certifications, industry standards, test reports, and rating data.

4.7.2 Defects. Conformance to 3.3, 3.7 and 3.8 shall be determined by examination for the defects listed in table II. Examination shall be visual, tactile, or by measurement with standard inspection equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

4.7.3 Performance tests.

4.7.3.1 Insulation resistance test. To determine conformance to 3.4.1 measure the insulation resistance between conductor and cable shield using an applied potential of 490 to 510 V dc.

4.7.3.2 Maximum voltage test. To determine conformance to 3.4.1.1 a voltage of 20 kv rms shall be applied between conductor and cable shield for 5 to 10 seconds.

4.7.4 Environmental tests.

4.7.4.1 Accelerated aging test. To determine conformance to 3.4.2.1, the ignition lead shall be placed dry, in an air oven and maintained at a maximum operating ambient temperature of 392°F (200°C) for a minimum period of 168 hours. During and upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.2 High temperature test. To determine conformance to 3.4.2.2, following test 4.7.4.2, ignition lead shall be subjected to high a temperature of 212°F (100°C) for a period of 100 hours. Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.3 Room temperature test. To determine conformance to 3.4.2.3, following test 4.7.4.2, ignition lead shall be subjected to room a temperature of 77°F (25°C) for a period of 8 hours. Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.4 Low temperature test. To determine conformance to 3.4.2.4, following test 4.7.4.3, ignition lead shall be subjected to low temperature of -65°F (-54°C) for a period of 30 hours. Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.5 Altitude range test. To determine conformance to 3.4.2.5, ignition lead shall be subjected to a maximum atmospheric pressure of 31.19 inches of mercury (1300 feet below sea level) and a minimum atmospheric pressure of 20.01 inches of mercury (10,000 feet above sea level). During and upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.6 Humidity test. To determine conformance to 3.4.2.6, the ignition lead shall be subjected to an atmosphere of clear water vapor for a period of 15 days under the conditions and cycle specified in table III. Immediately after 12 hours of the first test cycle, check the ignition lead for proper operation with the maximum specified voltage. During the last cycle of the 15 day test, operate the ignition lead throughout its entire range of operation under each of the ambient conditions specified. At the end of the 15 days of test, dry the ignition lead without forced convection for 12 hours in air at less than 69.8°F (21°C) with not less than 50% relative humidity. After this, disassemble and inspect the ignition lead. There shall be no corrosion or other defects present that affect the function or structural strength of the assembly. Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

TABLE III. Humidity conditions test cycle.

Time period (hours)	Relative humidity (percent)	Ambient temperature
8	95 ± 5	129 ± 5.4°F (54 ± 3°C)
4	Holding chamber moisture content constant	129 ± 5.4°F (54 ± 3°C) gradually down to 70 ± 5.4°F (21 ± 3°C)
8	Holding chamber moisture content constant	70 ± 5.4°F (21 ± 3°C)
4	Up to 95 ± 5, holding chamber moisture content or adding vapor to reach required value	70 ± 5.4°F (21 ± 3°C) uniformly up to 129 ± 5.4°F (54 ± 3°C)

4.7.4.7 Salt spray test. To determine conformance to 3.4.2.7, ignition lead shall be exposed to salt fog for a minimum of 48 hours. The fog solution s-nail be 5 percent NaCL by weight in 95 percent distilled water by weight. The temperature shall be maintained between 90 and 95°F (32 and 35°C). Fog density shall be 3 quarts of solution per 10 cubic feet of chamber volume per 24 hours, Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.8 Sand and dust test. To determine conformance to 3.4.2.8, the ignition lead shall be subjected to the sand and dust test in accordance with MIL-STD-810, method 510. The ignition lead need not be operated during the test; however, at the conclusion of the test and prior to any cleaning of the ignition lead, repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.9 Fungus test. To determine conformance to 3.4.2.9, ignition lead shall be Inoculated with a spore suspension and tested in accordance with MIL-STD-810, method 508. Temperature shall range from 80 to 84°F and the relative humidity from 96 to 100 percent for a period of 28 days. Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.10 Chemical test. To determine conformance to 3.4.2.10, ignition lead shall be exposed to fluids and vapors of materials listed in 3.4.2.8. Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.11 Vibration test. To determine conformance to 3.4.2.11, ignition lead shall be subjected to vibrations when normally mounted (with vibration isolators in place) and powered. The vibrations shall be of 5 g magnitude in each direction along 3 mutually perpendicular axes at a logarithmic sweep

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

rate. The vibration cycle time shall he equivalent to 20 minutes per axis from 5 to 2000 to 5 Hz with each 20 minute test period representing 1000 miles of vehicle operation. Conduct a resonance sweep to identify up to four of the most severe resonances and then accomplish resonance dwells for one-sixth of the total cycling vibration time at each resonance at the specified levels. Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.12 Shock.

4.7.4.12.1 Gun firing shock test. To determine conformance to 3.4.2.12.1, the ignition lead while mounted normally (with vibration isolators in place, if any) and powered shall be subjected to 3 shocks of 100 ± 10 g, 1.5 ± 0.2 ms along each of 3 mutually perpendicular axes (18 shocks). Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.12.2 Ballistic impact shock test. To determine conformance to 3.4.2.12.2, the ignition lead while mounted normally (with vibration isolators in place, if any) and powered shall be subjected to 3 shock waves of 200 ± 20 g half sine shock pulses along each of 3 mutually perpendicular axes (18 shocks). Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.12.3 Basic shock test. To determine conformance to 3.4.2.12.3, the ignition lead while mounted normally (with vibration isolators in place, if any) and powered shall be subjected to 3 half sine wave shock pulses of 40 g, 18 ms along each of 3 mutually perpendicular axes (18 shocks). Upon completion of test repeat tests 4.7.3.1 and 4.7.3.2.

4.7.4.13 Submergence test. To determine conformance to 3.4.2.13, ignition lead shall be tested in association with a fording test of a vehicle. The ignition lead when installed on an engine shall be utilized in the starting system. It shall be capable of meeting all performance requirements after submergence in 6 feet of water for 30 minutes.

4.7.5 Electromagnetic interference. To determine conformance to 3.5, the ignition lead shall be tested in accordance with MIL-STD-462.

4.7.6 Nuclear hardening. Verification that the ignition lead meets nuclear environment specified in 3.6 shall be determined by the acquisition activity on the basis of circuit analysis and laboratory testing or through nuclear test of a complete vehicle.

5. PACKAGING

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking for the desired level of protection shall be in accordance with the applicable packaging requirements specified by the contracting authority (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The ignition lead covered by this specification is intended to provide electrical continuity between the ignition exciter and spark igniter on the AGT 1500 gas turbine engine in the Ml (Abrams) military tank.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. If first article inspection is not required (see 3.1).
c. If responsibility for inspection shall be other than as specified (see 4.1).
d. If responsibility for inspection equipment shall be other than as specified (see 4.1.2).
e. If inspection conditions shall be other than as specified (see 4.3).
f. If first article sample size shall be other than as specified (see 4.5).
g. Selection of applicable level of protection and packaging requirements (see 5.1).

6.3 Definitions.

6.3.1 Recovered materials. "Recovered materials" means materials that have been collected or recovered from solid waste (see 6.3.2).

6.3.2 Solid waste. "Solid waste" means (a) any garbage, refuse, or sludge from a waste treatment plant, water supply treatment plant, or air pollution control facility; and (b) other discarded material, including solid, liquid, semisolid, or contained gaseous material resulting from industrial, commercial, mining, and agricultural operations, and from community activities. It does not include solid or dissolved material in domestic sewage, or solid or dissolved material in irrigation return flows or industrial discharges which are point sources subject to permits under section 402 of the Clean Water Act, (33 U.S.C. 1342 et seq.), or source, special nuclear, or byproduct material as defined by the Atomic Energy Act of 1954 (42 U.S.C. 2011 et seq.) (Source: Federal Acquisition Regulations, section 23.402).

6.4 Subject term (key word) listing.

Ignition, lead

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:47Z
Check the source to verify that this is the current version before use.

6.5 Supersession data. This specification supersedes AVCO Lycoming Division specification number E2107B, dated 26 April 1982 and ERR No. AVC-K7656, dated 21 July 1983.

Custodian:
Army - AT

Preparing activity:
Army - AT

(Project 2920-A008)

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:47Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Tank-Automotive Command
ATTN: AMSTA_GDS
Warren, MI 48397-5000

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5 PROBLEM AREAS

a Paragraph Number and Wording

b Recommended Wording

c Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:47Z
Check the source to verify that this is the current version before use.