MILITARY SPECIFICATION

STRAP ASSEMBLY

1. SCOPE

1.1 This specification covers requirements, quality assurance provisons, and the preparation for delivery criteria for one type of strap assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8851635 - Strap Assembly
8851636 - Strap
8851637 - Strap Tip
8852753 - Strap
8883534 - Bag, Packing for Repair Parts

FSC 1125

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The strap assembly shall comply with all requirements specified on the drawing(dwg) 8851635, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Strap (see dwg 8825753) and strap (see dwg 8851636) covering a detail of dwg 8851635.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Total length	*Measure
	102. Location of holes	*Measure
	103. Diameter of holes	*Measure
	104. Width	*Measure
	105. Material (see 3.1)	Visual

*Measure with suitable scale.

Minor:		
	201. Workmanship (see 3.3.)	Visual-Manual

4.3.2.1.2 Strap Assembly (see dwg 8851635)

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Objective evidence (see 6.2) for strap tip in accordance with dwg 8851637	Visual
	102. Tip properly assembled	Visual-Manual
Minor:		
	201. Workmanship (see 3.3)	Visual-Manual

4.3.2.1.3 Bag, packing for repair parts (see dwg 8883534 covering dwg part number 8883534-2 and section 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Material (see 3.1)	Visual
	102. Length before packing, min	*Measure
	103. Width before packing, min	*Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

104. Properly packed.....Visual-Manual
105. Proper heat seal.....Visual-Manual
106. Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116.....Visual
107. No tear, split, or hole in bag.....Visual

*Measure with suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.3).....Visual-Manual

4.3.2.1.4 Packing and marking for storage and shipments (see dwg 8808362 and section 5).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Gross load weight, max.....*Measure
102. Contents tight in package.....Manual
103. Correctly packed.....Visual-Manual
104. Material (see 3.1).....Visual

*Determine weight with suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.3).....Visual-Manual

4.3.3 Testing. Not applicable.
4.3.4 Acceptance inspection equipment. Not applicable.
4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).
5.1.1 Level A. The strap assembly shall be packaged in accordance with dwgs 8883534 and 8808362 using the specified moisture barrier.
5.1.2 Level C. The strap assembly shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.
5.2 Packing.
5.2.1 Level A and C. The strap assembly shall be packed in accordance with dwgs 8883534 and 8808362
5.3 Marking. Marking shall be as specified in accordance with dwgs 8883534 and 8808362 as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

Custodian:
Army - MU

Preparing activity:
Army-MU

Project No. 1125-A138

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-S-48015(MU) Strap Assembly

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.