# MILITARY SPECIFICATION

## TELESCOPE M83F

## 1. SCOPE

1.1 This specification covers a series of telescopes used as variable power telescopes in tanks for direct fire. The individual telescopes have a letter affixed to the model number to identify the type reticle employed.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitations for bids or requests for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-O-13830 | Optical Components of Fire Control Instruments; General Specification Governing the Manufacture, Assembly, and Inspection of |
| MIL-F-13926 | Fire Control Materiel: General Specification Governing the Manufacture and Inspection of |
| MIL-P-14232 | Parts, Equipment and Tools for Ordnance Materiel, Packaging of |
| MIL-I-45607 | Inspection Equipment, Supply and Maintenance of |

STANDARDS

Military

| | |
|---|---|
| MIL- STD-105 | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-109 | Quality Assurance Terms and Definitions |

DRAWINGS

U.S. Army, Frankford Arsenal

| | |
|---|---|
| F7597771 | Telescope M83F |
| F8565556 | Pressure Tester, Two-Station |
| A11738188 | Test Equipment for Telescope M83F |

PACKAGING DATA SHEETS

| | |
|---|---|
| 7597773 | Packaging of Telescope M83F |

(Copies of specifications, standards, drawings, and packaging data sheets required by supplier in connection with special procurement functions should

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

be obtained from the procuring activity or as directed by the contracting officer).

## 3. REQUIREMENTS

3.1 Fabrication.- The telescope shall be manufactured in accordance with Drawing F7597771 and drawings pertaining thereto.

3.2. General Specification.- The contractor shall be responsible for compliance with the following requirements of MIL-F-13926:

a. Order of precedence
b. Dimensions and tolerances
c. Inorganic protective surface finish
d. Part identification and marking
e. workmanship

3.3 Environmental.

3.3.1 Storage temperature.- The telescope shall show no evidence of physical failure such as glass breakage, bonding failure or casting failure due to storage at temperatures of -80° F and +160°F.

3.3.2 Extreme Operating Temperature.- The telescope shall meet the applicable requirements of 3.10 while exposed to and thermally stabilized at -40°F and +150°F.

3.3.3 Vibration.- The telescope shall show no evidence of physical failure due to being vibrated successively along three (3) mutually perpendicular axes. Vibration shall be a simple harmonic motion, the frequency varying either linearly or logarithmically from 5 to 55 to 5 cps in five (5) minute cycles for a total of fifteen (15) minutes along each of the axes. The amplitude of vibration shall be maintained constant at 1/64 inch (1/32 inch total excursion). Following the vibration test the telescope shall meet all subsequent requirements.

3.4 Cleanliness.- Subsequent to vibration, there shall be no more than two (2) particles of dirt visible on the reticle. The area of each particle shall not be in excess of the area equivalent to a size ten (10) Dig. (See MIL-I-13830). There shall be no other dirt within the telescope field of view which interferes with observation.

3.5 Sealing.- The telescope shall show no evidence of leakage when subjected to an external pressure of 5 ± 0.10 pounds per square inch gage pressure (psig) for a minimum period of five (5) minutes.

3.6 Optical.

3.6.1 Collimation.- The optical axis shall coincide with the geometric axis of the telescope within a radial distance of 0.25 mil as established with the spherical bearing surfaces of the mounting collars in a fixed position, and with the locating pin vertically downward.

3.6.2 Parallelism of Reticle and Image.- With the instrument locating pin in a vertical downward position, the 400 yard horizontal reticle line shall be parallel to the image of a horizontal target line within one (1) degree.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

3.6.3 Reticle Accuracy.- The angular value between the zero range cross and the maximum range mark in the finished telescope shall be as specified on the applicable reticle drawing within one percent of the elevation in mils.

3.6.4 Illumination.- When illuminated by instrument light M33 or equivalent, the reticle markings shall be clearly defined when observed in a darkened area.

3.6.5 Magnification.- The minimum magnifying power shall lie between 3.8 and 4.2 and the maximum magnifying power shall lie between 7.6 and 8.5.

3.7 Eyepiece focus.

3.7.1 Diopter adjustment.- The diopter adjustment shall provide sufficient movement within the limits of its stops to accommodate a range of plus and minus 2.0 diopters from a zero diopter setting, as read with a dioptometer.

3.7.2 Change in diopter setting.- The diopter setting shall not vary by more than plus or minus 0.25 diopter when magnification power is changed from minimum to maximum, using the minimum power position as a reference point.

3.8 Resolution.- The resolution on the optical axis shall be seven (7) seconds of arc or less at one focus setting with the telescope adjusted for minimum magnification.

3.9 Parallax.- At maximum magnification, parallax at the boresight point on the reticle shall not exceed 0.1 mil, viewing a target at 420 yards, plus or minus 20 yards to infinity.

3.10 Operability.

3.10.1 Magnification adjustment.- The running torque required to rotate the magnification change ring from any position shall be between 20 and 40 inch-pounds at standard ambient temperature (60° to 90°F) and shall not exceed the value obtained at standard ambient temperature by more than 15 inch-pounds when subjected to extreme temperatures of 3.3.2.

3.10.2 Diopter movement.- The running torque required to rotate the diopter adjustment ring from any position shall be between 30 and 50 inch-pounds at standard ambient temperature (60° to 90°F) and shall not exceed the value obtained at standard ambient temperature by more than 20 inch-pounds when subjected to extreme temperatures of 3.3.2.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibliity for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein,



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

unless disapproved by the Government. The Government reserve the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) telescopes plus three (3) each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.3 Inspection provisions.

4.3.1 Submission of product.- Unless otherwise specified by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and tests.

4.3.2.1 Components and subassemblies.- All components and subassemblies shall be inspected in accordance with the inspection provisions contained in Supplementary Quality Assurance Provisions (SQAP listed in the technical data package (TDP)). In the absence of SQAP's, the applicable Quality Assurance Provisions of MIL-F-13926 shall apply. Examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Tables I, II and III herein. Examination and tests for packaging, packing, and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Table I, II and III shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

TABLE I - CLASSIFICATION OF DEFECTS

| CLASS<br>CRITICAL: NONE<br>MAJOR: AQL 0.65% Defective | REQUIREMENT | TEST PROCEDURE |
|---|---|---|
| 101. Vibration | 3.3.3 | 4.6.3 |
| 102. Cleanliness | 3.4 | 4.6.4 |
| 103. Sealing | 3.5 | 4.6.5 |
| 104. Collimation | 3.6.1 | 4.6.6.1.1 |
| 105. Parallelism of reticle and image | 3.6.2 | 4.6.6.1.2 |
| 106. Reticle accuracy | 3.6.3 | 4.6.6.1.3 |
| 107. Magnification | 3.6.5 | 4.6.6.1.4 |
| 108. Diopter Adjustment | 3.7.1 | 4.6.6.1.5 |
| 109. Change in Diopter Setting | 3.7.2 | 4.6.6.1.6 |
| 110. Parallax | 3.9 | 4.6.6.1.7 |
| 111. Resolution | 3.8 | 4.6.7 |
| 112. Operability, Magnification Adjustment | 3.10.1 | 4.6.8 |
| 113. Operability, Diopter Movement | 3.10.2 | 4.6.9 |
| 114. Illumination | 3.6.4 | 4.6.10 |
| MINOR: NONE | | |

NOTE: The tests in Table I shall be conducted at a temperature between 60° and 90°F.

4.3.3 Acceptance and rejection.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special sampling.

4.4.1 General.- One telescope shall be selected at random as a special sampling from each 100 produced. The sample shall meet the requirements and tests in Table II.

TABLE II

| CHARACTERISTIC | REQUIREMENT | TEST PROCEDURES |
|---|---|---|
| 301. Fabrication | 3.1 | Applicable drawing - visual |
| 302. General specification | 3.2 | MIL-F-13926 - visual |

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

NOTE: The tests in Table II shall be conducted at a temperature between 60° and 90°F.

4.4.2 Environmental.- Three telescopes shall be selected at random as samples from each 50 produced, or from each months production, whichever occurs first. Each sample shall meet the requirements and tests in Table III and shall then meet the requirements and tests in Table I.

TABLE III

| NO. | CHARACTERISTIC | REQUIREMENT | TEST PROCEDURES |
|---|---|---|---|
| 303. | Storage temperatures (-80° to +160°F) | 3.3.1 | 4.6.1 |
| 304. | Operability, magnification adjustment | 3.10.1 | 4.6.2, 4.6.8 |
| 305. | Operability, diopter movement | 3.10.2 | 4.6.2, 4.6.9 |

NOTE: The tests for Characteristics 304 and 305 shall be conducted at -40° and +150°F.

4.4.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot shall be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted items have been approved (see 4.3.3).

4.5 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design.- All inspection equipment specified by drawing number in specifications or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data included in the technical data package list.

4.5.2.2 Contractor design.- The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.5.2.3 Inspection equipment design requirements.

4.5.2.3.1 Sealing.- Special testing equipment to test sealing of the telescope shall conform to the external pressure test requirements of Drawing F8565556, Pressure Tester-Two Station.

4.5.2.3.2 Performance.- Special test equipment to determine performance of the telescope shall be in conformance with the drawings specified on Drawing A11738188 which form a part of the test equipment.

4.6 Test methods and procedures.

4.6.1 Storage temperature.- The testing equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.3.1. The telescope shall be exposed to each temperature extreme specified in 3.3.1 for a minimum of 5 hours. After each temperature exposure the telescope shall be stabilized in an ambient temperature between +60° and +90° Fahrenheit (F) and subjected to visual, tactile, and audible examination. The telescope shall conform to the requirements of 3.3.1. Caution shall be exercised during this test to avoid subjecting the telescope to thermal shock.

4.6.2 Extreme operating temperature.- The testing equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.3.2. The telescope shall be exposed to each temperature extreme specified in 3.3.2 for a period of 5 hours. At the end of each 5 hour period, and while still at the temperature extreme, the telescope shall be subjected to the applicable test of 4.6.8 and 4.6.9. The telescope shall conform to the requirements of 3.3.2. Caution shall be exercised during this test to avoid subjecting the telescope to thermal shock.

4.6.3 Vibration.- Vibrating equipment capable of providing the amplitude and frequency specified in 3.3.3 shall be utilized for this test. The vibrating equipment shall also be capable of vibrating the telescope along 3 mutually perpendicular axes while the telescope is maintained in its using position, as depicted in the upper view on sheet 1 of Drawing F7597771. The telescope shall be horizontally mounted on the vibration table by means of an adapter. The telescope shall be vibrated in accordance with Procedure IX, Part 1 of MIL-STD-810, except that the frequency, frequency cycling, and amplitude of the vibration shall be as specified in 3.3.3. Upon completion of the vibration cycling the telescope shall be thoroughly examined for physical defects resulting from poor workmanship and materials to determine conformance with 3.3.3, prior to being subjected to the remaining tests specified herein. A visual examination shall be made for missing or damaged parts. A tactile examination shall also be conducted to determine looseness or improper functioning of moving parts for undue irregularities of movement, friction or looseness. An audible examination shall be made of the telescope by shaking it and listening for broken optical components, such as lenses, reticle,etc. Any one of the possible defects defined above shall be cause to consider a telescope defective. Telescopes which have passed the above examinations shall be subjected to the tests specified in 4.6.4 through 4.6.10 inclusive to determine overall compliance with 3.3.3.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.6.4 Cleanliness.- The optical surfaces in each of the two power positions, shall be inspected for cleanliness in accordance with MIL-O-13830. The telescope shall conform to the cleanliness requirements of 3.4. Dirt particles which interfere with the legibility or accuracy of the reticle pattern shall be cause for rejection.

4.6.5 Sealing.- The external pressurizing of the telescope to test sealing, shall be performed with special testing equipment conforming to 4.5.2.3.1. The magnification adjustment ring shall be positioned at its midpoint of travel during this test. Pressurize the equipment with dry nitrogen gas to 5.0 ± 0.10 psig in accordance with the procedure for external pressure testing on Drawing F8565556. The dry nitrogen gas shall have a dew point at least as low as minus 25°F. Retain the applied pressure on the telescope for the time period specified in 3.5. At the end of this time period there shall be no evidence of leakage as indicated on the pressure gage of the testing equipment to conform with the requirement of 3.5.

4.6.6 Orientation.- The following tests shall be performed with the telescope positioned on special testing equipment in compliance with 4.5.2.3.2. The testing equipment shall be placed on a surface plate or table that has been leveled by means of a precision (10 second) bench level. The target reticle of the projector collimator shall have an appropriate calibrated horizontal and vertical reticle crossline target test pattern containing a 0.50 mil diameter circle at the intersecting point of the horizontal and vertical reticle lines to determine conformance with collimation, as specified in 3.6.1. In addition, the target test pattern shall also contain a horizontal reticle line representing the 400 yard line (see 3.6.2) with tolerance marks incorporated on both sides of the line to determine conformance to parallelism of reticle and image, as specified in 3.6.2. The vertical reticle target line shall be adjusted plumb. Unless otherwise specified herein, the target projector collimator shall be set at infinity focus. The projector collimator shall be autocollimated to the mounting surfaces provided on the test equipment utilizing the collimating arrangement depicted on Drawing F7573430.

4.6.6.1 Minimum magnification.- Unless otherwise specified herein, the following tests shall be performed at the four power (4X) position of the telescope depicted on Drawing F7597771. The diopter adjustment ring shall be set for best focus of the telescope reticle.

4.6.6.1.1 Collimation.- View through the telescope and observe the projected target image. The line of sight through the top of the vertical dash line located at the center of the geometric axis of the telescope reticle under test shall be within the circle on the target test pattern to be in conformance with 3.6.1.

4.6.6.1.2 Parallelism of reticle and image.- Perform this test while viewing through the telescope with the unaided eye. The 400 yard horizontal line of the telescope reticle shall fall within the target image tolerance marks to be in conformance with 3.6.2.

4.6.6.1.3 Reticle accuracy.- This test shall be conducted in accordance with the test for reticle scale spacings of MIL-O-13830. The total angular



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

subtense of the reticle pattern between the zero range cross and the maximum range mark in the finished telescope shall meet the requirements specified in 3.6.3, as measured on the target test pattern.

4.6.6.1.4 Magnification.- The telescope shall be inspected for magnification utilizing a dynameter and a diaphragm with a known diameter (millimeters). With the telescope adjusted for minimum magnification (see 4.6.6.1), place the diaphragm at the telescope objective lens. Set the dynameter at the telescope eyepiece assembly. While viewing through the dynameter, adjust the dynameter for best focus of the diaphragm image. Measure the diameter of this image utilizing the millimeter reticle scale of the dynameter. Divide the known diameter (millimeters) by the diaphragm image diameter (millimeters) as read on the dynameter reticle scale. Record this value; it shall be within the values specified in 3.6.5 for a minimum magnification. Repeat the above procedure at the eight power (8X) position of the telescope (see Dwg. F7597771). Record this value; it shall be within the values specified in 3.6.5 for maximum magnification to determine overall compliance with 3.6.5. Readjust the telescope for minimum magnification (see 4.6.6.1) for subsequent testing.

4.6.6.1.5 Diopter adjustment.- This test shall be performed with the aid of a calibrated dioptometer having a magnification of at least three power (3X) and a diopter measuring range of at least plus and minus 2 diopters. Set the dioptometer diopter scale to zero and adjust the dioptometer eyepiece for best focus of the dioptometer reticle. Position the dioptometer at the telescope eyepiece and while viewing through the dioptometer, rotate the telescope diopter adjustment ring counterclockwise (backlash removed for direction of travel) until best focus of the telescope reticle is obtained. This is the zero diopter setting required in 3.7.1. Remove the dioptometer from the telescope eyepiece and set the dioptometer diopter scale to plus 2 diopters. Reposition the dioptometer at the telescope eyepiece and while viewing through the dioptometer, continue counterclockwise rotation of the telescope diopter adjustment ring until best focus of the telescope reticle is again obtained. There shall be sufficient movement of the diopter adjustment ring in the counterclockwise direction from the zero setting to provide a focus of plus 2 diopters, as measured with the dioptometer. Repeat this test with the dioptometer diopter scale set to minus 2 diopters and rotate the telescope diopter adjustment ring in the clockwise direction. There shall be sufficient movement of the diopter adjustment ring in the clockwise direction from the zero setting established herein to provide a focus of minus 2 diopters, as measured with the dioptometer. Diopter adjustment shall conform to the requirements of 3.7.1.

4.6.6.1.6 Change in diopter setting.- Perform this test utilizing the dioptometer specified in 4.6.6.1.5. The dioptometer shall be zeroed and adjusted as specified therein. With the telescope adjusted for minimum magnification (see 4.6.6.1), position the dioptometer at the telescope eyepiece. While viewing through the dioptometer, obtain best focus of the telescope reticle by adjustment of the telescope diopter adjustment ring. Record the dioptometer diopter scale reading. Adjust the telescope to the eight power (8X) position (see Dwg. F7597771) and reposition the dioptometer at the telescope eyepiece. While viewing through the dioptometer, obtain best focus of the telescope reticle by adjustment of the dioptometer diopter scale. Record the dioptometer diopter scale reading. Any difference between the first and second dioptometer diopter scale reading shall not exceed the values specified in 3.7.2.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.6.6.1.7 Parallax.- The telescope shall be adjusted to the eight power (8X) position (see Dwg. F7597771) for this test. Parallax requirements shall be met when the target image is adjusted as specified in 3.9. Parallax will be recognized by any apparent displacement of the telescope reticle lines with respect to the center target image lines when the observer's head is moved from side to side or up and down. Parallax shall be measured at the optical axis (center of the reticle pattern). Displacement between the telescope reticle and target image shall not exceed the tolerance specified in 3.9.

4.6.7 Resolution.- The test equipment specified in 4.6.6 is not required for this test. The telescope shall be adjusted for minimum magnification (see 4.6.6.1). Position the telescope on a holding device capable of accepting the spherical mounting collars of the telescope. Perform this test utilizing an observation telescope with a magnification of at least 4 power (4X) and a resolving power chart on a wall target. The test methods and procedures shall be in compliance with the "Resolution Test" specified in MIL-O-13830 and the resolving power chart shall contain 4 line sets as shown in Figure 1 therein. The focus of the observation telescope shall be established at one best focus setting for viewing of the detectable line structure and proper line count of the resolution target. Resolution of the telescope optical system shall meet the requirements specified in 3.8.

4.6.8 Operability, magnification adjustment.- Standard torque measuring equipment capable of measuring the torque values specified in 3.10.1 shall be utilized for this test. An appropriate adapter, to accommodate the magnification change ring shall be used with the torque measuring equipment. Torque shall be measured while rotating the magnification change ring through the range specified in 3.10.1. The running torque required to rotate the magnification change ring shall conform to the applicable requirement of 3.10.1 for the temperatures indicated.

4.6.9 Operability, diopter movement.- Standard torque measuring equipment capable of measuring the torque values specified in 3.10.2 shall be utilized for this test. An appropriate adapter, to accommodate the diopter adjustment ring shall be used with the torque measuring equipment. Torque shall be measured while rotating the diopter adjustment ring through the range specified in 3.10.2. The running torque required to rotate the diopter adjustment ring shall conform to the applicable requirements of 3.10.2 for the temperatures indicated.

4.6.10 Illumination.- A device consisting of a .19 ampere lamp energized by 3.0 volts shall be utilized to illuminate the telescope reticle. The reticle pattern shall be clearly defined when visually examined against a darkened background. Should the brightness of a reticle defect be greater than the brightness of a reticle line the defect shall be cause for rejection. This test shall be performed when the telescope is adjusted at the eight power (8X) position depicted on Drawing F7597771.

## 5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with packaging data sheet 7597773. The level of protection shall be as specified in the procurement document.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use.- The Telescope M83F is used in the Fire Control System of Light Tank, M24.

6.2 Ordering data.- Procurement documents should specify the following:

a. Title, number and date of this specification
b. Selection of applicable levels of preservation, packaging and packing.
c. Applicable packaging data sheet number (see 5.1)
d. Provisions for First Article testing

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1240-A291

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.