MIL-P-50911A(AR)
19 MARCH 1983
SUPERSEDING
MIL-P-50911(MU)
21 May 1971

MILITARY SPECIFICATION

PRIMING ASSEMBLY FOR DEMOLITION CHARGE ASSEMBLY: M183; PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the parts and loading, assembling and packing of Priming Assembly for Demolition Charge Assembly: M183.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.1), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-566	-	Box, Folding, Paperboard.
PPP-B-636	-	Boxes, Shipping, Fiberboard.

MILITARY

MIL-B-2427	-	Box, Ammunition Packing: Wood, Nailed.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the currentversion before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.3)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9219074 - Priming Assembly.

PUBLICATIONS

CODE OF FEDERAL REGULATIONS

TITLE 49 - Transportation, Parts 100-199.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D.C. 20402. Orders should specify,"49 CFR 100-199 (latest revision).")

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Priming assembly. The Priming Assembly shall comply with all requirements specified on Drawing (Dwg. 9219074, all associated drawings, and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dents, dirt, grease, rust, corrosion products, and other foreign matter. After loading, all external surfaces shall be free from explosive. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material may be permitted. All required marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantity
Cup, Booster	8861120	10
Booster Assembly	8861119	10
Priming Assembly	9219074	10

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

SIZE IN REVERSE

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-P-50911A(AR)

PARAGRAPH	TITLE: Priming Assembly		SHEET 1 OF 1		DRAWING NUMBER: See below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cup, Booster				
	Dwg. 8861120				
	Examination for Defects	10		3.2	4.4.2.1
	Booster Assembly				
	Dwg. 8861119				
	Examination for Defects	10		3.3	4.4.2.2
	Weight of booster charge	(a)		3.3	4.5.1
	Priming Assembly				
	Dwg. 9219074				
	Examination for Defects	10		3.3	4.4.2.3

NOTES: (a) A sample of ten (10) booster cups shall be selected before loading and marked for identification. After being subjected to the examination for defects, the weight of charge in each cup shall be determined.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Metal parts from not more than one lot interfix number from one manufacturer.
b. Detonating fuse from not more than two lots from one manufacturer.
c. Comp A5 from not more than two lots from one manufacturer.
d. PETN from not more than two lots from one manufacturer (when applicable).
e. Detonating cord clips: M1, of one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50911A(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.1	Cup, Booster	1	1	8861120
				NEXT HIGHER ASSEMBLY: 8861119

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Thickness through bottom, minimum (min)		0.65%	3.2	Gage
203	Inside diameter		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50911A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Booster Assembly	1 OF 1	8861119
			NEXT HIGHER ASSEMBLY 9219074

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Explosive charge	-	-	3.3	Certification (See 4.4.1)
102	Weight of charge	(a)	-	3.3	4.5.1
103	Depth to charge, min.		0.40%	3.3	Gage
104	Charge missing		0.40%	3.3	Visual
105	Assembly split, cracked or punctured		0.40%	3.3	Visual
Minor					
201	Outside diameter, max.		0.65%	3.3	Gage
202	Marking incorrect, illegible or missing		0.65%	3.3	Visual
203	Poor workmanship		1.0%	3.5	Visual

(a) A sample of thirty-two (32) empty booster cups shall be selected from each lot and marked for identification. After loading, the booster assembly shall be inspected as specified in 4.5.1. If one (1) or more samples fail to comply with the specified weight requirement, the lot shall be rejected.

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22 20:47:42
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50911A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Priming Assembly	1 OF 1	9219074
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Crimp incorrect, inadequate or missing		0.40%	3.3	Visual
102	Booster assembly improperly assembled or missing		0.40%	3.3	Visual
103	Detonating fuse missing		0.40%	3.3	Visual
104	Booster assembly damaged (dented, wrinkled, cracked or punctured)		0.40%	3.3	Visual
105	Detonating cord clip improperly assembled, damaged or missing		0.40%	3.3	Visual
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:

DRDAR-[illegible] Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First article and Quality conformance Inspection tables.

4.4.4 Submission of product. At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.4.5 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.5 Methods of inspection.

4.5.1 Weight of booster charge. Weigh each of the marked empty booster cups to the nearest 0.1 milligram. Record the weights and return the sample booster cups to the regular production lot. After loading of the booster cups, the loaded sample booster cups shall be weighed to the nearest 0.1 milligram. This weight shall be recorded. Calculate the weight of the booster charge as follows:

Weight = B - A

Where: A = weight of empty booster cup
B = weight of loaded booster cup

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation - packaging.

5.1.1 Level A. Place 100 Cup, Booster, 8861120, in a box conforming to Variety 2, Process II, of Spec PPP-B-566.

5.1.2 Level B. Level B shall be the same as Level A.

5.1.3 Level C. Cup, Booster shall be packaged in accordance with MIL-STD-1188.

5.2 Intermediate pack.

5.2.1 Level A. Two hundred boxes (20000 Cup, Booster) shall be packed into a fiberboard box conforming to Grade V3C, Class WWVR, Style RSC of PPP-B-636 and closed per PPP-B-636.

5.2.2 Level B. Level B shall be the same as Level A.

5.2.3 Level C. Level C, intermediate pack, shall be in accordance with MIL-STD-1188.

5.3 Packing.

5.3.1 Level A. Three intermediate, Level A, containers of Cup, Booster shall be over-packed in a wood box conforming to MIL-B-2427. Close and strap box in accordance with MIL-B-2427.

5.3.2 Level B. Level B shall be the same as Level A.

5.3.3 Level C. Cup, Booster shall be packed in accordance with MIL-STD-1188.

5.3.3.1 Priming Assemblies shall be packed in a manner which will insure arrival at destination in satisfactory condition. The priming assemblies shall be wrapped and cushioned to the extent necessary to provide protection from hazards of contamination and physical damage encountered in shipping, handling and storage. In no event shall the priming assembly be coiled to form a kink in the detonating fuse or to form a coil less than a 2 inch radius. The shipping container shall be in accordance with the rules and regulations of the Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Marking.

5.4.1 Levels A & B. Marking shall be in accordance with MIL-STD-129.

5.4.2 Level C. Marking of Cup, Booster, shall be in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the currentversion before use.

5.4.2.1 Marking of Priming Assemblies shall be in accordance with MIL-STD-129, and Code of Federal Regulations, Title 49, Parts 100-199, and shall include, but not be limited to, the following:

	SIZE (NOM)
NSN and DODIC	1 inch
LOT NUMBER	1 inch
DOT MARKING - DETONATING PRIMERS-HANDLE CAREFULLY	1 inch

5.5 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number.

6.3 Drawings. Drawings listed in section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsensal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.4 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U. S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-M, Dover, New Jersey 07801.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A260)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:44Z
Check the source to verify that this is the current version before use.