INCH-POUND

MIL-D-70752A(AR)
11 September 1992
SUPERSEDING
MIL-D-70752(AR)
25 August 1989

MILITARY SPECIFICATION

DETONATOR, STAB, PARTS, ASSEMBLY AND PACKAGING FOR

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1. Scope. This specification contains the requirements and quality assurance provisions for fabrication of parts, assembly and packing for a stab detonator (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550	-Ammunition and Special Weapons, General Specification for
MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-29T00:57Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109	-Quality Assurance Terms and Definitions.
MIL-STD-1168	-Lot Numbering of Ammunition
MIL-STD-1190	-Minimum Guidelines for Level C, Preservation, Packing and Marking
MIL-STD-1234	-Pyrotechnics: Sampling, Inspection and Testing

(Unless otherwise indicated, copies and federal and military specificaitons, standards and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094).

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.6)

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT

9384806	-Detonator Assembly
9384807	-Cup Detonator
9384808	-Disc, Closure
9384824	-Lead Assembly

PACKAGING

9384823	-Box, Set-up Packaging Ammunition

INSPECTION

12913007	-Lead Propagation Test Assembly
12913004	-Weight

PUBLICATIONS

CFR-100-199	-Department of Transportation Regulation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

(Copies of other Government documents, drawings, and publications required by manufacturers in connection with specif acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications. (See 4.5.1.)

3.2 Components and assemblies. The components and assemblies to be used in first article samples and production lots shall comply with all requirements specified on Drawing 9384806 and associated drawings and with all requirements specified in applicable specifications and standards. (See 4.5.1.)

3.3 Moisture content.

3.3.1 Lead azide. The moisture content of the lead azide used in loading the detonator shall not exceed 0.15 percent when tested as specified in 4.5.2.

3.3.2 Primer mixture. The moisture content of the primer mixture used in loading the detonator shall not exceed 0.15 percent when tested as specified in 4.5.3.

3.3.3 RDX. The moisture content of the RDX used in loading the detonator shall not exceed 0.15 percent when tested as specified in 4.5.4.

3.4 Function.

3.4.1 Sensitivity and output. The detonator shall function on the first attempt and initiate a lead (Dwg. 9384824) over an air gap of 0.285 inch minimum and cause the lead to indent a steel witness block to a minimum depth of 0.021 inch when tested as specified in 4.5.5.1.

3.5 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. All parts and assemblies shall be clean and free of burrs, sharp edges, cracks, surface defects, rust, chips, dirt, grease and oil, corrosion products and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any part or assembly, nor shall they be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and sharply defined. Required packing shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 and MIL-A-2550 shall apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (see 4.3).

b. Quality Conformance Inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. If closure is punched from strip, collect sample from punch station. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Cup, Detonator	9384807	25
Disc, Closure	9384808	25
Detonator, Stab	9384806	200

4.3.2 Inspections to be performed. The examinations and tests listed in Table I shall be performed on the first article sample. (See MIL-A-48078.)

4.3.3 Rejection. If any of the applicable components or subassembly or assembly fails to comply with the requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon the failure of any component, subassembly or assembly to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-D-70752A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
	Detonator Assembly and Metal Parts		See Below
			NEXT HIGHER ASSEMBLY
			--

CLASSIFICATION	EXAMINATION OR TEST		CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Cup, Detonator (Dwg. 9384807)				
	Examination for Defects	3/	25	3.2	4.4.2.1
	Disc, Closure (Dwg. 9384808)				
	Examination for Defects	3/	25	3.2	4.4.2.2
	Detonator, Stab (Dwg. 9384806)				
	Examination for Defects	1/	--	3.2	4.4.2.5
	Functioning-Sensitivity and Output	2/	200	3.4.1	4.5.5.1

NOTES: 1/ The sample shall consist of the detonators to be functioned per 4.5.5.1.
2/ Accept on one defect. Reject on two or more defects.
3/ Accept on zero defects, reject on one.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawing, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. In addition, inspection lots of detonators shall contain:

a. Components bearing the same lot interfix number from one manufacturer.

b. Lead azide of the same type from not more than two lots produced by the same manufacturer, in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plant.

c. RDX from not more than one lot.

d. Primer mixture consisting of batches blended by the same process. Each batch shall be composed of the same ingredients, each of which is to be from one interfix lot from one manufacturer.

4.4.2 Examinations and tests. (See MIL-A-48078). The examinations listed herein shall be performed on inspection lots as defined in 4.4.1. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristic paragraphs. The contractor's quality program or detailed inspection plan shall provide

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II. Attributes sampling inspection

Lot Size	Inspection Levels					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150000 to 500000	1250	500	200	125	50	13
500001 and over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Unless otherwise specified or provided for in the contract, alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.8). When required, the contractor shall demonstrate that the effectiveness of the proposed alternative(s) is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program plan or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-D-70752A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cup, Detonator	1 OF 1	9384807
			NEXT HIGHER ASSEMBLY 9384806

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Cup, split or cracked	Level II	3.2	Visual
MINOR				
201.	Poor workmanship	Level IV	3.6	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-D-70752A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Disc, Closure		9384808
			NEXT HIGHER ASSEMBLY 9384806

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Thickness	Level II	3.2	Gage 1/
102.	Diameter	Level II	3.2	Gage 1/
MINOR				
201.	Poor workmanship	Level IV	3.6	Visual

NOTES: 1/ If manufactured from strip during loading operation, inspect material thickness at beginning and end of each roll.

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-D-70752A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Detonator Assembly (Prior to Loading)	1 OF 1	9384806
			NEXT HIGHER ASSEMBLY: -------

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Moisture content of lead azide	Note 1, 4 & 5	3.3.1	4.5.2
102	Moisture content of primer mix (9384809)	Note 2, 4 & 5	3.3.2	4.5.3
103	Moisture content of RDX	Note 3, 4 & 5	3.3.3	4.5.4
MINOR	None defined.			

NOTE 1 A sample of 2 grams shall be selected from each lot of lead azide at the time of loading.

NOTE 2 A sample of 0.7 gram shall be selected from each lot of the primer mixture at the time of loading.

NOTE 3 A sample of 5 grams shall be selected from each lot of RDX at the time of loading.

NOTE 4 If the sample fails the test and loading has not begun, the lot of tested material shall be rejected until proper corrective action has been accomplished (where possible) as verified by reperforming the test. If loading has begun, action on the unloaded material shall be as specified above and all detonators loaded with the questionable material shall be rejected.

NOTE 5 As an alternate this requirement can be met by drying the material in a 135° ± 15°F oven for 72 hours. The oven is to maintain a relative humidity of less than 30%. Once dried the materials must be maintained in a dry controlled environment for example using desiccant or oven.

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-D-70752A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Detonator Assembly (Charge Weight)	1 OF 1	9384806
			NEXT HIGHER ASSEMBLY: -------

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR	None defined.			
MINOR				
201.	Weight of lower charge below minimum (Primer Mix)	Note 1/	3.2	SMTE
202.	Weight of intermediate charge below minimum (Lead Azide)	Note 1/	3.2	SMTE

NOTES: 1/ Check the first five (5) loaded each shift and a minimum of five (5) per hour thereafter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-D-70752A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Detonator Assembly	1 OF 1	9384806
			NEXT HIGHER ASSEMBLY: See paragraph 6.1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101.	Length	Level II	3.2	Gage
102.	Diameter	Level II	3.2	Gage
103.	Color incorrect, missing or on wrong end	Level II	3.2	Gage
104.	Functioning-sensitivity and output	Level II	3.4.1	4.5.5.1
105.	Cup cracked or split	100%	3.2	Visual
106.	Explosive exposed	100%	3.2	Visual
107.	Caked explosive on exterior	100%	3.2	Visual
MINOR				
201.	Poor workmanship	Level IV	3.6	Visual
202.	Crimp not full 360°	Level IV	3.2	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. The test (First article and Quality Conformance) shall be performed on inspection lots as defined in 4.4.1. The sampling plans for the test shall conform to the provisions of 4.4.2.c.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this specification is identified, either directly or by reference, in the "Paragraph Reference/Inspection Method" column of the first article or quality conformance inspection tables herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

PRECAUTION - The specification covers sampling and testing of explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Section 3 and 5 of this specification in accordance with 4.4.2 herein Table I.

4.5.2 Moisture content of the lead azide. The moisture content of the lead azide shall be determined at the time of loading. The moisture content of the lead azide shall be determined in accordance with MIL-STD-1234 method 102.2.

4.5.3 Moisture content of primer mixture. The moisture content of the primer mixture shall be determined at the time of loading in accordance with MIL-STD-1234 method 102.2.

4.5.4 Moisture content of RDX. The moisture content of the RDX shall be determined at the time of loading. The moisture content of the RDX shall be determined in accordance with MIL-STD-1234 Method 102.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

4.5.5 Functioning.

4.5.5.1 Sensitivity and output. A random sample of detonators shall be selected for each lot. Each detonator shall be assembled with a lead (Dwg/ 9284824) into the test setup specified in inspection equipment Dwg. 12913007 and 12913004, a 0.25 ± 0.01 ounce weight shall be dropped on a firing pin from a height of four inches, maximum. The drop height shall be measured from the top of the firing pin to the bottom of the weight.

A detonator that fails to fire shall be classed defective. A detonator that fires but fails to initiate the lead sufficiently to produce a dent in the steel witness block of the required depth shall be classed defective if the detonator confinement sleeve expands to less than 0.330 inch diameter. If the confinement sleeve expands to 0.330 inch diameter or greater, the test shall be classed defective and the result a no-test. The indentation depth shall be measured using a probe with a 0.017 inch plus or minus 0.002 inch spherical radius tip.

5. PACKAGING

5.1 Unit packaging.

5.1.1 Level A. Not available.

5.1.2 Level B. Unit packaging for the detonator shall be in accordance with Drawing 9384823.

5.1.3 Level C. Same as Level B.

5.2 Packaging.

5.2.1 Level A. Not available.

5.2.2 Level B. Packaging for the detonator shall be in accordance with Drawing 9384823.

5.2.3 Level C. Same as Level B.

5.3 Packing.

5.3.1 Level A. Not available.

5.3.2 Level B. Packing for the detonator shall be in accordance with Drawing 9384823.

5.3.3 Level C. Same as Level B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

5.4 Marking.

5.4.1 Level A. Not available.

5.4.2 Level B. Unit packaging, packaging, and packing shall be in accordance with Drawing 9384823.

5.4.3 Level C. Same as level B.

5.5 Packaging, packing and marking for inert detonator parts. Packaging shall be as specified on Drawing 9384823 and Department of Transportation Regulation 49 CFR 100-1.

5.6 Shipping. When detonators from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of lots in transit.

5.6.1 Unitization. Unitization shall be in accordance with MIL-STD-1190.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The detonator assemblies are intended for use in the following fuze:

25mm	M758	11820609

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.2).

c. Requirements for submission of first article sample (see 3.5).

6.3 Submission of inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army ARDEC, ATTN: SMCAR-QAF-I(D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

6.4 Check test for deterioration of detonators. The following test is designed to prevent detonators that have deteriorated from being assembled into major ammunition items. The tests shall be performed on detonators from each lot which have been stored under normal conditions for more than two years, or if the detonators have been subjected to adverse conditions at any time since previous tests. If the specification for the ammunition item into which the detonators are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration.

6.5 Sensitivity and output. A sample of two hundred and five (205) detonators randomly selected from each lot shall be tested as specified in 4.5.5.1.

6.6 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.7 Subject term (keyword) listing.

Closure Disk
Lead
Primer
Fuze

6.8 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality evaluation by the technical activity responsible for the preparation of this specification.

6.9 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AE35)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-D-70752	11 SEPTEMBER 1992

3. DOCUMENT TITLE

DETONATOR, STAB, PARTS, ASSEMBLY AND PACKAGING FOR

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U. S. Army ARDEC Specifications And Standardization Office/Bldg. 6	(1) Commercial (201) 724-6675	(2) AUTOVON 880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S Picatinny Arsenal, N. J. 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:57Z
Check the source to verify that this is the current version before use.