INCH-POUND

MIL-I-70698 (AR)
30 December 1988

MILITARY SPECIFICATION

IMPROVED LIFTING TARGET ELEVATING MECHANISM: 9375512

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the Improved Lifting Target Elevating Mechanism (ILTEM), Part No. 9375512, used on the Armor Moving Target Carrier (AMTC), Part No. 9365562, in the Remote Target System (RETS).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solication (See 6.2).

SPECIFICATIONS

MILITARY

MIL-F-13926	- Fire Control Material, General Specification Governing the Manufacture and Inspection of
MIL-P-14232	- Parts, Equipment and Tools for Army Material, Packaging of
MIL-I-45607	- Inspection Equipment, Acquisition, Maintenance and Disposition of
MIL-E-70694	- Electronic Control Unit

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions, and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6920
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-454	- Standard General Requirements for Electronics Equipment
MIL-STD-810	- Environmental Test Methods

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Navel Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9375512	- Improved Lifting Target Elevating Mechanism
11784504	- Electronic Control Unit

2.2 Order of precedence. In the event of conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General description. ILTEM consists of an electrical and hydraulic unit operating a three (3) inch diameter cylinder which forces a rotating drive shaft through an angular distance of 90 degrees. A removable electronic control unit provides front panel controls for on/off mode operations and hit sensitivity selection. Electronic selection and use of the hit sensor provide the ability to implement control functions such as the visual hit indicator lamp, target response to hits, the gunfire simulator and the visual hit smoke scorer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

3.2 Fabrication. The ILTEM shall be manufactured in accordance with drawing 9375512 and MIL-F-13926. The electronic control unit shall meet MIL-E-70694.

3.3 Functions.

3.3.1 Commands. The ILTEM shall receive through its electronic control unit commands to raise target, to lower target, to activate visual hit indicator lamp and gunfire simulator.

3.3.2 Mechanism control. The mechanism is remotely controlled and responds as follows:

a. Upon receiving a remote raise or lower command signal the mechanism moves the target to the position commanded. The mechanism does not respond in any manner if commanded to a position that it is already in.

b. The mode of operation is selectable directly on the target device by a rotary switch. At position 0 all electrical power is removed from the electronic control unit. At position 1, the target can be raised and lowered by remote command and hits on the target have no effect. At position 2, the target can be raised and lowered by remote command and a hit on the target when raised will lower and stay lowered until another raise remote signal is received. At position 3, the target can be raised and lowered by remote command and a hit on the target will lower, delay 11 seconds, and then automatically raise until another hit causes it to repeat the above operation. At positions 4, 5 and 6 the visual hit indicator lamp will illuminate when the target is hit. Modes 4, 5 and 6 are the same as modes 1, 2 and 3 except for visual hit indicator lamp operation.

c. The smoke scorer when connected, will operate when the target is hit, on modes 1 through 6. The target device has a manual momentary switch that permits testing the raise and lower cycle and visual hit indicator lamp illuminations.

3.3.3 Hostile fire simulator control. The target device will operate a hostile fire simulator when a remote command (fire) is sent. The output circuit terminates in a single female connector accessible from the outside housing.

3.4 Performance requirements.

3.4.1 Hydraulic oil tank. Capacity: 231 cubic inches.

3.4.2 Hydraulic electric motor.

a. Voltage: 230 VAC, single phase.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

b. Current: 10.2 amps.

3.4.3 Hydraulic pump.

a. Max oil pressure: 2000 psi

b. Relief valve: Adjustable

c. Flow rate: 2 gal/min.

3.4.4 Hydraulic cylinder.

a. Plunger diameter: 3.0 inches

b. Pressure area: 7.068 square inches

c. Inlet oil pressure max: 2000 psi

d. Stroke length: 8.5 inches

3.4.5 Electronic control unit.

a. Input voltage: 12 VDC

b. Electronics regulated voltage: 8 VDC

c. Relay operating voltage: 12 VDC

3.4.6 Output drive.

a. Turning angle: 90°, plus or minus 5°

b. Maximum torque moment: 5600 foot-pounds

c. Raise time with target: 10 seconds

d. Lower time with target: less than 8 seconds

e. Maximum target board: 8.5 feet high x 20 feet wide x 0.5 inch thick

f. Maximum target weight: 350 pounds

3.5 Environmental requirements.

3.5.1 Temperature.

3.5.1.1 Operating. The ILTEM shall meet the requirements of 3.3 and 3.4 when thermally stabilized at -250_{F} and at $+1250_{F}$.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

3.5.1.2 Non-operating (storage). The ILTEM shall not suffer permanent damage when subjected to at least four hours at each temperature extreme of -40°F and +160°F and shall meet the requirements of 3.3 and 3.4 when returned to and thermally stabilized at ambient temperature (+60°F to +90°F).

3.5.2 Upweight/wind test. The ILTEM shall meet the requirements of 3.3 and 3.4 when wind or weights are used to simulate a continuous 35 mph horizontal wind directed perpendicular to the target board.

3.5.3 Rain test. The ILTEM shall not suffer permanent damage when subjected to 4 inches per hour of rain with a 35 mph wind for a minimum of 1 hour.

3.5.4 Vibration. The ILTEM shall not suffer permanent damage when subjected to method 514.3 of MIL-STD-810 for one hour of random vibration.

3.5.5 Shock. The ILTEM shall not suffer permanent damage when subjected to mechanical shock during cycling in accordance with Method 516.3 of MIL-STD-810.

3.6 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.7 Workmanship. The workmanship requirement of MIL-STD-454 shall apply.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 General provisions. The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.5).

4.2.1 Inspection conditions. Unless otherwise specified, all examinations and tests shall be conducted at the following standard ambient conditions:

a.	Temperature	+50 deg to +90 deg F.
b.	Relative humidity	90% RH Max.
c.	Pressure	28 to 32 inches of Hg.

4.3 First article (initial production) submission. The requirement for first article approval and the responsibility (Government or contractor) for the first article testing shall be specified in the contract. The sample for first article approval tests shall consist of three items manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.3.1 Government testing. When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to ensure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certification of conformance for materials.

4.3.2 Contractor testing. When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

certification for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.4 Inspection provisions.

4.4.1 Submission of product. Unless otherwise specified by the contracting officer, inspection of lots shall be in accordance with MIL-STD-105.

4.5 Quality conformance inspection.

4.5.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions, and complies with the provisions for submission of product as specified in MIL-STD-105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.5.2 Examinations and tests.

4.5.2.1 Components, assemblies and subassemblies. All components, assemblies and subassemblies shall be inspected in accordance with the inspection provisions contained in this specification and the Quality Assurance Provisions (QAP) listed in the technical data package (TDP). In the absence of QAPs, the applicable quality assurance provisions of MIL-F-13926 shall apply.

4.5.2.2 Final acceptance inspection. Subsequent to first article approval, examinations and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in 4.5.2.3 herein. Examination and test for packaging and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in 4.5.2.3 shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

4.5.2.3 Functional tests. The tests in Table I shall be performed on a 100% basis.

TABLE I - Functional tests.
(100 percent inspection)

CHARACTERISTIC TEST PROCEDURES		REQUIREMENT
Critical:	None	
Major:		
101	Electrical	3.3 4.5.2, 4.5.3
102	Performance	3.4 4.5.2, 4.5.3
103	Workmanship	3.7 Visual
104	Mechanical Interface	3.2 Visual
Minor		

4.6 Inspection equipment.

4.6.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements of MIL-I-45607.

4.6.2 Contractor-furnished inspection equipment.

4.6.2.1 Government design. Unless otherwise specified in the contract, all inspection equipment identified by drawing number in specifications or QAPs forming a part of the contract shall be supplied by the contractor in accordance with the design specified. The contractor may, however, propose alternatives to Government designs for approval in accordance with 6.3.

4.6.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the "Methods of Inspection" specified in 4.7 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926 whenever Government designs are not specified (see 4.6.2.1). Since tolerance of test equipment is normally considered to be within 10 percent of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to ensure that the test equipment will reliably indicate acceptability of a

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

product which does not exceed 90 percent of the prescribed tolerance limit and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of test equipment. Contractor inspection equipment designs shall be submitted for approval in accordance with 6.3.

4.6.2.3 Test equipment. In conjunction with 4.5.2.1 and 4.5.2.2, the test equipment listed in 4.8.1 shall be used in the performance of the applicable methods of inspection as specified in 4.7.

4.7 Methods of inspection.

4.7.1 Environment. Environmental tests shall be conducted in accordance with the general requirements and test methods of MIL-STD-810 except as specified herein. Testing equipment used in environmental tests shall be in accordance with "Test Facilities and Apparatus" requirements of MIL-STD-810.

4.7.2 Non-operating.

4.7.2.1 Vibration. This test shall be performed as specified in MIL-STD-810, Method 514.3, Procedure I-3.2.1.2, using Fig. 514.3-34 test for one hour in the vertical axis. After vibration the assembly shall be tested as specified in 4.7.4 and 4.7.5 to determine compliance with 3.3 and 3.4.

4.7.2.2 Shock. This test shall be performed as specified in MIL-STD-810, Method 516.3, Procedure I-3.6, Table 516.3-II. After the shock impulses, the assembly shall be tested as specified in 4.7.4 and 4.7.5 to determine compliance with 3.3 and 3.4.

4.7.2.3 High temperature. Temperature shall be as specified in MIL-STD-810, Method 501.2, Procedure I, Table 501.2-I. After temperature testing, the assembly shall be tested as specified in 4.7.4 and 4.7.5 to determine compliance with 3.3 and 3.4.

4.7.2.4 Low temperature. Test shall be as specified in MIL-STD-810, Method 502.2, Procedure I-Storage, using 24 hours to obtain thermal stabilization at -65°F. After temperature testing, the assembly shall be tested as specified in 4.7.4 and 4.7.5 to determine compliance with 3.3 and 3.4.

4.7.2.5 Rain test. Test shall be performed as specified in MIL-STD-810, Method 506.2, Procedure I, using 4 in/hr rain ratio with 40 mph wind for minimum of 1 hour. After testing, the assembly shall be tested as specified in 4.7.4 and 4.7.5 to determine compliance with 3.3 and 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

4.7.3 Operating.

4.7.3.1 Low temperature. Test shall be as specified in MIL-STD-810, Method 502.2, Procedure II, stabilize at -25°F, the assembly shall be tested as specified in 4.7.4 and 4.7.5 to determine compliance with 3.3 and 3.4.

4.7.3.2 High temperature. Test shall be performed as specified in MIL-STD-810, Method 505.2, Procedure I. The assembly shall be tested as specified in 4.7.4 and 4.7.5 to determine compliance with 3.3 and 3.4 during the last cycle of the seven cycles.

4.7.3.3 Upweight/wind test. Test shall be performed as specified in 3.6. After completion of test, the improved lifting target elevating mechanism assembly shall be operationally checked as specified in 4.7.4 and 4.7.5 to determine compliance with 3.3 and 3.4. Stabilizer bars are to be out to prevent target from tipping.

4.7.4 Requirements. Verify the following criteria for adherences to the drawing Section 3 requirement.

a. Measure hydraulic oil tank capacity using standard measuring equipment to determine compliance with requirements of 3.4.1.

b. Measure hydraulic electric motor voltage and current using standard measuring equipment to determine compliance with the requirements of 3.4.2.

c. Measure hydraulic pump pressure out flow rate using standard measuring equipment to determine compliance with the requirements of 3.4.3.

d. Measure hydraulic cylinder pressure and physical dimension using standard measuring equipment to determine compliance with the requirements of 3.4.4.

f. Measure electronic control unit voltage using standard measuring equipment to determine compliance with the requirements of 3.4.5.

4.7.5 Functional tests. ILTEM shall be interfaced with the appropriate simulations as in 4.8.1. Systems shall be functional according to procedures in 4.6 to verify the following requirements:

a. Measure turning angle using standard measuring equipment to determine compliance with the requirements of 3.4.6.a.

b. Measure maximum torque moment using standard measuring equipment to determine compliance with the requirements of 3.4.6.b.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

c. Measure raise time using standard measuring equipment to determine compliance with the requirements of 3.4.6.c.

d. Measure lowering time using standard measuring equipment to determine compliance with the requirements of 3.4.6.d.

4.8 Test procedure.

4.8.1 Equipment.

a. Visual Hit Indicator Lamp Simulator (VHILS)

b. (TLS)Target Load Simulator (TLS)

c. Hostile Fire Simulator (HFS)

d. Power Cable (P.C.)

e. Target Arm Simulator (TAS)

4.8.2 Test set up.

4.8.3 Procedure.

4.8.3.1 Test set up.

a. Electronic box function switch should be on the "0" (zero) position.

b. Connect Power Cable 9375734 and 9375537 to the 12V DC battery supply.

c. Place the electronic box function switch on position one.

d. Operate the electronic box test switch momentarily to the up position. Target simulator should raise to the up position and stop within $\pm$ 3° of the up position (90°).

e. Tap each of the five hit sensors. The smoke scorer simulator lamp should light momentarily for each tap. The target simulator should remain in the up position.

f. Operate the electronic box test switch momentarily to the down position. Target simulator should lower to the down position. Place the electronic box function switch on position two.

4.8.3.2 Position #2 test.

a. Operate the electronic box test switch momentarily to the up position. Target simulator should raise to the up position and stop within $\pm$ 3° of the up position (90°).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

b. Tap one of the five hit sensors. Smoke scorer simulator lamp should light momentarily. The target simulator should lower to the down position.

4.8.3.3 Position #3 test.

a. Place the electronic box function switch on #3 position. Operate the electronic box test switch momentarily to the up position. Target simulators should raise to the up position and stop within $\pm 3^{o}$ from the up position (90°).

b. Tap one of the five hit sensors. Smoke scorer simulator lamp should light momentarily. The target simulator should lower to the down position, delay 10 to 12 seconds, then raise to the up position.

c. Operate the electronic box test switch momentarily to the down position. Target simulator should lower to the down position.

4.8.3.4 Position #4 test.

a. Place the electronic box function switch on position #4.

b. Operate the electronic box test switch momentarily to the up position. Target simulator should raise to the up position and stop within $\pm 3^{o}$ of the up position (90°).

c. Tap each of the five hit sensors. The smoke scorer simulator lamp should light momentarily for each tap. The visual hit indicator lamp simulator should light momentarily. The target simulators should remain in the up position.

d. Operate the electronic box test switch momentarily to the down position. The target simulator should lower to the down position.

e. Operate the electronic box test switch momentarily to the up position. The target simulator should raise to the up position and stop within $\pm 3^{o}$ of the up position (90°).

4.8.3.5 Position #5 test.

a. Place the electronic box function switch on position #5.

b. Tap one of the five hit sensors. The smoke scorer simulator lamp and visual hit indicator lamp simulator lamp should light momentarily. The target simulator should lower to the down position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

4.8.3.6 Position #6 test.

a. Place the electronic box function switch on #6 position.

b. Operate the electronic box test switch momentarily to the up position. Target simulator should raise to the up position and stop within ± 3° from the up position (90°).

c. Tap each of the five hit sensors. The smoke scorer simulator lamp and visual hit indicator simulator lamp should light momentarily. The target simulator should lower to the down position, delay approximately 10 to 12 seconds, then raise to the up position.

d. Operate the electronic box test switch momentarily to the down position. The target simulator should lower to the down position.

e. Place the electronic box function switch in the "0" position.

f. Wrap all five hit sensor cables with the 230 VAC power cable. The hit sensors should connect to the electronic box.

g. Place the electronic box function switch on position #2.

h. Operate the electronic box test switch momentarily to the up position. The target simulator should raise to the up position. The smoke scorer simulator lamp or the hostile fire simulator lamp should not light or flicker.

i. Operate the electronic box test switch momentarily to the down position. The target simulator should lower to the down position, the smoke scorer simulator lamp or the hostile simulator lamp should not light or flicker.

j. Repeat h and i three more times.

k. End of test.

5. PACKAGING

5.1 General. Preservation, packing and marking shall be in accordance with Packaging Data Sheet 11784504 and MIL-P-14232 or best commercial packaging in accordance with common carrier regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This specification details the specific requirements for performance, quality assurance, and testing for the Improved Lifting Target Elevating Mechanism (ILTEM). The ILTEM will support live fire armor weapons training and qualification programs. These systems will provide training in identifying and firing on simulated moving armored vehicles during training exercises.

6.2 Acquistion requirement. Procurement documents should specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this specification.

b. Quantity required and delivery schedules.

c. Place of inspection if not at place of manufacture.

d. Instructions for shipment of production lot samples.

e. Provision for preparation for delivery if required for indefinite storage of inter-plant shipment.

f. Provision for the supply, maintenance, and dispostion of test equipment for acceptance inspection process.

g. Procuring activity designation assembly number(s) and nomenclature(s).

h. Serialization requirements, if applicable.

i. Packaging requirements, if other than specified in Section 5.

6.2.2 Contract data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DID) Form 1664 and delivered in accordance with the approved Contract Data Requirements List (CDRL) incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

Reference Paragraph	DID Title	DID No.
4.6	Quality Engineering Acceptance Inspection Equipment Descriptive Documentation	DI-R-1714

(Data item descriptions related to this specification and identified in Section 6, will be approved and listed as such in DOD 5000.19L, Volume II, AMSDL. Copies of data item descriptions required by contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3 Submission of inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army AMCCOM, ATTN: AMSMC-QAF-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as, U.S. Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Subject term (key word) listing.

Electronic Control Unit (ECU)
Improved Lifting Target Elevating Mechanism (ILTEM)
Target Holding Mechanism/Tank Gunnery (THM/TG)
Remote Target System (RETS)

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 6920-A112)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-I-70698 (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.