INCH-POUND

MIL-C-24196A(SH)
AMENDMENT 1
22 January 1991

MILITARY SPECIFICATION

CLEANER SYSTEM, ULTRASONIC

This amendment forms a part of MIL-C-24196A(SH), dated 13 January 1988, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of Defense.

PAGE 2

TABLE II, under system size, delete “66” and substitute “6”.

PAGE 14

4.6.8: Delete and substitute:

"4.6.8 Safety thermostat test. To verify compliance with 3.4.5.3.1, the cleaning tank shall be filled with cold water and the recirculating system energized. When the water temperature reaches 185° ±5° degrees Fahrenheit (°F), the heater shall shut off.

4.6.14: Delete and substitute:

“4.6.14 Shock. The cleaning systems shall be tested for conformance to the requirements specified in 3.3.9.”

4.6.15: Delete and substitute:

“4.6.15 Vibration. The cleaning system shall be tested for conformance to the requirements specified in 3.3.10.”

AMSC N/A FSC 4940
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:55Z
Check the source to verify that this is the current version before use.

PAGE 17

6.2.1 (o): Delete and substitute:

"(o) Electromagnetic interference control requirements, if other than specified (see 3.7 and 4.6.11)."

Preparing activity
Navy - SH
(Project 4940-N615)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:55Z
Check the source to verify that this is the current version before use.