MILITARY SPECIFICATION

PERISCOPE, BATTERY COMMAND: M65

This amendment forms a part of Military Specification MIL-P-45602B(MU), dated 14 April 1969.

* Paragraph 3.9.21 Operability. Delete Table 1 and substitute the following:

"Table I

	-40°F	60° to 90°F	+150°
Angle of site knob	6 in.lb.	3 in. lb.	5 in. lb.
Elevation knob	13 in.lb.	10 in. lb.	17 in. lb.
Diopter adjustment (left)	28 in.lb.	11 in. lb.	11 in. lb.
(right) (See Note)			
Interpupillary knob	6 in.lb.	3 in. lb.	5 in. lb.
Filter selectors	5 in.lb.	2 in. lb.	2 in. lb.
Release plunger	operable	operable	operable

Minimum running torque shall not be less than 3 in lb."

Paragraph 4.5.2.3.1(c) Target Collimators, First sentence: Delete "of at least 2.0 inches" and substitute "of at least 1.5 inches."

Paragraph 4.6.7.11 Reticle focus: Second sentence, delete in its entirety and substitute the following:

"The periscope reticle shall be in best focus within the limit specified in 3.9.12, as measured on the diopter knob scale."

* Paragraph 4.6.3 Vibration: Delete second sentence in its entirety.

* The outside margin has been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 6650-A050

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:33Z
Check the source to verify that this is the current version before use.