MIL-S-45640(Ord)

10 May 1961

SUPERSEDING
FA(FC)-PD-525
12 August 1959

MILITARY SPECIFICATION

SPOT CORRECTION UNIT, DOWN-UP: 8644079

1. SCOPE

1.1 This specification covers one type of spot correction unit, down-up (D-U) a subassembly of the Gun Direction Computers: M15 and M15C which are part of the Field Artillery Fire Control Systems: M35 and M35C. The spot correction unit is used to convert a mechanical input of observer (D-U) spot correction to an electrical output signal.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-F-14619	Fire Control Parts, Equipment and Tools; Packaging of
MIL-I-45208	Inspection Requirements; General Specification for

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

DRAWINGS

Ordnance Corps

D8643862	Electrical Schematic, Spot Correction Unit
F8644074	Spot Correction Unit

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Production model.- At the beginning of production, one spot correction unit representative of production, shall be made available to the Government to determine that the spot correction unit meets all requirements of this specification.

3.2 Materials.- Materials shall be in accordance with drawings, materials specifications and general specifications forming a part of this specification.

3.3 Construction.- The spot correction unit shall be manufactured in accordance with Drawing F8644074, "Spot Correction Unit", and drawings pertaining thereto. The requirements of this specification are detailed only to the extent considered necessary to obtain the desired mechanical and electrical characteristics, performance and permanence to insure inherent quality and performance capabilities prior to final acceptance by the Government.

3.3.1 Ground potential.- The design and construction of the spot correction unit (D-U), shall insure that all external parts are at ground potential at all times.

3.4 General specification.- The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specification MIL-F-13926:

(a) Order of precedence
(b) Protective finished surfaces
(c) Special accuracy
(d) Finish, painting and protective
(e) Electrical
(f) Workmanship

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

3.5 Environmental.

3.5.1 Vibration.- The spot correction unit shall be subjected to a simple harmonic motion having an amplitude of 0.015 inch (0.03 inch maximum excursion). The frequency shall be varied uniformly between the limits of 10 and 55 cycles per second and return to 10 cycles and shall be traversed in approximately 1 minute. This motion shall be applied for a period of 10 minutes in each of the 3 mutually perpendicular directions (total of 30 minutes). Subsequent to vibration the spot correction unit shall not be damaged or adversely affected and shall meet all requirements of this specification.

3.5.2 Operating temperatures.- The spot correction unit shall meet all the performance requirements of this specification when thermally stabilized at ambient temperatures of minus 40 degrees and plus 150 degrees Fahreheit.

3.5.3 Storage temperatures.- The spot correction unit shall show no evidence of physical failure and shall meet all performance requirements of this specification at room temperature (plus 60 to 90 degrees Fahrenheit)after having been thermally stabilized at ambient temperatures of plus 160 degrees and minus 65 degrees Fahrenheit.

3.6 Input knob.- The input knob shall rotate in a clockwise direction for values of "up" and in a counterclockwise direction for values of "down" spot corrections.

3.7 Torque.- The torque required for rotation of the input knob shall be between 10 and 20 ounce-inches through the full range of travel at the temperatures specified in 3.5.2. Slippage of the knob shall occur between 2 and 3 pound-inches.

3.8 Counter.- The spot correction counter shall be capable of rotating to at least 249 meters in either direction from zero. One revolution of the right digit counter shall indicate a change of 10 meters.

3.9 Drum dial.- The drum dial shall indicate from 0 to 50 meters in either direction from zero.

3.10 Illumination of counter and drum dial.- The lamps for the windows of the counter and drum dial shall be energized from a 28 volt dc source and shall provide enough illumination to make the drum dial and counter readings legible throughout the entire ranges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

3.11 Backlash.- The backlash of the counter gear train shall be no greater than 1.5 times the smallest subdivision on the counter dial.

3.12 Reset push-button.- The drum dial shall be capable of being reset to zero by a reset push-button without affecting either the input sum appearing on the counter or the electrical output signal.

3.13 Electrical.

3.13.1 Circuitry. Circuitry shall be in accordance with electrical schematic, Drawing D8643862.

3.13.2 Reference voltages.- The reference voltages supplied shall be 2.5 volts, 400 cycles per second, phased instantaneously positive and negative as referred to a common ground and shall be applied to the upper and lower limits of the spot correction variable resistor respectively.

3.14 Electrical and mechanical output accuracy.- The electrical output signal shall be linearly proportional to the mechanical angular rotation of the spot correction unit variable resistor when loaded with 250,000 ohms plus or minus 0.5 percent from wiper to center tap of the variable resistor. The spot correction unit shall meet the conditions and requirements specified in Table I, when energized with plus or minus 2.5 volts, 400 cps.

TABLE I

Counter Reading(meters)	Output Voltages(volts)	Tolerance (millivolts)
249 ± 0.5*	2.490	± 10
200 ± 0.5*	2.000	± 10
100 ± 0.5*	1.000	± 10
0 ± 0.5	0	± 10
100 ± 0.5**	1.000	± 10
200 ± 0.5**	2.000	± 10
249 ± 0.5**	2.490	± 10

*Counterclockwise = Down
** Clockwise = Up

3.15 Alinement and calibration.- Alinement and calibration of all spot correction units shall be determined using the same power source to insure uniformity of product. The reference voltages supplied shall be from a power source maintained as a standard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

3.16 Identification marking.- Unless otherwise specified, identification marking shall be in accordance with Standard MIL-STD-130.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's quality assurance system.- The contractor shall provide and maintain an adequate quality assurance system acceptable to the Government covering the supplies under the contract. A current written description of the system shall be submitted to the contracting officer prior to initiation of production. The written description will be considered acceptable when it provides:

(a) The quality assurance required by the applicable drawings and specifications listed in the contract or order.
(b) Contractor's quality standards of acceptability.
(c) Procedure for continually evaluating product quality.
(d) Procedure for continually reporting evidence of actual product quality.
(e) Measures for preventing any significant departure of product quality from standards.

4.1.1 The contractor shall notify the Government of and obtain approval for any change to the written procedure that might affect the degree of assurance required by this specification and other applicable documents referenced herein.

4.2 Government verification.- All quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification shall consist of: (a) surveillance of the operations to determine whether the practices, methods, and procedures of the written plan are being properly applied, and (b) Government product inspection to measure quality of product offered for acceptance. Deviations from the prescribed or agreed-upon procedures, or instances of poor practices which might have an affect upon the quality of the product will be immediately called to the attention of the contractor. Failure of the contractor to promptly correct deficiencies discovered shall be cause for suspension of acceptance until corrections have been made or until conformance of product to prescribed criteria has been demonstrated. To avoid interference with operations, the contractor shall designate a responsible official or officials to whom the Government inspector will report such instances.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

4.3 Contractor's inspection system.- Contractor's inspection and Government verification of contractor's inspection shall be in accordance with Specification MIL-I-45208.

4.4 Production model.- Unless otherwise specified in the contract, one spot correction unit shall be selected by the Government inspector as soon as practicable after the start of production, and be inspected by the contractor under the surveillance of the Government. This inspection shall be conducted at the contractor's facility, or Government approved laboratory, using test equipment authorized for use on the contract. The model shall be inspected for all requirements of this specification by utilizing examination and testing methods prescribed herein.

4.4.1 Production model failure.- Should the production model fail to pass the prescribed tests, the contractor shall cease those operations which are causing the rejection and shall make the necessary corrections. When corrections in the process have been made, a new production model shall be examined and tested by the contractor under the surveillance of the Government. Acceptance of production lots will not commence until an acceptable production model is submitted and corrective actions have been taken to eliminate deficiencies.

4.5 Lot formation.- Inspection lot sizes and lot formation shall be in accordance with Standard MIL-STD-105.

4.5.1 Defective units and lots shall be processed as specified in Standard MIL-STD-105.

4.6 Inspection of components.- All positional and functional characteristics shown on the drawings contained in the contract shall be inspected by the contractor for conformance with drawing requirements prior to acceptance. These characteristics are defined as drawing requirements affecting concentricity, squareness, parallelism, micro-finishes 64 RMS or better, threads, identification marking, and all dimensions on which the tolerances indicate a precision requirement that have a bearing on the functional accuracy and performance of the spot correction unit. Also included in the above category are all performance requirements specified in notes directly on the drawings, or in separate performance specifications referenced therein.

4.6.1 Sampling inspection.- Sampling inspection of components may be used in lieu of 100 percent inspection, and shall be in accordance with Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

TABLE II - SAMPLING PLAN

Lot Size Inclusive	Sample Size	Accept Lot	Reject Lot
0 - 25	Use 100% Inspection		
26 - 35	20	0	1
36 - 50	25	0	1
51 - 150	30	0	1
151 - 300	30	1	2
301 - over	60	2	3

4.6.2 Disposition of non-conforming product.- Acceptance and rejection numbers are expressed in terms of defective units. One or more defects on any unit shall constitute a defective unit. Disposition of non-conforming components shall be in accordance with Standard MIL-STD-105.

4.7 Material.- Control of material shall be in accordance with Tests Data requirements of Specification MIL-I-45208.

4.8 Inspection equipment.- Supply, calibration, maintenance and use of inspection equipment shall be in accordance with Specification MIL-I-45208.

4.8.1 Accuracy requirements.- Inspection equipment which incorporates features for measuring values or sizes established by product requirements shall be capable of measuring those values within an accuracy of ten percent of the specified tolerance, except as otherwise specified. In cases where the ten percent accuracy imposes impractical or very difficult design and fabrication problems, or results in a test equipment cost factor which is exorbitant in relation to the cost and application of the product to be inspected, the Goverhment shall be expeditiously advised in order that necessary appropriate action can be taken.

4.8.2 Accuracy requirements for special testing devices.

4.8.2.1 Device to test vibration requirements.- The device shall consist of a vibrating machine which will produce motion as specified. It shall be equipped with a medium capable of holding the unit securely to the vibrating machine in the specified positions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

4.8.2.2 Devices to test torque.- The device shall consist of a torque wrench type tester which will permit reading in both the clockwise and counterclockwise directions with a minimum range of from zero to twenty-five ounce-inches, the accuracy of which shall be within plus or minus one-quarter pound-inches throughout the entire zone of excursion. The device shall be equipped with an adapter to accommodate the input knob. The device for knob slippage shall be similar, but with a range of from zero to five pound-inches, the accuracies of which shall be within plus or minus one pound-inch throughout the entire zone of excursion. The device shall accommodate the same adapter.

4.9 Tests.

4.9.1 Classification of defects.- The classification of defects in Tables III and IV shall constitute the minimum inspection requirements to be performed prior to acceptance or rejection by lots. The Government reserves the right to inspect for any or all applicable requirements and to reject individual non-conforming items.

4.9.1.1 Disposition of rejected lots.- Rejected lots shall be screened for all defective characteristics. After corrections have been made and the Government inspector informed of the corrective action taken, the lots shall be resubmitted for acceptance as outlined in Standard MIL-STD-105.

TABLE III- CLASSIFICATION OF DEFECTS

Use Inspection Level L7, and Sampling Plan Table IV-A of Standard MIL-STD-105

CRITICAL: NONE DEFINED

MAJOR: AQL 4.0%	Req't Par.	QA. Par.	Test Method
101. Post vibration	3.5.1	4.9.2	Device, Special Testing (DST)
102. Operating temperatures	3.5.2	4.9.3	DST

MINOR: NONE DEFINED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

TABLE IV- CLASSIFICATION OF DEFECTS

Use Inspection Level II, and Sampling Plan Table IV-A of Standard MIL-STD-105

CRITICAL: NONE DEFINED

MAJOR: AQL 1.5%		Req't Par.	QA. Par.	Test Method
101.	Input knob	3.6	4.9.5	Standard Measuring Equipment (SME)
102.	Torque	3.7	4.9.6	Device, Special Testing ((DST)
103.	Counter	3.8	4.9.7	Visual
104.	Drum dial	3.9	4.9.8	Visual
105.	Illumination	3.10	4.9.9	SME
106.	Backlash	3.11	4.9.10	SME
107.	Reset push button	3.12	4.9.11	SME
108.	Circuitry	3.13.1	4.9.12	Visual
109.	Output accuracy	3.14	4.9.13	SME
110.	Identification marking	3.16	4.9.14	Visual

MINOR: NONE DEFINED

4.9.2 Vibration.- This test shall be conducted in accordance with Method 201 of Standard MIL-STD-202, except that the time period for applied motion in each direction shall be as specified herein. Tests and performance measurements prior to or during vibration are not required for final acceptance. Subsequent to vibration, the spot correction unit shall be subjected to a visual-tactile examination for damage. The unit shall then be subjected to all the tests in this specification.

4.9.3 Operating temperatures.- This test shall be conducted in accordance with Procedure I of Specification MIL-F-13926, except that the temperature shall not be reduced beyond condition "C" or raised beyond condition "G". When the unit is stabilized at each indicated temperature, it shall be subjected to the tests specified in 4.9.5 to 4.9.13 inclusive and shall meet the requirements specified.

4.9.4 Storage temperatures.- This test shall be conducted in accordance with Procedure II, condition "B" and "H" of Specification MIL-F-13926. Upon completion of the storage temperature cycling, the unit shall be subjected to tests specified in 4.9.5 to 4.9.13 inclusive, and shall meet the requirements specified. This test shall be performed on the production model only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

4.9.5 Input knob.- Rotation of the input knobs shall cause the counters to record the specified values. A visual check shall be made to be assured that this condition exists.

4.9.6 Torque.- This test shall be performed with the aid of special testing devices, affixed to the input knob, that shall be capable of applying torque to the knob within the ranges specified. The torque required for rotation of the input knob and for clutch slippage shall be within the values specified.

4.9.7 Counter.- A visual check shall be made to determine if the specified number of mils rotation can be made.

4.9.8 Drum dial.- A visual check shall be made to be assured that the dials can indicate as specified.

4.9.9 Illumination.- This test shall be performed with the lamps energized as specified. All graduations of the counters and drum dials shall be legible when observed, with the unaided eye, in total darkness.

4.9.10 Backlash.- Energize the unit and advance the counter to some reading; record the output signal for that reading. Continue rotation of the counter in the same direction for one revolution, then reverse rotation and return until the output signal repeats the recorded reading. The counter shall have repeated its reading within the specified tolerance.

4.9.11 Reset push-button.- This test shall be performed concurrently with the test specified in 4.9.13. Depress the reset push-button after the input knobs are rotated to each rotational position listed in Table I. This actuation of the reset push-button shall cause the drum dials to return to zero, but shall not change the input sums indicated on the counters or output voltage values.

4.9.12 Circuitry.- A visual check shall be made to be assured that the circuits conform to the prescribed electrical schematics.

4.9.13 Electrical and mechanical output accuracies.- This test shall be performed with the required voltages and resistance applied as specified. Rotation of the spot correction variable resistors shall be performed with backlash excluded for direction of travel. When the counter readings of Table I are obtained, the measured output voltage values shall be within the tolerance specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

4.9.14 Identification marking.- Marking shall be visually inspected for conformance to Standard MIL-STD-130.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing.- The spot correction shall be cleaned, preserved, packaged, packed, and marked in accordance with Specification MIL-F-14619 P8534. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The spot correction unit, down-up, is a functional plug-in subassembly of the gun direction computers (see 1.1). It is intended to receive a manual input of observer down-up spot correction and record it on a total correction counter. This counter will continuouslytotal down-up spot corrections as they are added or subtracted in problem computation. Each change in spot correction will also appear on a drum dial so that each increment of spot correction remains recorded until changed by the computer operator. In use, the operator resets the drum dial to zero by depressing the reset button before inserting a change in spot correction. Resetting the drum dial does not affect the total correction appearing on the total correction counter; nor does it affect the electrical output signal.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification
(b) Selection of applicable level of preservation, packaging and packing
(c) Applicable stock number
(d) Provisions for production model including date of delivery (see 3.1)

6.3 Design information.- Information regarding specific design not covered or referenced by this specification may be obtained from the procuring activity upon the specific request of the contractor.

6.4 Definitions.

6.4.1 Device, special testing (DST).- Special testing devices are defined as special inspection fixtures, instruments, and modified SME.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

6.4.2 Standard measuring equipment (SME).- Standard measuring equipment (SME) includes the common hand-type measuring devices which are usually stocked by commercial supply houses for ready supply (shelf items), and which are normally used by an inspector to perform dimensional inspection of items under procurement. This category also includes commercial testing equipment such as meters, optical comparators, etc.

6.4.3 Tactile.- Skillful manipulation or sensing.

6.4.4 Production model.- A model in its final mechanical and electrical form of final production design made by production methods, tools, jigs, and fixtures.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any invention that may in any way be related thereto.

Custodian:

Army Ord

Preparing activity:

Army-Ordnance

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.