MIL-T-45603(Ord)
AMENDMENT 3
29 June 1962

MILITARY SPECIFICATION

TIMER, INTERVAL TD-114/M

This amendment forms a part of Military Specification MIL-T-45603(Ord), dated 31 December 1958.

Page 1, paragraph 2.1: Delete all under "SPECIFICATIONS" and substitute the following:

"Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-F-14619	Fire Control Parts, Equipment and Tools; Packaging of"

Page 1, paragraph 2.1, under "STANDARDS": Delete "MIL-STD-129" and "MS 20003", and add "MIL-STD-130 - Identification Marking of U.S. Military Property".

Page 2, paragraph 2.2: Delete in its entirety.

Page 3, paragraph 3.4: Delete and substitute the following:

"3.4 Environmental.

3.4.1 Vibration.- The timer shall be subjected to a simple harmonic motion having an amplitude of 0.015 inch (0.03 inch maximum excursion). The frequency shall be varied uniformly between the limits of 10 and 55 cycles per second and return to 10 cycles and shall be traversed in approximately 1 minute. This motion shall be applied for a period of 10 minutes in each of the 3 mutually perpendicular directions (total of 30 minutes). Subsequent to vibration the delay timer shall not be damaged or adversely affected and shall meet all requirements of this specification.

FSC 1285

Amd 9

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:33Z
Check the source to verify that this is the current version before use.

3.4.2 Operating temperatures.- The timer shall meet all the performance requirements of this specification when thermally stabilized at ambient temperatures of minus 40 degrees and plus 150 degrees Fahrenheit.

3.4.3 Storage temperatures.- The timer shall show no evidence of physical failure and shall meet all performance requirements of this specification at standard ambient temperature (plus 60 to 90 degrees Fahrenheit) after having been thermally stabilized at ambient temperatures of plus 160 degrees and minus 80 degrees Fahrenheit."

Page 3: Add paragraph 3.6 as follows:

"3.6 Identification marking.- Unless otherwise specified, identification marking shall be in accordance with Standard MIL-STD-130."

Page 5: Delete "TABLE III" and "TABLE IV" in their entirety.

Page 5, paragraph 4.2.2.2: Delete in its entirety.

Page 5, paragraph 4.2.3, line 3: Delete "Tables I, II and III" and substitute "Table I".

Page 6, paragraph 4.3.4.3, line 4: Delete "33 ± 7 seconds.", and substitute "22 ± 2 seconds.".

Page 7, paragraph 4.3.4.3.1, line 4: Delete "Switches S1 and S2", and substitute "Switch S2".

Page 7, paragraph 4.3.4.3.2: Delete and substitute the following:

"4.3.4.3.2 Switches S1 and S2 shall be set at position 1, and Switches S3 and S4 at position 2. The circuit shall be interrupted by operating Switch S4 to position 1 and then back to position 2. The same re-operate time limits shall apply, using the same interrupt time specified in 3.3.2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:33Z
Check the source to verify that this is the current version before use.

Page 7, paragraph 4.3.5: Delete in its entirety, and substitute the following:

"4.3.5 Environmental.

4.3.5.1 Vibration.- The timer shall be mounted on the vibration table in its normal mounting or operating position, and it shall be vibrated successively in each of the three (3) mutually perpendicular directions, that are parallel respectively to the edges of the equipment. The vibration shall be at an amplitude, duration and frequency specified in 3.4.1. At the conclusion of test, the timer shall be visually inspected for physical damage and shall meet the requirement specified in 3.4.1.

4.3.5.2 Operating temperatures.- This test shall be performed with the aid of a cold chest and an oven capable of maintaining the temperatures specified. When thermally stabilized, the timer shall be tested for compliance with 3.4.2.

4.3.5.3 Storage temperatures.- The timer shall be inspected at standard ambient temperature after having been thermally stabilized at the extreme temperatures specified. The timer shall be visually examined for physical damage and shall meet the requirements specified in 3.4.3."

Page 7, paragraphs 4.3.6, 4.3.6.1 and 4.3.6.2: Delete in their entirety.

Page 7, paragraph 4.3.7, line 2: Delete "and 5.5".

Page 7: Add paragraph 4.3.8 as follows:

"4.3.8 Identification marking.- The identification marking shall be visually inspected for compliance with Standard MIL-STD-130."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:33Z
Check the source to verify that this is the current version before use.

Page 8, Section 5: Delete in its entirety and substitute the following:

"5. PREPARATION FOR DELIVERY

5.1 Packaging and packing.- The timer shall be cleaned, preserved, packaged, packed, and marked in accordance with Specification MIL-F-14619 P7588. The level of protection shall be as specified in the procurement document."

Page 14, Figure 2: Delete

Custodian:

Army-Ord

Preparing activity:

Army-Ord

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:33Z
Check the source to verify that this is the current version before use.