MIL-B-43386B

16 August 1976

SUPERSEDING
MIL-B-43386A
25 September 1968

MILITARY SPECIFICATION

BINS, INGREDIENT, MOBILE, 150 and 250-POUND CAPACITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers stainless steel mobile storage bins with slide covers, 150 and 250-pound capacity.

* 1.2 Classification. Mobile ingredient storage bins shall be of the following sizes (see 6.2 and 6.3).

Size 1 - 150 pounds (68.04 kg) capacity
Size 2 - 250 pounds (113.4 kg) capacity

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

FF-C-77 - Casters, Rigid and Swivel (Institutional Duty).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Natick Research and Development Command, ATTN: DRXNM-TDG, Natick, MA 01760 by using self-addressed Standardization Document Improvement Proposal (DD Form 146) appearing at the end of the document or by letter.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:18Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-B-2316 - Bakery Equipment, Including Units Assemblies, Repair Parts and Tools, Preparation for Delivery of.

STANDARD

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of specifications and standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat Resisting Chromium-Nickel Steel Plate, Sheet, and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation; NSF Building, Ann Arbor, MI 48105.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 Standard product. The ingredient bins shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.2 Codes and standards. The ingredient bins shall comply with the applicable requirements of NSF Standard No. 2.

3.2.1 Compliance. Prior to commencing production, the contractor shall submit to the contracting officer, or his authorized representative, satisfactory evidence that the ingredient bins he proposes to furnish under this specification meet the applicable requirements of NSF Standard No. 2. Satisfactory evidence of compliance with this requirement shall be any of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished ingredient bin, or

(2) A certification for the ingredient bin issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the ingredient bins are being procured, indicating that the ingredient bins have been tested and conform to NSF.

3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer for ingredient bins, provided the completed item complies with all provisions of this specification.

3.3.1 Stainless steel. Stainless steel shall conform to any of the 300 series of ASTM A 167.

3.4 Design and construction. The ingredient bin shall be of the full open type, fabricated of stainless steel specified in 3.3.1. The ingredient bin shall consist of a body with a sliding type cover, mounted on casters.

3.4.1 Body. The body for the mobile ingredient bins shall conform to the dimensions specified in table I. The top edge of the bin body shall have a rolled edge to form a slide and a stop for the cover. The body shall be encompassed by a 1-inch (25.4 mm) bumper sealed to the body. The bottom exterior surface of the bin body shall be reinforced for caster mounting. All corners

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

shall have a minimum radius of 1-inch (25.4 mm). Welded seams, when applicable, shall be continuous and finished to the continuity and finish of the bin body. A plate to hold an identification card or label shall be attached to the front end of the bin body. The bin body, when filled with water, shall not leak when tested as specified in 4.4.1. The bin body shall not deflect or bulge more than 1/4-inch (6.35 mm) or permanently deform, when tested as specified in 4.4.2. The ingredient bin shall be fabricated with or without seams from stainless steel specified in 3.3.1. The bin body shall have a minimum thickness of 0.0375 inch (0.94 mm) after fabrication.

TABLE I. Dimensions

	Size 1 150 pounds capacity Maximum (inches)	Size 2 250 pounds capacity Maximum (inches)
Length (overall including bumper)	29 (.737 m)	29 (.737 m)
Width (overall including bumper)	22 (.559 m)	25 (.635 m)
Height (including casters and cover)	30 (.762 m)	30 (.762 m)
Bumper (height from floor)	11-1/4 (.286 m)	11-1/4 (.286 m)

3.4.2 Cover. The sides and one end of the sliding bin cover shall be rolled to conform to and slide on the top rolled edge of the ingredient bin body. The end of the sliding bin cover opposite the rolled end shall be turned up to form a grip edge. The cover shall be reinforced to withstand a 150-pound (68.04 kg) uniformly distributed load when in closed position without permanent deformation, when tested as specified in 4.4.3. The cover when closed shall completely cover the full bin opening. The cover shall be fabricated from a single piece of stainless steel specified in 3.3.1.

* 3.4.3 Casters. The ingredient bin shall have four casters attached to the body. Casters shall conform to type II, class A, 4-inch diameter wheels, style C, hard rubber or polyurethane thread, mounting optional and NSF listed of FF-C-77.

3.5 Welding. Exposed welds shall be sound and ground smooth. All surfaces shall be free from oxide, grease, or other foreign matter. All welds shall be continuous, sound, smooth and free from flash, porosity, cracks, incomplete fusion, undercut, or deformation of material. All scale or flux deposits (when flux is used) shall be removed from the finished welds.

3.6 Marking for identification. The ingredient bin shall be marked with the manufacturer's name or trade name or trademark of such known characters as to be readily identifiable with the manufacturer.

* 3.7 Finish. Finish shall comply with the applicable requirements of NSF Standard No. 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. All kinks, bends, and winds shall be removed from sheet metal used in the fabrication of the ingredient bin. The ingredient bins shall be clean and not contain any rough and sharp edges, burrs, slivers, or scratches; and shall be free from rough grind, die or trimming marks, rust or scale. Welding shall be accomplished in a manner that will prevent the occurrence of pits or flashes. The finished item shall not be fractured, buckled, bent, dented, punctured, or malformed. When bolts, nuts or other fasteners are used they shall be drawn up tight.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End product inspection. The inspection lot shall be all mobile ingredient bins of one capacity offered for inspection at one time. The sample unit shall be one completely fabricated mobile ingredient bin.

* 4.2.2.1 Visual examination. The ingredient bins shall be examined for the defects in table II. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Construction and workmanship (applicable to all components and assemblies)	Component missing.	X	
	Any burr, sliver, sharp edges, rough die, tool, gouge, trim or grind marks.	X	
	Any component fractured, buckled, bent, dented, punctured, or malformed.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Body	Identification card or label plate holder not attached.	X	
	Bumper not sealed to bin body.	X	
	Edge not rolled for cover.	X	
	Not reinforced for caster mounting.	X	
	Not joined properly at seams.	X	
Cover	Does not fit or slide on bin body.	X	
	Not reinforced.	X	
	One end not turned up to form a grip edge.	X	
Casters	Not swivel type.	X	
	Not roller or ball bearing type.	X	
Welding (when applicable)	Surfaces not ground smooth.	X	
	Not free from oxide, scale, grease or other foreign matter.	X	
	Not continuous, sound, smooth, or free from flash, porosity, cracks, incomplete fusion, undercut, or deformation of material.	X	
	Flux not removed.	X	
Bolts, nuts, screws, studs, and other types of threaded fasteners	Missing, broken, stripped, fractured, or loose.	X	
Identification marking	Missing, incomplete, or illegible.		X

4.2.2.2 Dimensional examination. Inspection shall be made of the mobile ingredient bin to determine compliance with dimensions specified. Any deviation from specified requirements shall constitute a defect. The inspection level shall be level S-2 and the AQL shall be 4.0 defects, expressed in terms of defects per hundred units.

* 4.2.2.3 End item testing. The end item shall be tested as specified in 4.4.1 through 4.4.3. The inspection level shall be S-2 with an AQL of 6.5 defects, expressed in terms of defects per hundred units. Any nonconformance shall be cause for rejection of the unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

4.2.3 Examination of packaging. Preservation, packaging, packing and marking shall be inspected in accordance with the quality assurance provisions in MIL-B-2316.

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the requirements of 3.2, shall be examined and validated.

4.4 Test methods.

4.4.1 Leak and capacity tests. The completed mobile ingredient bin shall be filled to capacity with water. The bin shall be examined for leaks to determine compliance with water tightness requirements of 3.4.1. Any nonconformance to meet the leak and capacity requirements shall constitute failure of this test.

4.4.2 Deformation test. After the test specified in 4.4.1 has been accomplished the liquid filled bin shall stand in one place for 8 hours. The ingredient bin shall then be emptied and examined for deflection and deformation to determine compliance with 3.4.1. Any nonconformance to meet the deformation requirements specified shall constitute failure of this test.

4.4.3 Cover test. The cover shall be inserted into its normally closed position on the ingredient bin and uniformly loaded with 150 pounds (68.04 kg) for 2 minutes. The load shall be removed and the cover examined to determine compliance with 3.4.2. Failure to meet the cover test requirements shall constitute failure of this test.

5. PACKAGING

5.1 Packaging requirements. Preservation, packaging, packing, and marking for each level of protection shall be in accordance with the applicable requirements of MIL-B-2316 (see 6.2).

6. NOTES

6.1 Intended use. The ingredient bins are intended for use in dining facilities. The mobile ingredient bins shall be used for storage and transporting of dry bulk, meats, and liquids. The bins are normally used in conjunction with food preparation tables in MIL-T-2256, except those food preparation tables supplied with undershelving.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size of ingredient bin required (see 1.2).
(c) Selection of the applicable level of preservation and packaging, and packing (see 5.1).

6.3 Classification data. The type I aluminum and type III plastic ingredient bins are no longer required and have been deleted from this specification. The 150 pound stainless steel ingredient bin has been added to this specification.

6.4 Changes from previous issue. The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Army - GL

Project No. 7320-0382

Review activities:

Army - MD
Navy - MC, SA

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-B-43386 Bins, Ingredient, Mobile, 150 and 250-Pound Capacity

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:18Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

DRXNM-TD G

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S. MAIL

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD
Natick, MA 01760

NATICK OP 1 Apr 76

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.