MIL-B-43395A
28 May 1981
SUPERSEDING
MIL-B-43395
6 January 1966

MILITARY SPECIFICATION

BELL, SANCTUS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers one type and size of sanctus bell.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-C-320	-	Chromium Plating (Electrodeposited)
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-676	-	Boxes, Setup
PPP-C-843	-	Cushioning Material, Cellulosic

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 9925

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

DRAWING

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

14-1-16 - Bell Sanctus; Assembly

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

U.S. DEPARTMENT OF COMMERCE, NATIONAL BUREAU OF STANDARDS

Handbook H-28 - Screw-Thread Standards for Federal Services

(Application for copies of Handbook H-28 should be addressed to Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.3), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.3).

* 3.2 Materials. The materials (see 6.4) used shall conform to the applicable specifications and requirements specifed hereinafter. When materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice.

* 3.2.1 Brass and bronze. The brass for the handle shall be a commercial brass and the bronze for the gong shall be of the type normally used for bells and gongs in accordance with the manufacturer's commercial practice.

3.2.2 Brass chain. The brass chain shall be standard commercial jack chain, 0.062 inch diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

3.3 Construction. The sanctus bell covered herein shall conform to the requirements of this specfication and Drawing 14-1-16. The handle shall be screwed into the gong assembly and drawn up tight. The tongue shall be attached to the handle by means of a chain consisting of three single jack chain links as specified in 3.2.2. The gong shall be fabricated of bronze and the handle shall be fabricated from brass specified in 3.2.1. The tongue shall be fabricated from cast iron.

3.3.1 Threaded parts. The threads of the handle and gong shall conform to Handbook H-28.

* 3.4 Finish. The sanctus bell shall be chromium plated in accordance with class 1, type I of QQ-C-320.

3.5 Workmanship. The completely fabricated sanctus bell shall conform to the quality of product covered by this specification. The sanctus bell shall be free from defects such as fractures, splits, dents, bows or miscasts. The finished components shall be free of sharp protrusions or edges, burrs or slivers which may cause injury to the user. Threads shall not be missing, broken or stripped.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required, it shall be examined for defects specified in 4.4.2.1 and 4.4.2.2. The presence of any defect shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

* 4.4.2 End item inspection. The end item shall be examined in accordance with 4.4.2.1 and 4.4.2.2. The lot shall consist of all sanctus bells offered for inspection at one time. The sample unit shall be one completely fabricated sanctus bell.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

* 4.4.2.1 Visual examination. The completely fabricated sanctus bell shall be examined for defects in table I. The inspection level shall be II and the acceptable quality level (AQL) shall be 2.5 major and 6.5 total (major and minor combined) defects per hundred units.

TABLE I. Visual defects

Examine	Defect	Classification Major	Minor
Finish	Not chrome plated	X	
Construction and workmanship (applicable to all components and assemblies)	Any fractures, splits, bows, miscasts, or dents	X	
Handle	Loose in gong	X	
Chain	Not single jack type links		X
	Not three links	X	
Threaded parts	Not type specified		X
	Threads, broken, missing, or stripped	X	

4.4.2.2 Dimensional examination. Examination shall be made of the sample unit to determine compliance with dimensions specified. Any noncompliance with a specified requirement shall constitute a defect. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

4.4.3 Packaging inspection. An examination shall be made to determine that perservation, packing, and marking comply with the section 5 requirements. Defects shall be scored as indicated in table II. The sample unit shall be one shipping container fully packaged. The lot shall be the number of containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

TABLE II. Packaging defects

Examine	Defect
Markings	Missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Weight	Net weight exceeds requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

* 5.1.1 Level A. The interior of the gong of each bell shall be filled with cushioning material conforming to type II, class A of PPP-C-843 so as to immobilize the tongue. Each bell shall be unit packed in a folding or set-up paperboard box conforming to variety 1, styles III or VIII, type G, class 1 of PPP-B-566, or type I, variety 1, class A or B, style 1 or 2 of PPP-B-676, respectively. Cushioning material specified shall be used in sufficient quantity so as to provide a minimum of 1/2-inch of cushioning between the circumference of the gong and the interior surfaces of the box and to fill all voids caused by the handle. Closure shall be in accordance with appendix of the applicable box specification.

* 5.1.2 Commercial. Bells shall be preserved in accordance with MIL-STD-1188.

* 5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

* 5.2.1 Level A packing. Bells, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636. The weight of contents of each shipping container shall not exceed 65 pounds.

* 5.2.2 Level B packing. Bells, preserved as specified in 5.1, shall be packed in a snug-fitting, fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Closure shall be in accordance with method II as specified in the appendix of PPP-B-636. The weight of contents of each shipping container shall not exceed 65 pounds.

* 5.2.2.1 Weather-resistant containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

* 5.2.3 Commercial packing. Bells, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

* 5.3 Marking. In addition to any special marking required by the contract, unit packs and shipping containers shall be marked in accorance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

* 6.1 Intended use. The sanctus bell is intended to be used at religious services.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When a first article is required (see 3.1, 4.3, 6.3).
(c) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 First article. When a first article is required, it shall be inspected and approved under appropriate provisions of DAR 7-104.55. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.2).

Custodians:

Army - GL
Navy - PE
Air Force - 28

Preparing activity:

Army - GL

Project No. 9925-0187

Review activity:

Armed Forces Chaplains Board

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-B-43395A Bell, Sanctus

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/3489 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.