MIL-C-43369A

10 May 1976

SUPERSEDING
MIL-C-43369
30 September 1965

MILITARY SPECIFICATION

CONTAINER ASSEMBLY, SAMPLE AND SPECIMEN SHIPPING, BOX TYPE, FOR MEAT AND DAIRY PRODUCT SAMPLES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a container assembly consisting of a paperboard mailing case and a metal can insert.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-96	-	Cans, Metal, 28 Gage and Lighter

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U.S. Military Property

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 8115

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:16Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial container, provided the completed item complies with all provisions of this specification.

3.2 Design and construction.

3.2.1 Can insert. The metal can insert shall conform to type V, class 2, 0.25-pound electrolytic tinplate, exterior coating Plan A of PPP-C-96. The can shall be round, with compound-lined, double-seamed ends, and shall meet the leakage test requirements for closure as specified in PPP-C-96.

3.2.2 Mailing case. The mailing case shall be fabricated from 0.030 inch thick nontest paperboard conforming to variety 1, style II, type D, class a, with notched tuck ends of PPP-B-566.

3.3 Dimensions.

3.3.1 Can insert. The can insert shall have the following dimensions.

3.3.1.1 Diameter. The outside diameter shall be 3-3/8 inches.

3.3.1.2 Height. The overall height shall be 3-7/8 inches.

3.3.2 Mailing case. The mailing case shall have the following inside dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:16Z
Check the source to verify that this is the current version before use.

3.3.2.1 Length. The length shall be 3-3/8 inches.

3.3.2.2 Width. The width shall be 3-3/8 inches.

3.3.2.3 Height. The height shall be 3-7/8 inches.

3.3.3 Tolerances. The tolerances allowed for the can insert and mailing case shall be one eight of an inch and be in consonance, one with the other, so that when the two are assembled, the mailing case will not bulge, nor will the can insert rattle within the mailing case.

3.4 Marking for identification. Each mailing case shall be marked for identification in accordance with MIL-STD-130. Marking shall be confined to one side of the mailing case.

3.5 Assemblies. The bottom flaps of the mailing case shall be closed with the notched tucks firmly engaging the flaps. The cover shall be loosely placed on top of the can insert and the can insert placed within the mailing case. The top flaps of the mailing case shall be loosely closed without engaging the notched tucks.

3.6 Workmanship. The container assembly shall conform to the quality and grade of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may utilize his own or any other facilities suitable for the performance of inspection requirements specified herein unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall consist of all the container assembly offered for inspection at one time. The sample unit for this inspection shall be one completely assembled container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:16Z
Check the source to verify that this is the current version before use.

4.2.2.1 Visual examination. Examination shall be made of the end item for defects set forth in table I. The inspection level shall be level S-3 with an acceptable quality level (AQL) of 2.5 for major defects and 10.0 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Can			
Shape and seams	Not round, not compound lined, double seamed ends	X	
	Cover missing or not on top of can	X	
Mailing case	Bottom flaps not secured as specified	X	
	Top flaps not closed as specified (see 3.5)		X

4.2.2.2 Dimensional examination. Inspection shall be made of the sample unit to determine compliance with dimensions specified. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-3 and the AQL shall be 4.0 defects, expressed in terms of defects per hundred units.

4.2.3 Examination of packaging. An examination shall be made to determine that the packing and marking as required by section V of this specification are complied with. Defects shall be scored in accordance with defects set forth in table II. The sample unit shall be one shipping container fully prepared for delivery except it need not be closed. The lot shall be the number of containers offered for delivery at one time. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

TABLE II. Examination of packaging

Examine	Defect
Markings (exterior)	Omitted, incomplete, incorrect, illegible or of improper size, location, sequence or method of application.
Materials	Any component missing, damaged or not as specified.
Contents	More or less than specified container assemblies per pack.
	Loose in shipping container.
Workmanship	Bulging or distortion of containers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:16Z
Check the source to verify that this is the current version before use.

4.2.3.1 Examination of shipping container. When shipping containers are required to comply with PPP-B-636, examination for defects in the closure, waterproofing and reinforcing, shall be in accordance with the appendix of PPP-B-636.

5. PACKAGING

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Seventy-two container assemblies shall be packed in a snug-fitting shipping container conforming to style RSC, grade V2s of PPP-B-636. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.1.2 Level B. Seventy-two container assemblies shall be packed in a snug-fitting shipping container conforming to style RSC, type CF, (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.1.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.1.3 Level C. Container assemblies, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall comply with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The container assembly described herein is intended for use by food inspection personnel for the collection and shipment of meat and dairy product samples from the field to military laboratories for analysis. The assembly is considered a one-time-use item.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Selection of applicable level of packing (see 5.1).
c. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:16Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - SA
Air Force - 69

Review activities:

Army -GL
Navy - MS
Air Force - 03

Preparing activity:

Army - GL

Project No. 8115-0392

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:16Z
Check the source to verify that this is the current version before use.

APPENDIX

REQUIREMENTS FOR CLOSURE AND MARKING OF FILLED CONTAINERS

10. SCOPE

10.1 This appendix covers requirements for closure of the container assembly when shipping via U. S. Mail.

20. APPLICABLE PUBLICATIONS. The following document forms a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

US Postal Service Manual

(Copies of the manual may be obtained from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

30. CLOSURE AND MARKING. The can insert and marking case shall be closed and marked in accordance with the requirements in the US Postal Service Manual.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-C-43369A Container Assembly, Sample and Specimen Shipping Box Type, for Meat and Dairy Product Samples

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 20260-21T21:16Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

US ARMY NATICK DEVELOPMENT [redacted] Research & Development Command

NATICK, MA 01760

OFFICIAL BUSINESS

PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S. MAIL

[redacted] DRXNM-TDG

Commander
US Army Natick [redacted] Research & Development
ATTN: [redacted] DRXNM-TDG Command
Natick, MA 01760

NATICK OP 1 MAY 75

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:16Z
Check the source to verify that this is the current version before use.