MIL-C-43391A
12 February 1973

SUPERSEDING
MIL-C-43391
28 December 1965

MILITARY SPECIFICATION

CONTAINER ASSEMBLY, SAMPLE AND SPECIMEN SHIPPING, BOX TYPE

FOR AVIATION FUELS AND LUBRICATING OILS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a container assembly consisting of a fiberboard box and a one-gallon metal can insert.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

UU-T-81	-	Tags, Shipping and Stock
PPP-B-636	-	Box, Shipping, Fiberboard
PPP-C-96	-	Cans, Metal, 28-Gage and Lighter

STANDARDS

FEDERAL

FED-STD-595	-	Colors

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

FSC 8115

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 61616.)

American Society For Testing And Materials (ASTM)

D270 - Standard Method of Sampling Petroleum and Petroleum Products

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 Materials.

* 3.1.1 Can. The can shall be an oblong, liquid tight can, provided with a bridge handle, having a capacity of one gallon, conforming to type V, class 4 of PPP-C-96 except as specified herein. Top, bottom, and side seams shall be soldered on the outside of the can. Seams shall not be compound lined. The inside diameter of the pour opening shall be not less than 1-3/8 inches. Tinplate shall be either 1.00 electrolitic or 1.25 hot dipped. The exterior shall be coated plan B except that commercial lacquer or enamel may be used. The color shall be yellow matching color No. 13538 of FED-STD-595. The handle and screw cap may be coated. The

Source: https://assist.dla.mil -- Downloaded: 20260-21T21:18Z
Check the source to verify that this is the current version before use.

overall dimensions of the can shall be 6-1/2 ± 1/4 inches by 4-1/8 ± 1/8 inches by 9-1/2 ± 1/8 inches excluding the handle and screw cap. The interior of each can shall be cleaned in accordance with ASTM D270.

* 3.1.2 Fiberboard box. The fiberboard box shall conform to style RSC V3c of PPP-B-636. The box shall be provided with a top and bottom pad made of the same material as the box. The bottom pad shall be flat and have dimension 1/8 inch less than the box interior. The top pad shall be a folded or built up pad to provide a minimum 1/8 inch clearance between the handle of the can and the interior surface of the inner top flaps of the box. The box size shall be such that the can fits without bulging the box nor allows more than 1/8 inch clearance between the can and any interior surface of the box with the pads in place.

* 3.1.3 Label. The label shall be of commercial white paper having a smooth surface suitable for writing on with ink, indelible pencil, general writing pencils, or ball point pens, and be not less than 4 inches wide and 4-1/2 inches long. A write-in space of at least 2 inches shall be provided for each line on the label. Printing shall be as follows:

"Activity submitting sample - - - - - - - - - - - - - - - -
Date sample taken -
Grade or type of product - - - - - - - - - - - - - - - - -
Fuel received from - - - - - - - - - - - - - - - - - - -
Sample taken from -
Type of sample -
Name of sampler -
Sample identification - - - - - - - - - - - - - - - - -
Remarks - "

* 3.1.4 Tag. The tag shall conform to type B class 2 of UU-T-81 and be marked the legend "THE INTERIOR OF THIS CAN HAS BEEN CLEANED IN ACCORDANCE WITH ASTM D 270".

* 3.2 Assembly.

3.2.1 Can. The screw cap shall be secured in place finger tight. The label specified in 3.1.3 shall be affixed to the main panel of each can with commercial water resistant adhesive. A tag (see 3.1.4) shall be secured to the handle of each can.

* 3.2.1.1 Can marking. Each can shall be marked with the words "FUEL AND LUBRICATING OIL SAMPLE CAN" with letters not less than 1/2 inch in height. Marking may be by any commercial means using commercial, noncorrosive, gasoline and waterproof ink. The marking shall be placed directly on the can above the label (see 3.1.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

* 3.2.2 Box. The bottom flaps of the fiberboard box shall be closed method III or IV of the appendix to PPP-B-636. The can and fiberboard pads shall be placed within the box, the top flaps of the box loosely closed and the outer flaps may be secured with a piece of tape.

* 3.3 Workmanship. The applied label shall not be wrinkled. The markings shall be legible, and not smear or rub off.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Inspection. Sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

* 4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

* 4.2.1.1 Testing of materials. Testing of materials shall be as specified in the applicable specification.

4.3 Inspection of the end item.

* 4.3.1 Examination of the end item. Examination of the end item shall be in accordance with the classification of defects set forth in table I and the inspection level shall be S3 and Acceptable Quality Level (AQL) shall be 10, expressed in terms of defects per hundred units. The sample unit for this examination shall be one complete container assembly. The lot size shall be expressed in terms of the applicable sample unit for purposes of determining the sample size.

Source: https://assist.dla.mil -- Downloaded: 20260-21T21:18Z
Check the source to verify that this is the current version before use.

TABLE I. Examination of end item

Characteristic	Defect
Can	Not type or class specified. Not size or capacity specified. Not oblong. Not liquid tight. Not handle specified. Pour opening less than 1-3/8 inch. Color not as specified. Not clean. Screw cap missing or not secured.
Label and marking	Marking missing, not as specified or wrong location. Missing. Not secured. Not smooth surface suitable for writing. Size less than 4 X 4-1/2 inches. Writing space less than 2 inches. Printing missing or not as specified.
Tag	Not type and class specified. Missing. Legend missing or not as specified.
Fiberboard box	Not type, style, or grade specified. Pads missing or not as specified. Box size not as specified. Method of closure not as specified.
Workmanship	Label wrinkled. Marking illegible, smeared, or rubbed off.

4.3.1.1 Examination for packing and marking. The sample unit for this examination shall be one shipping container. The lot size shall be expressed in terms of number of sample units. Examination shall be in accordance with the classification of defects set forth in table II and the inspection level shall be S-2 and the Acceptable Quality Level (AQL) shall be 2.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 20260-21T21:18Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of the shipping container for packing and marking

Characteristic	Defect
Packing	
Container assemblies	More or less than 12 assemblies per pack.
Marking	Omitted, incomplete, incorrect, illegible, of improper size, location, sequence, or method of application.

* 4.3.2 Examination of filled and closed shipping container. When shipping containers are required to be in accordance with PPP-B-636, examination for closure and waterproofing when applicable shall be in accordance with the inspection criteria in the appendix of that specification.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Twelve container assemblies shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V3s of PPP-B-636. Each shipping container shall be closed then waterproofed with tape in accordance with the appendix of PPP-B-636. Reinforcing with steel strapping or tape banding shall not be required.

5.1.2 Level B. Twelve container assemblies shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF or SF, class domestic of PPP-B-636. Closure shall be in accordance with the appendix of PPP-B-636.

5.1.2.1 When specified (see 6.2) the container shall be grade V3c, V3s, or V4s fiberboard fabricated in accordance with PPP-B-636, and closed in accordance with the appendix thereto.

* 5.1.3 Level C. Container assemblies shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

5.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129. No marking shall be placed upon the interior boxes.

6. NOTES

6.1 Intended use. The container assembly described herein is intended to be used for forwarding of specimens of aviation fuels and lubricating oils to petroleum laboratories for analysis and testing. The container assembly is intended for use by aviation shore activities and vessels.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Selection of applicable level of packing (see 5.1).
c. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1).

6.3 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, correction, deletions,) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 69

Preparing activity:

Army - GL

Project No. 8115-0300

Review activities:

Navy - AS, SH
Air Force - 82, 84

User activities:

Army - AT
Air Force - 11, 71, 80

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

APPENDIX

REQUIREMENTS FOR CLOSURE AND MARKING OF FILLED CONTAINERS

10. SCOPE

10.1 This appendix covers requirements for closure, marking, and shipping of filled container assemblies.

20. APPLICABLE DOCUMENTS

* 20.1 The following document, of the issue in effect on date of invitation for bids or request for proposal, forms a part of this specification to the extent specified herein:

PUBLICATIONS

49CFR - Department of Transportation Regulations for Transportation of Explosives and Other Dangerous Articles.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

30. REQUIREMENTS

30.1 Closure. The screw cap shall be tightly closed on the filled metal can and the can placed within the fiberboard box with the fiberboard pads in position. The top flaps of the box shall be closed in accordance with the appendix of PPP-B-636.

30.2 Marking. The fiberboard box of each container assembly shall be marked and labeled in accordance with MIL-STD-129 and the applicable Department of Transportation Regulations.

30.3 Shipping. The container assembly shall be shipped in accordance with the applicable Department of Transportation Regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-C-43391A Container Assembly, Sample and Specimen Shipping, Box Type for Aviation Fuels and Lubricating Oils

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY NATICK LABORATORIES
NATICK, MASS. 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S.MAIL

Commander
U. S. Army Natick Laboratories
ATTN: AMXRET-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:18Z
Check the source to verify that this is the current version before use.