MIL-F-43392B
12 April 1978
SUPERSEDING
MIL-F-43392A
3 June 1968

MILITARY SPECIFICATION

FOOD CONTAINER, DELIVERY AND STORAGE; DOLLY, FOOD HANDLING EQUIPMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers aluminum and plastic food containers and platform and rack type dollies for the containers.

1.2 Classification. The food containers and food handling dollies covered herein shall be of the following items, sizes and grades (see 6.2):

Item 1 - Food Containers

Size 1 - 65 pound (29 kg) minimum meat capacity
Size 2 - 100 pound (45 kg) minimum meat capacity
Size 3 - 75 pound (34 kg) minimum meat capacity

Grade A - Aluminum
Grade B - Polyethylene plastic

Item 2 - Dollies, Food Handling, Platform Type

Size 1 - 500 pound (227 kg) minimum load capacity
Size 2 - 700 pound (318 kg) minimum load capacity

Item 3 - Dolly, Food Handling, Rack Type
150 pound (68 kg) minimum load capacity

Item 4 - Covers and False Bottom for Item 1

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7320-7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-390	-	Plastic, Molding and Extrusion Material, Polyethylene and Copolymers (Low, Medium and High Density)
FF-C-77	-	Casters, Rigid and Swivel (Institutional Duty)
QQ-A-200/8	-	Aluminum Alloy Bar, Rod, Shapes, Tube and Wire, Extruded, and Structural, Shapes, 6061
QQ-A-200/9	-	Aluminum Alloy Bar, Rod, Shapes, Tube and Wire, Extruded, 6063
QQ-A-250/1	-	Aluminum Alloy 1100, Plate and Sheet
QQ-A-250/2	-	Aluminum Alloy 3003, Plate and Sheet
QQ-A-250/8	-	Aluminum Alloy 5052, Plate and Sheet
QQ-A-250/11	-	Aluminum Alloy 6061, Plate and Sheet
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-F-320	-	Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes

STANDARDS

FEDERAL

FED-STD-601	-	Rubber, Sampling and Testing

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads for 40 inch x 48 inch Pallets

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat Resisting Chromium-Nickel Steel, Plate, Sheet and Strip
A 412 - Stainless and Heat Resisting Chromium Nickel-Manganese Steel, Plate, Sheet and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment
Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, Box 1468, Ann Arbor, MI 48106.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The food containers and dollies covered herein shall be the manufacturer's standard commercial current product, except for any changes specified herein necessary to comply with requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the currentversion before use.

3.2 Codes and standards compliance. The dolly and containers shall conform to applicable requirements of NSF No. 2.

3.2.1 NSF compliance. Prior to approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the dolly and containers he proposes to furnish under this specification meets the applicable requirements of NSF No. 2. Satisfactory evidence shall be any of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seals on the finished item, or

(2) A certification for the items issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the containers and dolly are being procured, indicating that the containers and dolly have been tested and conform to NSF No. 2.

3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer for his commerical dolly and containers provided the completed items comply with all provisions of this specification (see 6.3).

3.3.1 Aluminum.

3.3.1.1 Sheet. Aluminum alloy sheet type 1100 shall conform to QQ-A-250/1, type 3003 to QQ-A-250/2, type 5052 to QQ-A-250/8, and type 6061 to QQ-A-250/11.

3.3.1.2 Extruded. Aluminum alloy extrusions shall conform to type 6061 of QQ-A-200/8 or type 6063 of QQ-A-200/9.

3.3.2 Stainless steel. Stainless steel shall conform to type 202 of ASTM A412 or type 301 or 302 of ASTM A167.

3.3.3 Tubing. The rack type dolly frame shall be fabricated from 1 inch (25 mm) nominal stainless steel or aluminum tubing.

3.3.4 Plastic. The plastic shall be a high density, linear, polyethylene conforming to type III, class H, grade 2 of L-P-390, except that compliance with thermal stress cracking resistance and electrical tests is not required. Clean, unburned, plastic material in the form of imperfect parts, tail, neck flash, or other scrap of the same composition as the basic material and produced in the molding or finishing operations, may be reground and mixed with the basic material specified.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the currentversion before use.

3.3.5 Casters. The casters shall be roller or ball bearing, swivel type stem mounted and removable conform to type II, class B, style c of FF-C-77. For the platform dolly the wheel shall be 3 inches (76 mm) in diameter. For the rack type dolly, the wheel shall be a minimum of 4 inches (102 mm) in diameter.

3.3.6 Bumpers. Bumpers shall be fabricated from non-marking rubber or rubber-like materials with a Shore A Durometer hardness of 75 ± 15. They shall be round doughnut type for the legs of the rack type dolly and right-angular for the corners of the platform type dolly and of such size as to conform to design requirements of 3.4.

3.4 Design. The food containers shall be able to stack and nest. Each food container for the platform type dolly shall have a combination stacking bracket and handle at each end. When specified (see 6.2), container covers and false bottoms for drainage shall be furnished. The dollies shall be of two types, the platform and rack types. The dollies shall have four swivel type casters and bumpers as necessary to prevent damage to walls and dolly. The dollies shall be capable of easy mobility when carrying the loaded food containers. The casters shall be capable of being removed for replacement or shipment. Bumpers as specified in 3.3.6 shall be installed and positioned and of such size so that upon impact with a vertical wall only the bumper shall make contact. Bumpers shall be removable and replaceable if necessary. The dolly, including casters, shall not show any evidence of parts breakage, looseness of parts, parts separation or permanent deformation in excess of 1/8 inch (3 mm) when subjected to the obstacle and impact tests (see 4.4.3 through 4.4.5).

3.4.1 Dimensional requirements for food containers. The size 1 food container shall have minimum usable volume of 1.35 cubic feet, (0.038 m^3) the size 2 of 2.10 cubic feet (0.059 m^3) and size 3 of 1.9 cubic feet (0.054 m^3) respectively, and conform to the dimensions specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

TABLE I. Food containers

Food Container	Length		Width		Height	
	Min. Inches	Max. Inches	Min. Inches	Max. Inches	Min. Inches	Max. Inches
Size 1						
Top (outside overall) 1/	23-1/2 (597 mm)	24-1/2 (622 mm)	15-1/2 (394 mm)	16-1/2 (419 mm)	8 (203 mm)	10 (254 mm)
Top (inside)	22 (559 mm)	23-1/2 (597 mm)	14-1/2 (368 mm)	15-1/2 (394 mm)	8 (203 mm)	10 (254 mm)
Bottom (exterior)	19-1/2 (495 mm)	20 (508 mm)	12-1/2 (318 mm)	13 (330 mm)	8 (203 mm)	10 (254 mm)
Size 2						
Top (outside overall) 1/	34 (864 mm)	34-1/2 (876 mm)	16-3/4 (425 mm)	17 (432 mm)	9-3/4 (248 mm)	12 (305 mm)
Top (inside)	32 (813 mm)	32-1/4 (819 mm)	13-1/4 (337 mm)	13-1/2 (343 mm)	9-3/4 (248 mm)	12 (305 mm)
Bottom (exterior)	29-1/2 (749 mm)	30 (762 mm)	11 (279 mm)	11-1/2 (292 mm)	9-3/4 (248 mm)	12 (305 mm)
Size 3						
Top (outside overall)	25-1/2 (648 mm)	26-1/2 (673 mm)	15-1/2 (394 mm)	16-1/2 (419 mm)	8 (203 mm)	9 (229 mm)

1/ Excluding handles.

3.4.2 Dimensional requirements for dollies. The dollies shall conform to the overall dimensions specified in table II (not including bumpers).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

TABLE II. Dollies

Dolly	Length + 3/4 in. (19 mm)	Width + 1/2 in. (13 mm)	Height + 1/4 in. (6 mm)
Size 1			
Platform	20-1/2 (521 mm)	13-1/2 (343 mm)	5 (127 mm)
Size 2			
Platform	30-1/2 (775 mm)	12 (305 mm)	5 (127 mm)
Size 3			
Rack (2 shelves)	27-1/2 (698 mm)	16 (406 mm)	33 (838 mm)

3.5 Construction.

3.5.1 Food container. The food container shall be formed seamless and have tapered ends and sides and an open rim on the top edge. The sides, ends, and bottom shall be reinforced by embossing or by a stiffening member. The open rim shall have holes for inserting stacking bracket rests. The aluminum container shall be fabricated from aluminum specified in 3.3.1.1 and shall be 0.050 inch (1.3 mm) minimum thickness. The plastic containers shall be fabricated from plastic specified in 3.3.4 and shall be 0.146 inch (3.7 mm) minimum thickness. The food container shall nest without binding and shall not be scratched on the exterior surface of the container being removed and the interior surface of the remaining container when tested as specified in 4.4.2. The food container shall not deflect more than 1/4 inch (6.4 mm) or permanently deform when carrying a 65 pound (29 kg) load in the size 1 container, and 100 pound (45 kg) load in the size 2 container, or 75 pounds (34 kg) in the size 3 container, when tested as specified in 4.4.1.

3.5.1.1 Stacking bracket and handle (size 1 and 2 container). The stacking bracket and handle combination shall hold the food container immediately above it when in the stacking position. A hinge shall be provided for the grade A food containers and shall be fabricated of aluminum alloy specified in 3.3.1.2 and be of a single or two-piece construction. The stacking bracket and handle combination shall be fabricated from a single piece of stainless steel specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

in 3.3.2. The stacking bracket and handle combination for the size 1 container shall be not less than 1/4 inch (6.4 mm) diameter and not less than 5/16 inch (7.9 mm) diameter for the size 2 container. The stacking bracket and handle combination shall be free swinging and shall not deflect more than 1/4 inch (6.4 mm) or permanently deform when carrying 65 pound (29 kg) load in the size 1 container, and a 100 pound (45 kg) load in the size 2, when tested as specified in 4.4.1.

3.5.2 Dollies.

3.5.2.1 Platform type dolly. The dolly shall have a solid aluminumm alloy platform, minimum 0.098 inches (2.5 mm) thick, with raised edges not less than 3/4 inch (19 mm) high, and welded corners. The platform shall be reinforced and shall have provisions for drainage and holes for a pulling hook. The dolly shall have four casters as specified in 3.3.5. The dolly shall not permanently deform, when 500 pounds (227 kg) are applied to the size 1 and 700 pounds (318 kg) are applied to the size 2 when tested as specified in 4.4.3.

3.5.2.2 Rack type dolly. The dolly shall be all welded construction, fabricated from tubing specified in 3.3.3, and have two shelves, each shelf to hold one container. The dolly, including casters, shall have a capacity of 150 pounds (68 kg).

* 3.6 Finish. The finished item shall be clean, not discolored or stained and all container surfaces shall be smooth for ease of cleaning.

3.7 Marking for identification. The food containers and dollies shall be permanently marked with the manufacturer's name, trade name, or trademark of such known character as to be readily identifiable with the manufacturer. The surface opposite the markings shall show no signs of penetration or uneveness nor shall the markings cause distortion of any part of the component marked.

3.8 Workmanship. The finished dollies and metal food containers shall not contain any burrs; slivers; sharp edges; or rough die, tool, gouge, or grind marks. The finished polyethylene food containers shall be free from flash, bubbles, tears, cuts, holes, burns, breaks, cracks, pits, and weld or sink marks. The finished items shall not be fractured, buckled, bent, dented, punctured malformed, deteriorated, or show any signs of foreign matter inclusion.

3.8.1 Welding. All surfaces to be welded shall be free from oxide, scale, grease, or other foreign matter. Exposed welds shall be continuous and free from incomplete fusion, porosity, cracks, undercuts, burn through, or deformation of material. All flux deposits (when flux is used) shall be removed from the finished welds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, the components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

* 4.2.2 In-process inspection. The lot shall consist of all bumpers offered for inspection at one time. The sample unit shall be one bumper.

* 4.2.2.1 Bumper marking test. The bumper shall be drawn across a sheet of white bond paper with moderate pressure. The paper shall then be examined. Marks that can be removed by rubbing with dry fingers shall not be considered as nonconformance to 3.3.6. Marks that can not be removed shall constitute failure of this test.

* 4.2.2.2 Bumper hardness test. The bumper shall be tested for hardness in accordance with Method 3021 of FED-STD-601. Any nonconformance shall constitute failure of this test (see 3.3.6).

4.2.3 End item inspection. The lot shall consist of all food containers of one size and grade and all dollies of the same size and type, as applicable, offered for inspection at one time. The sample unit for this inspection shall be one completely fabricated food container or dolly, as applicable.

* 4.2.3.1 Visual examination. Examination shall be made of the end item for defects in table III. The inspection level shall be level II with an acceptable quality level (AQL) of 10 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the currentversion before use.

TABLE III. Classification of defects

Examine	Defect
Construction and workmanship (applicable to all components and assemblies)	Any component not specified type Part missing or not as specified Burns, sharp edges, sharp corners, slivers Deformities, breaks
Food containers	Not tapered for nesting Not one piece construction Not seamless, not radius corners, or not open radius rim Stacking bracket and handle missing Stacking bracket and handle not one piece construction or not free swinging Not smooth
Dolly	Not all welded Dolly platform not reinforced Provisions for pulling missing (platform type)
Bumpers	Not removable
Casters	Not roller or ball bearing type Not swivel type casters Not removable
Welding	Cracked, porous, undercut, burn through, incompletely fused, or deformation of material Flash, splatter, or scale not removed Flux deposits not removed
Finish	Not clean. Discolored or stained
Identification marking	Missing, illegible, or incomplete

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

4.2.3.2 Dimensional examination. Examination shall be made of each size food container or type of dolly to determine compliance with dimensional and volumetric requirements, as applicable. Any noncompliance with the specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

* 4.2.3.3 End item testing. One unit from the initial production lot shall be tested in accordance with 4.4.1 through 4.4.4, as applicable. Any nonconformance shall be cause for rejection of the lot.

4.2.4 Packaging inspection. An examination shall be made to determine that preservation-packaging, packing and marking as required by section 5 are complied with. Defects shall be as specified in table IV. The sample unit shall be one shipping container fully prepared for delivery except it need not be closed. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with AQL of 4.0 defects, expressed in terms of defects per hundred units.

TABLE IV. Examination of packaging

Examine	Defect
Marking, exterior and interior	Omitted; incorrect, illegible, of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or not as specified.
Workmanship	Top and bottom pad missing. Kraft paper wrap missing. Interior boxes improperly closed.
Contents	Number not as specified.

4.2.4.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and reinforcing shall be in accordance with the appendix of PPP-B-636.

* 4.2.4.2 Examination of palletization. An examination shall be made to determine that palletization complies with the section 5 requirements. Defects shall be as listed in table V. The sample unit shall be one palletized unit load fully prepared for delivery. The lot shall be the number of palletized unit loads in the end item inspection lot.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the current version before use.

TABLE V. Examination of palletization

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirements.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Material	Bonding not in accordance with requirements. Pallet damaged or otherwise defective.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

4.3 Standards compliance. Proof of compliance with NSF requirements of 3.2 shall be made available to the Government representative.

4.4 Test methods.

4.4.1 Food container load test. The completed food container shall be uniformly loaded and suspended from the combination handle and stacking brackets for a period not less than 10 minutes. The size 1 food container shall be uniformly loaded to a minimum of 65 pounds (29 kg) and the size 2 to a minimum of 100 pounds (45 kg). The food container body and handles shall be examined for deflection and deformation to determine compliance with requirements of 3.5.1 and 3.5.1.1. The size 3 container shall be loaded with 75 pounds (34 kg) and examined for deflection to determine compliance with 3.5.1. Any non-compliance shall constitute failure of this test.

4.4.2 Nesting test. The empty food containers shall be tested for storage. The top nested container shall be lifted by the handles for removal. The exterior of the container being lifted and the interior of the remaining container shall be examined for compliance with 3.5.1.

4.4.3 Deformation test for platform type dolly. The dolly, with a test load of 500 pounds (227 kg) for the size 1 and 700 pounds (318 kg) for the size 2, shall stand in one position for 8 hours. At the end of 8 hours, the dolly and casters shall be examined for deformation to determine compliance with 3.3.5.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the currentversion before use.

* 4.4.4 Obstacle test for rack type dolly. The dolly shall be uniformly loaded with 75 pounds (34 kg) on each shelf. The loaded dolly shall then pass over 1/4 inch (6 mm) high obstacle 10 times at a minimum speed of 2 miles (3.2 k) per hour to determine compliance with 3.4 and 3.5.2.2. Any noncompliance shall constitute failure of this test.

* 4.4.5 Impact test for rack type dolly. The dolly shall be uniformly loaded with 75 pounds (34 kg) on each shelf. The loaded dolly shall be pushed into a solid wall at a speed of 2 miles per hour (3.2 k) once with each of the two ends head on and also each of the four corners impacted four times at an angle of 45 ± 5 degrees, making a total of eighteen impacts. The dolly shall be unloaded and examined to determine compliance with 3.4 and 3.5.2.2. Any non-compliance shall constitute failure of this test.

* 4.4.6 Caster floor marking. For this test the dollies shall have a uniformly distributed load of 500 pounds (227 kg), 700 pounds (318 kg) or 150 pounds (68 kg) as applicable for the size and type dolly.

* 5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Rack components.

5.1.1.1.1 Rack body. No packaging required.

5.1.1.1.2 Food containers. Two food containers, of one type only, shall be unit pack in a snug-fitting fiberboard box conforming to style RSC, type CF (variety SW) or type SF, class domestic, grade 200 of PPP-B-636. The containers shall be nested within the box. Each box shall be closed with 2-inch (51 mm) minimum width gummed or pressure-sensitive paper tape.

5.1.1.1.3 Casters. Each caster shall be completely wrapped in kraft paper. The four casters shall then be unit pack in a snug-fitting fiberboard box conforming to style RSC, type CF (variety SW) or type SF, class domestic, grade 200 of PPP-B-636. Each box shall be closed with 2-inch (51 mm) minimum width gummed or pressure-sensitive paper tape.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the currentversion before use.

5.1.2 Commercial packaging. The racks shall be preserved-packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A. Two food containers, or one dolly, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC end-opening, grade V2s of PPP-B-636. Fiberboard inserts shall be used to fill voids within the container caused by projections on the food container or dolly. Food containers shall be nested prior to packing. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.1.1 Item 3, rack type dolly. Each rack type dolly, unit pack as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with top and bottom pads conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-F-320. The fiberboard boxes containing the food containers and casters shall be secured within the rack in such a manner as to prevent movement during transit. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.1.2 Food containers (when procured separately). Four food containers, of one type only, shall be nested together and packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each fiberboard shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B. Two food containers or one dolly shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, end-opening, type CF (variety SW) or SF, class domestic, grade 200 of PPP-B-636. Fiberboard inserts shall be used to fill voids within the container caused by projections on the food container or dolly. Food containers shall be nested prior to packing. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Item 3, rack type dolly. Each rack type dolly, unit pack as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 200 of PPP-B-636. The inside of each shipping container shall be fitted with top and bottom pads conforming to type CF, class domestic, variety DW,

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the currentversion before use.

grade 275 of PPP-F-320. The fiberboard boxes containing the food containers and casters shall be secured within the rack in such a manner as to prevent movement during transit. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.2 Food containers (when procured separately). Four food containers, of one type only, shall be nested together and packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 200 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.3 Weather-resistant fiberboard shipping container. When specified (see 6.2), the fiberboard shipping container shall be grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial packing. The racks, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall comply with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Palletization. Unless otherwise specified (see 6.2), food containers or dollies, packed as specified, shall be palletized in accordance with load type I of MIL-STD-147, except that for overseas shipment the over-all height of the load shall not exceed 43-inches (109 m). Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Container patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the container patterns specified in MIL-STD-147, the container pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Food containers and dollies are intended for use in kitchens, galleys, and in temporary and permanent U.S. Armed Forces installations for temporary food storage during preparation and transportation of meat products within the installation. The size 1 and 2 food containers are intended to be used with the platform type dolly (item 2) and two size 3 food containers with item 3 dolly.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the currentversion before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Item, size and grade of food container or item, size and type of dollies to be furnished, as applicable (see 1.2).
(c) Whether container covers or false bottoms are required (see 1.2 and 3.4).
(d) Selection of the applicable level of packing (see 5.1).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.3).
(f) When palletization is not required (see 5.3).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification (see 3.3).

6.4 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling.

6.5 Changes from previous issue. The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Preparing activity:

Army - GL

Project No. 7330-0401

Review activities:

Army - MD, SM
DLA - GS

User activity:

Navy - MS

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-F-43392B - Food Container, Delivery & Storage/Equipment Dolly, Food Handling

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Natick Research and
Development Command
ATTN: DRXNM TD
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:19Z
Check the source to verify that this is the current version before use.