INCH-POUND
MIL-K-43359E
INT. AMENDMENT 3(SH)
28 October 1992
SUPERSEDING
INT. AMENDMENT 2(SH)
23 March 1990
USED IN LIEU OF
AMENDMENT 1
1 April 1988

MILITARY SPECIFICATION

KETTLES, STEAM-JACKETED, (STAINLESS STEEL), ELECTRICALLY HEATED

This interim amendment is approved for use within the Naval Sea Systems Command, Department of the Navy, with MIL-K-43359E, dated 16 December 1986.

PAGE 3

2.1.1, under "Standards/Military", add the following:

"MIL-STD-167/1 - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited).
MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of electromagnetic Interference.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement Of".

2.2, under "American Society of Testing and Materials": add the following:

"F 1166 - Standard Practice for Human Engineering Design for Marine Systems, Equipment and Facilities."

PAGE 14

3.6.5: Delete and substitute:

"3.6.5 Water level indicator. Each kettle shall be equipped with a device to indicate when the water in the steam-jacket is at a low level. Low level shall be the point at which there is still sufficient water in the jacket to cover the heating elements. The water level indicator shall be located in a position to be visible to the attendant. If a sight glass is used to indicate water level, it must have a permanent indelible marking to ensure the attendant can actually determine if a low water condition exists in the steam-jacket."

AMSC N/A FSC 7310
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:15Z
Check the source to verify that this is the current version before use.

PAGE 16

3.8, User's instructions (5), at the beginning add the following:

"Complete a daily check of the water level in the steam kettle prior to use. Fill reservoir if sight glass water level is low or if the low water indicator light is on."

PAGE 17

Add the following paragraphs:

"3.14 Naval shipboard use. When the electrically heated steam-jacketed kettles are to be for shipboard use (see 6.2), the following paragraphs apply:

3.14.1 Electromagnetic compatibility. When specified for shipboard use (see 6.2), the units shall be designed and equipped for electromagnetic compatibility in accordance with the requirements of MIL-STD-461, class A4 for surface ships and class A5 for submarines. The equipment shall meet the emission and susceptibility requirements for CE01, CE03 and RE02 (see 4.5.4).

3.14.2 Inclined operation. The electrical kettles shall operate satisfactorily when inclined at an angle of 15 degrees each side of the vertical in each of two vertical planes at right angles to each other, with no spillage of fluid or product when tested (see 4.5.5).

3.14.3 Environmental suitability. When specified for shipboard use (see 6.2), the electrically heated steam kettles shall withstand ship's vibration and motion. Controls, switches, moving parts and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness, or damage when tested (see 4.5.6).

* 3.14.4 High voltage labels. When specified for shipboard use (see 6.2), a Danger High Voltage label shall be affixed to the equipments outer case assembly, on or adjacent to each service access cover and adjacent to one of the fasteners which secures the cover. A high voltage warning label shall also be placed near the high voltage components inside the equipment. The label shall include but is not limited to the following warnings:

a. A warning of high voltage.
b. Power supply must be disconnected before using.
c. Access covers must be in place during use.
d. Servicing should be done by authorized individuals.

3.15 Human factors criteria. When shipboard use is specified (see 3.14 and 6.2), human factors engineering criteria, principles, and practices, as defined in ASTM F 1166, shall be used in the design of the electrical kettles. Maintenance and operational activities shall permit safe and efficient performance by the 5th percentile female to the 95th percentile male as defined in sections 5.6 and 5.10 of ASTM F 1166. Sufficient clearance or free area required around an item shall permit an individual with applicable body dimensions and physical capabilities to

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:15Z
Check the source to verify that this is the current version before use.

safely operate, maintain, remove, or replace that item. When establishing accessibility requirements, both physical and visual access must be provided along with access for the use of any tools, test equipment or repair parts needed. Controls, switches, valves, and indicator lights needed for operation or maintenance shall be selected and integrated into the machines so as to meet the applicable requirements of section 5.2 and 5.4 of ASTM F 1166. When inspecting for defects and performing tests (see section 4), the equipment shall adhere to the human factors engineering considerations listed herein."

PAGE 25

Add the following paragraphs:

"4.5.4 Electromagnetic interference test. When required for shipboard use, the unit shall be tested by the contractor in accordance with test methods CE01, CE03, and RE02 of MIL-STD-462. The contractor shall furnish written certification that the equipment meets the requirements of MIL-STD-462. Non-conformance with the requirements specified shall constitute failure of the test.

4.5.5 Inclined operational test. Position the electric kettle with the base set at an angle of 15 degrees, then operate the electric kettle for 30 seconds at each side of the vertical in each of two vertical planes at right angles to each other. At each of these positions observe for conformance with specified requirements in 3.14.2. For the test, the electric kettle shall be filled with water.

4.5.6 Shipboard environmental test. The electric kettle under normal operating conditions, shall be tested in accordance with MIL-STD-167/1, Type I equipment. The electric kettle shall be secured to the test machine in the same manner that it will be secured on shipboard (see 3.6.2.4). Failure of the electric kettle to perform its function during and after testing, or meeting requirements of 3.14.3, shall constitute failure of this test."

PAGE 26

5.1: Delete and substitute:

"5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2)."

5.1.1.1, Line 1: Delete "type I" and substitute "type II".
Line 4: Delete "type II" and substitute "type I".

5.1.2, Line 1: delete "level C" and substitute "Commercial".

PAGE 27

5.2, Line: Delete "C" and substitute "commercial".

5.2.2, Delete "packing".

5.2.3, Line 1: Delete "Level C" and substitute "Commercial", delete "package as specified in 5.1."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:15Z
Check the source to verify that this is the current version before use.

6.2, (o): Delete and substitute:

"o. Level of preservation and packing (see 5.1 and 5.2)."

6.2, (p): Delete.

6.2, add the following:

"q. When electric steam kettle is for shipboard use (see 3.14 and 3.15).
r. When electromagnetic compatibility is specified for shipboard use (see 3.14.1).
s. When environmental suitability is specified for shipboard use (see 3.14.3)."

Add the following paragraph

* "6.3.1 Technical manuals. The requirement for technical manuals should be considered when this document is cited on a contract. If technical manuals are required, a contract exhibit must be prepared to fully describe statement of work criteria and delivery instructions, and cite the applicable technical manual. The technical manuals must be acquired by separate Contract Line Item Number (CLIN) in the contract."

Add as new paragraph:

* "NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Preparing activity:
Navy - SH
(Project 7310-N817)

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:15Z
Check the source to verify that this is the current version before use.