INCH-POUND
MIL-H-24136/1(SH)
AMENDMENT 2
28 October 1991
SUPERSEDING
MIL-H-24136/1(SH)
AMENDMENT 1
30 July 1985

MILITARY SPECIFICATION

HOSE, SYNTHETIC RUBBER, SYNTHETIC FIBER REINFORCED, AND END FITTINGS, REUSABLE, FOR FLEXIBLE HOSE ASSEMBLIES (LOW PRESSURE SIZES -80 THROUGH -192) AND ADAPTERS

This amendment forms a part of Military Specification MIL-H-24136/1(SH), dated 18 June 1984, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* Table I: Delete and substitute:

"TABLE I. Dash number, performance characteristics and dimensions.

Dash no. (hose size)	Pressure (lb/in^2)		Hose dimensions (inches)				Hose reinforcement		Minimum bend radius (inches)	Impulse peak pressure (lb/in^2)
	Working pressure	Burst pressure	I.D.		O.D.		Construction	No. of layers		
			Min	Max	Min	Max				
-80	300	1,200	5.050	5.100	5.690	5.878	Spiral	6	36	375
-96	300	1,200	6.036	6.110	6.750	6.938	Spiral	6	42	375
-128	300	1,200	8.054	8.100	8.781	8.969	Spiral	8	54	375
-160	200	800	10.064	10.120	10.781	10.969	Spiral	8	66	250
-192	150	600	12.111	12.187	12.925	13.249	Spiral	10	78	188

"

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:30Z
Check the source to verify that this is the current version before use.

Table V, under "test sequence 8", opposite "Aging test": Delete "X".

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (addititons, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing activity:
Navy - SH
(Project 4730-N084)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:30Z
Check the source to verify that this is the current version before use.