MILITARY SPECIFICATION

HOSE, SYNTHETIC RUBBER, SYNTHETIC FIBER REINFORCED, AND END FITTINGS, REUSABLE, FOR FLEXIBLE HOSE ASSEMBLIES (LOW PRESSURE SIZES -40, -48 AND -64) AND ADAPTERS

This amendment forms a part of MIL-H-24136/4(SH), dated 18 June 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Table I: Delete and substitute:

"TABLE I. Dash number, performance characteristics and dimensions.

Hose size (dash no.)	Pressure (lb/in^2)		Hose dimensions (inches)				Hose reinforcement			Minimum bend radius (inches)	Peak impulse pressure (lb/in^2)
			I.D.		O.D.			No. of layers			
	Working (max)	Burst (min)	Min	Max	Min	Max	Construction 1/	Spir	Bra		
-40	1000	4000	2.454	2.531	3.230	3.360	Braided	6	3	20	1500
-48	900	3600	2.954	3.031	3.730	3.860	or	6	3	24	1350
-64	600	2400	3.938	4.062	4.800	5.050	Spiral	6	3	30	900

1/ Regardless of construction, the hose shall work with a common end fitting."

Preparing activity
Navy - SH
(Project 4730-N069)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-19T19:31Z
Check the source to verify that this is the current version before use.