FED. SUP CLASS
6630

USER ACTIVITIES: ARMY - AV, EL, ME, MC
NAVY - CG, OS, YD

PART NUMBER	NOMINAL API GRAVITY SCALE				STEM	
	RANGE	LG	DIVISIONS	ACCURACY	DIA	LG
MS36540-1	10 - 45	120 mm	1/2 deg	1 deg	12 mm	177 mm
MS36540-2	30 - 60	145 mm	1/5 deg	1/10 deg	9 mm	177 mm

MATERIAL: Hydrometers shall be of borosilicate glass in
with Federal Specification DD-G-541, Type

Ballast shall be of mercury, lead sho
alloy.

Scales shall be printed on
ledger paper.

Graduation lines a
permanent black

DESIGN: Hydrometer
displac

B

ed in
grees.

e lower portion

ilibration shall be at 60°F.

ring the API gravity in

ing from this Military Standard by minor
s in design or dimensions are considered standard
this document, provided such variations do not affect
formance and are not in conflict with the material
requirements as specified herein.

2. Referenced document shall be of the issue in effect on the date of invitations for bid.

CANCELLED
CANCELLED AFTER 9 JUL 1986 NO SUPER-
SEDING STANDARD

APPROVED [illegible] REVISED Ⓐ 9 JUL 1986

This military standard is approved by the Department of the Army, Navy, and Air Force and is available for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering activities shall be made from this document.

Ⓐ CANCELLATION

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-512/A-1963

P.A.	MU	TITLE	MILITARY STANDARD
Other Cust	MS 82	HYDROMETER, GRADUATED SCALE API gravity (w/o thermometer)	MS36540
Procurement Specification NONE		SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 83 672 (Coordinated) EDITION OF 1 SEP 67 MAY BE USED.

CANCELLATION
Proj. No. 6630-0438

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:42Z
Check the source to verify that this is the current version before use.