COMMERCIAL ITEM DESCRIPTION

CASTER, INDUSTRIAL, HEAVY DUTY WITH TOWING APPLICATION

This General Services Administration has authorized the use of this Commercial Item Description for all federal agencies

1 SCOPE This Commercial Item Description (CID) covers industrial heavy duty rigid or swivel casters for powered material transport equipment with towing application no more than 5 mile per hour (mph)

2 SALIENT CHARACTERISTICS

2 1 Casters furnished under this CID shall be equipped with brake and swivel lock and shall be flat mounted plate type rigid casters or double ball-bearing swivel casters Rigid or swivel casters shall conform to the dimensions and load rating as specified in Table I and figures below




FIG 1 RIGID CASTER




FIG 2 SWIVEL CASTER




FIG 3 MOUNTING PLATE FOR RIGID OR SWIVEL CASTERS

BENEFICIAL COMMENTS, RECOMMENDATIONS, ADDITIONS, DELETIONS, CLARIFICATIONS, ETC , AND DATA WHICH MAY IMPROVE THIS DOCUMENT SHOULD BE SENT TO DEFENSE INDUSTRIAL SUPPLY CENTER, ATTN DISC-EED, 700 ROBBINS AVENUE, PHILADELPHIA, PA 19111-5096

DISTRIBUTION STATEMENT A APPROVED FOR PUBLIC RELEASE, DISTRIBUTION IS UNLIMITED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:56Z
Check the source to verify that this is the current version before use.

TABLE I DASH NUMBERS AND DIMENSIONS

DASH NO	ØA	WHEEL WIDTH	WHEEL MATERIAL	MIN LOAD CAPACITY (LBS)	OVERALL HEIGHT B MAX	MOUNTING BOLT DIAMETER	SWIVEL OFFSET C ± 06
8	8 00	3 00	RUBBER	840	10 50	500	2 30
			POLYURETHANE	2500			
10	10 00	3 00	RUBBER	1000	12 50	500	2 50
			POLYURETHANE	3000			
12	12 00	3 00	RUBBER	1140	15 50	500	3 00
			POLYURETHANE	3400			

2 1 1 Rigid caster Rigid caster has a rigid horn and wheel assembly permitting only straight line travel

2 1 2 Swivel caster Swivel caster has a swivel horn and wheel assembly that will rotate through 360°

2 2 Mounting plate and horn assembly The mounting plate and horn assembly shall be made of steel plate, cast or forged steel, or aluminum The horn legs shall be either an integral part of the horn plate or welded thereto

2 2 1 Finish Except for aluminum, exposed metal surfaces of the caster assemblies shall be zinc plated

2 2 2 Kingpin The kingpin for swivel casters shall be constructed of steel with minimum 1 00 inch diameter The kingpin shall be secured with slotted adjusting nut and cotter pin so that in swiveling it will not rotate in frictional contact with component members of the swivel bearing assembly

2 2 3 Swivel assembly The ball bearing assembly shall be bi-level with a smooth non-binding operation The raceways shall be heat treated, smooth and full-case hardened and shall be filled to capacity with commercial quality steel ball bearings

2 2 4 Wheel bearing Wheel bearing shall be precision tapered roller bearing having a minimum life rating of 2500 hours at rated loads and rated speed and shall be manufactured in accordance with high-grade bearing manufacturing practice

2 2 5 Axle The axle shall be constructed of steel and shall secure the wheel by means of a locknut During operation, the axle shall not rotate loose or bind the wheel

2 2 6 Shock mounting Caster shall be provided with shock-mounted wheels capable of absorbing shock, vibration, and torsional stresses and shall preclude shimmy Tracking shall permit vertical and longitudinal movement of the wheel within the caster horn assembly legs for the purpose of load, equipment, operating surface, and running gear protection

2 2 7 Wheel hardness The hardness of treads shall be 70 ±5 points for rubber, and 92 ±5 points for polyurethane, measured on the face of the treads by a type A shore durometer

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:56Z
Check the source to verify that this is the current version before use.

2 2 8 Swivel lock A four position plunger type swivel lock shall be furnished When engaged, the swivel lock shall prevent the caster from swiveling while rolling or shall prevent rolling while at right angles to the normal path of the equipment When disengaged, the swivel lock shall permit full 360° free swiveling

2 2 9 Brake A manually operated with side or front mounted control lever parking brake shall be provided The control lever shall be readily accessible for operation, permitting quick and easy brake application release The control lever shall not require a physical force in excess of 30 pounds to set the brake

2 2 10 Lubrication fitting The swivel assembly and wheel assembly shall have pressure lubrication fittings and shall be prelubricated with water repellent grease having a -32° C to +71° C (-10° F to +160° F) operating temperature range

2 3 Casters furnished shall be able to withstand the following tests

2 3 1 Static load test The caster shall be able to withstand four (4) times its rated capacity for one (1) minute without damage

2 3 2 Endurance test The casters shall be loaded to rated capacity and shall be run continuously (see 4 3) at eight (8) mph minimum on an endless belt or drum type testing machine with a smooth, uninterrupted running surface for a period of forty (40) hours At the completion of the test, there shall be no indication of excess wear on the bearing races, looseness of bearings, scuffing of tires or looseness of tire tread

2 3 3 Obstacle test. The caster shall be loaded to rated capacity and shall be run continuously (see 4 3) at 5 mph minimum on an endless belt or drum type testing machine for a minimum duration of 2 hours There shall be an obstacle (see 2 3 3 1) at every 6 feet of travel of the machine At the completion of the test, there shall be no indication of excess wear to the bearing races, looseness of bearings, scuffing of tires, or looseness of tire tread

2 3 3 1 Obstacles shall consist of a rectangular cross-sectioned steel bar 250 inch in thickness, so mounted that the longitudinal axis of the obstacles perpendicularly across the path of the casters

2 3 4 Brake Test The brake must prevent wheel rotation from a horizontal pulling force equal to 3 percent (%) minimum of the caster capacity Test results shall be based on a spring loaded scale applying a horizontal force on a load evenly distributed over four casters, with two side mounted brakes engaged Tests should be repeated 4 times and conducted on level concrete floor

3 QUALITY CONFORMANCE PROVISIONS

3 1 The suppliers shall be responsible for those in process controls and inspections necessary to supply a product consistently conforming to the requirements of this document.

3 2 Upon request, the supplier will certify with documented test/inspection evidence, that the part supplied meets the requirements of this document

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:56Z
Check the source to verify that this is the current version before use.

4 NOTES


4 1 Unless otherwise specified, all dimensions are in inches

4 2 Unless otherwise specified in the contract or purchase order, packaging shall be in accordance with ASTM D3951

4 3 "Continuously" shall mean 45 minutes of rolling operation for each hour of work The cycling of the stop and go periods shall be at the option of the manufacturer

4 4 Unless otherwise specified, tolerance .xx ± 09, xxx ± 030

4 5 The part identification number (PIN) shall consist of the basic commercial item description number followed by a dash number from Table I, "R" for rigid caster or "S" for swivel caster and a code letter for wheel material Add "B" for Brake (optional) and/or "L" for swivel lock (optional) after PIN number



Military Interests

Custodians
Army - AR
Navy - AS
Air Force - 99

Review Activity
Air Force 82

Civil Agency Coordination Activity
GSA-FSS

Preparing Activity
DLA-IS

(Project 5340-2238)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1 The preparing activity must complete blocks 1 2 3 and 8 In block 1, both the document number and revision letter should be given
2 The submitter of this form must complete blocks 4, 5 6 and 7
3 preparing activity must provide a reply within 30 days from receipt of the form
4 This form may not be used to request copies of documents, or to request waivers, or clarification of requirements on current contracts
Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual

1 RECOMMEND A CHANGE	1 DOCUMENT NUMBER A-A-55618	2 DOCUMENT DATE (YYMMDD) 950929

3 DOCUMENT TITLE CASTER, INDUSTRIAL, HEAVY DUTY WITH TOWING APPLICATION

4 NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible Attach sheets if needed)

5 REASON FOR RECOMMENDATION

[redacted]

8 PREPARING ACTIVITY DLA-IS

a NAME	b TELEPHONE (Include Area Code)
Emelia Altomari	(1) Commercial (215) 697-6827
ADDRESS (Include Zip Code) Defense Industrial Supply Center 700 Robbins Avenue Bldg 3 (Code DISC-EED) Philadelphia PA 19111-5096	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike Suite 1403 Falls Church, VA 22041 TELEPHONE (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:56Z
Check the source to verify that this is the current version before use.