A-A-56019
6 October 1989

COMMERCIAL ITEM DESCRIPTION

TAPE, PRESSURE-SENSITIVE, FLUORINATED ETHYLENE-PROPYLENE

Scope. This commercial item description covers pressure sensitive adhesive tape, available in three classes (Class A, transparent; Class B, white; and Class C, light gray), of the following types:

Type I	-	General purpose
Type II	-	Cementable film
Grade I	-	One side cementable
Grade II	-	Two sides cementable
Type III	-	Special film for applications requiring unusual flex endurance or extreme thermal and chemical service.

Salient characteristics. The tape film shall consist of a fluorinated ethylene-propylene (FEP) co-polymer, and shall be made in accordance with ASTM D3368, Standard Specification for FEP-Fluorocarbon Resin Sheet and Film. The adhesive shall be pressure-sensitive of a type specified by the purchaser. The tape shall comply with selected requirements shown in table I. The issue of the ASTM standards in effect on the date of the solicitation shall be used to determine compliance with these requirements. The tape shall have a shelf life of at least 1 year in the original unopened containers at 25° ± 10°C (77° ± 18°F). No material under this description having a remaining shelf life of less than 6 months shall be delivered.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Missile Command, ATTN: AMSMI-RD-SE-TD-ST, Redstone Arsenal, AL 35898-5270, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5970

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

TABLE I. Required test methods.

	ASTM Test Method
FEP Film	
Composition	D3368
Density	D3368
Tensile Strength	D3368
Tear Strength	D3368
Dielectric Strength	D3368
Peel Strength	D3368
Width	D3368
Thickness	D3368
Elongation	D3368
Tape	
Water Absorption	D570
Transparency	D1746
Overall Thickness	D1000
Length of roll	D1000
Breaking strength and elongation	D1000
Adhesion Strength	D1000
Unwind Force	D1000
Resistance to Accelerated Aging (Heat and Moisture)	D1000

Regulatory requirements. None.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes.

1. Application for copies of ASTM standards referenced in this document should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103. Non-Government standards and publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other information services.

ASTM D570 - Water Absorption of Plastics, Standard Test Method for
ASTM D1000 - Pressure-Sensitive Adhesive Coated Tapes Used For Electrical Insulation, Standard Methods of Testing
ASTM D1746 - Transparency of Plastic Sheeting, Standard Test Method for
ASTM D3368 - FEP-Fluorocarbon Resin Sheet and Film, Standard Specification for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

2. As a minimum, purchasers should specify:

a. Type
b. Grade
c. Class (with T_s - specular transmittance)
d. Style (roll or sheet)
e. Length (M)
f. Width (mm)
g. Type of adhesive.

Custodians:
Army - MI

Preparing Activity:
Army - MI

Project Number 5970-1061

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.