A-A-58018
9 Aug 1993

COMMERCIAL ITEM DESCRIPTION

Recovery Unit, Anti-Freeze

Abstract. This Commercial Item Description (CID) describes an anti-freeze recovery system which recycles engine coolants by distillation.

Salient characteristics. The unit shall be portable and hoses shall be provided for removing the contaminated coolant from the radiator and over flow, draining coolant from the block and replenishing the system. Additives shall be available and easily capable of being added to the purified solution. The recycled solution shall be capable of being held in a separate reservoir and/or dispensed from the machine. Additives shall be capable of being dispensed from the unit in order to restore the proper silica and corrosion inhibitors. The unit shall be designed and constructed for withstanding the strains, shocks and vibrations incident to shipping and operations. The unit shall be designed to be corrosion resistant.

The unit shall be supplied with a distillation process vessel, a vacuum pump, a chiller, a outlet drain for the purified anti-freeze, a container for the new coolant and a container for the processed water.

Pump flow rate of 2-6 gallon per minute (gpm).

The pump and all accessories used on the unit shall be operable from a 115 volt, 1 phase, 60 Hz, 20 amp output receptacle.

The unit shall be capable of distilling contaminated ethylene glycol at a minimum rate of 1 gallon per hour. -

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: SA-ALC/LDIPE, Kelly AFB, Tx 78241-7280

DISTRIBUTION STATEMENT A. Approved for pulic release; distribution is unlimited.

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

The unit shall be capable of distilling ethylene glycol to the following minimum levels:

Constituent	Diluted Glycol Before Purification	Diluted Glycol After Purification
Glycol	40 +/- 5%	50 +/- 5%
Organic Acids	200 ppm max.	Less than 10 ppm
Total Dissolved Solids	5900 ppm max.	Less than 300 ppm
Chloride	80 ppm max.	Less than 10 ppm
Sulfate	300 ppm max	Less than 10 ppm
Iron	27 ppm max.	Less than 1 ppm
Copper	20 ppm max.	Less than 1 ppm
Aluminum	0.5 ppm max.	Less than 1 ppm
Lead	6 ppm max.	Less than 0.05 ppm
Silicate	100 ppm max.	Less than 3.0 ppm
Hardness	600 ppm max.	Less than 150 ppm

The recycled coolant, anti-freeze plus supplemental coolant additives (SCA), must exhibit the following properties:

Freezing point $^{o}F(^{o}C)$	-10(-23) to -80(-62)
Nitrate, ppm	1200 to 2200

Regulatory Requirements. The recovery unit shall comply with the Federal OSHA Requirement in effect as of the date that the proposal issued. In the event that state and local OSHA regulations are also in effect, the Federal OSHA regulation shall take precedence.

preservation, Packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

MILITARY INTEREST:

Military Coordinating Activity
Air Force - 82

Custodians
Air Force - 99

Review Activities

User Activities

Agent
Air Force - 99

Project 4940-0656

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.