METRIC

A-A-58020
December 30, 1993
TO SUPERSEDE
PPP-C-1337B
November 26,1975
NOTICE-1
March 5, 1976
NOTICE-2
December 1, 1976

COMMERCIAL ITEM DESCRIPTION

DRUMS, SHIPPING, STEEL WITH POLYETHYLENE INSERT

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for PPP-C-1337B, which is cancelled.

1. ABSTRACT

This description covers metal and polyethylene drums intended for use together as a composite packaging configuration (Department of Transportation specification 6HA1), neither of which is intended to be used separately. This configuration is intended for shipment of liquid or solid chemicals that do not physically or chemically affect, or are affected by, polyethylene. It is not intended to be used for shipment of concentrated hydrochloric acid or liquids with an absolute vapor pressure exceeding 100 kPa at 55 degrees C.

2. CLASSIFICATION

This description covers drums to be used as follows:

Type I: Domestic and Overseas, Surface shipment only.

Type II: Domestic and Overseas, Air and Surface shipment.

Beneficial comments (recommendations, additions, deletions, clarification, etc.) and any other data which may improve this document should be sent by letter to: Air Force Packaging Evaluation Activity, HQ AFMC/LGTP, 5215 Thurlow Street, Wright-Patterson AFB, OH 45433-5540

AMSC N/A FSC 8115

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:59Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 Steel. The steel drum shall be designed and assembled so that it can withstand the performance tests in paragraph 5. The drum assembly shall be reusable providing it meets or exceeds requirements set out in Code of Federal Regulations Title 49 (49CFR)170-180. Covers shall be fully removable.

3.2 Polyethylene drum. The reusable close head drum shall be of quality polyethylene conforming to the requirements set forth in Code of Federal Regulations Title 49 (49CFR) 170-180. The minimum total capacity of the drum, excluding outage, shall be the following:

Class	Capacity
1	19.6 Litres (5 gallon)
2	58.1 Litres (15 gallon)
3	113.5 Litres (30 gallon)
4	208.2 Litres (55 gallon)

3.3 Cleaning, coatings, and workmanship. The interior and external surfaces of all steel drums and chime reinforcement shall be free of dirt, oil, rust, scale and other foreign matter. All sharp edges and metal splinters shall be removed. The internal surface shall be coated with a uniformly applied rust inhibiting primer. The external surfaces shall be coated with a uniformly applied enamel. The internal surface shall be coated with a uniformly applied primer. The enamel and primer must be of a thickness which can be expected to maintain its appearance through a one-trip life cycle. Color, if not olive drab, shall be determined by the purchaser. Olive drab shall conform to color number 24087 of FED-STD-595.

3.4 Polyethylene drum closures.

Type I, classes 1 and 2. The closure shall be a flexible spout, accessible through the drum cover, which can be raised for pouring and then pushed back into the flush position for storage and stacking.

Type II, classes 1 and 2. The closure opening shall be a minimum of 4 centimeters (cm) to a maximum 7 cm in diameter and shall be external threaded. The insert shall be equipped with a spout or other means adequate for pouring contents over the edge of the drum without leakage or spilling.

Type I or II, classes 3 and 4. The primary closure shall have either a 50 mm (2 inch) national pipe thread or buttress style, while the vent closure shall have a 20 mm (3/4 inch) national pipe thread. If required in the purchase order, a 50 mm closure may be substituted for the 20 mm closure with an appropriate adapter to 20 mm.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:59Z
Check the source to verify that this is the current version before use.

3.5 Vent holes.

Type I drums - If vent holes are used, the following requirements must be followed:

Vent holes in drums must not exceed 0.5 cm and must be provided with tight-fitting plugs and be in either of the following configurations:

Two vent holes located diametrically and immediately above the double or triple seam of the bottom chime or three holes on center 120 degrees apart on the bottom head.

Type II drums - No vent holes are permitted.

3.6 Bail ears. Bail ears for type I and II class 1 drums shall be attached by welding or flush rivets. The internal surface at ear attachment points shall be smooth.

3.7 Marking. Both drum components, the liner and steel drum, shall be marked in accordance with 49CFR 178. Permanent markings shall be placed on the bottom of the steel drum and on the top of the polyethylene drum. The side markings on the drum must be distinguishable from a meter away and may be painted or stenciled.

4. REGULATORY REQUIREMENTS

4.1 Recycled materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical and as allowed in 49CFR 100-199.

4.2 Required testing. Fully assembled drum configurations must meet all tests required under Code of Federal Regulations Title 49 (49CFR) Part 178 and the vibration test required in 49CFR Part 173 Subpart B, for the material being shipped.

Type I drums shall pass all the performance tests listed in 49CFR Part 178 Subpart M, except the hydrostatic pressure test may be performed.

Type II drums shall pass the tests listed in 49CFR Part 178, Subpart M. The hydrostatic pressure test requires passage of a 100 kPa minimum pressure.

5. QUALITY ASSURANCE

Test reports. The manufacturer or mark certifying activity, as defined in 49CFR 178.2, shall supply two copies of the testing documentation to the final user. This testing documentation shall outline packaging limitations identified by 49CFR 178.2 and shipper closure requirements including the test configuration assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

6. PACKAGING

Preservation, packaging, packing, labeling and marking shall be in accordance with ASTM D3951 unless otherwise specified in the contract or order.

7. NOTES

7.1 Ordering information. Purchaser must specify the following:

a. Type and Class required.
b. Product, including physical characteristics, to be placed into drums (required for polyethylene compatibility and certification testing).
c. Quantity.
d. Primary closure either national pipe thread or buttress style.
e. Closure sizes for Types 3 and 4, if not the standard 50 mm (2 inch) and 2 cm (3/4 inch) closures.
f. Vent hole configuration (if allowed).
g. Primary color (if not olive drab).
h. Additional test documentation copies.
i. Preservation, packaging, packing, labeling and marking requirements, if different than stated in specification.

7.2 Part Number. The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor. The part number is determined as follows:

```
A - XXXX - B - 1
:      :    :   `--- Class 1 = 19.6 Litres
:      :    :              2 = 58.1 Litres
:      :    :              3 = 113.5 Litres
:      :    :              4 = 208.2 Litres
:      :    `---Type A = Type A
:      :             B = Type B
:      `---CID Number
 `--- Designates a CID
```

7.3 Referenced documents

The following documents form a part of this Commercial Item Description to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation to bid or request for proposals shall apply.

7.3.1 Federal Regulations

49 CFR 100-199	Transportation	
Public Law 94-580	Environmental	(Resource Conservation and Recovery Act)

(Copies may be obtained through the U.S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

7.3.2 Federal standards

FED-STD-595 Colors Used in Government Procurement

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Commercial Item Descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Single copies of this Commercial Item Description or other Commercial Item Descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

7.3.3 American Society for Testing and Materials (ASTM)

D3951 Commercial Packaging, Standard for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

MILITARY CUSTODIANS:
Army - GL
Navy - SA
Air Force - 69

REVIEW ACTIVITIES:
Air Force - 11, 70, 71, 84, 99
Army - EA, SM
Defense Logistics Agency - GS
Navy - AS

USER ACTIVITIES:
Navy - OS, SH
Army - MI

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

PREPARING ACTIVITY
Air Force - 69

(Project 8115-0549)

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:59Z
Check the source to verify that this is the current version before use.