[INCH-POUND]
A-A-58023
March 30, 1994

COMMERCIAL ITEM DESCRIPTION

ANALYZER, GASOLINE ENGINE EXHAUST

The General Services Administration has authorized the use of this Commercial Item Description by all federal agencies.

1. SCOPE. This Commercial Item Description describes a portable exhaust gas analyzer used for measuring exhaust gas emissions from motor vehicles.

2. SALIENT CHARACTERISTICS.

2.1 Size. The complete unit shall not exceed any of the following dimensions and weight:

a. Height - 10 inches

b. Depth - 20 inches

c. Length - 30 inches

d. Weight - 120 pounds

2.2 Design and construction. The unit shall he portable, and supplied with heavy-duty wheels and handles to facilitate movement. The unit shall he capable of withstanding strains, shocks, and vibrations incident to shipping and operation. Construction shall be solid state, micro-processor based and non-dispersive infrared design with built in barometric pressure compensation and be automatically self-calibrated. The unit shall be capable of simultaneously displaying readings of CO, CO2, HC, and O2. The display shall also be capable of displaying air fuel ratio LAMBA, RPM, and oil temperature of the vehicle under test. Readings shall he capable of being frozen, continuously updated, or printed. Total time to complete the analysis of one vehicle shall not exceed 25 minutes, including start up time.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to: The Resources and Logistics Services Division, SA-ALC/TILDM, Kelly AFB TX 78241 - 5000.

AMSC N/A FSC 4910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

2.3 Performance Specifications. The unit shall be capable of reading the parameters to the ranges and resolutions as identified in TABLE I.

TABLE I Criteria

Parameter:	Range:	Resolution:
CO	0 – 10	0.01%
CO2	0 - 20	0.01%
HC	0 – 2000	1 RPM
O2	0 – 21	0.1%
AFR	5.0 – 30.0	0.01
LAMBA	0.8 – 2.0	0.01
RPM	0 – 9000	1 RPM
Oil Temperature	- 20°C to +150°C	1°C

3. REGULATORY REQUIREMENTS. All units shall comply with Federal OSHA and NFPA standards in effect at the time the proposal in issued. The units shall conform to BAR 90 accuracy standards. The contractor is encouraged to use recovered materials in accordance with Public Law 91 - 580 to the maximum extent practical.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformation.

4.2 Market Acceptability. The manufacturer shall have at least one years experience in the production and sale of the unit. Proof of such experience shall be provided to the government upon request.

4.3 Bid Sample. The government reserves the right to request a bid sample if the literature submitted is inadequate for acceptance. Bid samples will be subjected to a 14 to 30 day evaluation. Evaluation criteria is maintained by the preparing activity and will be furnished upon request.

5. PACKAGING. The preservation, packaging, packing, labeling, and marking of the units shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians :
Air Force - 99

CIVIL AGENCY
COORDINATING ACTIVITY

GSA - FSS

Preparing Activity:
Air Force - 82

DoD Project 4910-0764

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.