INCH POUND

A-A-58026
April 11, 2002

COMMERCIAL ITEM DESCRIPTION

TRACTOR, AIRCRAFT TOWING, U-30

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. The new commercial aircraft towing tractor, herein after called tow tractor must be capable of towing military aircraft up to 850,000 pounds on dry level concrete. The tow tractors will have a minimum weight of 100,000 pounds with a minimum drawbar pull of 72,000 pounds. The primary intended use of this tow tractor is to tow C-5 military aircraft on US Air Force installations.

2. SALIENT CHARACTERISTICS. Failure of the tow tractor to meet the above and the following salient characteristics will require rejection of the offer. The tow tractors shall be free from faulty construction or any defect that affects appearance, serviceability, and durability. The tow tractor shall be representative of the quality and workmanship found in tow tractors offered for new commercial sale.

a. Tow tractors shall have a minimum gross vehicle weight (GVW) of 100,000 pounds.
b. Tow tractors shall have a minimum drawbar pull (DBP) of 72,000 pounds on dry level concrete.
c. Tow tractor shall have a diesel engine and power train sufficient to develop the required drawbar pull. Diesel engine shall be unaffected by the use of Jet A-1 (JP-8) fuel. Power train shall feature a standard winterization package that is good for starting down to minus 20F, or a heavy-duty winterization package good for storage down to minus 65F and starting to minus 40F. When specified (Paragraph 6.1 a), tow tractor shall comply with California regulations governing air pollution control in effect on the date of manufacture.
d. Tow tractor shall have four-wheel drive and four wheel steering. Four wheel steering shall feature both crab and coordinated steering. Tow tractors which feature electronic four wheel steering, or electronically controlled diesel engines, shall comply with EMI requirements of SAE J551/1 and SAE J551/2. Wheel-wells shall be designed so that tire chains may be used without interference.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: 295 Byron Street, WR-ALC/LEE Robins AFB, GA 31098-1611

AMSC N/A FSC 1740

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

e. Tow tractor shall be capable of traveling a minimum of 15 MPH forward and 2.5 MPH in reverse.
f. Tow tractor shall feature hydraulic operated brakes.
g. Tow tractor shall feature a 12V or 24V electrical system.
h. Tow tractor shall be equipped with an enclosed two-man cab. Interior cab sound level shall not exceed 84 dB (A) with doors and windows closed. Cab instrumentation shall be standard commercial installation to include an hour meter, odometer, tachometer and speedometer.
i. Tow tractor cab shall be equipped with wipers, mirrors, visors, heater/defroster, ventilating fan, interior light and other equipment as found in standard commercial offering.
j. Tow tractor shall be equipped with a spring applied and hydraulic release parking brake.
k. A flashing beacon light shall be mounted on the cab roof.
l. Tow tractor shall be equipped with front and rear pin and clevis type coupler located 20 inches above the ground.
m. Tow tractor lighting shall be equivalent to the standard commercial offering to include a rear coupling light.
n. Tow tractor shall be equipped with a dry chemical type fire extinguisher.
o. Tow tractor shall be painted Dark Green (Color 24052, FED-STD-595) or Desert Sand (Color 33303, Fed-STD-595) using offeror's standard commercial paint system.
p. Tow tractor shall be rust proofed and undercoated in accordance with FED-STD-297. The level of corrosion treatment shall be tropical, and the use of proprietary material shall require Government approval.
q. Tow tractor shall be so constructed as to provide maximum visibility in all directions. Rearward visibility shall be provided within an envelope defined by a point fifteen feet from the rear of the tractor and 30 inches from the ground to a point one foot behind the tractor and 54 inches above the ground.
r. Tow tractors offered under this specification shall comply with applicable safety requirements imposed on vehicles of this type in the commercial market.
s. Tow tractor shall be air transportable on C-5 and C-17 aircraft in accordance with MIL-HDBK-1791.

3. RECLAIMED MATERIAL. The contractor shall utilize reclaimed materials to the maximum extent practical. Used, rebuilt, or remanufactured components shall not be incorporated in the vehicle.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product Conformance. The product provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer’s own drawings, specifications, standards, and quality assurance practices, and be substantially the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

4.2 Commercial item requirement. The vehicle furnished must meet the "commercial item" definition, as specified in FAR 2.101, as of the date of award. The offeror/contractor shall provide two copies of their commercial, descriptive catalogs with their offer, as specified in Clause I106. The offeror/contractor shall identify all modifications made to their commercial model in order to meet the performance and descriptive requirements of the CID or the referenced documents. In regard to the offered item, the offeror/contractor shall identify any enhancements or improvements to the performance requirements of paragraph 2 of the CID or the referenced documents.

4.3 Contractor requirements. The contractor shall provide copies of the truck manuals for review 30 days prior to the time of tests or demonstration of the first truck. The contractor's parts manuals shall list the part numbers for contractor-manufactured parts, plus the part numbers for purchased sub-level components and whole components. The contractor shall also provide with each truck a product familiarization videotape that verbally and visually provides all information for the operation and routine maintenance of the truck and its components, using the commercial manuals as a baseline.

4.4 Verification. Prior to delivery of the first truck, the contractor shall demonstrate or test, at his facility, each requirement of the CID or referenced documents, prior to delivery.

4.5 Reconfiguration Criteria. Failure to comply with the requirements of this CID, reference documents, or the tests shall be cause for reconfiguration and re-demonstration. Causes for reconfiguration shall include: structural failure; non-correctable misalignments; component interference; conditions presenting a safety hazard to the user or maintainer: instability during operation; spillage of fuel or coolant; and overheating.

4.6 User Tests. If specified in the contract, contractor will provide a specified number of sample units to be placed in service at representative Air Force bases. These sample units will be used interchangeably with existing U30s to determine their fitness for use. The period of testing and evaluation will be 90 days.

5. PACKAGING, PACKING, and MARKING. Unless otherwise provided in the contract, the vehicle shall be packaged in accordance with the contractor's commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage while in transit.

a. The tractor shall have an identification plate and a rear license plate mounting bracket. The identification plate shall include as a minimum the following:
   1. Vehicle Nomenclature
   2. Manufacturer's Model Number
   3. Vehicle Identification (serial) Number or VIN
   4. Manufacturer's address and phone number
   5. Date of Manufacture
   6. National Stock Number
   7. Contract Number
   8. Registration Number

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

b. The vehicle shall be provided with a lubrication data plate that shall direct attention to all lubrication fittings and components that require lubrication. The plate shall identify the type and grade of lubricant required for all operational temperatures.

c. A transportation data plate shall be provided. The plate shall contain at least the following information:
   1. Side and rear silhouette views of the vehicle
   2. Horizontal and vertical location of the center of gravity of the vehicle in air transportable configuration, marked on the silhouette views
   3. Shipping weight
   4. Loading cubage
   5. Overall height, width, and length
   6. Front and rear axle loads
   7. Tie down information

6. NOTES.

6.1 Options. The purchaser shall specify the following at the time of purchase:

a. If tow tractor shall comply with California regulations governing air pollution control in effect on the date of manufacture.

MILITARY INTERESTS:
ACTIVITY:

CUSTODIAN:
Air Force – 99
Army – AV

CIVIL AGENCY COORDINATING

GSA-FSS – 7FXE

PREPARING ACTIVITY:
Air Force – 84

(Project 1740-0186)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:

1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYYYMMDD)
A-A-58026	2002/04/11

3. DOCUMENT TITLE TRACTOR, AIRCRAFT TOWING, U-30

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION

c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE *Include Area Code)* (1) Commercial	(2) AUTOVON
Robert Yohe	912-926-1183	DSN 468-1183

c. ADDRESS *(Include Zip Code)*	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:**
295 Byron Street, WR-ALC/LEE Robins AFB, GA 31098-1611	Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman road, Suite 2533 Ft. Belvoir, VA 22060-2533 Telephone (703) 767-6888 AUTOVON 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.