A-A-58040
16 March 1995

COMMERCIAL ITEM DESCRIPTION

Gasoline-Engine Driven and Pneumatic-Powered Vibrating Screeds

This commercial item description covers gasoline-engine driven and pneumatic-powered, vibratiing screeds.

Type I - Engine driven

Type II - Air driven, convertible

Salient characteristics:

A. Frame. Triangular frame shall be of heavy duty steel truss sections (weight shall be no less than 14 pounds per linear foot) with vibration-proof welds and a vibration dampening system. When type II is required the top pipe shall be schedule 80 steel.

B. Power source. Type I. The engine driven screed shall be powered by a four-stroke, air cooled, gasoline engine (5hp, minimum), which operates on unleaded fuel. The power and speed to meet the performance requirements of the screed shall not be greater than the continuous rated horsepower and maximum rated speed. The engine shall be mounted on the screed by a suitable vibration dampening system. The engine shall be furnished with accessories normally equipped on the manufacturer's standard commercial screed and have, as a minimum, the following:

1. A governor set to keep the engine from exceeding the maximum rated engine.

2. A fuel tank with a sufficient capacity for not less than 3 hours of continuous operation.

3. a suitable serviceable dry type or oil bath type intake air cleaner.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: WR-ALC/LVRE, 225 Ocmulgee Ct, Robins AFB, GA 31098-1647.

AMSC N/A FSC 3895

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

4. A manual speed control and choke.

5. A recoil starter.

6. A stop control.

7. An exhaust muffler.

Type II. The air driven screed shall be powered by a portable air compressor. When required, an air compressor shall be provided, see NOTES. Any components required for proper operation shall be provided as part of the screed. The screed shall be furnished with accessories normally provided on the manufacturer's commercial standard screed and have, as a minimum, a hand off-on valve (air control system) for control of vibration speed. (The Type II air driven, convertible screed shall be capable of being converted to an engine powered screed. If components are needed to accomplish this conversion, they shall be listed in detail, see NOTES.)

C. Screed blades. Screed blades shall be the contractor's standard commercial size, shape, and material.

D. Vibrating mechanism. The vibrating mechanism shall be engine driven for type I and pneumatic for type II. Vibrating frequency shall be not less than 4000 vibrations per minute (at maximum governed engine speed for type I) and shall not vary by more than $\pm$ 10 percent.

E. Propelling system. Two manual winch assemblies, one attached to each end of the screed, shall be provided to facilitate propelling the screed. Each winch shall be free spooling, heavy duty 2500 pounds, with 100 feet of 1/8 inch air craft type cable.

F. Width. The screed shall be 5 to 30 feet wide in 5 and/or 7 1/2 feet increments as specified (see NOTES). If no width is specified a 20 foot wide screed shall be provided and increments shall be contractor's choice.

G. Lift handles.

H. Bearings. Type I. Replaceable, grease type.

I. Reinforcement boxes. Type II.

J. Operational requirements. The screed shall be capable of operating satisfactorily in ambient temperatures from 0 degrees Fahrenheit up to 125 degrees Fahrenheit.

K. Safety. All rotating or reciprocating parts and all parts subject to high operational temperatures or pressures, that are of such a nature or are so located as to be or become a hazard to the safety of the operating personnel, shall be insulated, enclosed, or guarded to the extent necessary to eliminate the hazard. The screed shall comply with applicable DOL, OSHA regulations in effect at time of manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

L. Lubrication. Means for lubrication shall be in accordance with the manufacture's standard practice. The lubricating points shall be easily visible and accessible.

M. Identification plate. An identification plate, permanently marked in accordance with MIL-STD-130, shall be securely attached to the vehicle in a readily accessible location. The identification plate shall contain the following information:

NOMENCLATURE

MANUFACTURER'S MODEL NUMBER

MANUFACTURER'S SERIAL NUMBER

MANUFACTURER'S NAME

MANUFACTURER'S ADDRESS

MANUFACTURER'S SERVICE PHONE NUMBER

DATE OF MANUFACTURE

CONTRACT NUMBER

NATIONAL STOCK NUMBER

REGISTRATION NUMBER

N. The screed furnished must be the latest model as of the date of award (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-39(f)(2)(ii)(A)) for at least three years immediately preceding the issuance date of the solicitation. The screed furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements.

NOTE TO OFFERORS: Offerors shall provide, as part of their proposals, the following information on the screed (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years immediately preceding the issuance date of the solicitation.

(2) Total sales of the item to the general public during the three years immediately preceding the issuance date of the solicitation.

(3) Length of time the item has been sold in the commercial market

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.