A-A-58041
15 MARCH 95

COMMERCIAL ITEM DESCRIPTION
TRAILER, LD-3 CONTAINER, SIDE TRANSFER, TURNTABLE

The General Services Administration has authorized the use of this commercial item description.

1. SCOPE:
This Commercial Item Description (CID) describes a commercial LD-3 container trailer having single container capability. This trailer shall have side transfer capability, a fully rotatable deck, four-wheel coordinated steering, and a capacity of 3500 pounds.

2. SALIENT CHARACTERISTICS: Failure of the trailer to meet the following salient characteristics will require rejection of the offer.

2.1 The trailer shall be free from faulty construction or any defect which affects appearance, serviceability, or durability. All components and accessories shall be represented in the manufacturer's sale data as standard or optional. The trailer shall be representative of the quality and workmanship found in trailer offered for new commercial sale.

2.2 The following is the purchaser provided data:

2.2.1 The deck shall handle one fully loaded LD-3 cargo container (gross weight 3500 pounds).

2.2.2 The deck shall be of the side loading type, accepting containers from either side, with sufficient width to accommodate container misalignment.

2.2.3 The deck shall be furnished with suitable stops, guides, and vertical restraints. The container stops and vertical restraints shall be designed to retract into the deck and then automatically return to position once the container is positioned onto the roller deck.

2.2.4 A walkway with a nonskid surface shall be provided across the deck to allow personnel a tread surface when pushing a container off the deck.

2.2.5 The height to the top of the deck rollers, as measured from the ground shall be 20 inches, plus or minus 0.25 inch.

Beneficial comments, recommendations, additions, deletions, clarifications, etc, and any data which may improve this document should be sent to: WR-ALC/TILC Robins AFB, GA 31098-1647

AMSC N/A FSC 3920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

2.2.6 Each roller shall have a minimum diameter of 2.5 inches and a minimum capacity of 400 pounds.

2.2.7 The distance between the centerlines of the rollers shall be 10 inches maximum.

2.2.8 The lateral roller spacing shall be 20 inches maximum to accommodate the walkway between the rollers.

2.2.9 The deck shall be manually rotatable 360 degrees. Deck rotation stops shall be provided every 180 degrees to facilitate correct positioning for loading/offloading from either side.

2.2.10 The running gear shall be completely within the confines of the trailer frame. All steering linkages, brake system components, or other mechanisms located beneath the trader, shall be protected from damage. The running gear shall be capable of 15 mph operation when part of a trailer train or when towed singly.

2.2.11 The steering shall be of the four-wheel-coordinated type, using the towbar to control the direction of wheel turn.

2.2.12 The towbar shall be of sufficient length to prevent the corners of each trader in a trailer train from contacting during the minimum turning radius. The towbar shall be fitted with a MS51336 lunette eye or similar lunette which is compatible with an MS51335 pintle hook.

2.2.13 The trailer shall have a towbar-actuated parking brakes on two front wheels. The parking brakes shall be of the internal expanding type drum brakes.

2.2.14 The trailer shall be equipped with wheels and tires which meet all Tire and Rim Association or European Tyre and Rim Technical Organization requirements for this application. The trailer shall be equipped with pneumatic, tubeless tires mounted on remountable rims.

2.2.15 A MS51335 pintle hook or similar pintle hook shall be mounted on the rear of the trailer in order to connect the towbar of the following trailer when operating in a train.

2.2.16 The trailer shall be painted Forest Green, Color Number 24052 of FED-STD-595 or the contractor's closest commercial equivalent. The paint shall be a polyurethane paint. All outer surfaces shall be painted and all exterior items (such as wheels, wheel covers, and bumpers) shall be painted,

3. REGULATORY RETIREMENTS:

3.1 The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent possible.

3.1.1 For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the trailer(s) maybe newly fabricated from recovered materials to the maximum extent practicable, provided the trader(s) produced meets all other requirements of this CID. Used, rebuilt, or remanufactured components, pieces and parts, shall not be incorporated.

4. QUALITY ASSURANCE PROVISIONS:

4.1 Contractor Certification:

The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

drawings, specifications, standards, and quality assurance practices. The government reserves right to require proof of such conformance prior to the delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2. Market Acceptability:

4.2.1 Commercial. The trailer furnished must be the latest model as of the date of award (with minor modifications, as that term is defined in DOD Federal Acquisition Regulation (FAR) Supplement 252.211-7012, para K-85 of the solicitation) of an established product previously produced and sold in substantial quantities (exceeding the criteria at FAR 15.804-3 (f) (2) (ii) (A)) for at least two years immediately preceding the issuance date of the solicitation. The trailer furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spares/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer (ACO) with verification of compliance with these requirements. Offerors shall provide, as a part of their proposals, the following information on the trailer (or its earlier models) being offered as a commercial item:

(a) Total sales to the U.S. Government or to contractor for U.S. Government use during the two (2) years immediately preceding the issuance date of the solicitation.
(b) Total sales of the item to the general public during the two (2) years immediately preceding the issuance date of the solicitation.
(c) Length of time the item has been sold in the commercial market place.
(d) Points of contact and phone numbers of customers to which the item has been sold in the commercial market place.
(e) Other pertinent information necessary to determine that the item is an established commercial item.

5. PACKAGING. PACKING, AND MARKING:

An identification plate, permanently marked, shall be securely mounted on the trailer body. The identification plate shall contain the following information:

NOMENCLATURE
MANUFACTURER'S MODEL NUMBER
MANUFACTURER'S SERIAL NUMBER
MANUFACTURER'S NAME
MANUFACTURER'S ADDRESS
MANUFACTURER'S SERVICE PHONE NUMBER
DATE OF MANUFACTURE
CONTRACT NUMBER
NATIONAL STOCK NUMBER

CUSTODIAN:
AIR FORCE -99

PREPARING ACTIVITY:
AIR FORCE -84

Project Number: 3920-0001

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.