MILITARY SPECIFICATION

CARTRIDGE, 40MM, HE, M406; BALL AND SKIRT ASSEMBLY AND OGIVE FOR METAL PARTS FOR

This amendment forms a part of Military Specification MIL-C-60984A (MU), dated 20 March 1969, and is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is appro ed for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 8

4.3.2.3:

Add Major defect 102 as fo..lows:

"102. Any foreign matter (Prior to assembling skirt) Visual 03006".

Minor Category:

Delete "AQL 1.50 Percent" and substitute "AQL 2.50 Percent."

Add Minor defect 205 as follows:

"205. Plating improper Visual 03009."

PAGE 9

4.3.2.5: Add Major defect 102 as follows:

"*102. Gap max. Gage 05006.

*The lot shall be rejected if any item in the sample has a gap exceeding .035 or the number of defectives over .020 exceeds the acceptance number."

FSC 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

PAGE 10

Add new paragraph 4.3.2.9 as follows:

"4.3.2.9 Ball and skirt, prior to applying adhesive (see dwg. 8833699).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 Percent		
101.	Evidence of protective coating	Visual	18001
Minor:	None defined."		

PAGE 14

4.3.3.7: Delete in its entirety and substitute the following:

"4.3.3.7 Push test of ball on ball and skirt assembly (see dwg. 8833699), Major Defect, Code. No. 19001. - Fifty (50) ball and skirt assemblies shall be selected from each lot and subjected to this test. If two (2) or more ball and skirt assemblies fail to comply with the requirement specified on the applicable drawing, or if one (1) or more is below a reading of 1000 lbs., the lot shall be rejected. The reading used shall be the adhesive separation, not the crimp separation reading. The test shall be performed as specified in 4.4.7 using equipment in accordance with 4.3.4."

Add new paragraphs 4.3.3.9 and 4.3.3.10 as follows:

"4.3.3.9 Pot life of adhesive, (see 6.5) (See Dwg. 9247217), Major defect, Code No. 16001. - Each batch of adhesive mixed for use in assembly of ball and skirts shall be subjected to this determination. If any material fails to comply with the applicable requirement, it shall not be used for assembly of ball and skirts. Ball and skirts which have been assembled with adhesive which excluded the pot life requirement shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.3.3.10 Curing temperature of ball and skirt assembly, before removal from oven, Major defect (See Dwg. 9247217) Code No. 17001. - Five (5) ball and skirt assemblies shall be selected from each four (4) hours of production or portion thereof, and subjected to measurement of the curing temperature specified on the applicable drawing. If any assembly fails to comply with the specified requirement, the quantity represented by the failing part shall be rejected. The test shall be performed as specified in 4.4.8 using equipment in accordance with 4.3.4."

PAGE 15

Add new paragraphs 4.4.7 and 4.4.8 as follows:

"4.4.7 Pot life of adhesive. - The time from preparation of the adhesive for use in assembly of ball and skirts to its application to the skirt shall be determined. Any method considered satisfactory to the Contracting Officer may be used in performing this determination. This is a non-destructive test. Adhesive so tested shall be returned to the lot.

4.4.8 Curing temperature of ball and skirt assembly, before removal from oven. - The ball and skirt assembly shall be subjected to this test using equipment specified on the equipment list. This test is a non-destructive test. Parts so tested shall be returned to the lot."

PAGE 18

Add new paragraph 6.5 as follows:

"6.5 The pot life of the adhesive is defined as the time from mixing the adhesive to its application to the skirt. If the adhesive is frozen immediately after mixing, the pot life is defined as the time the adhesive reaches ambient temperature to the time of application to the skirt."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A282)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.