MILITARY SPECIFICATION

CARTRIDGE, CALIBER .50, TRACER, PLASTIC PRACTICE: M860

This Amendment forms a part of Military Specification MIL-C-64038(AR), dated 16 August 1983, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.9: Delete "2750" and "50"; Substitute "2790" and "80" respectively.

PAGE 4

3.11: Delete in its entirety and substitute:

"Trace. When viewed in total darkness at points from behind and to the side of the weapon, the bullet of the tracer cartridge shall exhibit a visible trace of full luminosity from a point not greater than 20 meters from the muzzle to a point not less than 150 meters from the muzzle when tested as specified in 4.5.8.

3.12: Delete "600 yards" and substitute "150 meters"

PAGE 5

Table I, Defect 2: Delete "0" for acceptance number and substitute "1"; delete "1" for rejection number and substitute "2".

PAGE 7

Table II, Note 3/: Delete "600 yards" and subsitute "150 meters".

PAGE 8

4.4.1.1 Delete in its entirety.

FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

PAGE 9

* 4.4.2.1: Add the following criticals:

"2. Case split in K, L or M location 1/	100%	3.3	Visual
3. Case split in I, S or J location when loss of powder occurs 1/	100%	3.3	Visual
4. Perforated case 1/	100%	3.3	Visual
5. Cocked primer 1/	100%	3.3	Visual
6. Inverted primer 1/	100%	3.3	Visual"

* Delete: Majors 106, 107 and 110" in their entirety.

* Major 109: Delete "Split case 1/ .40" and substitute "Case split in I, S or J location 1/ 100%"

PAGE 10

4.4.2.1: Delete note 3/ in its entirety and substitute:

"3/ Failure of the cartridges in the first sample to comply with the applicable requirement shall require testing a second sample consisting of double the quantity of cartridges used in the first test. Failure of the cartridges in the second sample to comply with the applicable requirement shall be cause for rejection of the lot."

Add: "Major 125. Gap, Max, for 360° between metal head and plastic body .40 3.3 Gage"

* After Note 4/ add: "After the required number of readings have been recorded for velocity and chamber pressure, only action time readings shall be continued to be recorded."

PAGE 12

Table III, Defect 2: Delete "0" for first sample and substitute "1"; delete "1" for cumulative and substitute "2".

PAGE 14

4.5.7: Delete "...for pressure measurement." and substitute: "...for pressure measurement at mid-case position."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

4.5.8: Delete in its entirety and substitute:

"All trace testing shall be performed in total darkness firing into a mound of sand located at 150 meters from the gun muzzle. An observer shall be located approximately three (3) meters to the side of the weapon to observe for presence of visible trace of full luminosity to a point no greater than 20 meters from the gun muzzle. A second observer shall be located behind the weapon to observe for presence of trace of full luminosity to a point not less than 150 meters from the gun muzzle. Lights or other suitable visible markers shall be placed at a point to insure a line of sight from the side of observation point to the path of the trajectory. The ammunition shall not be conditioned to temperature but shall be fired under ambient conditions. Three cartridges shall be fired to sight, warm and foul each weapon prior to the test. The sample cartridges shall be fired in regular sequence permitting sufficient time between shots for each observer to record trace characteristics at each observation point. A cartridge shall be considered as a defective once only in the event it fails at more than one observation point. During the performance of this test, observation shall also be made for (a) bullet bursting before striking terminal or target; (b) trace muzzle flash and (c) erratic flight.

PAGE 16

6.5: Delete in its entirety and substitute:

"Contract data requirements. When warranted, requirements for reports of the results of examination and testing shall be specified on DD Form 1423 included in the contract."

6.6: Delete in its entirety.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AB34)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.