MIL-C-55021A
AMENDMENT 3
21 November 1975
SUPERSEDING
AMENDMENT 2
13 February 1970

MILITARY SPECIFICATION

CABLES: TWISTED PAIRS AND TRIPLES, INTERNAL HOOKUP,
GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-C-55021A, dated 10 December 1965, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1, paragraph 1.1, line 3: Change "triple" to "triples" and delete "combinations."

Page 1, paragraph 1.1, line 6: Delete "80 degrees C" and substitute "105 degrees C."

Page 3, under Symbol, line 8: Delete "ST" and substitute"STX."

Page 3, opposite STX: Delete "Shielded and covered with Polytetrafluoroethylene jacket" and substitute "Shielded and covered with extruded Polytetrafluoroethylene jacket."

Page 3, paragraph 1.2.1.4, under Symbol: Add "STW."

Page 3, opposite STW: Add "Shielded and covered with wrapped Polytetrafluoroethylene jacket."

Page 3, paragraph 1.2.1.6, under Symbol: Add "F".

Page 3, opposite F: Add "Fluorinated Ethylene Propylene Jacket."

Page 3, paragraph 1.2.1.6, under Symbol: Add "S."

Page 3, opposite S: Add "Shielded."

Page 4, paragraph 1.2.1.6, under Symbol: Add "SF."

Page 4, opposite SF: Add "Shielded and covered with Fluorinated Ethylene Propylene Jacket."

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:17Z
Check the source to verify that this is the current version before use.

Page 4, under Symbol, line 5: Delete "ST" and substitute "STX".

Page 4, opposite STX: Delete "Shielded and covered with Polytetrafluoroethylene jacket" and substitute "Shielded and covered with extruded Polytetrafluoroethylene jacket."

Page 4, paragraph 1.2.1.6, under Symbol: Add "STW."

Page 4, opposite STW: Add "Shielded and covered with wrapped Polytetrafluoroethylene jacket."

Page 4, under specifications Federal delete: "J-C-98 Cable and Wire, Insulated, Methods of Sampling and Testing."

Page 5, under standards, add: "FED-STD-228, Cable and Wire, Insulated; Methods of Testing."

Page 9, paragraph 3.5.3, line 2: Between the words "shrinkage" and "shall" add the words "of the conductor insulation."

Page 9, paragraph 3.7, delete entire paragraph and substitute the following:

"3.7 Cable identification. The method of identification shall be compatible with the cable construction. Identification shall be at intervals of one to three feet and may be by marking of the outer jacket or tape placed under the shield or jacket. All materials used for identification shall conform to the environmental requirements of the particular construction. The identification shall be clear and legible and shall include the following where practicable:

MIL-C-55021/(add detail specification number and revision), manufacturer's name or trade mark, type designation, and year of manufacture.

EXAMPLE: MIL-C-55021/3A Blank Mfgr Co.
EC24P904-903-902SP 1968.

Finished unjacketed/unshielded cable shall be identified with the printed marking, specified above, applied to the surface of each basic wire of the multiple conductor cable. The size of the printed characters shall be compatible with the basic wire size. No other printed marking shall be applied to the basic wire. Where the basic wire specification specifies printed identification on the basic wire, this requirement shall be waived for the basic wire in the unjacketed/unshielded multiconductor cable of this specification. If, because of temperature rating of the



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:17Z
Check the source to verify that this is the current version before use.

finished cable, printed marking is not practicable in either of the above conditions, only the manufacturer of the finished cable shall be identified. In this case, a distinctive marker of colored threads or thread, as approved by the procuring activity, shall be incorporated in the basic wire in addition to whatever identification marking may be required for the basic wire by the basic wire specification or by this specification for identification of individual wires of a multiconductor cable."

Page 12, paragraph 4.5.3.3, line 2, delete: "Method 6111 of J-C-98", and substitute: "FED-STD-228."

Page 13, paragraph 4.5.3.3, line 2, delete: "Method 6211 of J-C-98" and substitute: "FED-STD-228".

Page 14, paragraph 4.5.3.5, line 3: Delete "80 degrees C (176 degrees F) and substitute "105 degrees C (221 degrees F)."

Page 15, paragraph 6.1.2, line 3: Delete "80" and substitute "105."

Page 15, paragraph 6.1.3, line 2: Delete "80" and substitute "105."

Custodians:
Army - MI
Air Force -11

Preparing Activity:
Army - MI

Project No. 6145-0692

Review Activities:
Army - EL, MU, AT
Air Force - 11
Other - IS, NSA

User Activities:
Army - WC, ME
Air Force -85



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:17Z
Check the source to verify that this is the current version before use.