MILITARY SPECIFICATION

GRENADES (GP), CONE FOR

This amendment forms a part of Military Specification MIL-G-50935B (AR), dated 14 May 1980, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense

PAGE 1

2.1 Military Specifications, Add:
"MIL-A-70625 - Automated Acceptance Inspection Equipment for Non-Electronic components, Design, Testing and approval of"

PAGE 6

4.4.2.1 Delete table in its entirety and substitute new table (see attached table).

PAGE 9

4.4.3.2 Add new paragraph.

"4.4.3.2 Dimensional control of parts. In place of normal sampling associated with the classification of defects, a qualification sample of at least ten parts shall be inspected for verification of dimensional conformance in order to qualify each machine prior to production and after each production stoppage of more than one hour. Upon qualification, one process sample shall be selected per 600 parts produced and at the end of a shift.

4.4.3.2.1 Qualification of machine. If any defective parts are found during qualification of the machine, the machine producing the defective part shall not be used in production.

4.4.3.2.2 Process sample. If any defective part is found when inspection is performed on the process sample, the machine that produced the defective part shall be removed from production. Further, that portion of production since the last process sample shall be rejected.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.1	CONE		9215346
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101	Outside diameter	(b)	0.40%	3.2	Gage
102	Length to smaller basic diameter	(b)	0.40%	3.2	Gage
103	Length to larger basic diameter	(b)	0.40%	3.2	Gage
104	Total length	(b)	0.40%	3.2	Gage
105	Wall thickness between specified planes	(b)	0.40%	3.2	Gage
106	Wall thickness variation between planes max. (360° planes)	(b)	0.40%	3.2	Gage
107	Wall thickness variation between planes along conical elements as specified, max	(b)	0.40%	3.2	Gage
108	Wall thickness outside datums	(b)	0.40%	3.2	Gage
109	Concentricity of outside diameter with basic diameters	(b)	0.40%	3.2	Gage
110	Part cracked or dented		0.40%	3.2	Visual
111	Straightness	(a)		3.2	4.5.1
112	Outside surface profile	(a)		3.2	4.5.1
113	Skirt Straightness	(c)		3.2	4.5.1
114	Inner Surface Profile	(c)		3.2	4.5.1
115	Inner tip profile	(c)		3.2	4.5.2
Minor					
201	Radius between outside diameter and junction with conical surface	(b)	0.65%	3.2	Gage

NOTES:
(a) Sampling per para. 4.4.3.1
(b) In lieu of sampling by MIL-STD-105, alternative sampling per 4.4.3.2 may be used.
(c) One per machine per hour.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9215346
4.4.2.1	Cone (continued)				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
202	Finish improper (stain or unusual discoloration)		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil--(6a)
Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.4.3.2.3 Adjustment or rework of production machines. All machines removed from production because of some fault may, after adjustment or rework, be returned to production provided they pass the qualification test above.

4.4.3.2.4 Statistical Process Control (SPC) Plan. The alternate sampling plan shall be used only with the implementation of a procuring agency approved Statistical Process Control (SPC) Plan. See 6.4. The SPC plan shall record and monitor variable data. The data that are gathered from the acceptance sample may be used in the SPC data base.

4.4.4 Insert as the next to last sentence: "When Automated Acceptance Inspection equipment is to be used, the provisions of MIL-A-70625 shall apply."

4.5.1 line 1, Delete: "outside".

line 3, Delete: "outside".

Add new paragraph:

"4.5.2 Inner tip profile. Each sample selected for this inspection shall have a mold taken with an approved material. These shall then be inspected on an optical comparator for an inside tip having a spherical radius that blends with the inside straight wall surface."

6.4 and 6.5 Add new paragraphs:

"6.4 Submission of SPC Plan. The SPC plan should be submitted to the procuring agency for review. Guidance for preparing the SPC plan is outlined in Statistical Process Control Plans. Preparation and Evaluations, ARDEC, dated 04 April 1986. Copies may be obtained through the procuring agency.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

"6.5 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract.

Reference Paragraphs	DID Number
4.4.3.2	DI-NDTI-80809A

DID Title	Suggested Tailoring
Test/Inspection Reports	Tailoring as appropriate"

Custodian
Army - AR

Preparing activity:
Army - AR

(Project 1330-A367)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.