INCH-POUND

MIL-P-50569C (AR)
AMENDMENT 3
25 June 1990
SUPERSEDING
AMENDMENT 2
8 February 1985

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, ROCKET ASSISTED M549, MOTOR BODY BONDING ASSEMBLY FOR

This amendment forms a part of Military Specification MIL-P-50569C (AR), dated 01 June 1982, and is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.1.2, Delete "9201550 - Fixture Hydrostatic Test".

PAGE 5

3.5, Delete in its entirety.

PAGE 9

Table 1, Delete "Hydrostatic Test 15 - 35 4.5.2".

PAGE 12

4.4.2.2, Title: Delete "and Hydrotesting".

PAGE 13

4.4.2.3, Title: Delete "Hydrostatic Testing,"

Delete Critical Defect 1 in its entirety.

Delete Note a. in its entirety.

PAGE 21

* Add Note d. as follows: "d. Testing for Major Defects 102 and 103 may be conducted on samples prior to knurling."

4.4.3.1, Delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:29Z
Check the source to verify that this is the current version before use.

PAGE 25

4.4.3.8.1, Delete in its entirety and substitute the following:

"4.4.3.8.1 Salt spray. After qualification in accordance with TT-C-490, two (2) salt spray samples shall be taken each week, one during the first 30 minutes of production and a second at any other time. Failure to comply with the requirements of the applicable drawing shall be cause for taking the corrective action prescribed in TT-C-490."

PAGE 27

4.5.2, Delete in its entirety.

PAGE 28

4.5.5, line 6: Delete "M185 or".

4.5.6.1, Delete in its entirety and substitute the following:

"4.5.6.1 Salt spray testing. Salt spray testing shall be accomplished on production projectiles or sectioned projectiles that were acceptable at the time of painting and were sectioned subsequent to painting. If sectioned projectiles are used, sectioning shall be accomplished to allow testing of all major areas of the projectiles on an alternating basis. The salt spray test shall be performed utilizing the equipment and procedures specified by Federal Test Method Standard No. 141 and TT-C-490 with the exception that test samples shall be selected in accordance with 4.4.3.8.1 and test samples shall be dried in accordance with Drawing 9235997."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AC12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.