INCH-POUND

MIL-S-51547(EA)
30 June 1989

MILITARY SPECIFICATION

SMOKE POT, HC, M1, COMPONENTS FOR

This specification is approved for use by the U.S. Army Chemical Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers components for the Ml smoke pot.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

STANDARDS

FEDERAL

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-SPT-S, Aberdeen Proving Ground, MD 21010-5423 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1365

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147		Palletized Unit Loads
MIL-STD-1168	-	Ammunition Lot Numbering

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. ARMY CHEMICAL RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

DRAWINGS

36-1-88	-	Container Assembly
36-1-89	-	Body
36-1-92	-	Cover, Inner
36-1-93	-	Retainer, Starter Cup
36-1-94	-	Cup, Starter
36-1-128	-	Cover, Outer, Assembly
36-4-1	-	Card, Instruction

(Copies are available from Commander, U.S. Army Chemical Research, Delopment and Enigineering Center, Attn: SMCCR-SPT-O, Aberdeen Proving Ground, MD 21010 -5423.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and components. All materials and components cited on the applicable drawings, which are listed on Drawings 36-1-88 and 36-4-1 and subsidiary drawings, shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

3.2 Leakage.

3.2.1 Body. The body (36-1-89) shall not leak when subjected to an internal air pressure of 15 pounds per square inch (psi) and tested in accordance with 4.4.5.1(a).

3.2.2 Starter cup. The starter cup (36-1-94) shall not leak when subjected to an internal pressure of 3 psi and tested in accordance with 4.4.5.1(b)

3.2.3 Outer cover assembly. The outer cover assembly (36-1-128) shall not leak when subjected to an internal air pressure of 5 psi and tested in accordance with 4.4.5.1(c).

3.3 Outer cover assembly (36-1-128). The lugs shall not separate from the outer cover when subjected to a 30 pound load per lug when tested in accordance with 4.4.5.2

3.4 First article. Prior to the start of regular production, a first article sample of components shall be produced in accordance with this specification for examination and tests (see 4.3).

3.5 Workmanship. The components shall be free from contamination (foreign matter) and damage such as dents, cracks and deformation which would impair their intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

4.1.2 Objective evidence. Thecontractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of Inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Lot. A first article sample of 50 of each component shall be produced using the same methods, materials, equipment and processes as will be used in regular production.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components, and test specimens may be subjected to any or all of the examinations and tests specified in this detail specification and be inspected for compliance with any or all requirements of the applicable drawings. The starter cup (Drawing 36-1-94) may be tool controlled after tooling qualification.

4.3.2 Rejection criteria. If any assembly, component, or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of any assembly, component, or test specimen to comply with any of the requirements.

4.4 Quality conformance inspection.

4.4.1 Lotting. Lotting shall be in accordance with MIL-STD-1168. A lot shall consist of the components of one interfix number, produced by one manufacturer, at one plant, from the same materials, under essentially the same manfacturing conditions.

4.4.2 Sampling. Sampling shall be as specified in the contract (see 6.2 and 6.4).

4.4.3 Inspection procedure. Sample smoke pot components shall be inspected for the defects listed in 4.4.4 and shall be tested in accordance with 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

4.4.4 Classification of defects. "SME" indicates the use of stanard measuring equipment.

(a) Body (Drawing 36-1-89)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Leakage	4.4.5 .1(a)
102	Inside diameter incorrect	SME
103	Height incorrect	SME
104	Workmanship (3.5)	Visual
105	Bottom crimped depth incorrect	SME
Minor:		
201	Finish missing, inadequate or incorrect	Visual
202	Double seam outside diameter incorrect	SME

(b) Cup, starter (Drawing 36-1-94)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Leakage	4.4.5 .1(b)

(c) Cover, outer, assembly (Drawing 36-1-128)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Leakage	4.4.5.1(c)
102	Lug handle separation	4.4.5.2
103	Welding incorrect	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

104	Interface clearance with inner cover (Drawing 36-1–92) diameter incorrect	SME
105	Workmanship (3.5)	Visual

Minor:

201	Finish missing, inadequate, or incorrect (where required)	Visual
202	Lug dimensions or location incorrect	SME
203	Handle dimensions incorrect	SME

(d) Cover, inner (Drawing 36-1-92)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Interface clearance with outer cover (Drawing 36-1-128) and body (Drawing 36-1-89) diameter incorrect	SME
102	Lip diameter (2.300) incorrect	SME
103	Lip height (.188) incorrect	SME
104	Ring dimensions incorrect	SME
105	Welding incorrect	Visual
106	Cover height incorrect	SME
107	Sealing material missing or incorrect	Visual
108	Lacquer missing, inadequate, or incorrect	Visual

(e) Card, instruction (Drawing 36-4-1)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Dimensions incorrect	SME
102	Instructions incorrect, illegible, or missing	Visual
103	Print type incorrect	Visual
104	Ink color incorrect	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:04Z
Check the source to verify that this is the current version before use.

105	Acrylic coating missing or incorrect	Visual
106	Paper color or type incorrect	Visual

(f) Retainer, starter cup (Drawing 36-1-93)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Inside diameter incorrect	SME
102	Hole diameter incorrect	SME
103	Height (.14) incorrect	SME
104	Overall height incorrect	SME
105	Dimension (2.268) incorrect	SME

(g) Packaging (section 5)

Categories.	Defects	Inspection method
Critical:	None defined	
Major:		
101	Containers damaged	Visual
102	Marking missing, illegible, or incorrect	Visual

4.4.5 Tests.

4.4.5.1 Leakage.

(a) Body. The body shall be sealed by means of an adapter, subjected to a minimum internal air pressure of 15 psi and submerged in water for a minimum period of 30 seconds (seamed design only). Leakage is indicated by a steady stream or a recurring succession of bubbles.

(b) Starter cup. The starter cup shall be sealed by means of an adapter, subjected to a minimum internal air pressure of 3 psi and submerged in water for a minimum period of 30 seconds. Leakage is indicated by a steady stream or a recurring succession of bubbles.

(c) Outer cover assembly. The outer cover assembly shall be attached to an appropriate fixture and subjected to a minimum internal air pressure of 5 psi and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

submerged in water for a minimum period of 30 seconds. Leakage is indicated by a steady stream or a recurring succession of bubbles.

4.4.5.2 Handle lug separation. The lug shall be subjected to a direct pull of 30 pounds or the handle held by the lugs shall be subjected to a direct pull of 60 pounds. The lug and outside cover shall be observed for separation.

5. PACKAGING

5.1 Interplant shipment. A uniform quantity of components shall be unit packed and packed to prevent damage in shipment from the supply source to the destination set forth in the contract. Shipping containers shall be in compliance with the rules and regulations applicable to the mode of transportation.

5.2 Parelletization. When specified in the contract, components shall be palletized in accordance with MIL-STD-147 (see 6.2).

5.3 Marking. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with Fed. Std. No. 123 and shall include the contract number and name and address of the prime contractor. Palletized loads shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The items covered by this specification are used in assembling the Ml smoke pot.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification
(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1)
(c) First article instructions:
(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract
(2) Name and address of test facility and shipping instructions when testing is performed by the Government
(3) Time required for the Government to notify the contractor whether or not to proceed with production
(d) Sampling for quality conformance inspection (see 4.4.2 and 6,4)
(e) The shipment group size and marking (when required)

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:04Z
Check the source to verify that this is the current version before use.

(f) Military or interplant shipment marking required
(g) If palletization is required (see 5.3)

6.3 Interplant shipment. lnterplant shipment is for material which will not enter the military supply system. Typical are shipments of component parts from a vendor to a prime contractor or a sub-contractor or from a contractor to a military arsenal or plant.

6.4 Recommended sampling.

6.4.1 For nondestructive tests. For lot sizes of 1,200 or less, it is recommended that 32 samples be taken and the acceptance/rejection numbers be 0/1, respectively. For lot sizes over 1,200, it is recommended that 125 samples be taken and the acceptance/rejection numbers be 0/1, respectively.

6.4.2 For destructive tests. For lot sizes up to 3,000, it is recommended that 32 samples be taken and the acceptance/rejection numbers be 0/1, respectively.

6.5 Subject term (key word) listing.

Body
Outer cover assembly
Starter cup

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1365-A098

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Commander
U.S. Army Chemical Research, Development
and Engineering Center
ATTN: SMCCR-SPT-S
Aberdeen Proving Ground, MD 21010-5423

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-51547(EA)	SMOKE POT, HC, M1, COMPONENTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION FOR NEW DESIGN

INCH-POUND

MIL-S-51547(EA)
NOTICE 1
27 December 1995

MILITARY SPECIFICATION

SMOKE POT, HC, M1, COMPONENTS FOR

This notice should be filed in front of MIL-S-51547(EA) dated 30 June 1989.

MIL- S-51547(EA) is inactive for new design and is no longer used except for replacement purposes.

Preparing activity:

Army - EA

AMSC N/A

FSC 1365

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.