MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, PRACTICE: M274

This amendment forms a part of Military Specification MIL-W-70467 (AR), dated 15 May 1986, and is approved for use within the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Delete "INSPECTION EQUIPMENT DRAWINGS 9201212
Envelope Drawing, Safety, and Arming Inspection Equipment"

PAGE 6

4.3.1, Delete "Plug 9370245 15"

Add the following:

"Washer, Felt	12599973	15
Cap, Smoke Tube	12599974	15
Tube, Smoke	12599976	15
Smoke, Tube Assembly	12599977	25"

PAGE 8

Table I: Delete Plug (Dwg. 9370245) in its entirety.

PAGE 12

Table I: Add the following:

"Tube, Smoke (Dwg. 12599976) Examination for defects	15	3.2	4.4.2.25
Cap, Smoke Tube (Dwg. 12599974) Examination for defects	15	3.2	4.4.2.26

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

Washer, Felt (Dwg. 12599973) Examination for defects	15	3.2	4.4.2.27
Smoke Tube Assembly (Dwg. 12599977) Examination for defects	25	3.2	4.4.2.28"

PAGE 18

4.4.2.5, Under Major 101: Delete "Diameter" and substitute "Outside Diameter".

Add Major 103 as follows:

"103 Location of Hole	0.40%	3.2	Gage:.

Add Minor 201 as follows:

"201 Inside Diameter	0.65%	3.2	Gage".

PAGE 21

4.4.2.8, Delete in its entirety.

PAGE 22

4.4.2.9, Delete Major 104 in its entirety.

Add Minor 204 as follows:

"204 Diameter of partition hole	0.65%	3.2	Gage".

PAGE 23

4.4.2.10, Delete Major 107 in its entirety.

Add Majors 111 and 112 as follows:

"111 Retainer groove diameter	0.40%	3.2	Gage
112 Retainer groove location	0.40%	3.2	Gage".

Page 37

4.4.2.23, Delete Minor 201 in its entirety.

PAGE 38

Add 4.4.2.25 enclosed as Page 3 (38a).
Add 4.4.2.26 enclosed as Page 4 (38b).
Add 4.4.2.27 enclosed as Page 5 (38c).
Add 4.4.2.28 enclosed as Page 6 (38d).

Source: https://assist.dla.mil -- Downloaded: 20261O-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70467 (AR)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Tube, Smoke	1 OF 1	12599976
			NEXT HIGHER ASSEMBLY: 12599977

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Wall thickness of radius end		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Wall thickness		0.65%	3.2	Gage
204	Thread pitch		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.18	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70467 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12599974
4.4.2.26	Cap, Smoke Tube				NEXT HIGHER ASSEMBLY 12599977
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined.				
Minor					
201	Height		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Thread pitch		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.18	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23 03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70467 (AR)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.27	Washer, Felt		12599973
			NEXT HIGHER ASSEMBLY 9370252

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined.				
Minor					
201	Thickness		0.65%	3.2	Gage
202	Hole diameter		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.18	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2022-08-30 06:07
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70467 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12599977
4.4.2.28	Smoke Tube Assembly				NEXT HIGHER ASSEMBLY 9370252
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Joint of smoke tube cap and smoke tube taped incorrectly (note 4)		0.40%	3.2	Visual
102	Smoke tube cap installed incorrectly		0.40%	3.2	Visual
Minor					
201	Weight of smoke composition		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.18	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-28T08:30Z
Check the source to verify that this is the current version before use.

PAGE 51

4.5.12, Delete in its entirety and substitute the following:

"4.5.12 Ballistic test. The requirement for the warhead is to provide a visible signature at impact with a functional reliability of greater than 93.7% when fired with Mk 66 motors. Performance shall be evaluated by ground launching a sample of 36 M274 warheads. 12 rockets shall be conditioned at $-50^{\circ}F \pm 5^{\circ}F$, 12 rockets at $70^{\circ}F \pm 15^{\circ}F$, and 12 rockets at $150^{\circ}F \pm 5^{\circ}F$ for a minimum of 8 hours. All 36 rockets shall be fired from an M260 or M261 launcher to impact at 6000 meters. If three or more warheads fail to function the lot shall be rejected."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A822)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.