INCH-POUND

MIL-DTL-17/73B
w/AMENDMENT 1
13 April 2010

SUPERSEDING
MIL-C-17/73B
18 July 1985

DETAIL SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL, 50 OHMS, M17/73-RG212

Inactive for new design after 13 August 1993. For new design use MIL-C-17/188.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-17.

NOTE: This cable uses PVC material and is not to be used in enclosed environments or shipboard applications. The replacements that are to be used in enclosed areas or shipboard applications are referenced in the following table.

The Air Force has restricted use of PVC in aerospace and ground support applications.

Cables listed on the current QPL may continue to be manufactured and supplied for existing enclosed applications only for a period not to exceed 3 years from the date of this specification.

TABLE I. Cross-reference data.

Canceled Part or Identifying Number (PIN)	Replacement PIN
M17/73-RG212	M17/188-00001




FIGURE 1. Configuration.

AMSC N/A

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:05Z
Check the source to verify that this is the current version before use.

TABLE II. Description.

Components	Construction details		
Inner conductor	Solid silver-coated copper wire. Overall diameter: 0.0556 inch ± 0.0010.		
Dielectric core	Type A-1: Solid, polyethylene. Diameter: 0.185 inch ± 0.004.		
Outer conductor	Double braid of AWG #34, silver coated copper wire. Diameter: 0.265 inch maximum.		
			Alternate
Inner braid	Coverage:	95.0% nominal	95.0% nominal
	Carriers:	16	24
	Ends:	9	6
	Picks/inch:	5.9 ± 10%	8.8 ± 10%
Outer braid	Coverage:	95.0% nominal	95.0% nominal
	Carriers:	16	24
	Ends:	9	6
	Picks/inch:	8.7 ± 10%	13.0 ± 10%
Jacket	Type IIa: PVC. Diameter: 0.332 inch ± 0.004.		

ENGINEERING INFORMATION

Continuous working voltage: 2,200 V rms, maximum.

Operating frequency: 11 GHz, maximum.

Velocity of propagation: 65.9 percent, nominal.

Power rating: See figure 2.

Operating temperature range: -40°C to +85°C.

Inner conductor properties:

DC resistance (maximum at 20°C): 0.348 ohm per 100 feet.

Elongation: 25 percent, minimum.

Tensile strength: Not applicable.

Engineering notes: This cable useful in general purpose medium low temperature applications. (See connector series “N”, “C” and “SC” in accordance with MIL-PRF-39012.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:05Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions, configuration, and descriptions: See figure 1 and table II.

Environmental and mechanical:

Visual and mechanical examination:

Out-of-roundness: Not applicable.

Eccentricity: 10 percent, maximum.

Adhesion of conductors:

Inner conductor to core: 5 pounds, minimum; 45 pounds, maximum.

Aging stability: +98ºC ± 2ºC.

Stress crack resistance: Not applicable.

Outer conductor integrity: Not applicable.

Cold bend: -40ºC ± 2ºC.

Dimensional stability: +85ºC ±2ºC.

Inner from conductor core: 0.062 inch, maximum.

Inner conductor from jacket: 0.125 inch, maximum.

Contamination: Applicable.

Bendability: Not applicable.

Flammability: Not applicable.

Weight: 0.089 pound per foot, maximum.

Electrical:

Continuity: Applicable.

Spark test: 8,000 V rms, +10%, -0%.

Voltage withstanding: 7,000 V rms, +10%, -0%.

Insulation resistance: Not applicable.

Corona extinction voltage: 3,000 V rms, minimum.

Characteristic impedance: 50 ohms ± 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:05Z
Check the source to verify that this is the current version before use.

Attenuation: See figure 2.

Structural return loss: See figure 3.

Capacitance: 32.2 pF per foot, maximum.

Capacitance stability: Not applicable.

Capacitance unbalance: Not applicable.


Transmission unbalance: Not applicable.

Mechanically induced noise voltage: Not applicable.

Time delay: Not applicable.

PIN: M17/73-RG212. See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:05Z
Check the source to verify that this is the current version before use.



FREQUENCY MHz	ATTENUATION dB	POWER WATTS
50	2	1,000
400	6.5	350
1,000	12	200
3,000	24	100
11,000	60	56

MAXIMUM ATTENUATION ———

MAXIMUM POWER ·———-

AT 25°C SEA LEVEL

Tabulated values are for reference only.
The values on the chart represent to requirements.

FIGURE 2. Power rating and attenuation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:05Z
Check the source to verify that this is the current version before use.




FIGURE 3. Structural return loss.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:05Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-17, this document references the following:

MIL-PRF-39012
MIL-C-17/188

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 6145-2010-027)

Review activities:
Army – AT, CR4, MI
Navy – AS, MC, OS, SH, TD
Air Force – 19, 99
DLA - IS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:05Z
Check the source to verify that this is the current version before use.