[INCH-POUND]
KKK-T-2893
March 14, 1997
SUPERSEDING
MIL-T-81098F
20 February 1991

FEDERAL SPECIFICATION

TRUCK, AMMUNITION HANDLING: STAKE AND PLATFORM BODY, 24,000 POUNDS GVW, 4 BY 2 OR 4 BY 4

The General Services Administration has authorized the use of this specification by all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a commercial, gasoline or diesel engine-driven, four-wheel, two-rear-wheel-drive, or four-wheel-drive, stake and platform truck having a gross vehicle weight (GVW) rating of not less than 24,000 pounds (lbs) (10 886 kilograms (kg)), equipped with a rear-of-cab mounted revolving articulating boom type crane. The trucks procured under this specification are commercial items which shall be warranted as specified in the procurement documents.

1.2 Classification. Truck shall be one of the following types, as specified (see 6.2):

Type I - 4 by 2 truck chassis.
Type II - 4 by 4 truck chassis.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Commanding Officer (Code 1581), Naval Construction Battalion Center, 1000 23rd Avenue, Port Hueneme, CA 93043-4301, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government publications. The following documents, of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications

ZZ-T-381 - Tire, Pneumatic, Vehicular (Highway).

Federal Standard

FED-STD-297 - Rustproofing of Commercial (Nontactical Vehicles).

Commercial Item Descriptions

A-A-393 - Extinguisher, Fire, Dry-Chemical (Hand-Portable).
A-A-50271 - Plate, Identification

Military Specification

MIL-E-6051 - Electromagnetic Compatibility Requirements, Systems.

Military Standards

MIL-STD-209 - Slinging and Tiedown Provisions for Tying Down Military Equipment.
MIL-STD-1223 - Non-Tactical Wheeled Vehicles Treatment, Painting, Identification Marking, Data Plates Standards.
MS51318 - Headlight: Blackout, 24 Volt (Waterproof).
MS51335 - Pintle Assembly, Towing, 18,000 lbs. Capacity, Manual Release.
MS52125 - Composite Light, Tail Stop, Turn and Marker.
MS52126 - Composite Light-Front Turn, Park and Marker.

(Copies of federal and military specifications and standards required by contractors in connection with specific procurement specifications are obtained from the Defense Automated Printing Service, Attn: DoDSSP, Building. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.1 Other Government documents and publications. The following other Government documents and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines: Certification and Test Procedures.
Interstate Motor Carrier Noise Emission Standards Motor Vehicle Air Pollution Standards.
Title 40, CFR, Part 204 Subpart B - Noise Emission Standards for Construction Equipment.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852; or CFR, Title 40 should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

OSHA 1916.550 - Cranes and Derricks.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on the date of invitation for bids or request for proposal shall apply.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Standards and Recommended Practices

SAE J350 - Spark Arrestor Test Procedure for Medium Size Engines.
SAE J534 - Lubrication Fittings, Standard.
SAE J537 - Storage Batteries, Standard.
SAE J551 - Performance Levels and Methods of Measurements of Electromagnetic Radiation.
SAE J560 - Seven-Conductor Electrical Connector for Truck-Trailer.
SAE J682 - Rear Wheel Splash and Stone Throw Protection (DoD adopted).
SAE J683 - Tire Chains Clearance-Truck, Buses, and Combinations of Vehicles.
SAE J704 - Openings for Six-and Eight-Bolt Truck Transmission Mounted Power Take-Offs.
SAE J706 - Rating of Winches.
SAE J1063 - Cantilevered Boom Crane Structure-Method of Test.
SAE J1349 - Engine Power Test Code-Spark Ignition and Compression Ignition.

(Private sector and civil agencies may purchase copies of this voluntary standard from the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Private sector and civil agencies may purchase copies of this voluntary standard from the Tire and Rim Association, Inc., 175 Montrose West Avenue, Suite 150, Copley, OH 44321.)

THE EUROPEAN TYRE AND RIM TECHNICAL ORGANIZATION (ETRTO)

Standards Manual.

(Private sector and civil agencies may purchase copies of this voluntary standard from the European Tyre and Rim Technical Organization publications should be addressed to the European Tyre and Rim Technical Organization, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

(DoD activities may obtain copies of those adopted voluntary standards listed in the DoD Index of Specifications and Standards free of charge from the Defense Automated Printing Service, Attn: DoDSSP, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The truck shall be a four-wheel, two-rear-wheel-drive, or four-wheel-drive gasoline or diesel engine-driven-truck cab-and-chassis having a GVW rating of not less than 24,000 lbs (10 886 kg). A fully hydraulic, articulated boom type crane shall be frame mounted at rear of the cab. A platform body may be equipped, on an optional basis, with a cargo conversion unit consisting of removable type body front and side panels, and tailgate.

3.2 First article. When specified (see 6.2), the contractor shall furnish a truck for first article inspection (see 4.2.1 and 6.2).

3.3 Standard truck components and accessories. Except as specified in 3.3.1. through 3.3.1.15, the truck, components, and accessories shall be standard or optional items which meet or exceed the requirements of this specification. All items shall be represented and rated in the manufacturer's sales information, including special or mounted equipment. Sales information shall be limited to specifications and technical material, identical to that furnished to the authorized company representative for selection of truck model and components. Such items shall be constructed as commercial motor vehicle products, and shall comply with all DoT Federal Motor Vehicle Safety Standards and Regulations applicable, on the data of manufacture. The chassis model furnished shall not be older than the chassis manufacturer's current model on the date of invitation for bids.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.3.1 Special requirements. In addition to standard truck and components specified in 3.3, truck shall be furnished with special equipment as specified herein.

3.3.1.1 Identification plate. Unless otherwise specified (see 6.2), an identification plate for each truck will be furnished by the contracting officer. The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix it to each truck in a conspicuous place with nonferrous screws, rivets, or bolts not less than 0.125-inch (3 mm) in diameter. The application nomenclature shall be: TRUCK, AMMUNITION HANDLING, STAKE AND PLATFORM BODY.

3.3.1.2 Shifting instruction plate(s). A plate or plates showing applicable data concerning operating positions of shift handles for transmission transfer-case and power takeoff shall be furnished.

3.3.1.3 Crane instruction plates. Three crane operating instruction plates shall be provided as follows:

a. One plate shall be installed inside the cab, visible to the operator at all times, with the following statement: "CRANE OPERATION requires that truck shall be located as level as possible, and parking brake shall be engaged."

b. Two crane operating instruction plates shall be furnished, with one installed on each side, providing unobstructed visibility to a person standing at either control station. The plates shall be of nonmetallic material which will remain legible while exposed to direct sunlight and the elements for not less than five years. The plates shall contain all instructions required for safe operation, including (but not limited to) outriggers, boom, hoist, extension, and swing. The instructions written on the plates shall be in the English language, but may include international symbols indicating lever control of crane movements. As a minimum, the plates shall include the following:

(1) Read all crane instructions prior to starting operation.
(2) Engage PTO and set throttle position for crane operation.
(3) Extend outriggers fully. Lower outriggers as required to raise truck from suspension and to a level position for crane operation.
(4) Return crane to cradle position prior to raising outriggers.
(5) Raise and return outriggers to travel position.
(6) Secure throttle for normal truck operation.

3.3.1.4 Drain plugs. Drain plugs installed in manual transmissions, rear axle, and those installed for the purpose of draining crane and outrigger hydraulic fluid, shall be of the permanent magnet type.

3.3.1.5 Heavy-duty cooling system. A heavy-duty cooling system shall be furnished that shall maintain engine coolant at a temperature below the boiling point with truck loaded to rated

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

GVW, and operated at an altitude of 10,000 feet (3 048 metre (m)) above sea level or in an ambient temperature of not less than 125 degrees Fahrenheit (°F) (52 degrees Celsius (°C)).

3.3.1.6 Coolant system and indicators. Coolant system shall include a deaeration system, a surge tank or a coolant recovery reservoir of not less than 2 quart (1.9 litre (L)) capacity. A low coolant level or high coolant temperature alarm buzzer and red indicator warning light shall be provided on the dash instrument panel.

3.3.1.7 Towing devices. Not less than two hooks or loops mounted to the frame or to rigid members which are attached to the frame, shall be furnished in front of the truck, for towing purposes.

3.3.1.8 Pintle assembly. A pintle assembly shall be furnished and shall conform to MS51335, part no. 51335-2. Rearmost portion of installed pintle shall be not more than 4 inches (102 millimetre (mm)) forward of the rearmost part of the vehicle. The attachment devices shall be capable of accommodating a standard grab hook that is 2.1875 inches (56 mm) wide, 0.6875-inch (18 mm) thick, and with a 0.484-inch (12 mm) throat width for a 0.375-inch (9.52 mm) chain. When specified (see 6.2), the pintle height, measured to the centerline at the pintle, shall be 20 inches (+5 inches, -0 inches) (508 mm (+12.7 mm, -0 mm)). Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. The pintle shall be installed with bracket reinforcements to transfer a vertical tongue load of not less than 1,800 lbs (817 kg) and a horizontal draw bar load of not less than 18,000 lbs (8 165 kg) directly to the chassis rails. The installation shall be capable of withstanding towed loads equal to the GVW of the truck without permanent deformation.

3.3.1.9 Splash guards and shields. Rear wheels shall have metal splash shields ahead of the wheels and rubber splash guards to the rear. Splash and stone throw protection shall be in accordance with SAE J682.

3.3.1.10 Radio interference suppression. The truck shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.3.1.11 Air pollution control. Trucks shall comply with the EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, trucks destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.3.1.12 Sound level. The exterior sound level produced by the truck shall conform to the Environmental Protection Agency Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks. The cab interior sound level shall not exceed 84 dB(A) when measured in accordance with Federal Motor Carrier Safety Regulation 393.94.

3.3.1.13 Lifting and tiedown attachments. When specified (see 6.2), the truck shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to type II or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the truck. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tiedown of the truck on the carrier when shipped.

3.3.1.14 Engine hour meter. An engine hour meter, having a totalizing mechanism of not less than 9,999 hours, shall be furnished for the truck chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to ensure continuous trouble-free performance under severe operating conditions. Engine hour meter shall be mounted on the cab instrument panel or in the engine component and system in a readable location.

3.3.1.15 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

3.3.1.16 Brake lights. No less than one pair of brake lights shall override the four-way emergency flasher, or the two systems shall be independent of each other. Modification to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Vehicle Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis manufacturer's standard matching hardware.

3.3.1.17 4 by 4 conversion. When type II truck chassis is required, the chassis manufacturer's standard 4 by 2 truck chassis may be modified to provide all-wheel drive requirements specified herein if:

a. The conversion axle manufacturer's engineering department specifically approves and certifies that all such modifications meet the design requirements and standards of the conversion axle manufacturer. Certification shall be based on both design analysis and proving ground test reports, which shall be made available to the engineering and quality assurance offices of the procuring activity.

b. The chassis manufacturer's front axle before conversion has the same load rating as the conversion axle to be installed.

c. Components used in the all-wheel drive conversion are of current production.

d. Components used in the all-wheel drive conversion are approved for the conversion application by the component manufacturers.

e. The converted vehicle is certified to conform to Federal Motor Vehicle Safety Standard No. 121, by the intermediate or final manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

f. Replacement headlights, if required to be added to meet the height requirement of Federal Motor Vehicle Safety Standard No. 108, are equivalent in mounting, protection, and range and precision of adjustment to the chassis manufacturer's original standard headlights.

g. Unused headlight cavities are covered in a neat workmanlike manner, treated, and painted to match the chassis cab color with treatment and painting equivalent to the chassis cab manufacturer's process for the remainder of the chassis cab. Cavities and their covers shall be rustproofed in accordance with 3.14.

h. Complete installation drawings are available to the procuring activity.

3.4 Interchangeability. All units of the same classification furnished with similar option under a specific contract shall be identical to the extent necessary to ensure interchangeability of component parts, assemblies, accessories, and spare parts.

3.5 Weight, ratings and dimensions.

3.5.1 Curb weight. Curb weight shall include weight of chassis and cab, with all attachments, accessories, equipment, body, full complement of fuel, lubricants, and coolant.

3.5.2 Weight ratings. The chassis shall be original equipment manufacturer rated at not less than 24,000 lbs (10 886 kg). Components ratings shall not be raised to meet the requirements of this specification.

3.5.3 Cab-to-axle. The cab-to-axle dimension shall be not less than 102 inches (2 591 mm) and not greater than 120 inches (3 048 mm).

3.5.4 Overall width. The overall width of the vehicle, exclusive of mirrors, lights. reflectors and tires, shall be not more than 96 inches (2 438 mm). The width over the tires shall be not more than 100 inches (2 540 mm).

3.6 Speeds and gradeability. The low and high speed requirements shall be demonstrated with truck loaded to chassis GVW rating (GVWR).

3.6.1 High speed gradeability. Truck shall ascend a continuous 2.50 percent grade at 50 miles per hour (mph) (81 kilometre per hour (km/h)). Gradeability requirements shall be met with the main transmission in direct drive, transfer case in high range and with the auxiliary transmission or transfer case on high speed range. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

3.6.1.1 Low speed. Low speed, with engine operating at not less than 35 percent of recommended governed speed, shall provide a truck speed of not more than 5 mph (8 km/h).

3.6.1.2. Maximum geared speed. Maximum geared speed at engine governed speed shall be not less than 58 mph (93 km/h).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.6.2 Brake performance. Service brakes shall comply with the performance requirements specified in DoT Federal Motor Carrier Safety Regulations, section 393.52. Service brakes shall control and hold the truck, loaded to the specified GVW, on a 30 percent grade. Parking brake shall hold the truck, loaded to the specified GVW, headed either up or down the grade, without slipping on a 30 percent grade.

3.7 Chassis components.

3.7.1 Engine. The engine furnished shall be the chassis manufacturer's standard gasoline or diesel engine for the commercial model truck which meets or exceeds the requirements of this specification. Engine net hp used in performance prediction calculations shall be determined in accordance with SAE J1349. A fan clutch to reduce fan speed automatically, when not required for engine cooling, shall be provided. The fan clutch shall be asbestos free.

3.7.1.1 Oil filter. Full flow type oil filter shall be furnished.

3.7.1.2 Governor. Engine governor shall be set and sealed to limit engine to the engine manufacturer's maximum recommended operating speed.

3.7.2 Electrical system.

3.7.2.1 Ignition system. For gasoline engine driven trucks, the ignition system shall be 12 volts (V) potential negative ground. Alternator of not less than 50 ampere rated capacity, and which provides not less than 16 amperes direct current output at normal engine idle speed, shall be furnished. The entire exposed wiring system shall be normally resistant to moisture and fungi without treatment.

3.7.2.2 Starting system. For diesel engine driven trucks, a 12- or 24V starting system, with 12V direct current lighting system, and not less than a 60 ampere alternator, shall be furnished. Engine starting equipment shall include an ether starting system, a manifold air heater, or glow plug. When an ether starting system is furnished, it shall be of the measured shot type, key operated or manually controlled from the driver's compartment and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 ounces (355 millilitre) shall be furnished. A reservoir need not be furnished.

3.7.2.3 Battery. Each battery shall be 12V potential. For gasoline engine driven trucks, the total cold reserve capacity rating shall be not less than 100 minutes and the total cold cranking ampere rating at 0 °F (-17 °C) shall be not less than 450 amperes. For diesel engine driven trucks, the total reserve capacity rating shall be not less than 320 minutes and the cold cranking ampere rating at 0 °F (-17 °C) shall be not less than 1,200 amperes. The batteries shall be of the maintenance free type with the maintenance free characteristics listed in SAE J537.

3.7.2.4 Lighting. All truck lights, reflectors, and wiring shall be as specified herein and shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.12, 393.19 through 393.31, as applicable. Lights and reflectors shall not be mounted on vertical surfaces of rub rails (unless recessed and fully protected) or mounted on bumpers. Brake lights shall override the emergency flashers on this vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.7.2.5 Blackout lights. When specified (see 6.2), in addition to lighting specified in 3.7.2.4, trucks shall be provided with combination blackout lights, taillights, and spotlights. Blackout lights shall be wired in such a manner as to preclude inadvertent lighting of the service lights when blackout lights are turned on, except for service spotlights which shall function during all operating conditions when brakes are applied. Blackout lights shall be installed at front and rear of truck. Those at the front shall be as far apart as practicable. Those at the rear shall be in the same housing as stop and tail lamps. The headlight blackout light, conforming to MS51318, shall be located on the left side front of the truck, and the blackout marker lights, conforming to MS52126, shall be located on the right and left side on the front of the truck. The rear blackout lights, conforming to MS52125, shall be located, one on each side, at the rear of the truck. All lighting shall be equipped with 12V bulbs.

3.7.2.6 Trailer electrical connector. A seven connector trailer electrical connector and cover assembly, conforming to SAE J560, with conductors connected and color coded as specified therein, shall be provided at a readily accessible location on the rear of the truck.

3.7.2.7 Electromagnetic compatibility requirement. When specified (see 6.2), the truck shall conform to electromagnetic compatibility requirements in accordance with MIL-E-6051.

3.7.3 Fuel system. Fuel system shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.65 and 393.67. The fuel system shall include a fuel/water separator with visual display to alert operator when service is required.

3.7.3.1 Air cleaner. A dry type air cleaner shall be furnished.

3.7.3.2 Fuel tank(s). Fuel tank(s) shall be manufacturer’s standard for the truck furnished. Fuel capacity shall be not less than 43 gallons (163 L). When more than one tank is furnished on diesel engine driven trucks, means shall be provided to assure equalized fuel level in both tanks. When more than one fuel tank is furnished on gasoline engine driven trucks, a selector valve shall be provided connecting either fuel tank to the engine fuel intake. Means shall be provided to monitor the fuel level of either tank from a single fuel gage.

3.7.4 Exhaust system. Exhaust system shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.83. A spark arrestor shall be furnished on vehicles, except with turbocharged engines. The spark arrestor shall have an 80 percent arresting efficiency when rated in accordance with SAE J350. A shield plate shall be installed, where necessary, to prevent spilled fuel and lubricants from coming in contact with the exhaust system. When furnished, vertical exhaust mufflers capable of being reached easily by personnel entering or leaving either side of the cab shall be provided with a heat shield. When furnished, vertical exhaust system shall be provided with a hinged rain cap.

3.7.5 Automatic or semiautomatic transmission. Unless otherwise specified, (see 3.7.6), the vehicle shall be provided with an automatic or semiautomatic transmission. The input torque capacity of the transmission shall be at least equal to the maximum torque deliver by the engine. The automatic or semiautomatic transmission furnished shall be of the fixed ratio type and shall include a hydraulic torque converter and not less than five forward gear ratios. Normal driving

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

range selector position shall be provided with not less than four gear ratios without movement of the selector. The transmission shall be provided with an SAE J704 power takeoff opening.

3.7.6 Transmission. When specified (see 6.2), a manually shifted five forward speed main transmission shall be furnished. Input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. Gear ratios in transmission, auxiliary transmission or transfer case (when furnished) and rear axle shall be matched to provide a progressive shifting pattern throughout the complete range. Transmission shall provide a progressive shifting pattern throughout the complete range and shall provide the required truck performance (see 3.6.1). Transmission shall be provided with SAE J704 power takeoff openings at right and left sides. The transmission shall provide for maximum ease of shifting at all speeds. A positive, manually operated, securing device shall be provided to lock the truck transmission to prevent transmission of power to the truck wheels when the power takeoff is engaged.

3.7.6.1 Speeds. The vehicle shall be provided with not less than ten forward speeds. The 4 by 2 model vehicle shall have an auxiliary transmission or 2-speed rear axle. The 4 by 4 model vehicle shall have a 2-speed transfer case and a single-speed rear axle. Gear ratios in the transmission or other gear selection equipment shall be matched to provide a progressive shifting pattern throughout the complete range and shall provide the required vehicle performance specified in 3.6.1.

3.7.6.2 Transfer case (model 4 by 4). Unless the transfer case is equipped with devices which compensate for differential torque and speeds between the front and rear axles, the transfer case shall provide for driver selection of either two-wheel or four-wheel drive. When interaxle compensating devices are furnished, they shall provide for the positive transfer of power to all the driving axles. A two-speed transfer case shall be furnished. The vehicle speedometer shall read accurate mph with the speed selector in high or low range.

3.7.6.3 Clutch. Clutch shall be the largest capacity optional clutch offered for the truck chassis and engine furnished, with torque capacity exceeding the maximum delivered engine torque.

3.7.7 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.7.8 Frame. The chassis frame shall withstand all loads imposed by the crane (see 3.8) with the crane loaded to rated capacity in all its attainable positions.

3.7.9 Suspension. Truck shall be equipped with suspension system with components having a minimum rated capacity equal to the load imposed on each member, measured at the ground, with truck loaded to rated GVW. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. The chassis shall be equipped with hydraulic double-acting shock absorbers at the front wheels.

3.7.10 Axles. Axles shall be rated for not less than specified minimum GVWR (see 3.5.2). The wheel bearings and axle spindles shall be oil lubricated. All nondriving axles shall be furnished

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

with hubcaps providing visual inspection of oil levels, and ventilation or replenishment of oil supply without removal. A single speed axle shall be furnished.

3.7.10.1 Traction control. The rear axle shall be furnished with an increased traction device. Maximum traction capabilities shall be maintained at all times under each drive wheel during operation.

3.7.11 Wheels, rims, tires, and tubes. Truck shall be equipped with single front and dual rear wheels. Rims and tire ratings (steel belted radial or tube type) shall conform to TRA or ETRTO recommendations for the type and size furnished. Tire and rims size shall be the same for all wheels on each truck. Disk type wheels shall be furnished. Multi-piece rims shall not be used in this vehicle.

3.7.11.1 Tires. Steel belted radial ply tubeless type with highway tread design shall be furnished. The tires shall be rated to not less than the minimum GVWR (see 3.5.2), or not less than OEM chassis rated GVWR if higher.

3.7.11.2 Tubes. When tube-type tires are furnished, tubes shall be of the heavy-duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with TRA recommendations.

3.7.11.3 Spare wheel assembly. A spare wheel shall be mounted on a carrier and installed in a readily accessible location on the truck. The spare wheel/tire location shall not require personnel to position any part of their body under the spare tire assembly during removal or installation.

3.7.11.4 Tire chain clearance. Tire chain clearance shall be in accordance with SAE J683. Allowance for spring deflection shall be included.

3.7.12 Brakes. Brakes shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.40 through 393.42, and 393.45 through 393.52.

3.7.12.1 Air brakes. The trucks shall be equipped with full air brakes on all wheels. The braking system, complete with all necessary components, shall include:

a. Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7.25 cubic feet per minute (cfm) (205 L per minute).

b. Air storage reservoir(s) with not less than 2,000 cubic inches (32 774 cm^3) total capacity, each tank equipped with a drain, and with safety and check valves between compressor and last reservoir tank.

c. Foot control, suspended or treadle type.

d. Air control valves.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

e. Air pressure gage, visible to the driver.

f. Low air pressure warning, visible and audible.

g. Service brake stop lamp switch.

h. Automatic moisture ejector.

i. When specified (see 6.2), automatic slack adjusters on cam type brakes or internal self adjusting devices on wedge or disc type brakes on all axles.

3.7.12.2 Air dryer. A replaceable cartridge desiccant type air dryer shall be installed in the air brake system. The dryer shall have the capability of removing not less than 95 percent of the moisture in the air being dried. The dryer shall have a pre-cooler and a filter to screen out oil and solid contaminants. The dryer shall have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve.

3.7.13 Cab. The chassis manufacturer's standard production full width type cab of either the conventional or cab-over design shall be furnished. When a conventional design with engine hood is furnished, the hood shall be of the full tilt style. Cab doors shall be equipped with locks, operable from inside the cab and with not less than one door equipped with external, key-operated lock. Drip rails shall be provided above the cab doors. Interior dome lighting shall be provided. Manufacturer's standard full width seat and three pairs of seat belts shall be furnished on the truck. The color of the upholstery and interior finish shall be compatible with the exterior color (see 3.13). White upholstery shall not be furnished.

3.7.14 Heater and defroster. Manufacturer's standard hot water heater and defroster shall be provided. The system shall have include fresh air intakes and discharge areas for floor and windshield defrosting. Heater and defroster controls shall be convenient to the operator's position.

3.7.15 Windshield wipers and washers. Truck shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by either air or electric motor(s). When electric powered wipers are furnished, controls shall include intermittent operation mode.

3.7.16 Steering. Manufacturer's standard power assisted steering shall be furnished.

3.7.17 Controls and operating mechanism. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.7.18 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following equipment, as a minimum, shall be furnished:

a. Combination (flat and convex) outside rearview mirrors shall be provided on each side of cab. Each combination mirror shall have not less than 50 square inches (32 258 mm^2) of flat reflective area and a convex surface having not less than 25 square inches (16 129 mm^2) of reflective area. Each mirror shall have not less than two supporting arms.

b. Key-operated ignition switch.

c. Ammeter or voltmeter charging indicator.

d. Fuel gage(s).

e. Oil pressure gage.

f. Engine temperature gage.

g. Speedometer with recording odometer.

h. Dual sun visors.

i. Door mounted armrest on driver's side.

j. Driver's compartment ventilator other than window.

k. Manufacturer's standard horn.

l. Adjustable throttle, for hoist operations.

m. Audible backup alarm device.

3.7.19 Front bumper. Manufacturer's standard front bumper shall be furnished.

3.7.20 Rear end protection. Rear end of the truck shall be protected in accordance with DoT Federal Motor Carrier Safety Regulations, section 393.86. Rear bumper or bumperettes shall be furnished.

3.7.21 Front mounted winch. When specified (see 6.2), truck shall be furnished with a winch assembly, mounted on the front of the truck and powered by manufacturer's standard power takeoff. The winch shall conform to SAE J706. Winch shall be single drum type and shall have not less than one forward and one reverse speed. All winch controls shall be inside cab mounted. Winch controls shall be located to provide no interference with the ingress or egress of the driver.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

Winch shall have a rated single line pull capacity of not less than 20,000 lbs (9 072 kg) on the bare drum. Winch shall be wound with not less than 185 feet (56 388 mm) of 0.625-inch (15 875 mm) diameter cable of improved plow steel, wire strand core, and shall be equipped with end chain and hook. An integral, adjustable, automatic safety brake shall be provided. Winch shall be equipped with a roller guide. Angles of the winch drive line U-joints shall be not greater than 17 degrees.

3.7.21.1 Winch drum guard. Winch drum guard shall be furnished. The guard shall confine the cable to the area between the drum flanges.

3.7.22 Angle of approach. The angle of approach shall be not less than 22 degrees, with or without winch assembly, when the truck is loaded to its maximum GVW.

3.7.23 Fire extinguishers and brackets. When specified (see 6.2), two fire extinguishers and two brackets for retaining the fire extinguishers shall be furnished. Fire extinguishers shall be in accordance with A-A-393, type II, class 2, size 10. The fire extinguisher shutoff valve shall be located at the outlet of the discharge hose. Design of each bracket shall enable extinguisher to be readily released in one operation with one hand. Brackets shall be mounted one on each side of the truck. Adequate protection from splashing of mud and water shall be provided. Fire extinguishers shall be located as to be readily accessible to anyone standing on the ground.

3.7.24 Rotating warning light. Two strobe type, amber lights shall be furnished and mounted to provide 360-degree visibility. The strobe lights shall be operated through a single switch located within easy reach of the driver's position, and equipped with a red color, dash mounted, indicator light, indicating when the light is activated. The switch and indicator shall be marked to identify the function.

3.8 Crane. A one-man operated, fully hydraulic, articulated boom type crane shall be mounted on the truck chassis frame between the cab and platform body. The space behind the cab for crane installation shall be not greater than 36 inches (914 mm). The crane shall be powered by transmission mounted power takeoff. The boom shall consist of an upper and lower section and include a hydraulically operated extendible jib. The total extension and retraction of the jib shall be hydraulically controlled. The boom, when fully extended, shall reach not less than 18 feet (457 mm) and hoist not less than 23 feet (584 mm) above ground level, and shall not rotate safely through not less than 190 degrees with no drift rotation. The boom shall fold to a nestable travel height between platform body and truck cab, and shall be not greater than 85 inches (2 159 mm) above truck chassis frame. A means shall be provided to protect the truck cab from damage due to crane rotation during stowage positioning and crane swing operations. The crane design shall provide for smooth and quiet operation, ease and flexibility of operation, and versatility of performance. Crane shall be provided with load holding capability that will enable the crane under static load conditions to be not greater than 0.25 inches (6 mm) per minute vertical downward creep while loaded to maximum capacity rating at any extension point. The truck mounted crane shall comply with all applicable OSHA regulations, including OSHA 1926.550.

3.8.1 Crane capacity. With outriggers in a down position, the crane shall be capable of lifting a load of not less than 4,000 lbs (1 814 kg), when the load is positioned at a horizontal working

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

radius of 10 feet (3 048 mm), and a load of not less than 2,000 lbs (907 kg) at a horizontal working radius of 18 feet (5 486 mm). The crane horizontal working radius is the measured distance from centerline of crane rotation to the centerline of the lifting hook. A capacity chart shall be provided showing, as a minimum, the maximum allowable loads at working radii of 18 feet (5 486 mm), 16 feet (4 876 mm), 14 feet (4 267 mm), and 10 feet (3 048 mm). The crane capacity chart shall be provided and shall be located one on each side of the truck, in a position to enable the crane operator to read it from ground level.

3.8.2 Crane hoist hook. Unless otherwise specified (see 6.2), manufacturer's standard hoist hook shall be provided, furnished with a swivel safety hook, and shall have not less than a 2-inch (51 mm) throat opening. The rated capacity of the crane hook shall be not less than the rated capacity of the crane for which it is furnished. The hook shall be of the forged steel, swivel type with an ultimate strength of four times the maximum safe-rated load and shall include a safety latch on the hook. The rated capacity of the crane hook shall be not less than the rated capacity of the crane for which it is furnished. The hook shall be forged steel, swivel type with an ultimate strength of not less than four times the maximum safe rated load and shall include a safety latch on the hook. The hook furnished shall permit disassembly for visual and nondestructive testing. The hook shall not be painted.

3.8.3. Outriggers. Double-acting hydraulic outriggers, independently controlled and integrally mounted to the crane base, shall be furnished. Two outriggers shall be provided, one on each side of the truck. Each outrigger landing pad shall be not less than 140 square inches (90 322 mm^2). Pads shall be pinned to outrigger if removal is necessary. The outriggers shall provide side-to-side leveling of the truck on inclined surfaces and on level surfaces. The overall length of the fully retracted outrigger shall be not greater than the width of the platform body.

3.8.3.1 Outrigger warning light. A red warning light shall be located and installed in the cab in a conspicuous location to warn the driver that the outriggers are not fully retracted. The warning light shall be suitably labeled to indicate light function.

3.8.4 Crane mounting. Unless otherwise specified (see 6.2), the mounting of the crane on the truck chassis frame shall be the manufacturer's standard method.

3.8.5 Hydraulic system. Hydraulic system with power takeoff, pump, piping, valves, controls, and other components necessary for a complete installation, shall be furnished for the crane and outriggers. Power takeoff for the hydraulic pump shall be controlled from the inside of the truck cab. A hydraulic fluid filter and a reservoir shall be provided. The hydraulic system shall contain not less than the following features:

a. Check valve system in boom and outrigger system to prevent load drop due to hydraulic system failure.

b. Consistent flow valve in hydraulic lines to preclude boom damage due to sudden load lowering stops.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

c. Cushioning valves in boom rotating hydraulic system to preclude damage due to sudden stops or extreme induced side loads.

d. A pressure relief valve shall be provided to prevent damage to pump, valves, and hoses when the hydraulic system is over pressurized.

e. Sign with 1-inch lettering, visible to the operator at both sets of crane controls: OUTRIGGERS MUST BE FULLY EXTENDED AND IN PLACE BEFORE LIFT IS MADE.

f. Each safety check pilot valve, flow valves, cylinder, and hydraulic lines shall be free of contaminates.

g. Clearly identify power takeoff lever in cab for engaging crane hydraulic pump.

h. Provide positive seating or holding valves that will enable crane, under static load condition, to hold maximum load with specified acceptable vertical creep due to hydraulic system malfunction or failure.

i. A red warning light shall be located and installed in the cab in a conspicuous location to warn the driver that the power takeoff unit is engaged. The warning light shall be suitably labeled to indicate light function. A caution plate reading: “Do not operate vehicle with power takeoff engaged” shall be installed.

3.8.6 Controls. Crane controls shall be provided in each side of the truck. Each outrigger control shall be located on the same side of the truck as the outrigger. Crane and outrigger controls shall be accessible from ground level. Controls shall be of the deadman type to ensure automatic return to neutral position in event of either inadvertent of intentional release by the operator. All crane and outrigger controls shall be identified to indicate what it is and how it is to be used. Provisions to ensure against engagement of power to truck wheels and crane at the same time shall be provided. Controls shall have fine metering qualities to provide infinitely variable raising, lowering, and rotating motions of the crane boom. There shall be no acceleration or surging of the load when activating crane control.

3.8.7. Stability warning device. An audible warning device shall be provided that will alert the crane operator when swinging the load, that a potentially unstable truck position exists either caused by overload or partially extended outrigger. This device shall be installed in conjunction with power takeoff operation and shall activate from 5 degrees off the truck horizontal plane.

3.8.7.1 Overload shutdown system. The crane shall be provided with an overload shutdown system that shall preclude structurally overloading the crane. All crane functions shall shut off when the crane’s capacity is exceeded by 20 percent during such operations of load lowering, boom extension, or both, of the load that would increase the crane’s working radius. A manual override, of the deadman type, shall be provided to return the crane to normal operation after the overload shutdown system has been activated. The crane overload system shall be designed

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

fail-safe operation in event the crane's electrical or hydraulic system should become inoperative. Truck engine shutdown when system is activated is not acceptable.

3.8.8 Environmental performance. The crane shall be certified by the crane manufacturer, to perform satisfactorily all requirements specified herein in any ambient temperature from -25 °F to +125 °F (-4 °C to 52 °C) without any malfunction.

3.8.9 Stress requirements. Design of the truck mounted crane shall be such that the sustained maximum unit stress imposed by the rated load shall be not more than the minimum strength margins established in SAE J1063 for cantilevered boom crane structures. When specified (see 6.2), a strain gage test shall be performed on the specific crane (identified by serial number), furnished as the first article in accordance with the methods and procedures set forth in SAE J1063.

3.9 Body. The truck shall be equipped with an all steel constructed platform type body. The overall length of body shall be not less than 144 inches (3 658 mm). The overall width of body shall be not greater than 96 inches (2 438 mm). The platform body frame shall be provided with longitudinal members and crossmembers of sufficient strength to support the payload (see 3.5.2 through 3.5.4). The platform body shall be provided with sufficient stake pockets to accommodate the removable type body front and side panels specified herein (see 3.9.1 through 3.9.1.2). The stake sides and pockets shall include retention devices to prevent accidental detachment. The devices shall not require tools to remove stake sides. Unless otherwise specified (see 6.2), the platform body shall be mounted on the truck chassis frame with the manufacturer's standard method. The floor of the platform body shall be steel, of sufficient thickness to support a concentrated load of 300 pounds per square foot (1 334 Newton meter (N·m)) at any point on the floor load space. The steel platform deck shall be covered with 0.75-inch (2 mm) exterior marine grade plywood fastened with countersunk aluminum bolts. Effective means shall be provided to impede electrolytic/galvanic corrosion between nonferrous fasteners and steel floor. When specified (see 6.2), the platform body shall be mounted on the truck chassis frame with quick-disconnect devices incorporating quick-release bolts so body can be quickly removed from truck chassis for helicopter lift as a separate unit.

3.9.1 Cargo conversion unit. Unless otherwise specified (see 6.2), a cargo conversion unit shall be furnished and shall consist of body front, sides, tailgate, apertures, and cargo ties as specified herein. The body front, sides, and tailgate shall be fabricated from steel, and provide a smooth inside surface. The stakes of the body sides and front panels shall face to the exterior of the body. The body panels shall face toward the load space. The body panels and tailgate shall be of not less than 0.0478-inch (1.21 mm) (US revised standard gage No. 18) thick sheet steel.

3.9.1.1 Body front panel. The permanent body front panel shall be not less than 14 inches (356 mm) in height and shall be provided with not less than four vertical supports and not less than four stake pockets for additional body front panels not less than 12 inches (305 mm) in height. The top and bottom of the panel shall be formed outward into a box section of sufficient width to provide stake pockets. The body panel stakes shall be not less than 3 by 2 rectangular steel section of not less than 0.125-inch (3 mm) and shall be attached to the outside of the panel

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

through the stake pockets. The body front panel shall be secured to the platform using the same retention devices as the side stakes.

3.9.1.2 Body side panels. Body side panels shall be not less than 14 inches (356 mm) in height and shall be not more than 48 inches (1 219 mm) in length shall be provided for each side of the platform body. Each body side panel shall be provided with not less than two stakes. The body panel stakes shall be not less than 3 by 2 rectangular steel section of not less than 0.125-inch (3 mm), and shall be attached to the outside of the panel. The stake length shall be such as to be attached for the full height of the body panel plus the required length to allow attachment into stake pocket. Each forward side panel shall be attached to the intermediate side panel. Each side and end panel shall be furnished with attachment devices to lock to each other. These devices shall not require tools to operate, and shall allow individual panel removal.

3.9.1.3 Tailgate. The tailgate shall be not less than 16 inches (406 mm) in height. The tailgate shall be flanged outward into a box section on top and sides and reinforced on the bottom edge. The tailgate shall be hinged at the bottom with four hinges; the upper hinge strap shall run the full height of the tailgate. Removable type fastenings shall be provided for the tailgate hinges that are secured to the platform body. Tailgate locking devices shall be provided. Tailgate shall be capable of traversing 180 degrees from the vertical, closed position. Tailgate shall be provided with duck covered stay-chains of a length to retain the tailgate at a horizontal position. When tailgate is lowered to the horizontal position, the tailgate shall be flush with the platform body. Stirrup steps, of 200 lbs (91 kg) capacity each, shall be attached on the top flange on each side of the tailgate to assist personnel in mounting and dismounting. The tailgate assembly shall support, without deformation, a total of not less than 400 lbs (181 kg). Tailgate shall not interfere with pintle hook assembly. Rear lights and reflectors shall be positioned to preclude damage by lowering of gate.

3.9.1.4 Apertures. The platform body floor shall be provided with 24 apertures. Each aperture shall be 2.5 inches (64 mm) in diameter. The apertures shall be arranged in the following pattern: 1-foot (305 mm) from each platform edge, and 2 feet (610 mm) between centerline of apertures. The apertures shall be deburred to preclude the edge from cutting the cargo ties.

3.9.1.5 Cargo ties. Eight sets of cargo ties shall be furnished for each truck. Each set shall consist of two units. One unit shall be not less than 3 feet (914 mm) long webbing having a buckle secured on one end and a pin permanently attached to the other end. The second unit shall be not less than 15 feet (4 572 mm) long webbing having a pin permanently attached to one end, and the other end shall have a metal protective device to prevent fraying. The webbing shall be 1.75 inches (44 mm) wide, fire, water, weather, and mildew resistant nylon. The buckle shall be 1.75 inches (44 mm) heavy duty, corrosion-resistant ratchet type. The pin shall be not less than 0.375-inch (10 mm) round steel bar shock 4.5 inches (114 mm) long. The total assembly of set consisting of the two units, shall have a tensile strength of not less than 5,000 lbs (2 268 kg). A separate, lockable, weatherproof, storage compartment shall be furnished for eight sets of cargo ties.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.10 Floodlights. Two, adjustable floodlights, not less than 6 inches (152 mm) in diameter shall be installed, one on or near each rear corner of the cab, to illuminate crane working area and platform body area. Each floodlight shall be provided with a weather-resistant toggle switch.

3.11 Tool compartment. A weatherproof tool compartment of not less than 8 cubic feet (0.74 m^2) capacity shall be furnished. The tool compartment shall be installed at the forward end of the body under the chassis at the curb side. Provisions for locking with padlock shall be provided.

3.12 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch (113 N·m) or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.13 Treatment, painting, identification marking. As specified by the procuring activity for the appropriate service (see 6.2), treatment, painting, and identification marking shall be in accordance with MIL-STD-1223.

3.14 Rustproofing. When specified (see 6.2), the truck cab, chassis frame, and chassis underside shall be rustproofed in accordance with FED-STD-297.

3.15 Servicing and adjusting. Prior to acceptance of the truck by the Government, the contractor shall service and adjust the truck for immediate operational use as required in the operator's manual. The servicing and adjusting shall include not less than the following:

a. Inflation of all tires.

b. Adjustment of brakes (when required).

c. Proper functioning of all lighting and electrical systems.

d. Wheel alignment (when required).

e. Adjustment of engine to include tune-up.

f. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.

g. Cooling system filled to capacity with a clean solution of equal parts by volume of water and antifreeze (ethylene glycol).

The truck shall be conspicuously tagged to identify the lubricants and their temperature range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.16 Prohibited materials. Asbestos, cadmium, and radioactive material shall not be used in this item. Radioactive material is defined by Title 10, Code of Federal Regulations (CFR), Parts 30 and 40, and other radioactive material in which the specific activity is greater than 0.002 microcuries per gram or activity per item equals or exceeds 0.01 microcuries.

3.17 Safety. Noise levels shall be less than 85 dB(A) at the operator's position and other occasionally occupied positions as measured during typical operating conditions and environments. If noise levels cannot be reduced to below 85 dB(A) then hearing protection warnings will be placed on the unit where they can be read by those personnel exposed to the hazard.

3.18 Workmanship.

3.18.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to ensure uniformity of size and shape.

3.18.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.18.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened shall be of approved shape and of uniform size for the same diameter or rivet. The rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.18.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification, where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submissions of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. This inspection shall include the examination of 4.3 and the tests of 4.4. The purpose of the inspection shall be to determine vehicle conformity with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3 and the tests of 4.4.4 and 4.4.5.

4.3 Examination. Each truck shall be examined for compliance with the requirements specified in section 3 of this document. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Test. Failure to pass any test shall constitute cause for rejection.

4.4.1 Vehicle weight. The completed truck assembly, shall be weighed to determine total weight. The total weight shall be subtracted from the GVW rating to determine the total payload capacity. A payload equal to the total capacity, less allowance for the driver and the inspector, shall be equally distributed over the body floor. The truck shall be weighed again to determine individual axle loading and confirm loading of maximum GVW rating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

4.4.2 Road test (Type I, 4 by 2 truck). The type I truck, loaded to the specified GVW, shall be driven at a speed of 50 mph (81 km/h) over improved roads for not less than 30 miles (48.3 km), and at a speed of 20 mph (32 km/h) over unimproved roads for not less than 20 miles (32 km). The truck, loaded to the specified GVW, shall be driven at speeds varying from 5 mph (8 km/h) to 20 mph (32 km/h), acceleration and deceleration operation, for not less than 10 miles (16 km). Upon completion of the test, the truck and equipment shall be inspected for leaks, warping, distortion, malfunction.

4.4.2.1 Road test (Type II, 4 by 4 truck). Type II truck, for models built to four-wheel drive, while on the chassis manufacturer's production line, shall be road tested by the contractor with payload to provide specified GVW. The road test shall be for not less than 30 miles (48 km) at speeds up to 55 mph (89 km/h), and for not less than 20 miles (32 km) at a speed of 20 mph (32 km/h). When unimproved roads are not available, the test shall include a total of not less than 100 paved surface miles. The vehicle, for four-wheel drive models qualifying under 3.1.1.15, shall be road tested with and without payload. Payload shall be distributed first, so that the front axle is loaded to GVWR and the vehicle is loaded to GVW. The road test for each of the three conditions shall be not less than 30 miles (48 km) at speeds up to 50 mph (81 km/h) over highways and gravel roads and for not less than 5 miles (8 km) at speeds up to 15 mph (24 km/h) over cross country terrain with ground and grade requiring all-wheel drive. During the loaded and empty portions of the road test, the brakes shall be applied firmly, bringing the vehicle to a sudden stop not less than five times during each portion of the road test. During the road test, the front and rear suspension and the drivetrain shall be periodically inspected for interference and contact with other vehicle components. Abnormal contact of the drivetrain or suspension components with other components shall be cause for rejection. Front spring bumpers shall not make contact with frame stops except under the most extreme cross country conditions. Operational or mechanical failures of vehicle components during the road test shall be cause of rejection. Failure includes permanent deformation as well as breakage.

4.4.2.2 Documentation. The contractor shall furnish to the Government copies of the certification and test reports required by 3.3.1.17(a) for Type II vehicles with 4 by 4 conversion.

4.4.3 Service brake test. The truck shall be loaded to rated capacity. The truck shall be subjected to three emergency stops in rapid succession from 20 mph (32 km/h) on clean, dry, smooth, level, paved surface free from loose material. Each stop shall be accomplished in not more than one-minute intervals. The truck shall stop within 40 feet (12 192 mm) from the point the brakes are applied. This test shall be conducted not less than four times over the duration of the road test.

4.4.4 Crane operation test. The crane shall be operated through not less than 10 cycles of loading and unloading truck at each safe rated load capacity and radii to verify conformance to the capacity requirements of 3.8.1. During the cycle tests, the following shall be accomplished:

a. The rotational and lifting requirements shall be verified to determine conformance to 3.8.

b. Verify that hydraulic system safety features and devices conform to requirements of 3.8.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

c. Verify that crane controls conform to the requirements of 3.8.6.

d. Verify that the stability warning device conforms to the requirements of 3.8.7.

e. Verify that the overload shutdown system conforms to the requirements of 3.8.7.1.

4.4.5 Static overload test. Static overload test shall be performed on the crane with 110 percent of rated capacity at the minimum and maximum rated radii.

4.4.6 Vertical creep test. Verify conformance to 3.8.5(h) as follows:

a. With the outriggers set, boom at minimum and maximum extension position approximately horizontal in the most stable direction, lift a rated load, and hold the rated load for 10 minutes. The load shall not lower more than 0.25 inches (6 mm) each minute (total of 2.5 inches (64 mm) during 10 minutes), due to internal hydraulic leakage. There shall be no external hydraulic leakage or component failure during this test. A copy of the test report of this verification shall be provided with each truck shipped.

4.4.7 Environmental test. The truck mounted crane shall be tested to verify conformance to operational capabilities at low and high temperature requirements of 3.8.8. After a minimum 8-hour soak period at each temperature range, the crane shall be operated under load through all crane functions. The truck cab heater and defroster shall be checked during low temperature tests. To determine conformance to 3.8.8, the manufacturer may certify that a complete test has been conducted on an identical truck mounted crane model and test records are available for inspection. If this certification is not furnished, and test records are not available, then the test shall be conducted as specified herein.

4.4.8 Crane stress requirement test. When crane strain gage stress requirement verification test is required, the truck mounted crane shall be tested in accordance with SAE J1063 as set forth in 3.8.9.

4.4.9 Lifting attachment test. When lifting attachments are required, the components shall be suspended by the lifting attachments with suitable slings. The load on each lifting attachment shall be determined with the component on suspension. The component shall be lowered and each lifting attachment shall be subjected to a pull equal to or greater than 2.5 times the load reading previously obtained in the same lifting attachment while the component was suspended to determine conformance to 3.3.1.13.

4.4.10 Production sample. Upon acceptance of the first article vehicle, it shall remain at the manufacturing facility as a production sample, and may be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging requirements. The preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The trucks covered by this specification are intended for use in loading, unloading, and transporting munitions at military installations.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type of truck chassis required (see 1.2).
c. When first article vehicle inspection is required (see 3.2).
d. When identification plates are furnished by contractor (see 3.3.1.1).
e. When pintle height of 20 inches (+5 inches, -0 inches) (508 mm (± 12.7 mm, -0 mm)) is required (see 3.3.1.8).
f. When lifting attachments are required (see 3.3.1.13).
g. When gasoline or diesel engine is required (see 3.7.1).
h. When blackout lights are required (see 3.7.2.5).
i. When electromagnetic compatibility requirement is required (see 3.7.2.7).
j. When manual shift transmission is required (see 3.7.6).
k. When full automatic slack adjusters are required (see 3.7.12.1).
l. When front mount winch is required (see 3.7.21).
m. When fire extinguishers are required (see 3.7.23).
n. When crane hoist hook other than specified is required (see 3.8.2).
o. When mounting of the crane is not manufacturer's standard method (see 3.8.4).
p. When crane strain gage stress requirement verification test is required (see 3.8.9.).
q. When mounting of the platform body is manufacture's standard method and when quick-disconnect type platform body mounting devices are required (see 3.9).
r. When cargo conversion body unit is not required (see 3.9.1).
s. Appropriate service for treatment, painting, and identification marking (see 3.13).
t. When rustproofing is required (see 3.14).


6.3 Performance prediction. Completed copies of SAE Truck Ability Prediction Procedure form and computation for speed requirements for each vehicle model furnished under contract should be submitted as specified in the contract. The SAE Work Sheet Item should include vehicle model number, wheelbase, engine model number, and vehicle type. Unless other conditions are sighted in the contract, computations should be made for normal atmospheric pressure; normal ambient air temperature; and still, dry air.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

The factors to be used in predicting truck ability (see 3.6.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Table 1	- Tire factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.	
Table 2	- Altitude factor.	1.00
Table 3	- Rolling factor.	1.613
Table 4	- Area factor. Use factor.	0.1173
Table 5	- Velocity factor.	250.0
Table 6	- Altitude factor.	1.00
Table 7	- Chassis friction. Use applicable power unit GVW (to nearest, high 1,000 lbs (453 kg)) and the engine 100 revolutions which is required for 50 mph (85 km/h) geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated.	
Table 8	- Grade factor.	0.75
Table 8A	- Correction factor.	Not required.
Table 9	- Road factor.	0.0

6.4 Part or Identifying Numbers (PINs). The specification number and type are combined to form PINs for ammunition trucks covered by this document (see 1.2). PINs for ammunition trucks are established as follows:



6.5 Supersession data. This specification replaces Military Specification MIL-T-81098F dated 20 February 1991.

6.6 Subject term (key word) listing.

Ammunition
Diesel engine
Platform
Truck

6.7 Classification cross reference. Classifications used in this specification (see 1.2) are identical to those found in the superseded Military Specification MIL-T-81098F.

6.8 Changes from previous issue. Marginal notations are not used to identify changes with respect to the superseded document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - YD1

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

Preparing Activity:
Navy - YD1

(Project 2320-0687)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** KKK-T-2893	**2. DOCUMENT DATE (YYMMDD)** 970314

3. DOCUMENT TITLE **TRUCK, AMMUNITION HANDLING: STAKE AND PLATFORM BODY, 24,000 POUNDS GVW, 4 BY 2 OR 4 BY 4**

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7. DATE SUBMITTED** (YYMMDD)

8. PREPARING ACTIVITY

a. NAME RUDY PAMPLONA	b. TELEPHONE *Include Area Code)* (1) Commercial (805) 982-5843 (2) AUTOVON 551-5843
c. ADDRESS *(Include Zip Code)* COMMANDING OFFICER, NCBC CODE 15E2D 1000 23RD AVENUE PORT HUENEME, CA 93043-4301	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE QUALITY AND STANDARDIZATION OFFICE 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22401-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.