[INCH-POUND]
KKK-T-2921
April 14, 1997
SUPERSEDING
MIL-T-45381E
30 March 1991

FEDERAL SPECIFICATION

TRAILER, CABLE REEL

The General Services Administration has authorized the use of this specification by all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers cable reel trailers designed to carry one reel. Trailers procured under this specification are modified commercial items which shall be warranted by the manufacturer as specified in procurement documents. This specification covers one classification of cable reel trailer.

2. APPLICABLE DOCUMENTS

2.1 Government publications. The issues of the following documents, in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Commercial Item Description

A-A-52464 - Coupler, Drawbar, Ring: Light Duty, 60,000 lb GVW; Offset (Taper Shank), 60,000 lb GVW; and Heavy Duty 120,000 lb GVW.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Commanding Officer (Code 1581), Naval Construction Battalion Center, 1000 23rd Avenue, Port Hueneme, CA 93043-4301, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

Military Standards

MIL-STD-209	-	Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MS75021	-	Connector, Receptacle, Electrical-12 Contact, Intervehicular, 24 Volt Waterproof.

(Copies of military specifications and standards required by contractors in connection with specific procurement specifications are obtained from Defense Automated Printing Services, Attn: DoDSSP, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.1 Other Government documents and publications. The following other Government documents and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on the date of invitation for bids or request for proposal shall apply.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE J534	-	Lubrication Fittings.
SAE J560	-	Seven Conductor Electrical Connector for Truck-Trailer Jumper Cable.
SAE J588	-	Turn Signal Lamps.
SAE J682	-	Rear Wheel Splash and Stone Throw Protection (DoD adopted).
SAE J697	-	Safety Chain of Full Trailers or Converter Dollies.
SAE J702	-	Brake and Electrical Connection Location-Truck-Tractor and Truck-Trailer.

(Private sector and civil agencies may purchase copies of this voluntary standard from the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Private sector and civil agencies may purchase copies of this voluntary standard from the Tire and Rim Association, Inc., 175 Montrose West. Avenue, Suite 150, Copley, OH 44321.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

THE EUROPEAN TYRE AND RIM TECHNICAL ORGANIZATION (ETRTO)

Standards Manual.

(Private sector and civil agencies may purchase copies of this voluntary standard from the European Tyre and Rim Technical Organization publications should be addressed to the European Tyre and Rim Technical Organization, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

(DoD activities may obtain copies of those adopted voluntary standards listed in the DoD Index of Specifications and Standards free of charge from Defense Automated Printing Services, Attn: DoDSSP, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The trailer shall be a hydraulically operated, self-contained commercial vehicle of the manufacturer's latest standard single-reel design and shall include the requirements specified herein. Trailer frame shall be of all-steel construction with towbar, spring suspension, reel holders, landing leg, brakes, pneumatic tires, standard lighting system, and all other parts and accessories to make a complete and serviceable unit.

3.2 First production trailer. When specified (see 6.2), the contractor shall furnish a trailer for first production trailer inspection (see 4.2.1).

3.3 Standard commercial product. The trailer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the trailer being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs or brochures and represents the latest production model.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

Unless otherwise specified, none of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification.

3.5 Interchangeability. All trailers of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to ensure interchangeability of component parts, assemblies, and spare parts.

3.6 Design and construction. Design and construction of the trailer shall be such that no member or part shall show evidence of failure or permanent deformation under severe service conditions.

3.6.1 Hydraulics. The trailer shall be provided with a self contained, hydraulically operated, reel lifting system. Reels shall be loaded without tilting the trailer. The hydraulic system shall be either manual or powered. All hydraulic controls shall be mounted in one location at the front of the trailer.

3.7 Performance.

3.7.1 Travel speed. The trailer, fully equipped and loaded to rated payload capacity (see 3.9), shall be capable of being towed over unimproved roads and reasonably hard uneven terrain at a speed of 10 miles per hour (mph) (16 kilometre per hour (km/h)), and over improved roads at speeds as great as 45 mph (72 km/h) (see 6.4).

3.7.2 Turning ability. When towed, the trailer shall be capable of forming a 70-degree angle with the towing vehicle without cramping or damage to the trailer or towing vehicle.

3.7.3 Tracking ability. The trailer shall not exceed the allowance for tracking deviation specified in DoT Federal Motor Carrier Safety Regulations, section 393.70(a).

3.7.4 Brake performance. The brakes shall comply with the performance requirements specified in DoT Federal Motor Carrier Safety Regulations, section 393.52.

3.8 Dimensions and clearances.

3.8.1 Overall height. Overall height of the trailer (less reel) shall be the minimum practicable.

3.8.2 Width. The overall width of the trailer shall be the minimum practicable for the reel size specified (see 3.8.4), but shall be not greater than 102 inches (2 591 millimetre (mm)).

3.8.3 Ground clearance. Ground clearance shall be not less than 9 inches (229 mm) with maximum sized reel in transport position.

3.8.4 Reel width. Unless otherwise specified (see 6.2), trailer shall accommodate cable reels up to 60 inches (1 524 mm) in width.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.8.5 Reel diameter. The trailer shall accommodate cable reels from 24 inches (610 mm) to 108 inches (2 743 mm) in diameter.

3.9 Rated payload capacity. Unless otherwise specified (see 6.2), the rated payload capacity shall be not less than 15,000 lbs (6 795 kilograms (kg)).

3.10 Components.

3.10.1 Frame and towbar. The frame and towbar shall be of sturdy integrated construction, fabricated from steel tubing or structural steel sections, and braced to prevent distortion under operating conditions specified in 3.7. Length of towbar shall be sufficient to satisfy the turning ability requirement of 3.7.2. The towbar shall conform to applicable requirements of DoT Federal Motor Carrier Safety regulations, section 393.71(h).

3.10.2 Coupler ring. Unless otherwise specified (see 6.2), coupler ring shall be manufacturer's standard of 3-inch (76 mm) inside diameter. When specified (see 6.2), trailer towbar shall be provided with coupler ring conforming to A-A-52464. Provisions shall be made to adjust the height of the coupling device with the trailer in a horizontal position on level ground. The coupler shall be adjustable from a height of not less than 18 inches (457 mm) to not greater than 26 inches (660 mm). The coupler shall have not less than four adjustment positions.

3.10.3 Axle and suspension. The trailer shall be equipped with standard type axle(s) adequate to support the specified maximum load. Unless the loaded reel is spring suspended, the axle suspension system shall be of a springing capacity to sustain the rated payload under the performance characteristics specified herein without transmitting damaging shock to the trailer.

3.10.4 Reel spindle. The reel spindle shall be 2.5 inches (64 mm) in diameter and shall be provided with adjustable cone-shaped collars or guides for various reel widths. The spindle shall be hydraulically adjustable for height from reel holders to enable leveling of the spindle when the trailer is on uneven ground or embankment.

3.10.5 Reel holders. Construction of reel holders shall be such as to enable the reel to be picked up hydraulically and mounted on the trailer by one man without the aid of a separate winch or crane.

3.10.6 Landing leg. The landing leg shall be hydraulically operated and adjustable for vertical rise and shall be capable of supporting the loaded trailer in a level attitude without tipping, and shall be provided with a safety lock.

3.10.7 Cable payout brake. A cable payout brake shall be provided with an adjustment to control braking action.

3.10.8 Safety chain. The trailer shall be equipped with a safety chain or steel cable conforming to DoT Motor Carrier Safety Regulations, sections 393.70(d) and SAE J697.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.10.9 Wheels and rims. Wheels shall be the manufacturer's current standard. The rim size shall be as recommended by the TRA or ETRTO for the size of tire furnished.

3.10.10 Tires. Tires shall be tubeless type with highway tread. Tires shall be of rated capacity not less than equal to the load imposed on each tire measured at the wheel at the ground, with the trailer loaded as specified in 3.9. Tires shall conform to TRA or ETRTO.

3.10.11 Fenders and splash guards. The trailer shall be equipped with fenders and splash guards. Fenders shall withstand loads of 200-pound force per square foot (9.6 kilopascal (kPa)) without evidence of permanent deformation. Splash and stone-throw protection shall be in accordance with SAE J682.

3.10.12 Service brakes. Service brakes shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.40 through 393.43 and 393.45 through 393.47. Brake linings shall be of nonasbestos material.

3.10.12.1 Electric brakes. Unless otherwise specified (see 6.2), trailer shall be provided with electric-type brakes wired through the seven contact lighting socket specified in 3.10.16. An electric brake controller shall be furnished for subsequent installation in the towing vehicle. Brakes shall be operable on the 12-volt (V) system of the towing vehicle. Provisions for mounting and connecting the battery, required to operate the brakes in the event of a breakaway from the towing vehicle, shall be furnished.

3.10.12.2 Hydraulic brakes. When specified (see 6.2), trailer shall be equipped with hydraulic brakes of manufacturer's current standard type.

3.10.13 Parking brake. The trailer shall be provided with a hand-lever-operated parking brake, capable of holding the trailer, loaded with the rated payload, on a 20 percent grade on a dry hard surface, when uncoupled from the towing vehicle and headed up or down the incline. The parking brake shall conform to DoT Federal Motor Carrier Safety Regulation 393.41.

3.10.14 Chock blocks and cradles. When specified (see 6.2), two pairs of tire chocks with captive chains and two cradles shall be furnished with wood, steel, aluminum or molded rubber as specified. The hook of each captive chain shall be secured to the cradle. The captive chains shall be long enough to be wrapped around the cradle to hold the chocks in place during travel, and to allow the wheels to be chocked in front and behind while parked. The chock blocks shall be of sufficient size and strength to prevent trailer movement during reel operations and while parked and headed either up or down a 20 percent slope.

3.10.15 Lighting system. The lighting system shall be of 12-volt (V) potential and shall conform to DoT Federal Motor Carrier Safety Regulations as applicable. Wiring pattern, wire color code, and coupling connector receptacle shall conform to SAE J560. The receptacle shall be located in accordance with SAE J702. Turn signal lamps shall conform to SAE J588. Taillights and turn signals shall be guarded and wiring shall be routed and anchored for protection from damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.10.16 Receptacle system, 24V. When specified (see 6.2), the trailer shall be equipped with a 24V receptacle system consisting of one 12-contact receptacle with cover and one 7-contact receptacle with cover installed at the front of the trailer. The 12-contact receptacle shall conform to MS75021, part no. MS75021-1. The 7-contact receptacle shall conform to SAE J560 round socket for jumper cable. The 12-contact receptacle shall be provided with resistance to each circuit to reduce the voltage of a tactical military design towing vehicle from 24V to 12V. A pulse system is acceptable in lieu of a resistor box. The 7-contact socket shall be wired in accordance with SAE J560 to supply 12V directly to the trailer circuits. The 24V, 12-contact receptacle shall be connected through the necessary resistors into the 12V trailer circuits as follows:

A - Do not connect.
B - Connect to circuit No. 3.
C - Do not connect.
D - Connect to circuit No. 1.
E - Connect to circuits No. 2 and 6.
F - Do not connect.
H - Do not connect.
I - Is not used.
J - Connect to circuit No. 5.
K - Connect to circuit No. 7.
L - Do not connect.
M - Do not connect.
N - Do not connect.

Circuits B and J on tactical truck-tractors are combination stop and turn indicator circuits. The normal 12V turn signal lights will function both as turn signals and stoplights and the normal 12V stoplights will not be in operation when the trailer is connected to a towing vehicle with a 24V power supply. Because of this condition, the No. 4 stoplight circuit is not connected to the 24V, 12-contact receptacle.

3.11 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. All parts requiring lubrication shall be lubricated as specified in 3.12. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where high pressure lubricating equipment is used, (1,000 pound-force per square inch (6 895 kPa) or higher, will damage grease seals or other parts), a suitable warning shall be affixed to the equipment in a conspicuous location.

3.12 Servicing and adjusting. Prior to acceptance of the trailer by the Government, the contractor shall service and adjust the trailer for immediate operational use as required in the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.

b. Adjustment of brakes (when required).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

c. Proper functioning of all lighting and electrical systems.

d. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.

The trailer shall be conspicuously tagged to identify the lubricants and their temperature range.

3.13 Lifting and tiedown attachments. Unless otherwise specified (see 6.2), the trailer shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to type II or type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the trailer. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tiedown of the trailer on the carrier when shipped.

3.14 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to ensure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 0.0025-inch (0.065 mm) over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.15 Identification marking. Identification shall be permanently and legibly marked directly on a corrosion-resisting metal plate securely attached to the trailer at the source of manufacturer. Identification shall include the manufacturer’s model and serial number, name, and trademark to be readily identifiable to the manufacturer.

3.16 Workmanship.

3.16.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to ensure uniformity of size and shape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.16.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.16.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. The rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.16.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.16.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or other defect which reduces the casting's ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification, where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in this document shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submissions of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

a. First production trailer inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First production trailer inspection. The first production trailer produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. This inspection shall include the examination of 4.3 and the tests of 4.4. The purpose of the inspection shall be to determine vehicle conformity with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3 and the tests of 4.4.

4.3 Examination. Each trailer shall be examined for compliance with the requirements specified in section 3 of this document. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 First production trailer test. When a first production trailer is required, the first trailer shall be subjected to the tests by the contractor as specified in 4.4.1 through 4.4.6 and when applicable, 4.4.7 through 4.4.9. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all trailers until corrective action has been taken.

4.4.1 Trailer weight. The trailer shall be weighed to determine net weight and distribution of net weight on coupler ring and axle. The weight distribution shall be computed using net weight and the rated payload. Calculated imposed loads on coupler ring and axle shall be utilized to ascertain that tires, axles, and suspension are of adequate capacity to meet the contract requirements.

4.4.2 Towing tests. The fully equipped trailer shall be towed over roads and terrain specified in 3.7.1, at a distance not less than 10 miles (16 km), loaded with rated payload and 5 miles (8 km) without load. Not less than 20 percent of the distance shall be over improved roads and reasonably hard terrain. Towing speeds shall be as specified in 3.7.1. Tracking shall be checked for conformance to 3.7.3. Trailer shall be observed during the run and examined after the test for evidence of misalignment, part failure, or other defects.

4.4.3 Turning ability test. The trailer, loaded with rated payload, shall be tested for turning ability to verify compliance with 3.7.2.

4.4.4 Service brake test. Service brakes shall be tested with rated payload on the trailer to verify compliance with the requirements of 3.7.4. Breakaway situation shall be simulated to verify braking ability upon breakaway.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

4.4.5 Operated equipment test. All operated equipment shall be maneuvered to verify conformance to this specification. All adjustments shall be tested within their range for interference or defects.

4.4.6 Pick up and loading test. Pick up and loading of a reel not less than 108 inches (2 743 mm) in diameter and weighing not less than 15,000 lb (6 795 kg) shall be performed five times to verify conformance with 3.10.5.

4.4.7 Parking brake test. Parking brake, when required, shall be tested to verify conformance to the requirements of 3.10.13.

4.4.8 Chock block test. When chock blocks are required, test shall be performed to verify conformance with 3.10.14.

4.4.9 Lifting and tiedown attachment tests. When required, the lifting and tiedown attachments shall be tested to verify conformance to 3.13.

4.5 Production sample. Upon acceptance of the first production trailer, it shall remain at the manufacturing facility as a production sample and shall be the last trailer shipped on the contract. The contractor shall maintain the trailer in a serviceable condition for the duration of the contract.

4.6 Production unit tests. The contractor's testing system shall, as a minimum, ensure that the trailer is capable of meeting the performance requirements specified herein. The trailer shall be exercised to ensure brake adjustment, light operation, landing leg operation, tracking ability, and reel pickup and loading. These operations shall be made as a final inspection check.

5. PACKAGING

5.1 Packaging requirements. The preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Trailer covered by this specification is intended for use by the Government in transporting and handling of cable reels, and for use in cable-laying operations.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When first production trailer is required for inspection and approval (see 3.2 and 4.2).
c. If cable reel width is other than specified (see 3.8.4).
d. Rated payload if other than specified (see 3.9).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

e. Coupler ring if other than specified (see 3.10.2).
f. When coupler ring shall conform to A-A-52464 (see 3.10.2).
g. Electric brakes if other than specified (see 3.10.12.1).
h. When hydraulic brakes are required (see 3.10.12.2).
i. When chock blocks are furnished with specificied type of material required (see 3.10.14).
j. When 24V receptacle system is required (see 3.10.16).
k. When lifting and tiedown attachments are required (see 3.13).
l. Color of finish coat required (see 3.14).

6.3 Supersession data. This specification replaces Military Specification MIL-T-45381E dated 30 March 1991.

6.4 Definitions.

6.4.1 Improved road. An improved road is a smooth, hard surfaced road, such as a concrete or asphalt-paved highway.

6.4.2 Unimproved road. An unimproved road is an unpaved, unstabilized road with undulating surface having occasional chuckholes and exposed rocks.

6.5 Subject term (key word) listing.

Power loading
Self-contained
15,000 lb (6 795 kg) capacity
12V, 24V, lighting system

6.6 Changes from previous issue. Marginal notations are not used to identify changes with respect to the superseded document.

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - YD1
Air Force - 99

Review Activities:
Navy - MC
Air Force - 84

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

Preparing Activity:
Navy - YD1

(Project 2330-0262)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** KKK-T-2921	**2. DOCUMENT DATE (YYMMDD)** 970414

3. DOCUMENT TITLE
TRAILER, CABLE REEL

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7. DATE SUBMITTED** (YYMMDD)

8. PREPARING ACTIVITY

a. NAME RUDY PAMPLONA	b. TELEPHONE *Include Area Code)* (1) Commercial 805-982-5843 (2) AUTOVON 551-5843
c. ADDRESS *(Include Zip Code)* COMMANDING OFFICER, NCBC CODE 15E2D 1000 23RD AVENUE PORT HUENEME, CA 93043-4301	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE QUALITY AND STANDARDIZATION OFFICE 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22401-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.